



MONITORING FOR AIRBORNE ASBESTOS FIBERS: VINYL ASBESTOS FLOOR TILE

Final Report

December 1979

**By: Richard Walcott, Industrial Hygienist
James Warrick, Industrial Hygienist**

Prepared for:

**Resilient Floor Covering Institute
1030 15th St. N.W.
Suite 350
Washington, D.C. 20005**

SRI Project 7988

Approved by:

**Sherry J. Hanen, Associate Director
Center for Occupational and Environmental Safety and Health**

Ernest J. Moore, Vice President

SRI INTERNATIONAL

SRI International is a problem-solving organization that provides consulting and research under contract for clients in business and government throughout the world.

Since SRI was founded in 1946, the problems confronting our clients have so increased in complexity that few of them can be solved within the confines of a single discipline. The organization is uniquely qualified to deal with such intricate problems. Professionals representing more than 100 disciplines comprise nearly two-thirds of the 3,000 staff members.

SRI performs consulting and research for the public sector in such areas as urban management; health, education, and welfare; environmental management, and national security. In addition to broad-ranging activities for the U.S. and other national governments, SRI serves city, state, and county governments in the U.S., and also their international equivalents. One of the most attractive aspects of life at SRI for the staff is the opportunity to share in important work in the public interest.

For private commercial and industrial clients, SRI engages in management consulting and corporate strategy determination; technoeconomic, market, and operational studies; new product, process, and equipment development; and the provision of information services. A significant percentage of SRI's professional staff have had a number of years of major responsibility in business prior to joining SRI.

SRI is an independent, nonprofit corporation, using revenues in excess of operating costs to purchase advanced scientific equipment and to enhance its ability to continue to provide the highest quality consulting and research for its clients. SRI International has no shareholders and no endowment.

SRI's annual revenues for consulting and research contracts exceed \$125 million.

SRI's headquarters are on a 70-acre site in Menlo Park, California, a suburban community about 20 miles south of the San Francisco International Airport and a few miles from the campus of Stanford University. Other offices and laboratories are located in major centers in North America, Europe, East Asia, and the Middle East.

STATEMENT OF OBJECTIVE

The principal objective of this study was to monitor for airborne asbestos fibers, if any, during conditions of use, maintenance, installation and removal of vinyl asbestos floor tile and to determine their concentrations.

TABLE OF CONTENTS

	<u>Page</u>
I. Introduction, Vinyl Asbestos Tile	1
II. Test Site Location	2
III. Methodology	7
IV. Summary of Results	8
V. Conclusions	10
VI. In-Use Tests, Site #2	11
VII. Maintenance Tests, Site #2	16
VIII. Complete Removal Tests, Site 3	22
IX. Installation Tests	24
X. Attachments:	
A. NIOSH Analytical Method	
E. Representative Ambient Air Asbestos Concentrations in Cities	

1. INTRODUCTION

Vinyl asbestos tiles are widely used in many homes and institutional and commercial locations. Fibrous asbestos is used in the manufacture of vinyl asbestos floor tiles. The unique combination of resistance to physical and chemical deterioration and high tensile strength with flexibility are asbestos characteristics useful in the production and durability of the tile.

It has been determined that the inhalation of airborne asbestos fibers over long periods of time may result in asbestosis or other serious illness. However, in vinyl asbestos floor tile, the asbestos is "locked-in" by polymeric binders of various types. SRI International was retained to measure the amount, if any, of airborne asbestos fibers associated with use, maintenance, installation and removal of vinyl asbestos floor tiles when RFCI recommended procedures are followed, i.e., the operations are performed without sanding or sweeping an existing floor.

11. TEST SITE LOCATIONS

Test Site #1.

December 6, 1978. Installation was made in a model of a new housing development in Northern Virginia. With the exception of some interior finishing work, construction of the model home was essentially complete and the home was being heated at the time of the test. Two types of vinyl asbestos tile were installed: GAF "Taj Mahal" in a small utility room on the first floor, and GAF "Wood Block #1725" in the basement. In both areas, the vinyl asbestos tile was installed directly on concrete subfloors. Before the tile was installed, GAF "FB-50" asphalt cut-back adhesive was applied to the floor and allowed to dry. Some tiles were cut for edge and corner fitting. The utility room was approximately 15 square feet in area and the basement area was about 315 square feet. The time required for the basement tile-laying operation was about 2 hours, and approximately 20 minutes for the utility room. Figure 1 is a diagram of the site.

Test Site #2.

January 23-25, 1979, and January 29, 1979. This site, an office building called Hoffman #2 located in Alexandria, Va., was selected for in-use and maintenance tests. The building is approximately five years old and has a steel-reinforced concrete structure. The internal structure of the building is essentially suspended ceilings, plasterboard walls, and vinyl asbestos floor tile. There is no sprayed-on fire-proofing in the building. With regard to the mechanical air movement in the building, 75% is recirculated and 25% is brought in as make-up air through the roof airhandling units. From the roof, the air is moved via metal ducts to individual heating and cooling units on the individual floors. Here the air is passed through metal mesh filters before being sent to the individual rooms. The ductwork from the air-handlers to the rooms is partially lined with resin-impregnated mineral wool. A diagram of the site is shown in Figure 2.

This same site was also used on April 16, 1979, to further evaluate potential asbestos-fiber generation during buffing operations for longer periods of time than during the January 23-25, 1979, monitoring tests.

Test Site #3.

June 28, 1979. A private home in Newark, Delaware. Monitoring was done for both removal and installation of vinyl asbestos tile. The existing GAF vinyl asbestos tile was removed in the laundry room, powder room, closet, and hallway. The sub-floor was concrete. After the removal operation, which took about 2 hours, Amtico adhesive-backed "Sunbeam Duravynyl" vinyl asbestos tile was installed. The tiles were 12 inches square and 0.080 inches thick. This operation took approximately 4 hours. The relative room positions are shown in Figure 3.





Figure 1 SITE PLAN - TEST SITE NO. 1




Figure 2. SITE PLAN - TEST SITE NO. 2




Figure 3 SITE PLAN - TEST SITE NO. 3

III. METHODOLOGY

1. Use, Maintenance, Preparation, Installation and Removal

The operations were done according to recommended procedures.*

2. Determination of Airborne Asbestos Fibers

The NIOSH method for determining asbestos fibers in the air was employed (see Attachment "A," NIOSH Method No. P&CAM 239, "Asbestos Fibers in Air").

Note: Personal and area samples were collected with a Mine Safety Appliance Company Model G portable sampling pump. High-volume samples were taken with a Gast pump.

* Recommended procedures involve preparation, installation, and removal without sanding, use of equipment that would unduly shatter the tile instead of a flat-bladed wall scraper, or breaking the tile by hand before placing in a disposal bag. For the impact of deviation from recommended procedures, see SRI International Report, "Comparison Testing, Monitoring for Airborne Asbestos Fibers: Vinyl Asbestos Floor Tile." (December, 1979)

IV. SUMMARY OF RESULTS

The following Tables list the concentrations, if any, of airborne asbestos fibers measured at the various test sites during specified operations.

NOTE: The OSHA Standard for a safe workplace allows a concentration of 2 fibers per cc of air on an 8-hour time-weighted-average (TWA). TWA exposures were calculated by assuming a full-days exposure to these conditions.

Table No. 1

In-Use Text

<u>Site No. and Description</u>	<u>Asbestos Fibers/cc</u>
2 - Copy Center	0
2 - Snack Shop	0

Table No. 2

Maintenance

<u>Site No. and Description</u>	<u>8-Hr. TWA (Asbestos Fibers/cc)</u>
2 - Mopping	0
2 - Buffing	0

Table No. 3

Installation

<u>Site No.</u>	<u>8-Hr. TWA (Asbestos Fibers/cc)</u>	
	<u>Man C-102</u>	<u>Man C-1062</u>
1	0.0046	0.0092
	<u>Man JS</u>	<u>Man TD</u>
3	0.027	0.008

Table No. 4

Removal

<u>Site No.</u>	<u>8-Hr. TWA (Asbestos Fibers/cc)</u>	
	<u>Man JS</u>	<u>Man TD</u>
3	0.006	0.015

V. CONCLUSIONS

1. Use

In use of vinyl asbestos floor tile there is no exposure to airborne asbestos fibers.

2. Maintenance

In the maintenance of vinyl asbestos floor tile there is no exposure to airborne asbestos fibers.

3. Installation and Removal

In the installation and removal of vinyl asbestos floor tile, the results of these tests show that when recommended procedures are used the exposure to airborne asbestos fibers is substantially below the allowed OSHA limit.

VI. IN-USE TESTS, SITE #2

Purpose:

To monitor for airborne asbestos fibers during light and heavy pedestrian traffic (in-use) conditions of vinyl asbestos floor tile and to measure any increased fiber concentrations above background levels.

Discussion:

At the time of the testing, the floors of the two areas sampled, a snack shop and a small copy room, were in the unwaxed condition (wax had been stripped) and had received traffic in that condition. This was purposely done to simulate a very poor maintenance condition and/or a "worst-case" situation.

The analyses of both the background (collected after working hours) and in-use (collected during working hours) air samples did not show any asbestos fibers in heavily traveled areas.

Sampling Procedure:

The sampling protocol was designed to determine:

1. The background dust level in the building and outside air, with specific consideration to any ambient fibers. The sampling strategy for this involved placement of sampling units both inside and outside the building. The inside units were placed at 1, 3, and 5 feet above the floor in both the snack shop and copy room, with single filters at other selected locations such as in the area of an air diffuser in these two areas. Outside samples were placed randomly. The multilevel sampling protocol could not be met in the snack shop so the following alternate sampling plan was used for this area: The dust level in the supply air entering the snack

shop was monitored by sampling air from the air-handling unit as it entered the duct leading to the air diffusers. An additional sample was collected in the hallway next to the snack shop. In both cases the sampling was performed several hours after the office work force had gone home.

2. The concentration of asbestos, if any, dispersed from the floor tile during light and heavy pedestrian traffic. In this case, the multilevel sampling outlined in 1, was used, except that two such sampling units were placed in different locations of both the snack shop and copy room.

Figure 2, page 5, shows the relative locations of the area-sampling units during the testing.

Sampling Results:

The results of the individual filter analyses are shown in Table No. 5. The types of fibers found in the samples collected were not asbestos but rather textile fibers that appeared to have been shredded off from larger textile fibers. The morphologic appearance of these fibers was quite different from asbestos. For illustrative purposes, in Figure 4, the first photomicrograph shows an asbestos sample that was prepared for the Proficiency and Accuracy Testing Program (sponsored by NIOSH) and shows fiber bundles of varying thicknesses. The second photomicrograph, not taken from these samples, shows two fibers which are examples of probable chrysotile asbestos. Characteristically in field samples of this type, the fiber bundles are much shorter than textile fibers. The third and final photomicrograph shows cotton fibers. This type shows typically twisted shapes. Additionally, the fiber diameter is substantially greater than that of asbestos, but is comparable to most other types of textile fibers, such as the types observed during this aspect of the sampling program. Figure 5, shows an electromicrograph of chrysotile asbestos. At this magnification (40,000x), the appearance of these types of fibers is drastically different from the appearance of textile fibers, especially in the lack of twisting, much smaller fiber diameter (10 to 25 millimicrons), and the characteristic hollow core of the asbestos fibers. Consequently, we concluded that the fibers observed were textile fibers and not asbestos fibers.

Table No. 5

In-Use Testing Results


<u>Description</u>	<u>Filter No.</u>	<u>Air Vol. (liters)</u>	<u>Time (min)</u>	<u>Fibers/ sq mm*</u>	<u>Total Fibers/cc</u>	<u>Asbestos** Fibers/cc</u>
BACKGROUND SAMPLES						
Air Vent	C-1066	588	294	4.7	0.0067	0
Hallway	XX005	556	278	4.7	0.007	0
Copy Center	XJB	590	295	0	0	0
Outside	XX102	616	308	0	0	0
Outside	XX031	834	417	0	0	0
Outside	XX006	840	420	0	0	0
Copy Center						
1 ft high	XX015	594	297	2.5	0.0035	0
3 ft high	XX008	594	297	0	0	0
5 ft high	XX016	594	297	0	0	0
Snack Shop	C-1051	264	142	0	0	0
IN-USE SAMPLES						
Copy Center - Table						
1 ft high	XX027	838	419	4.4	0.0044	0
3 ft high	XX030	838	419	0	0	0
5 ft high	XX011	838	419	11.1	0.011	0
Copy Center - Middle Room						
1 ft high	C 1078	822	411	2.3	0.0023	0
3 ft high	C 1096	822	411	4.5	0.0046	0
5 ft high	C 1083	822	411	4.6	0.0047	0
Snack Shop						
Bookcase - 1 ft	XX017	260	130	0	0	0
Bookcase - 3 ft	XX022	260	130	0	0	0
Bookcase - 5 ft	XX002	260	130	2.5	0.0079	0
Storage Door - 1 ft	XX023	266	133	4.5	0.0618	0
Storage Door - 3 ft	XX019	266	133	2.4	0.0088	0
Storage Door - 5 ft	XX029	266	133	0	0	0

*Fibers/sq mm of filter surface area.


**Analyst determined that none of the fibers were asbestos.



NO. 1. ASBESTOS SAMPLE



NO. 2. CHRYSOTILE ASBESTOS



NO. 3. COTTON FIBERS

Figure 4. FIBER PHOTOMICROGRAPHS



Figure 5 ELECTRON MICROGRAPH, CHRYSOTILE ASBESTOS

Evaluation:

The average background fiber count calculated on this floor of this building was 0.0025 fibers/cc of air (calculated from filters C-1066, XX005, XJB, XX015, XX008, XX016, and C-1051) as compared to the outside air fiber concentration of 0 (calculated from filters XX102, XX031, XX006). Comparing the average value of the background indoor samples to the heavy and light pedestrian traffic areas, we found the following: the relative average concentrations for the copy room and snack shop were 0.0045 fibers/cc (calculated from filters C-1078, C-1096, C-1083, XX027, XX030, XX011) and .0056 fibers/cc (calculated from filters XX-002, XX-022, XX-017, XX-019, XX-023, XX-029), respectively. The finding that these concentrations are approximately 2 times the background concentrations is not surprising since the level of activity during a normal working day should increase the dust level over the background samples that were collected after working hours.

Comparing the values found for the light and heavy pedestrian traffic areas, we found that the individual values in the snack shop are approximately 2 times those in the copy room, except for the 0 levels. This is due to the difference in the time of sampling and sample volume. The values found in the copy room are very consistent and represent 8-hour concentrations, while the snack shop samples could only be collected during the peak traffic time, from 10:52 a.m. to 1:05 p.m. These levels represent somewhat of a peak concentration for the day. Had the sampling been continued for the remainder of the day, the average concentration would probably have been lower by including the less dusty periods in the afternoon in the total sampling time.

Conclusion:

Based on the absence of any detectable asbestos fibers during the pedestrian traffic tests, we conclude that, when properly maintained, the asbestos constituent of the floor tile does not pose a potential health risk to office employees or maintenance personnel.

The description of the fiber counts relating to textile fibers have been included in this report for purposes of completeness and clarity. General interest in a floor covering is greater in regard to use than to installation since most persons' contact with a flooring is mainly through its use over a 10-20 year period rather than through the occasional process of installation.

VI. MAINTENANCE TESTS, SITE #2

Purpose:

To monitor for airborne asbestos fibers during maintenance operations of vinyl asbestos floor tile and to measure any increased fiber concentrations above background levels.

Discussion:

The actual sampling took place in a snack shop and in a copying room during prescribed routine maintenance. The wax was removed (stripped) and no-wax maintenance procedures followed. This consisted of buffing the floor using a light misting of a mild cleaning solution, or of wet mopping.

Sampling Procedure:

The sampling protocol was designed to determine:

1. The background dust level in the building and outside air, with specific consideration to any ambient fibers. The sampling strategy for this involved placement of sampling units both inside and outside the building. The inside units were placed at 1, 3, and 5 feet above the floor in both the snack shop and copy room, with single filters at other selected locations such as in the area of the air diffuser in these two areas. Outside samples were placed randomly. The multilevel sampling protocol could not be met in the snack shop so the following alternate sampling plan was used for this area: the dust level in the supply air entering the snack shop was monitored by sampling air from the air-handling unit as it entered the duct leading to the air diffusers. An additional sample was collected in the hallway next to the snack shop. In both cases the sampling was performed several hours after the office work force had gone home.

2. The difference in the concentration of asbestos in the air during floor maintenance as compared to background concentrations of asbestos, if any, during operations such as damp mopping and floor stripping; personal sampling was performed in addition to area sampling.

In all cases samples were collected for the maximum time allowed by the operation in order to collect a representative air sample. However, several of the sample volumes were very small (less than 50 liters) due to extremely short operations. The impact of the smaller sampling times will be discussed in the section on sampling results.

Figure 2, page 5, shows the relative locations of the area sampling units during the testing.

Sampling Results:

The results of the individual filter analyses are shown in Table No. 6.

Evaluation:

The average textile fiber concentration found during the wet-stripping operation was 0.0771 fibers/cc of air (calculated from filters XX-026, XX-001, XX-014, XX-000, XX-025, and QTH-1). The average sample volume was 34.5 liters. Prior to this operation, a background sample (C-1051) was collected (284 liters) in the snack shop and showed no fibers when microscopically examined. This indicates that the operation may resuspend dust that has settled out during the several hours following the end of the office-employee work shift. Comparing the low value of the general area sample (QTH-1) collected during the wet stripping of the snack shop (0.0075 textile fibers/cc of air) with the results of the sampling of the worker performing the wet mopping (0.1351 textile fibers/cc - sample #XX-000), we see that the operation also tends to resuspend the dust in the worker's immediate area. However, the small sample volumes collected in the snack shop may have biased the results toward the high side because a particularly dusty spot on the floor was stripped during the sampling time; this might have averaged out somewhat in a longer operation, ie, in a larger sampling

Table No. 6

Maintenance

<u>Description</u>	<u>Filter No.</u>	<u>Air Vol. (liters)</u>	<u>Time (min)</u>	<u>Fibers/sq mm*</u>	<u>Total Fibers/cc</u>	<u>Asbestos** Fibers/cc</u>
BACKGROUND SAMPLES						
Air Vent	C1066	588	294	4.7	0.0067	0
Hallway	XX005	556	278	4.7	0.007	0
Copy Center	XJB	590	295	0	0	0
Outside	XX102	616	308	0	0	0
Outside	XX031	834	417	0	0	0
Outside	XX006	840	420	0	0	0
Snack Shop	C1051	284	142	0	0	0
MAINTENANCE SAMPLES						
Mopping - Copy Center	XX026	30	15	4.9	0.1351	0
Buffing - Copy Center	XX001	30	15	4.3	0.1210	0
Mopping - Snack Shop	XX000	42	21	9.8	0.1949	0
Buffing - Snack Shop	XX025	42	21	0	0	0
Buffing - Copy Center	KGB-1	22	11	2.4	0.0921	0
Buffing - Copy Center	XX	60	30	0	0	0
High-Volume Sample (Mopping)	QTH-1	537	54	4.9	0.0075	0
Floor Area	XX-014	30	15	2.5	0.682	0

*Fibers/sq mm of total filter surface area.

**Analyst determined that none of the fibers were asbestos.

volume. It is interesting to note that the personal sample from the buffer operator did not detect any textile fibers. Additionally, the worker was outside the snack shop during the wet mopping.

While the results of the buffing operation recommended for a no-wax maintenance floor did not show any asbestos fibers, several factors prohibit drawing a firm conclusion on this aspect. The relative size of the operation tested was small, requiring only 11 minutes to complete. The air sample size was also small (22 liters). The size was possibly too small for any asbestos fibers that may have been generated to have been picked up.

Because of the small size of the sample collected during the buffing operation, a second sample (XX) was collected during a buffing operation at a later date. The duration of the second buffing was 30 minutes and a 60-liter sample was collected. Again, no asbestos fibers were found.

An operation like the wet-stripping operation does tend to resuspend dust that has settled out of the air after working hours. This was shown by comparing filters XX-002 (0.0079 textile fibers/cc) and XX-029 (0 fibers/cc), listed in Table 5, page 13, both of which were taken during the day in the snack shop at the 5-foot level, with filter KGB-1 (0.0921 textile fibers/cc), the personal sample of the buffer operation.

Conclusion:

Based on the absence of any detectable asbestos fibers during either the wet-stripping or buffing operations, we conclude that, when floor tile is properly maintained, its asbestos constituent does not pose a potential health risk to office employees or maintenance personnel. The data relative to textile fibers have been included in this report for purposes of completeness and clarity. Fibers were generated from maintenance, but they were all textile fibers.

VIII. COMPLETE REMOVAL TESTS, SITE 3

Purpose:

To monitor for airborne asbestos fibers during the complete removal of vinyl asbestos floor tile.

Discussion:

The tests were done in the laundry room, powder room, closet, and hallway of a private home. Removal was accomplished by heating the tile with a commercial air blower. However, there was an unusually large amount of adhesive under the tile and the heating compounded the difficulty of removal. In main pedestrian traffic areas there was quite a bit of tile breakage and many small pieces were generated. In other areas, the tiles came up quite readily without excessive breaking. In the closet and bathroom areas, access for good leverage on the hand tools was difficult and the mechanics had to be very close in to do the work. Discarded tile was placed in trash bags for disposal.

Sampling Procedure:

A personal sampling pump was attached to the belt of each mechanic and a filter clipped to his collar. Four additional sampling pumps were placed to obtain area and background data. A background determination was also made the day prior to the test.

A GCA Dust Monitor was used to measure total dust (by weight) in the area. This is a direct reading instrument; dust levels were below the detection level in 2 samples.

A sketch of the work and indications of sample placement are presented in Figure 3, page 6.

Sampling Results

The results of fiber counting, other pertinent sampling data, and identifiers are listed in Table No. 7.

Table No. 7

<u>Description</u>	<u>Filter No.</u>	<u>Air Vol. (liters)</u>	<u>Time (min)</u>	<u>Fibers/ sq. mm*</u>	<u>Total Fibers/cc</u>	<u>Asbestos** Fibers/cc</u>	<u>8-Hr. TWA</u>
Background	RFCI #8	567	326	0	0	0	
Background	MWCO 700	594	297	10	0.014	0.001	
Area-Breezeway	MWCO 692	537	316	70	0.111	0.011	
Area-Laundry Room	MWCO 686	739	389	140	0.161	0.016	
Area-Powder Room	MWCO 685	725	372	75	0.088	0.009	
Mechanic JS	MWCO 662	246	123	18	0.062	0.006	0.006
Mechanic TD	MWCO 687	255	134	44	0.147	0.015	0.015

*Fibers/sq mm of filter surface.

**Analyst estimated that 10% of the fibers were asbestos.

Conclusion:

The number of asbestos fibers on the filters was very small, all well below 0.1 fibers/cc. Compared to the OSHA limit of 2.0 fibers/cc, the concentrations measured when recommended procedures were followed, 0.006 to 0.015 fibers/cc, are insignificant .

IX. INSTALLATION TESTS

A. Site #3

Purpose:

To monitor for airborne asbestos fibers during the installation of vinyl asbestos floor tile.

Discussion:

The tests were done in the laundry room, powder room, closet, and hallway of a private home. The tiles were precoated with adhesive; installation consisted of removing the release paper from the back and then pressing the tile firmly in place on the concrete slab floor. Where cutting or trimming were required, it was done before the paper was removed.

Sampling Procedure:

A personal sampling pump was attached to the belt of each mechanic and a filter clipped to his collar. Four additional sampling pumps were placed to obtain area and background data. A background determination was also made the day prior to the test.

A GCA Dust Monitor was used to measure total dust (by weight) in the area. This is a direct reading instrument; dust levels were below the detection limit in 2 samples.

A sketch of the work and indications of sample placement are presented in Figure 3, page 6.

Sampling Results:

The results of fiber counting, other pertinent sampling data, and identifiers are listed in Table No. 8.

Table No. 8

<u>Description</u>	<u>Filter No.</u>	<u>Air Vol. (liters)</u>	<u>Time (min)</u>	<u>Fibers/sq. mm*</u>	<u>Total Fibers/cc</u>	<u>Asbestos** Fibers/cc</u>	<u>8-Hr TWA</u>
Background	RFC1 #8	587	326	0	0	0	
Background	MWCO 700	594	297	10	0.014	0.001	
Area - Breezeway	MWCO 692	537	316	70	0.0111	0.0011	
Area - Laundry	MWCO 686	739	389	140	0.161	0.016	
Area - Powder Room	MWCO 685	725	372	75	0.088	0.009	
Mechanic JS	MWCO 682	464	232	145	0.267	0.027	0.027
Mechanic TD	MWCO 664	418	220	40	0.081	0.008	0.008

*Fibers/sq mm of filter surface area.

**Analyst estimated that 10% of the fibers were asbestos.

B. Site #1

Discussion:

The tests were done in the basement and in a small utility room. The tile was installed directly on a concrete floor. The installation required about 2 hours for the basement and about 20 minutes for the utility room.

Sampling Procedure:

Two area samples were collected for background analysis -- one inside the home and another outside. A personal sample was collected for each of the two mechanics involved. In addition a high-volume sample was also collected. A sketch of the sampler placements is shown in Figure 1, page 4.

Sampling Results:

The results of fiber counting and other identifiers are listed below in Table No. 9. The filters were heavily loaded with dust, making the fiber counting very difficult.

Table No. 9

<u>Description</u>	<u>Filter No.</u>	<u>Air Vol. (liters)</u>	<u>Time (min)</u>	<u>Fibers/sq mm*</u>	<u>Total Fibers/cc</u>	<u>Asbestos** Fibers/cc</u>	<u>8-Hr. TWA</u>
Indoor Background	C1069	876	438	111.7	0.104	0.0052	
Outdoors	XX-1	660	330	4.7	0.003	0.003	
High-Volume Sample	XXII	1710	90	38.1	0.28	0.0014	
Head Mechanic	C102	228	114	27	0.092	0.0046	0.0046
Assistant Mechanic	C1062	226	113	52.3	0.184	0.0092	0.0092

*Fibers/sq mm of filter surface area.

**Analyst estimated that about 5% of the fibers were asbestos except for filter XX-1.

Conclusion:

The number of asbestos fibers on the filters was very small, all well below 0.1 fibers/cc. Compared to the OSHA limit of 2.0 fibers/cc, the concentrations measured when recommended procedures were followed, 0.0046 (Table 9) to 0.027 (Table 8) fibers/cc, are insignificant.

ATTACHMENT A

ASBESTOS FIBERS IN AIR

ASBESTOS FIBERS IN AIR
National Institute for Occupational Safety and Health
Analytical Method

Analyte:	Asbestos fibers	Method No.:	P&CAM 239
Matrix:	Air	Range:	0.1-60 fibers/cm³
Procedure:	Filter collection, microscopic count	Precision (CV_r):	0.24 to 0.38
Date Issued:	3/30/77	Classification:	D (Operational)
Date Revised:			

1. Principle of the Method

- 1.1 This method describes the equipment and procedures for collecting, mounting, and counting asbestos fibers on cellulose ester membrane filters in the evaluation of personal samples of airborne asbestos fibers. The purpose of the method is to determine an employee's index of exposure to airborne asbestos fibers. The method is primarily a personal monitoring technique, but can be used for area monitoring.
- 1.2 The sample is collected by drawing air through a membrane filter by means of a battery powered personal sampling pump. The filter is transformed from an opaque solid membrane to a transparent optically homogeneous gel. The fibers are sized and counted using a phase-contrast microscope at 400-450X magnification.
- 1.3 Definitions. Asbestos fiber, for counting purposes, means a particulate which has a physical dimension longer than 5 micrometers and with a length to diameter ratio of 3 to 1 or greater. Asbestos includes chrysotile, cummingtonite-grunerite (amosite), crocidolite, fibrous tremolite, fibrous anthophyllite, and fibrous actinolite.
- 1.4 Any laboratory attempting to use this procedure should have at least one counter attend a training course conducted by an experienced, proficient laboratory. Novice, untutored counters, using only published instructions, can easily obtain counts of half those performed by experienced, proficient counters. Large differences between laboratories can be caused by: 1) differences in technique and observing ability among counters and 2) small, but significant, differences between microscopes meeting the basic specifications of Section 6.2. The following procedures are recommended:
 - 1.4.1 All microscopists who perform asbestos counting should meet together for an "asbestos counting workshop" at least quarterly. This is best accomplished with counters from several laboratories using their own microscopes.
 - 1.4.2 Each microscopist should count the same series of slides and with the results being compared.
 - 1.4.3 Differences between counters should be resolved with side-by-side counting of the fields by the different counters.
 - 1.4.4 Individuals who are found to be persistent outliers over several sessions should be encouraged to seek other tasks in their respective laboratories.

2. Range and Sensitivity

- 2.1 The usable range is primarily a function of sample volume, microscope count field area, and background airborne particulates. The influence of these variables is discussed in 8.1.3. For a microscope count field area of 0.003 mm^2 (see Figure 1) and a pump flow rate of 1.7 lpm, the optimal fiber densities would be produced over the range of 0.4 fiber/cm³ (8-hour sample) to about 60 fibers/cm³ (15-minute sample). For a field area of 0.006 mm^2 (see Figure 2) and a pump flow rate of 1.7 lpm, the optimal range is 0.2 fiber/cm³ (8-hour sample) to about 30 fibers/cm³ (15-minute sample). In each case, the optimal detection limits are inversely proportional to pump flow rate.

The upper detection limit can be extended by using sample times less than 15 minutes or using lower flow rates. The lower detection limit can be extended by increasing the flow rate up to about 2.5 lpm. Filter surface fiber densities less than optimal (less than about 0.5 to 1.0 fiber per count field) are still adequate, but will lead to decreased precision for the method (increased coefficient of variation, see Section 4).

The minimum total fiber count in 100 fields considered adequate for reliable quantitation is 10 fibers. Thus, the lower limit of reliable quantitation is 0.1 fiber/cm³ (100,000 fibers/m³). For this level, a flow rate of about 2.5 lpm is recommended. For a field area of 0.003 mm^2 , the minimum sample time would be about 2 hours. For a field area of 0.006 mm^2 , the minimum sample time would be about 1 hour.

- 2.2 This method considers only fibers with a length to diameter ratio of 3 to 1 or greater and a length greater than 5 micrometers.

3. Interferences

In an atmosphere known to contain asbestos, all particulates with a length to diameter ratio of 3 to 1 or greater, and a length greater than 5 micrometers should, in the absence of other information, be considered to be asbestos fibers and counted as such.

4. Precision and Accuracy

- 4.1 In the past decade, there have appeared a number of articles examining sources of variation in the asbestos sampling and counting procedure. These include: Lynch et al. (11.1), Weidner and Ayer (11.2), Conway and Holland (11.3), Leidel and Busch (11.4), Beckett and Attfield (11.5), and Rajhans and Bragg (11.6). The sources of variation will be discussed by stages in the membrane filter evaluation procedure.

- 4.2 Sources of Variation in the Sampling Process. These include variations in pump flow rate, proximity of the filter to the employee's body, and filter location (left to right) in the employee's breathing zone.

- 4.2.1 Section 9.1 requires that the personal sampling pump be calibrated with sufficient accuracy such that the 95% confidence limits on the flow rate are $\pm 10\%$. This is equivalent to a coefficient of variation (CV) of about 5%. However, this CV makes a negligible contribution to the total CV for the method due to the relatively large CV of the counting procedure.

- 4.2.2 Conway and Holland (11.3) concluded that positioning of the filter cassette on the wearer (regarding the angular portions of the filter and their proximity to the wearer) is not a significant factor in determining the fiber distribution on filters.

- 4.2.3 Weidner and Ayer (11.2) concluded that there is no appreciable difference between samples collected on either the right or left sides of a breathing zone or between samples collected side-by-side, especially for samples with concentrations less than 2.5 fibers/cm³.

4.3 Sources of Variation in the Counting Procedure

4.3.1 Random variations exist in the fiber distribution on a filter wedge (intra-wedge variability). The industrial hygiene literature has seen considerable debate in the last 20 years concerning whether or not the distribution of mineral dust or asbestos fibers on a filter surface is adequately described by a Poisson distribution probability density function. Leidel and Busch (11.4) found excellent agreement between empirical error variance and theoretical variance calculated from the assumption of Poisson distributed true counts. They concluded that there was not excessive variation among count fields for a filter wedge and that clumping of fibers (non-random coalescence) did not occur.

4.3.2 Variations exist in the fiber distribution on the total filter surface (inter-wedge variability) due to the random or non-random distribution of fibers across the total surface of the filter. This type of variation is easily confused with intra-wedge variations. The count procedure does not require counting of multiple sectors of the filter. There may be significant differences between average counts for different wedges, or the fiber distribution variations for the total filter surface may be greater than the variations of the Poisson distribution. If either of these occur experimentally, one must use the experimental variations to estimate the minimum precision of the count procedure. The minimum precision is governed by the variations of the fiber distribution on the total surface of the filter.

Conway and Holland (11.3) concluded the distribution of fibers on filters is not uniform and the distribution of fiber counts is more disperse than Poisson. For their filters which had significant variations in fiber concentrations between sectors (as much as 50-60% of the total filter mean), they described the following relation for the standard deviation of the total number of fibers counted on a wedge (N)

$$\text{empirical } s(N) = 1.6 (N)^{1/2}$$

where N is about 100. The Poisson standard deviation would be:

$$\text{Poisson } \sigma (N) = (N)^{1/2}$$

Rajhans and Bragg (11.6) in Series I of their study found significant variation between filter segments and rejected the Poisson distribution for the total filter surface. However, in Series II of their study, utilizing various experimental modifications, they found no significant variation between filter segments and no reason to reject the assumption of Poisson distributed fiber counts.

4.3.3 Systematic variations due to differences between microscopes were studied by Leidel and Busch (11.4). In their study using five different brands of microscopes, they found no significant differences among four, but the fifth gave counts approximately 45% higher on the average than the other four.

4.3.4 Variations due to differences between counters should be examined at three levels: experienced counters occasionally counting, experienced counters routinely counting, and inexperienced (new or untutored) counters. Leidel and Busch (11.4) studied five experienced counters, with one counting only occasionally. There were no significant differences among three of the counters, but a fourth was 16% lower than the first three. The fifth, who occasionally counted, averaged 27% higher than the first three. Conway and Holland (11.3) studied three experienced counters and three inexperienced counters. They found statistically significant differences between the means of both the experienced and inexperienced counters that typically were in the range plus or minus 5 to 15%. They concluded that experience as a fiber counter is not a significant parameter affecting intercounter variations.

Rajhans and Bragg (11.6) found no significant differences among means of five experienced counters in Series I of their study. But in their carefully controlled Series II, an analysis of variance showed significant variations between counters that were plus or minus 1 to 15%.

4.3.5 Variations between laboratories are most likely due to systematic biases and are not a significant additional source of random variations. Any additional variations are most likely due to differences in counting technique. Beckett and Aufeld (11.5) observed that standard counters improved greatly after personal instruction; also new counters, after instruction, tended to overcompensate and get exceedingly high counts. Additionally, they found that counts from an experienced laboratory that had not had contact with other laboratories performing the same analysis were as far from the standard values as were the counts by new counters.

4.4 Sources of variations between samples taken at different times on one employee during one work shift can affect the exposure estimate for that employee. These are primarily due to a) differences in exposure concentrations during the day, b) differences in location of the employee within the plant, and c) differences in work operation performed by the employee during the day. These sources of variation can be controlled by proper choice of sampling strategy. Refer to Leidel and Busch (11.7) and Leidel, Busch, and Lynch (11.8) for an extended discussion of sampling strategies. Interday temporal variations can affect the exposure estimates obtained on different days. Refer to Leidel, Busch, and Crouse (11.9) for a discussion of this type of variation.

4.5 Until recently, the total coefficient of variation (CV_T) for the sampling and counting procedure was best estimated from the work of Conway and Holland (11.3). The conclusions of their study included:

4.5.1 The precision of their procedure for filters not containing an abundance of fine fibers can be estimated by a coefficient of variation of 16.2%. This value includes variation among counters and observed interaction effects.

4.5.2 The accuracy of the procedure for similar filters may be estimated for a 100-fiber count by a coefficient of variation of 21.4%. This assumes that the contribution of the overall variance from the nonuniform fiber distribution is additive.

4.5.3 A high percentage of very fine fibers on the filter can significantly affect the standard deviation and confidence limits for counts by different counters. After combining variations in fiber concentrations over the entire filter with those for different counters, it was concluded:

a. For filters with a low concentration of fine fibers, the coefficient of variation is estimated at 21% and the 95% confidence interval is $\pm 43\%$.

b. For filters with a high concentration of fine fibers, the coefficient of variation is estimated at 25% and the 95% confidence interval is $\pm 50\%$.

Lynch, Kronoveter, and Leidel (11.1) have also reported on variations of the method. Their intralaboratory study utilized the data from a large number of dust counts made by different methods by experienced counters over a period of years in an epidemiologic study of the asbestos products industry. They concluded that the standard deviation of counts of fibers longer than 5 micrometers on membrane filters could be estimated from the relation $s = (N)^{0.21}$. Thus for counts of about 100 fibers, the coefficient of variation could be estimated at about 15.2% and the 95% confidence limits at $\pm 30.4\%$. These values are lower than the values reported by Conway and Holland (11.3).

Recently, the Johns-Manville Corporation conducted an in-house investigation of the asbestos count method (11.10). The study data contained total fiber counts for over

100 filters with each filter counted by two to five counters. From the Johns-Manville data, NIOSH calculated over 100 estimates of the count CV for the method (11.11). The NIOSH CV estimates included random intrafilter variations and intercounter variations, but did not include random pump flow rate variations. It was found that the count coefficient of variation (all random variations except for pump variations) was a function of the total fiber count. NIOSH then included a CV of 0.05 for random pump variations (see Section 9.1) in the CV-estimator equation to obtain a CV_T-estimator. The CV_T-estimator line is plotted on Figure 3 for total fiber counts in the range 10 to 100 fibers. Or the following equation can be used:

$$CV_T = [\text{antilog}_{10}(-0.215 - 0.203 (\log_{10} FB)) + 0.0025]^2$$

where FB is total fiber count as discussed in Section 10.

Figure 3 demonstrates that for a total fiber count of 100, the best CV_T is attainable with the appropriate sampling times given in 8.1.3 and the count rules in 8.3.9. When making decisions regarding compliance with the OSHA asbestos exposure standards in 29 CFR 1910.1001, the statistical procedures given in Leidel et al. (11.11) should be followed. The procedures are based on statistical theory and assumptions given in References 11.12, 11.13.

Because of the possibility of systematic biases due to differences between microscopes, counters, and laboratories as discussed above, it is strongly recommended that any laboratory counting asbestos should participate in an interlaboratory quality control program that includes the counting of standard reference filters. These standard filters are available from NIOSH through the Proficiency Analytical Testing (PAT) Program. The PAT Program is used by the American Industrial Hygiene Association (AIHA) as part of its Laboratory Accreditation Program. Each laboratory's quality control program must include protocols for routinely adjusting and calibrating sampling and counting equipment plus training and evaluation programs for counters.

5. Advantages and Disadvantages of the Method

- 5.1 The method is intended to give an index of employee exposure to airborne asbestos fibers of specified dimensional characteristics.
- 5.2 It is not meant to count all asbestos fibers in all size ranges or to differentiate asbestos from other fibrous particulates.

6. Apparatus

6.1 Sampling Equipment

The personal sampling equipment train consists of 1) personal sampling pump, 2) tubing, 3) clothing spring clip, 4) tubing-to-field monitor metal adaptor, and 5) field monitor (filter and holder).

- 6.1.1 Personal Sampling Pump. The pump must be capable of sampling at 1.0 to 2.5 liters per minute (lpm) against a flow resistance of 7.5 inches of water (1.4 cm H₂O) for 8 continuous hours on a fully charged battery.
- 6.1.2 Tubing. Laboratory tubing such as rubber or plastic with 6-mm bore and about 100 cm length.
- 6.1.3 Clothing Spring Clip. The clip attaches the rubber tubing to the lapel or shirt of the individual being monitored.
- 6.1.4 Tubing-to-field Monitor Adapter. A short metal adaptor with ridges on one end to grip the inside of the tubing. The other end is designed for a pressure fit into the field monitor.
- 6.1.5 Field Monitor (Filter and Holder). The only field monitor currently considered acceptable by NIOSH is manufactured by the Millipore Corporation. The unit con-

sists of 1) a three section styrene plastic case designated Millipore Aerosol Monitor Case, 2) a 37-mm diameter plain white cellulose ester membrane filter designated Millipore AA (pore size of 0.8 micrometer), 3) a support pad, and 4) two plastic sealing caps. If a large number of samples are to be taken, it may be less expensive to reuse the plastic cases. Great care must be taken in the cleaning and reassembly process. The outside mating surfaces of the field monitors may be covered with a "shrink-fit" band to provide proper sealing and a writing surface for filter identification.

6.2 Optical Equipment and Microscope Features

6.2.1 Microscope body with binocular head.

6.2.2 10X Huygenian eyepieces are recommended. Other eyepieces can be substituted if necessary. Wide field eyepieces can be used; however, wide field eyepieces may yield a count field area less than 0.003 mm² with the Porton reticle. This is not always desirable from the standpoint of obtaining optimum sampling times (see Section 8.1.3). If wide field eyepieces are used, it is preferable to use the Patterson Globe and Circle reticle to obtain a larger count field area.

6.2.3 Koehler illumination (preferably built-in with provisions for adjusting light intensity).

6.2.4 A Porton reticle is recommended. Others such as the Patterson Globe and Circle can be substituted.

6.2.5 Mechanical stage.

6.2.6 Phase-Contrast condenser with a numerical aperture (N.A.) equal to or greater than the N.A. of the objective.

6.2.7 40-45X phase contrast achromatic objective (N.A. 0.65 to 0.75).

6.2.8 Phase-ring centering telescope or Bertrand lens.

6.2.9 Green or blue filter, if recommended by microscope manufacturer.

6.2.10 Stage micrometer with 0.01 mm subdivisions.

6.2.11 For general guidance on phase contrast microscopy, consult Needham (11.12), Clark (11.15) and McCrone (11.14).

6.3 Filter Mounting Equipment. Experience has shown that certain equipment is useful for efficient sample mounting. The following items are recommended for extracting and mounting a portion of the filter for counting.

6.3.1 Microscope slides. 2.5 by 7.5 cm glass slides are most commonly used. Sample number, date, initials, etc., can be conveniently written on a frosted end slide.

6.3.2 Cover Slips. Cover slips are a necessary part of the slide mount and optical system. The shape should be appropriate for the size of the filter wedge. The appropriate cover slip depends upon the objective to be used. Ordinarily, objectives are optically corrected for a #1½ (0.17 millimeter) thickness cover slip. Improper cover glass thickness will detract from the final image quality.

6.3.3 Scalpel. A scalpel is needed to cut out a portion of the filter to be examined. A number-ten curved blade scalpel is recommended.

6.3.4 Tweezers. A pair of fine-tipped tweezers is used to remove the membrane filter slice from the field monitor and place it upon the slide.

6.3.5 Lens Tissue. To insure cleanliness, a lint-free tissue is recommended. This tissue should also be used for wiping mounting tools and for cleaning slides and cover slips.

6.3.6 Glass Rod. A fire-polished glass rod may be used to spread the mounting solution on the slide.

6.3.7 Wheaton Balsam Bottle. This special glass container has a glass top which prevents contamination of the mounting solution. A glass rod is included for dispensing the solution.

7. Reagents

Chemicals should be reagent grade, free from particles and color, conforming to the specifications of the Committee on Analytical Reagents of the American Chemical Society, where such specifications are available.

7.1 Dimethyl phthalate

7.2 Diethyl oxalate

Avoid getting the mounting solution on the skin. Wash skin promptly with soap and water if skin contact occurs.

8. Procedure

8.1 Sampling

8.1.1 General Information

Guidelines for the monitoring of employee exposures to industrial atmospheres are given in Reference 11.8. The Federal requirements for monitoring employee exposure to airborne asbestos are found in 29 CFR 1910.1001.

8.1.2 Mounting the Sampling Pump on the Worker

Fasten the sampling pump to the worker's belt and fasten the field monitor to the lapel or shirt front (as close to the breathing zone as is practical). Remove the top cover of the plastic monitor, then invert the monitor making certain the exposed filter is facing downward. Turn the pump on and adjust to the calibrated flow rate (1.0 to 2.5 lpm). Record the following information in a logbook.

1. Filter number
 2. Pump start time and date
 3. Flow rate
 4. Subject's name and job title
 5. Type of operation or process
 6. Ventilation controls and is the worker wearing a respirator approved for asbestos?
- The pump should be checked periodically during the sampling period for proper operation and flow rate.

8.1.3 Optimum Sampling Times

The requirement for the minimum count of 100 fibers or 20 fields in 8.3.9 was determined to be the best compromise to achieve adequate precision for the airborne fiber estimate and reasonable counting times. An optimum fiber density of about 1 to 5 fibers per microscope count field is recommended. To estimate appropriate sampling times for feasible counting and optimal counting, one must consider the following constraints:

1. microscope count field area (generally 0.003 to 0.006 mm²)
2. pump flow rate (typically 2.5 lpm maximum)
3. average airborne fiber concentrations
4. counting rule range of 20 to 100 fields
5. adequate fiber density to obtain a minimum count of 10 fibers in 100 fields, which is the least total fiber count that yields an acceptable count precision
6. background airborne particulate levels that can reduce the count precision due to an obscuring of fibers on the filter surface

The preceding constraints were considered in drawing Figures 1 and 2. These figures were developed from the following relationship:

$$\text{sampling time} = \frac{(\text{FB/FL}) (\text{ECA/MFA})}{(\text{FR}) (\text{AC}) (1000)} \text{ minutes}$$

where:

FB/FL = 1 to 5 fibers/field

ECA = effective collecting area of filters (855 mm² for 37-mm filter with effective diameter of 33 mm)

MFA = microscope field area (generally 0.003 to 0.006 mm²)

FR = Pump flow rate (generally 1.0 to 2.5 lpm)

AC = Air concentration of fibers in fibers/cm³.

Figure 1 (microscope field area = 0.003 mm²) and Figure 2 (microscope field area = 0.006 mm²) show optimum and feasible sampling times for a pump flow rate of 1.7 lpm. Each individual responsible for sampling asbestos should prepare a similar chart for his particular pump flow rate and microscope field area before sampling is performed to aid in estimating proper sampling times. On Figures 1 and 2, the areas with solid shading lines are generally the optimum conditions for counting. The broken shading lines are for conditions very close to optimal.

However, feasible counting conditions may extend down to about 0.1 fiber/field and and above 5 fibers/field. Recommended sampling times are most strongly influenced by background airborne particulate levels, once all the other constraints have been estimated. For heavy particulate levels, it may be necessary to limit each filter to about 60 to 180 minutes sampling duration. Each individual responsible for sampling should work closely with the microscopist to attain as high as possible filter surface fiber densities (up to about 5 fibers/field), while avoiding filter surface background particulate levels that create very difficult or impossible counting conditions. If one has very little idea of airborne fiber and particulate levels, the best procedure is to take several long samples (as one 8-hour or two consecutive 4-hour samples) in conjunction with several short samples (as four consecutive 2-hour or eight consecutive 1-hour samples). If the longer samples prove very difficult to count, the microscopist will have the shorter samples to fall back on.

From Figures 1 and 2, it can be seen that there are certain sampling times which will yield optimum fiber densities on the filter for almost all airborne fiber concentrations from 1 to 10 fibers/cm³. These optimum times have been calculated and are presented in Figure 4. Note that the optimum times given by Figure 4 are approximate and can be varied by as much as $\pm 25\%$. The nomogram is intended as a guide to be used where no prior knowledge of the air concentration is available.

8.1.4 End of Sampling Period

Remove the field monitor, replace the plastic top cover and the small end caps, and store the monitor. Always shut off the pump when changing monitors to avoid contaminating or damaging the pump. Record the pump shutoff time and flow rate in the logbook.

8.1.5 Blanks

With each batch (25 to 50 filters) of samples sent for analysis, submit two unopened field monitors which have been subjected to the same treatment as the samples except that they were not exposed to the sampling environment. Label these as blanks. If the blanks yield fiber counts greater than 5-fibers/100 fields, then the entire sampling procedure should be examined carefully for the cause of contamination. The

mounting solution of Section 8.2.1 should also be examined for contamination and/or crystal growth.

8.1.6 Shipping

The field monitors in which the samples are collected should be shipped in a rigid container with sufficient packing material to prevent crushing.

8.1.7 Numbers of Samples

When sampling for the Federal ceiling standard of 10 fibers ($>5\mu\text{m}$)/ cm^3 , [29 CFR 1910.1001(b) (3), effective July 7, 1972], only one sample (15 minutes maximum duration) is necessary, theoretically. However, several samples should be taken during expected periods of peak air concentrations to allow for detection of gross sampling or counting errors.

When sampling for determination of noncompliance with the Federal 8-hour TWA standard of 2 fibers ($>5\mu\text{m}$)/ cm^3 , [29 CFR 1910.1001(b) (2)], one should continuously sample as large a portion of the work day as is feasible for airborne concentrations of about 2 to 10 fibers/ cm^3 . However, for a lower airborne concentration such as 0.5 fiber/ cm^3 , one sample might require 4 to 8 hours sampling time in order to get the proper filter fiber density (Section 8.1.3). For this situation, the 8-hour TWA exposure would be determined from one 8-hour or two 4-hour samples as appropriate.

8.2 Sample Preparation

8.2.1 Preparation of Mounting Solution

A very important part of the sample evaluation is the mounting process. This process involves a special mounting medium of prescribed viscosity. The proper viscosity is important in order to expedite filter dissolving and still minimize particle migration. After the sample has been mounted, an elapsed time of approximately sixty minutes is needed before the sample is ready for evaluation.

Combine the dimethyl phthalate and diethyl oxalate in a one to one ratio by volume and pour into a Wheaton balsam bottle. Add approximately 0.05 (≈ 0.005) grams of new membrane filter per milliliter of solution to reach the necessary viscosity. The mixture must be stirred periodically until the filters have dissolved and a homogeneous mixture is formed. The normal shelf life of the mounting solution is about three months. Twenty milliliters of mounting solution will prepare approximately 300 samples.

8.2.2 Sample Mounting

Cleanliness is important! A dirty working area may result in sample contamination and erroneous counts. The following steps should be followed when mounting a sample.

1. Clean the slides and cover slips with lens tissue. Lay each slide down on a clean surface with the frosted end up. It is a good practice to rest one edge of the cover slip on the slide and the other edge on the working surface. By doing this, you keep the bottom surface (the one which contacts the filter) from becoming contaminated.
2. Wipe all the mounting tools clean with lens tissue and place them on a clean surface (such as lens tissue). All tools should be wiped clean prior to mounting each sample.
3. Using the glass rod supplied with the Wheaton balsam bottle, apply a drop of mounting solution onto the center of the slide. It may be necessary to adjust the quantity of solution so that after the cover slip has been placed on top, the solution extends only slightly beyond the filter boundary. If the quantity is greater than this, particle migration may occur.

4. Using another glass rod, spread the mounting media into a triangular shape. The size of this triangle should coincide with the dimension of the filter wedge.
5. Separate the middle and bottom sections of the field monitor case to expose the filter. Cut a triangular wedge from the center to the edge of the filter using the scalpel. The size of the wedge should approximate one-eighth of the filter surface. The filter can be very carefully removed from the cassette for cutting, but this should only be done with great care.
6. Grasp the filter wedge with the tweezers on the perimeter of the filter which was clamped between the monitor case sections. Do not touch the filter with your fingers. Place the wedge, sample side up, upon the mounting medium.
7. Pick up a clean cover slip with tweezers and carefully place it on the filter wedge. Once this contact has been made, do not reposition the cover slip.
8. Label the slide with the sample number and current date before proceeding to the next filter. On the bottom (backside) of the slide, trace the perimeter of the filter wedge with a felt tip marking pen. This will enable the counter, after the filter has become transparent, to stay within the filter perimeter when counting.
9. The sample should become transparent within fifteen minutes. If the filter appears cloudy, it may be necessary to press very lightly on the cover slip. This is rarely necessary; however, counting should not be started until an hour after the mounting. This allows the microscopic texture of the filter to become invisible to microscope viewing.
10. Discard the sample mount after two days if it has not been counted. Crystals appearing similar to asbestos fibers may begin to grow at the mounting media/air interfaces. They seldom present any problems if the slide is examined before two days. In any case, stay away from the filter's edges when counting and sizing.

3 Counting of Fibers

- 3.3.1 Place the slide on the mechanical stage of the microscope and position the center of the wedge under the objective lens and focus upon the sample. Start counting from one end of the wedge and progress along a radial line to the other end (count in either direction from perimeter to wedge tip). Random fields are selected, without looking into the eyepieces, by slightly advancing the slide in one direction with the mechanical stage control.
- 3.3.2 It is essential to continually scan over a range of focal planes (generally the upper 10 to 15 micrometers of the filter surface) with the fine focus control during each field count. This is especially necessary for asbestos fibers due to their impaction into the filter matrix.
- 3.3.3 On most airborne samples, asbestos fibers will generally have fiber diameters less than one micrometer. Therefore, it is necessary to look carefully for faint fiber images.
- 3.3.4 Regularly check phase ring alignment.
- 3.3.5 When an agglomerate (mass of material) covers a significant portion of the field of view (approx 1/6 or greater) reject the field and select another. (Do not include it in the number of fields counted.) However, report the fact as it may have meaning on other data collection.
- 3.3.6 Bundles of fibers are counted as one fiber unless both ends of the fiber can be clearly resolved.
- 3.3.7 Count only fibers with a length to width ratio greater than or equal to 3:1.
- 3.3.8 Count only fibers greater than 5 micrometers in length. (Do as accurate as possible in accepting fibers near this length.) Measure curved fibers along the curve to estimate the total length.

8.3.9 Count as many fields as necessary to yield a total count of at least 100 fibers. Exceptions: a) count at least 20 fields even if you count more than 100 fibers, and b) stop at 100 fields even if you haven't reached 100 fibers.

8.3.10 For fibers that cross either one or two sides of the counting field, the following procedure is used to obtain a representative count.

COUNT any fiber greater than 5 micrometers in length, that lies entirely within the counting area. COUNT as "½ fiber" any fiber with only one end lying within the counting area. DO NOT COUNT any fiber crossing any two sides.

Reject and do not count all other fibers. Refer to Figures 5 through 10. Note that the fibers in Figures 5 through 10 are not representative of the appearance of most asbestos fibers. Most fibers have a very faint image.

9. Calibration and Standards

9.1 Sampling Train Calibration

The accurate calibration of the sampling pump is essential to the correct calculation of the air volume sampled. The frequency of calibration is dependent on the use, care, and handling to which the pump is subjected. Pumps must be recalibrated if they have just been repaired, misused, or received from the manufacturer. If the pump receives hard usage, more frequent calibration may be necessary. Ordinarily, pumps should be calibrated in the laboratory both before they are used in the field and after they have been used to collect a large number of field samples.

The accuracy of calibration is dependent upon the type of instrument used as a reference. The choice of a calibration instrument will depend largely on where the calibration is performed. For laboratory testing, a 1-liter buret used as a soap bubble flow meter or wet-test meter is recommended. Other standard calibrating instruments, such as a spirometer, Mariott's bottle, or dry gas meter can be used. The calibration should be of sufficient precision that the 95% confidence limits on the flow rate are $\pm 10\%$ (95% of the flow rates will fall within $\pm 10\%$ of the calibrated value).

Instructions for calibration with the soap bubble flow meter follow. The sampling train used (pump, hose, filter cassette) in the pump calibration should be the same as the one used in the field.

9.1.1 Check the voltage of the pump battery with a voltmeter both with the pump off and while it is operating to assure adequate voltage for calibration. If necessary, charge the battery to manufacturer's specifications.

9.1.2 Fill a beaker with 10 ml of soap solution.

9.1.3 Connect the filter cassette inlet to the top of the buret with a length of hose.

9.1.4 Turn the pump on and moisten the inside of the soap bubble meter by immersing the open end of the buret into the soap solution and drawing bubbles up the inside of the buret. Perform this task until the bubbles are able to travel the entire length of the buret without breaking.

9.1.5 Adjust the pump rotameter to provide a flow between 1.5 to 2.5 lpm.

9.1.6 With a water manometer, check that the pressure drop across the filter is less than 13 inches of water (about 1 inch of mercury).

9.1.7 Start a soap bubble up the buret and measure the time it takes for the bubble to travel a minimum volume of 1 liter.

9.1.8 Repeat the procedure in 9.1.7 at least three times, average the results, and calculate the calibrated flow rate by dividing the volume traveled by the soap bubble by the elapsed time. If the range between the highest and lowest of the three flow rates is greater than about 0.33 lpm, then the calibration should be repeated since it is likely that the precision is not adequate.

9.1.9 Data required for the calibration include the volume measured, elapsed time, pressure drop, air temperature, atmospheric pressure (or elevation), pump serial number, date, and name of person performing the calibration.

9.1.10 Corrections to the flow rate for pumps with rotameters may be necessary if the pressure (elevation) or temperature where the samples are collected (actual flow rate) differs significantly from that where the calibration was performed (indicated flow rate). Actual flow rates at time of sampling may be calculated for a linear scale rotameter by using the following correction formula:

$$Q_{\text{actual}} = Q_{\text{indicated}} \sqrt{\frac{P_{\text{cal}}}{P_{\text{actual}}} \cdot \frac{T_{\text{actual}}}{T_{\text{cal}}}}$$

where both pressure (P) and temperature (T) are in absolute units such as:

psia = psig + 14.7
deg Rankin = deg Fahrenheit + 460
deg Kelvin = deg Celsius + 273

9.2 Microscope Setup

9.2.1 Porton Reticle and the Counting Field

The asbestos fiber count procedure consists of comparing fiber length to the diameters of calibrated circles of a Porton reticle, and counting all fibers greater than 5 micrometers in length lying within a given counting field area. The Porton reticle is a glass plate inscribed with a series of circles and rectangles. The left half of the reticle is divided into six rectangles constituting the counting field. The counting field is illustrated in Figures 5 through 10.

9.2.2 Placement in Eyepiece

The Porton reticle is placed inside the Huygenian eyepiece where it rests on the field-limiting diaphragm. If other types of eyepieces are used, it may be necessary to insert a counting collar for retaining the reticle. The reticle should always be kept clean, since dirt on the reticle is in focus and could complicate the counting and sizing process.

9.2.3 Stage Micrometer

The Porton reticle cannot be used for counting until it has been properly calibrated with a stage micrometer. Most stage micrometer scales are approximately two millimeters long and are divided into units of one-hundredth of a millimeter (ten micrometers).

9.2.4 Microscope Adjustment

When adjusting the microscope, follow the manufacturer's instructions while observing the following guidelines.

1. The light source image must be in focus and centered on the condenser iris or annular diaphragm.
2. The particulate material to be examined must be in focus.
3. The illuminator field iris must be in focus, centered on the sample, and opened only to the point where the field of view is illuminated.
4. The phase rings (annular diaphragm and phase-shifting elements) must be concentric.

9.2.5 Porton Reticle Calibration Procedure

Each eyepiece-objective-reticle combination on the microscope must be calibrated. Should any of the three be changed (disassembly, replacement, zoom adjustment, etc.), the combination must be recalibrated. Calibration may change if interpupillary dis-

tance is changed. For proper calibration, the following procedure should be followed closely.

With a 10X objective in place, place the stage micrometer on the mechanical stage, focus the millimeter scale, and center the image. Change to the 40-45X objective and adjust the first millimeter scale division to coincide with the left boundary of the Porton rectangle. Measure the distance between the left and extreme right boundaries of the Porton rectangle, estimating any portion of the final division. This measurement represents 200 L units. The rectangle is 100 L units on the short vertical dimension. The calculated "L" is inserted into the formula $D = L(2^N)^{1/2}$ where "N" is the circle number (indicated on the reticle) and "D" is the circle diameter. Since the circle diameters vary logarithmically, every other circle doubles in diameter. For example, circle number three is twice the diameter of number one; number four is twice the diameter of number two. When the circle sizes have been determined, the counting field area which consists of the left six smaller rectangles can be calculated from the relation $10,000 L^2$. This completes the reticle calibration for this specific objective-eyepiece-reticle combination.

Example for Porton Reticle

The following calibration was obtained for a pair of 10X Huygenian eyepieces and a 43X objective:

200 L = 0.148 mm = 148 micrometers

100 L = 0.074 mm = 74 micrometers

One L-unit = 0.74 micrometers

Thus Circle #1 has a diameter $D = L(2^N)^{1/2} = 0.74(2^1)^{1/2} = 0.74 (1.414) = 1.05$ micrometers.

Then our circle diameter calibration table looks like:

Diameter of Circle #1 = 1.05 micrometers

#2 = 1.48

#3 = 2.09

#4 = 2.96

#5 = 4.19

#6 = 5.92

Field area = $(10,000) (L^2) = (100 L) (100 L) = (0.074) (0.074) = 0.0055$ mm²

Thus fibers with a length greater than a distance halfway between the diameters of the #5 and #6 circles would be counted.

If a Patterson Globe and Circle reticle is used, a different calculation procedure is required. The circle diameters are related as follows. The #25 circle diameter is (0.1) (reticle length).

The circle diameters are proportional to the ratio of their numbers. Thus the #20 circle diameter is (20/25) or 0.8 times the #25 circle diameter.

10. Calculations

10.1 The average airborne asbestos fiber concentration estimated by the filter sample may be calculated from the following formula:

$$AC = \frac{[(FB/FL) - (BFB/BFL)] (ECA)}{(1000) (FR) (T) (MFA)}$$

where:

- AC = Airborne fiber concentration in (fibers > 5 μ m)/cm³.
BFB = Total number of fibers counted in the BFL fields of the blank or control filters in fibers > 5 μ m.
BFL = Total number of fields counted on the blank or control filters.
ECA = Effective collecting area of filter (855 mm² for a 37-mm filter with effective diameter of 33 mm).
FR = Pump flow rate in liters/min (lpm).
FB = Total number of fibers counted in the FL fields in fibers > 5 μ m.
FL = Total number of fields counted on the filter.
MFA = Microscope count field area in mm² (generally 0.003 to 0.006).
T = Sample collection time in minutes.

- 10.2 Recount criteria. It is very desirable for a counter to conduct a "blind recount" for about 1 in every 10 filter wedges (slides) counted. Alternatively, a second counter could perform the blind recount. In training sessions for novice counters, the trainee should conduct a blind recount for filter wedges counted by an experienced, proficient counter. In all cases, we will observe differences between the first and second counts of the same filter wedge. Most of these differences will be due to chance alone, that is, due to the random variability (precision) of the count method. Statistical recount criteria enable us to decide whether observed differences can reasonably be explained due to chance alone or are probably due to systematic differences between counters or microscopes or due to some other biasing factor. The following recount criterion is for a pair of counts that estimate some airborne fiber concentration (AC) in fibers/cm³. The criterion is given at the type-I error level. That is, there is a 5% maximum risk that we will reject a pair of counts for the reason that one might be biased, when the large observed difference is really due to chance. Reject a pair of counts because one might be biased if:

$$(AC_2 - AC_1) \text{ exceeds } 2.77(\overline{AC})(CV_{FB})$$

where:

- AC₁ = lower estimated airborne fiber concentration
AC₂ = higher estimated airborne fiber concentration
 $\overline{AC}$ = average of the two airborne concentration estimates
CV_{FB} = average CV for the two concentration estimates which are a function of the total fiber count (FB) in each case. Use the relation in Section 4 or Figure 3.

For a pair of counts on the same filter, reject the pair because one might be biased if:

$$(FB_2 - FB_1) \text{ exceeds } 2.77(\overline{FB})(CV_{FB})$$

where:

- FB₁ = lower fiber count on the filter (total fibers)
FB₂ = higher fiber count on the filter (total fibers)
 $\overline{FB}$ = average of the two total fiber counts
CV_{FB} = CV_T for the value FB. Use the relation in Section 4 or Figure 3.

1. References

- 11.1 Lynch, J. R., K. J. Kronoveter, and N. A. Leidel, "Validity of the Poisson Distribution in Dust Counting", unpublished.
11.2 Weidner, R. B. and H. E. Ayer, "Dust Exposure in Asbestos Processing", Transactions of the

- American Conference of Governmental Industrial Hygienists, May 1972, pp. 103-121, San Francisco, California.
- 11.3 Conway, R. E. and W. D. Holland, "Statistical Evaluation of the Procedure for Counting Asbestos Fibers on Membrane Filters", LFE Corporation, Richmond, California. Prepared for the Asbestos on Membrane Assoc/North America, New York, 1973.
 - 11.4 Leidel, N. A. and K. A. Busch, "An Evaluation of Phase Contrast Microscopes for Asbestos Counting", presented at the 1974 American Industrial Hygiene Conference, Miami Beach, Florida, May 18, 1974, unpublished.
 - 11.5 Beckett, S. T. and M. D. Attfield, "Inter-Laboratory Comparison of the Counting of Asbestos Fibers Sampled on Membrane Filters", Ann Occup Hyg 17:85-96, 1974.
 - 11.6 Rajhans, G. S. and G. M. Bragg, "A Statistical Analysis of Asbestos Fiber Counting in the Laboratory and Industrial Environment", Am Ind Hyg Assoc J 36(12):909-915, 1975.
 - 11.7 Leidel, N. A. and K. A. Busch, "Statistical Methods for the Determination of Noncompliance with Occupational Health Standards", NIOSH Technical Publication 75-159, 1975.
 - 11.8 Leidel, N. A., K. A. Busch, and J. R. Lynch, "Occupational Exposure Sampling Strategy Manual", NIOSH Technical Publication 77-173, 1977.
 - 11.9 Leidel, N. A., K. A. Busch, and W. E. Crouse, "Exposure Measurement: Action Level and Occupational Environmental Variability", NIOSH Technical Publication 76-131, 1975.
 - 11.10 Comments of the Johns-Manville Corporation with Respect to the Notice of Proposed Rule-making: Occupational Exposure to Asbestos, Federal Register, October 9, 1975. Submitted to the public record at the U. S. Department of Labor, Occupational Safety and Health Administration, April 1976.
 - 11.11 Leidel, N. A., S. G. Bayer, R. D. Zumwalde, and K. A. Busch, USPHS/NIOSH Membrane Filter Method for Evaluating Airborne Asbestos Fibers, to be published by NIOSH in 1977.
 - 11.12 Needham, G. H., The Practical Use of the Microscope, Charles C. Thomas Publishing Corporation, Springfield, Illinois, 1958.
 - 11.13 Clark, G. L., The Encyclopedia of Microscopy, Reinhold Publishing Corporation, New York, 1961.
 - 11.14 McCrone, W. C. and J. G. Dolly, I. The Particle Atlas, Edition Two, Ann Arbor Science Publishers, Inc., Ann Arbor, Michigan, 1973.




FIGURE 1. Optimum Sampling Times for airborne asbestos where microscopic field area = 0.003 mm²




FIGURE 2. Optimum sampling times for airborne asbestos where microscopic field area = 0.006 mm^2

239-17

Baron & Budd
Butler County
August 1, 1997




FIGURE 3. Total coefficient of variation as a function of total fiber count

239-18




FIGURE 4. Nomogram of optimum sampling times for airborne asbestos fibers in concentrations of 1 to 10 fibers/cm³

239-19




FIGURE 5




FIGURE 6




FIGURE 7




FIGURE 8




FIGURE 9




FIGURE 10

LIST OF FIGURES

(5 through 10)

FIGURE 5. DO NOT COUNT. Fiber crosses top and bottom sides.

FIGURE 6. COUNT. One fiber.

FIGURE 7. COUNT. One-half fiber. Fiber crosses left side and one end lies within count area.

FIGURE 8. COUNT. One-half fiber. Fiber crosses bottom side and one end lies within count area.

FIGURE 9. DO NOT COUNT. Fiber crosses two sides.

FIGURE 10. DO NOT COUNT. Fiber crosses two sides (bottom left corner).

COUNT. One-half fiber. Fiber crosses bottom side and one end lies within count area.

COUNT. One fiber (top right corner).

ATTACHMENT B
REPRESENTATIVE AMBIENT-AIR ASBESTOS CONCENTRATIONS

**Representative Ambient-Air
Asbestos Concentrations**

<u>Location</u>	<u>Fibers/cc</u>
New York	0
Washington	0.0022
Miami	0.0027
Cleveland	0.0067
Denver	0.0041
San Francisco	0.0038
Spokane	0.0154