

FILE NAME: Asbestos Cement Pipe and Sheet (ACPS)

DATE: 1986 Jan 21

DOC#: ACPS115

DOCUMENT DESCRIPTION: Memo RE J-M's Material Safety Data Sheets
with Several Revised Versions Attached

J-M Manufacturing Co., Inc.

Internal Correspondence

To : Ernie Pronske
From : E. E. Wang
Copies : Wilfred Wang, C.J. Chen, All Plant Managers
Subject : J-M's Material Safety Data Sheets

Date: January 21, 1986


To comply with the OSHA Hazard Communication Standard, I have revised our MSDS's. Enclosed please find five different MSDS's to be duplicated and distributed to our customers through J-M sales representatives. (Please duplicate copies as many as you need.)

Copies of those revised MSDS's should be provided to our customers/distributors with the next shipment of our products. This is required by law even when the customers/distributors have not requested our MSDS's.

E. E. Wang
EEW:rac

JAN 21 1986

J-MM_Hill_000712





U.S. DEPARTMENT OF LABOR
Occupational Safety and Health Administration

Form Approved
OMB No. 44-R1387

MATERIAL SAFETY DATA SHEET

Prepared By:
Dr. E.E. Wang

Required under USDL Safety and Health Regulations for Ship Repairing,
Shipbuilding, and Shipbreaking (29 CFR 1915, 1916, 1917)

Rev. 1-16-86

SECTION I

MANUFACTURER'S NAME

J-M A/C Pipe Corporation

EMERGENCY TELEPHONE NO.

(209) 982-1500

ADDRESS (Number, Street, City, State, and ZIP Code)
1051 Sperry Road, Stockton, CA 95206

CHEMICAL NAME AND SYNONYMS

Asbestos-Cement Pipe

TRADE NAME AND SYNONYMS

TRANSITE Pipe

CHEMICAL FAMILY

Mineral

FORMULA

N/A

SECTION II - HAZARDOUS INGREDIENTS

PAINTS, PRESERVATIVES, & SOLVENTS	%	TLV (Units)	ALLOYS AND METALLIC COATINGS	%	TLV (Units)
PIGMENTS	N/A		BASE METAL	N/A	
CATALYST	N/A		ALLOYS	N/A	
VEHICLE	N/A		METALLIC COATINGS	N/A	
SOLVENTS	N/A		FILLER METAL PLUS COATING OR CORE FLUX	N/A	
ADDITIVES	N/A		OTHERS	N/A	
OTHERS	N/A				
HAZARDOUS MIXTURES OF OTHER LIQUIDS, SOLIDS, OR GASES				%	TLV* (Units)
Asbestos [CAS #: 1332-21-4], A Carcinogen Determined By IARC				15	2f/cc
Silica [CAS #: 7631-86-9]				35	5mg/m ³
Portland Cement				50	15mg/m ³
* TLVs Refer To Airborne Concentrations Over 8-Hr TWA.					

SECTION III - PHYSICAL DATA

BOILING POINT (°F.)	N/A	SPECIFIC GRAVITY (H ₂ O=1)	1.85
VAPOR PRESSURE (mm Hg.)	N/A	PERCENT VOLATILE BY VOLUME (%)	N/A
VAPOR DENSITY (AIR=1)	N/A	EVAPORATION RATE (_____-1)	N/A
SOLUBILITY IN WATER	N/A		
APPEARANCE AND ODOR	Grayish-White Pipe; Odorless;		

SECTION IV - FIRE AND EXPLOSION HAZARD DATA


FLASH POINT (Method used)	N/A	FLAMMABLE LIMITS	N/A	Lel	Uel
EXTINGUISHING MEDIA	N/A				
SPECIAL FIRE FIGHTING PROCEDURES	N/A				
UNUSUAL FIRE AND EXPLOSION HAZARDS	None				

PAGE (1)

(Continued on reverse side)

Form OSHA-20
Rev. May 72

J-MM_Hill_001696



A/C Pipe

SECTION V - HEALTH HAZARD DATA	
THRESHOLD LIMIT VALUE Shown On First Page; Inhalation Of Excessive Silica May Cause Silicosis.	
EFFECTS OF OVEREXPOSURE Over-Exposure To Excessive Concentrations Of Airborne Asbestos Fibers May Cause Pulmonary Disease. Smoking Greatly Increases Risk From Asbestos Exposure.	
EMERGENCY AND FIRST AID PROCEDURES Inhalation: Move Person To Fresh Air. Eyes: Wash With Water For 15 Minutes. Skin: Clean Area Of Contact. Ingestion: Seek Medical Attention If Necessary.	

SECTION VI - REACTIVITY DATA			
STABILITY	UNSTABLE		CONDITIONS TO AVOID POWER Driven Saws With Abrasive Discs Should NOT Be Used For Dry Cutting Or
	STABLE		Beveling Asbestps-Cement Pipe. Always Avoid Creating And Breathing Dust.
INCOMPATIBILITY (Materials to avoid) None			
HAZARDOUS DECOMPOSITION PRODUCTS None			
HAZARDOUS POLYMERIZATION	MAY OCCUR		CONDITIONS TO AVOID
	WILL NOT OCCUR	X	N/A

SECTION VII - SPILL OR LEAK PROCEDURES	
STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED	
Pipe Fragments And Installation Debris Must Be Handled In A Manner Which Avoids Airborne Dispersion Of Asbestos Dust. Use Wet Or Vacuum Method For Clean-Up.	
WASTE DISPOSAL METHOD	
Comply With All Applicable Local, State, And Federal Regulations.	

SECTION VIII - SPECIAL PROTECTION INFORMATION			
RESPIRATORY PROTECTION (Specify type) Not Required When Recommended Work Practices Are Followed.			
VENTILATION	LOCAL EXHAUST	N/A	SPECIAL N/A
	MECHANICAL (General)	N/A	OTHER N/A
PROTECTIVE GLOVES Not Required		EYE PROTECTION Not Required	
OTHER PROTECTIVE EQUIPMENT Not Required When Recommended Work Practices Are Followed.			

SECTION IX - SPECIAL PRECAUTIONS	
PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING Follow "Recommended Work Practices For A/C Pipe" Published By A/C Pipe Producers Association.	
OTHER PRECAUTIONS All Tools Which May Release Asbestos Fibers In Excess Of The Exposure Limits Shall Be Provided With Local Exhaust Ventilation Systems.	

Note: This Information Is Given Without Warranty, Representation, Inducement Or
PAGE (2) License Of Any Kind, Except That It Is Accurate To The Best Of Our Knowledge
CPD 033-510 Or Obtained From Sources Believed By Us To Be Accurate, And We Do Not
Assume Any Legal Responsibility For Use Or Reliance Upon Same.