

Table Z-2

| Material                                        | 8-hour time weighted average | Acceptable ceiling concentration | Acceptable maximum peak above the acceptable ceiling concentration for an 8-hour shift. |                                                              |
|-------------------------------------------------|------------------------------|----------------------------------|-----------------------------------------------------------------------------------------|--------------------------------------------------------------|
|                                                 |                              |                                  | Concentration                                                                           | Maximum duration                                             |
| Benzene (Z37.4-1969) <sup>1</sup>               | 10 p.p.m.                    | 25 p.p.m.                        | 50 p.p.m.                                                                               | 10 minutes.                                                  |
| Beryllium and beryllium compounds (Z37.29-1970) | 2 µg./M <sup>3</sup>         | 5 µg./M <sup>3</sup>             | 25 µg./M <sup>3</sup>                                                                   | 30 minutes.                                                  |
| Cadmium dust (Z37.8-1970)                       | 0.2 mg./M <sup>3</sup>       | 0.5 mg./M <sup>3</sup>           |                                                                                         |                                                              |
| Cadmium fume (Z37.8-1970)                       | 0.1 mg./M <sup>3</sup>       | 0.3 mg./M <sup>3</sup>           |                                                                                         |                                                              |
| Carbon disulfide (Z37.3-1968)                   | 20 p.p.m.                    | 30 p.p.m.                        | 100 p.p.m.                                                                              | 30 minutes.                                                  |
| Carbon tetrachloride (Z37.17-1967)              | 10 p.p.m.                    | 25 p.p.m.                        | 200 p.p.m.                                                                              | 5 minutes in any 4 hours.                                    |
| Chromic acid and chromates (Z37.7-1971)         |                              | 1 mg./10M <sup>3</sup>           |                                                                                         |                                                              |
| Ethylene dibromide (Z37.31-1970)                | 20 p.p.m.                    | 30 p.p.m.                        | 80 p.p.m.                                                                               | 5 minutes.                                                   |
| Ethylene dichloride (Z37.21-1968)               | 50 p.p.m.                    | 100 p.p.m.                       | 200 p.p.m.                                                                              | 5 minutes in any 4 hours.                                    |
| Fluoride as dust (Z37.28-1969)                  | 2.5 mg./M <sup>3</sup>       |                                  |                                                                                         |                                                              |
| Formaldehyde (Z37.16-1967)                      | 3 p.p.m.                     | 5 p.p.m.                         | 10 p.p.m.                                                                               | 30 minutes.                                                  |
| Hydrogen fluoride (Z37.28-1969)                 | 3 p.p.m.                     |                                  |                                                                                         |                                                              |
| Hydrogen sulfide (Z37.2-1968)                   |                              | 20 p.p.m.                        | 50 p.p.m.                                                                               | 10 minutes once only if no other measurable exposure occurs. |
| Lead and its inorganic compounds (Z 37.11-1969) | 0.2 mg./m <sup>3</sup>       |                                  |                                                                                         |                                                              |
| Mercury (Z37.8-1971)                            |                              | 1 mg./10M <sup>3</sup>           |                                                                                         |                                                              |
| Methyl chloride (Z37.18-1969)                   | 100 p.p.m.                   | 200 p.p.m.                       | 300 p.p.m.                                                                              | 5 minutes in any 3 hours.                                    |
| Methylene Chloride (Z37.23-1969)                | 500 p.p.m.                   | 1,000 p.p.m.                     | 2,000 p.p.m.                                                                            | 5 minutes in any 2 hours.                                    |
| Organo (alkyl) mercury (Z37.30-1968)            | 0.01 mg./M <sup>3</sup>      | 0.04 mg./M <sup>3</sup>          |                                                                                         |                                                              |
| Styrene (Z37.15-1969)                           | 100 p.p.m.                   | 200 p.p.m.                       | 500 p.p.m.                                                                              | 5 minutes in any 3 hours.                                    |
| Tetrachloroethylene (Z37.22-1967)               | 100 p.p.m.                   | 200 p.p.m.                       | 300 p.p.m.                                                                              | 5 minutes in any 3 hours.                                    |
| Toluene (Z37.12-1967)                           | 200 p.p.m.                   | 300 p.p.m.                       | 500 p.p.m.                                                                              | 10 minutes.                                                  |
| Trichloroethylene (Z37.19-1967)                 | 100 p.p.m.                   | 200 p.p.m.                       | 300 p.p.m.                                                                              | 5 minutes in any 2 hours.                                    |

<sup>1</sup> Occupational exposures to benzene are subject to the requirements of Section 1910.1028 except as specifically exempted by Section 1910.1028(a)(2). Exposures exempted by Section 1910.1028(a)(2) are covered by this Section 1910.1000.

Table Z-3—Mineral Dusts

| Substance                                                                              | Mppcf <sup>a</sup>   | Mg/M <sup>3</sup>                           | Aerodynamic diameter (unit density sphere) | Percent passing selector |
|----------------------------------------------------------------------------------------|----------------------|---------------------------------------------|--------------------------------------------|--------------------------|
| Silica:                                                                                |                      |                                             | 2                                          | 90                       |
| Crystalline:                                                                           |                      |                                             | 2.5                                        | 75                       |
| Quartz (respirable).....                                                               | 250 <sup>c</sup>     | 10mg/M <sup>3</sup> =                       | 3.6                                        | 50                       |
|                                                                                        | %SiO <sub>2</sub> +5 | %SiO <sub>2</sub> +2                        | 5.0                                        | 25                       |
| Quartz (total dust).....                                                               |                      | 30mg/M <sup>3</sup>                         | 10                                         | 0                        |
|                                                                                        |                      | %SiO <sub>2</sub> +2                        |                                            |                          |
| Cristobalite: Use 1/5 the value calculated from the count or mass formulae for quartz. |                      |                                             |                                            |                          |
| Tridymite: Use 1/5 the value calculated from the formulae for quartz.                  |                      |                                             |                                            |                          |
| Amorphous, including natural diatomaceous earth.....                                   | 20                   | 80mg/M <sup>3</sup>                         |                                            |                          |
|                                                                                        |                      | %SiO <sub>2</sub>                           |                                            |                          |
| Silicates (less than 1% crystalline silica):                                           |                      |                                             |                                            |                          |
| Mica.....                                                                              | 20                   |                                             |                                            |                          |
| Soapstone.....                                                                         | 20                   |                                             |                                            |                          |
| Talc (non-asbestos form).....                                                          | 20 <sup>a</sup>      |                                             |                                            |                          |
| Talc (fibrous). Use asbestos limit.                                                    |                      |                                             |                                            |                          |
| Tremolite (see talc, fibrous).....                                                     |                      |                                             |                                            |                          |
| Portland cement.....                                                                   | 50                   |                                             |                                            |                          |
| Graphite (natural).....                                                                | 15                   |                                             |                                            |                          |
| Coal dust (respirable fraction less than 8% SiO <sub>2</sub> ).....                    |                      | 2.4mg/M <sup>3</sup> or 10mg/M <sup>3</sup> |                                            |                          |
| For more than 8% SiO <sub>2</sub> .....                                                |                      | %SiO <sub>2</sub> +2                        |                                            |                          |
| Inert or Nuisance Dust:                                                                |                      |                                             |                                            |                          |
| Respirable fraction.....                                                               | 15                   | 5mg/M <sup>3</sup>                          |                                            |                          |
| Total dust.....                                                                        | 50                   | 15mg/M <sup>3</sup>                         |                                            |                          |

Note: Conversion factors—  
mppcfX35.3 = million particles per cubic meter  
= particles per c.f.  
<sup>a</sup> Millions of particles per cubic foot of air, based on impinger samples counted by light-field techniques.  
<sup>b</sup> The percentage of crystalline silica in the formula is the amount determined from air-borne samples, except in those instances in which other methods have been shown to be applicable.  
<sup>c</sup> Both concentration and percent quartz for the application of this limit are to be determined from the fraction passing a size-selective with the following characteristics:  
• Containing < 1% quartz; if > 1% quartz, use quartz limit.

### § 1910.1000 Asbestos

(a) Definitions. For the purpose of this section, (1) "Asbestos" includes chrysotile, amosite, crocidolite, tremolite, anthophyllite, and actinolite.

(2) "Asbestos fibers" means asbestos fibers longer than 5 micrometers.

(b) Permissible exposure to airborne concentrations of asbestos fibers—(1) Standard effective July 7, 1972. The 8-hour time-weighted average airborne concentrations of asbestos fibers to which any employee may be exposed shall not exceed five fibers, longer than 5 micrometers, per cubic centimeter of air, as determined by the method prescribed in paragraph (c) of this section.

(2) Standard effective July 1, 1976. The 8-hour time-weighted average airborne concentrations of asbestos fibers to which any employee may be exposed shall not exceed two fibers, longer than 5 micrometers, per cubic centimeter of air, as determined by the method prescribed in paragraph (c) of this section.

(3) Ceiling concentration. No employee shall be exposed at any time to airborne concentrations of asbestos fibers in excess of 10 fibers, longer than 5 micrometers, per cubic centimeter of air, as determined by the method prescribed in paragraph (c) of this section.

(c) Methods of compliance—(1) Engineering methods. (i) Engineering controls. Engineering controls, such as, but not limited to, isolation, enclosure, exhaust ventilation, and dust collection, shall be used to meet the exposure limits prescribed in paragraph (b) of this section.

(ii) Local exhaust ventilation. (a) Local exhaust ventilation and dust collection systems shall be designed, constructed, installed, and maintained in accordance with the American National Standard ~~Handbook~~ Governing the Design and Operation of Local Exhaust Systems, ANSI Z9.2-1971, which is incorporated by reference herein.

(b) See § 1910.6 concerning the availability of ANSI Z9.2-1971, and the maintenance of a historic file in connection therewith. The address of the American National Standards Institute is given in § 1910.100.

(iii) Particular tools. All hand-operated and power-operated tools which may produce or release asbestos fibers in excess of the exposure limits prescribed in paragraph (b) of this section, such as, but not limited to, saws, scorers, abrasive wheels, and drills, shall be provided with local exhaust ventilation systems in accordance with subdivision (ii) of this subparagraph.

(2) Work practices—(i) Insofar as practicable, all handling, processing, or use of asbestos shall be done in a state such that the exposure limits prescribed in paragraph (b) of this section, unless the usefulness of the product would be diminished thereby.

(ii) Particular products and operations. No asbestos cement, mortar, coating, grout, plaster, or similar material containing asbestos shall be removed from bags, cartons, or other containers in which they are shipped, without being either wetted, or enclosed, or ventilated so as to prevent effectively the release of airborne asbestos fibers in excess of the limits prescribed in paragraph (b) of this section.

(iii) Special handling of asbestos. (1) Asbestos shall be removed from pipes, tanks, or other equipment or insulation only if the removal is provided with respiratory protection in accordance with paragraph (d)(2)(iii) of this section and with special clothing in accordance with paragraph (d)(3) of this section.

(d) Personal protective equipment—(1) Compliance with the exposure limits prescribed in paragraph (b) of this section may not be achieved by the use of respirators or shift rotation of employees, except:

(i) During the time period necessary to install the engineering controls and to institute the work practices required by paragraph (c) of this section;

(ii) In work situations in which the methods prescribed in paragraph (c) of

this section are either technically not feasible or feasible to an extent insufficient to reduce the airborne concentrations of asbestos fibers below the limits prescribed by paragraph (b) of this section; or

(iii) In emergencies.

(iv) Where both respirators and personnel rotation are allowed by subdivisions (i), (ii), or (iii) of this subparagraph, and both are practicable, personnel rotation shall be preferred and used.

(2) Where a respirator is permitted by subparagraph (1) of this paragraph, it shall be selected from among those approved by the Bureau of Mines, Department of the Interior, or the National Institute for Occupational Safety and Health, Department of Health, Education, and Welfare, under the provisions of 30 CFR Part 11 (37 F.R. 6244, Mar. 25, 1972), and shall be used in accordance with subdivisions (i), (ii), (iii), and (iv) of this subparagraph.

(i) Air purifying respirators. A reusable or single use air purifying respirator, or a respirator described in subdivision (ii) or (iii) of this subparagraph, shall be used to reduce the concentrations of airborne asbestos fibers in the respirator below the exposure limits prescribed in paragraph (b) of this section, when the ceiling or the 8-hour time-weighted average airborne concentrations of asbestos fibers are reasonably expected to exceed no more than 10 times those limits.

(ii) Powered air purifying respirators. A full facepiece powered air purifying respirator, or a powered air purifying respirator, or a respirator described in subdivision (iii) of this subparagraph, shall be used to reduce the concentrations of airborne asbestos fibers in the respirator below the exposure limits prescribed in paragraph (b) of this section, when the ceiling or the 8-hour time-weighted average concentrations of asbestos fibers are reasonably expected to exceed 10 times, but not 100 times, those limits.

(iii) Type "C" supplied-air respirators, continuous flow or pressure-demand class. A type "C" continuous flow or pressure-demand, supplied-air respirator shall be used to reduce the concentrations of airborne asbestos fibers in the respirator below the exposure limits prescribed in paragraph (b) of this section, when the ceiling or the 8-hour time-weighted average airborne concentrations of asbestos fibers are reasonably expected to exceed 100 times those limits.

(iv) Establishment of a respirator program. (a) The employer shall establish a respirator program in accordance with the requirements of the American National Standards Practices for Respiratory Protection, ANSI Z88.2-1969, which is incorporated by reference herein.

b. See § 1910.6 concerning the availability of ANSI Z88.2-1969 and the maintenance of an historic file in connection therewith. The address of the American National Standards Institute is given in § 1910.100.

(c) No employee shall be assigned to tasks requiring the use of respirators if, based upon his most recent examination, an examining physician determines that the employee will be unable to function normally wearing a respirator, or that

the safety or health of the employee or other employees will be impaired by his use of a respirator. Such employee shall be rotated to another job or given the opportunity to transfer to a different position whose duties he is able to perform with the same employer, in the same geographical area and with the same seniority, status, and rate of pay he had just prior to such transfer, if such a different position is available.

(3) Special clothing. ~~The employer shall provide, and require the use of, special clothing, such as coveralls or similar whole body clothing, head coverings, gloves, and foot coverings for any employee exposed to airborne concentrations of asbestos fibers, which exceed the ceiling level prescribed in paragraph (b) of this section.~~

(4) Change rooms. (i) At any fixed place of employment exposed to airborne concentrations of asbestos fibers in excess of the exposure limits prescribed in paragraph (b) of this section, the employer shall provide change rooms for employees working regularly at the place.

(ii) Clothes lockers. The employer shall provide two separate lockers or containers for each employee, so separated or isolated as to prevent contamination of the employee's street clothes from his work clothes.

(iii) Laundry. (a) Laundering of asbestos contaminated clothing shall be done so as to prevent the release of airborne asbestos fibers in excess of the exposure limits prescribed in paragraph (b) of this section.

(b) Any employer who gives asbestos-contaminated clothing to another person for laundering shall inform such person of the requirement in (a) of this subdivision to effectively prevent the release of airborne asbestos fibers in excess of the exposure limits prescribed in paragraph (b) of this section.

(c) Contaminated clothing shall be transported in sealed impermeable bags, or other closed, impermeable containers, and labeled in accordance with paragraph (g) of this section.

(e) Method of measurement. All determinations of airborne concentrations of asbestos fibers shall be made by the membrane filter method at 400-750 X (magnification) (4 millimeter objective) with phase contrast illumination.

(f) Monitoring. (1) Initial determination. Within 6 months of the publication of this section, every employer shall cause every place of employment where asbestos fibers are released to be monitored in such a way as to determine whether every employee's exposure to asbestos fibers is below the limits prescribed in paragraph (b) of this section. If the limits are exceeded, the employer shall immediately undertake a compliance program in accordance with paragraph (c) of this section.

(2) Personal monitoring. (i) Samples shall be collected from within the breathing zone of the employees, on membrane filters of 0.8 micrometer porosity mounted in an open-face filter holder. Samples shall be taken for the determination of the 8-hour time-weighted average airborne concentrations and of the ceiling concentrations of asbestos fibers.

(ii) Sampling frequency and patterns. After the initial determinations required by subparagraph (1) of this paragraph, samples shall be of such frequency and pattern as to represent with reasonable accuracy the levels of exposure of employees. In no case shall the sampling be done at intervals greater than 6 months for employees whose exposure to asbestos may reasonably be foreseen to exceed the limits prescribed by paragraph (b) of this section.

(3) Environmental monitoring. (i) samples shall be collected from areas of a work environment which are representative of the airborne concentrations of asbestos fibers which may reach the breathing zone of employees. Samples shall be collected on a membrane filter of 0.8 micrometer porosity mounted in an open-face filter holder. Samples shall be taken for the determination of the 8-hour time-weighted average airborne concentrations and of the ceiling concentrations of asbestos fibers.

(ii) Sampling frequency and patterns. After the initial determinations required by subparagraph (1) of this paragraph, samples shall be of such frequency and pattern as to represent with reasonable accuracy the levels of exposure of the employees. In no case shall sampling be at intervals greater than 6 months for employees whose exposures to asbestos may reasonably be foreseen to exceed the exposure limits prescribed in paragraph (b) of this section.

(4) Employee observation of monitoring. Affected employees, or their representatives, shall be given a reasonable opportunity to observe any monitoring required by this paragraph and shall have access to the records thereof.

(g) Caution signs and labels. (i) Caution signs. (ii) Posting. Caution signs shall be provided and displayed at each location where airborne concentrations of asbestos fibers may be in excess of the exposure limits prescribed in paragraph (b) of this section. Signs shall be posted at such a distance from such a location so that an employee may read the signs and take necessary protective steps before entering the area marked by the signs. Signs shall be posted at all approaches to areas containing excessive concentrations of airborne asbestos fibers.

(ii) Sign specifications. The warning signs required by subdivision (i) of this subparagraph shall conform to the requirements of 20" x 14" vertical format signs specified in § 1910.145(d) (4), and to this subdivision. The signs shall display the following legend in the lower panel, with letter sizes and styles of a visibility at least equal to that specified in this subdivision.

| Legend                                             |       | Notation                           |
|----------------------------------------------------|-------|------------------------------------|
| Asbestos                                           | ----- | 1" Sans Serif, Gothic, or Block.   |
| Dust Hazard                                        | ----- | 1/4" Sans Serif, Gothic, or Block. |
| Avoid Breathing Dust                               | ----- | 1/4" Gothic.                       |
| Wear Assigned Protective Equipment                 | ----- | 1/4" Gothic.                       |
| Do Not Remain In Area Unless Your Work Requires It | ----- | 1/4" Gothic.                       |

[Sec. 1910.1001(g)(1)(iii)]

## Legend

## Notation

Breathing Asbestos Dust- 14 point Gothic.  
May Be Hazardous To  
Your Health.

Spacing between lines shall be at least equal to the height of the upper of any two lines.

(2) **Caution labels**—(i) **Labeling.** Caution labels shall be affixed to all raw materials, mixtures, scrap, waste, debris, and other products containing asbestos fibers, or to their containers, except that no label is required where asbestos fibers have been modified by a bonding agent, coating, binder, or other material so that during any reasonably foreseeable use, handling, storage, disposal, processing, or transportation, no airborne concentrations of asbestos fibers in excess of the exposure limits prescribed in paragraph (b) of this section will be released.

(ii) **Label specifications.** The caution labels required by subdivision (i) of this subparagraph shall be printed in letters of sufficient size and contrast as to be readily visible and legible. The label shall state:

## CAUTION

Contains Asbestos Fibers

Avoid Creating Dust

Breathing Asbestos Dust May Cause  
Serious Bodily Harm

(h) **Housekeeping**—(1) **Cleaning.** All external surfaces in any place of employment shall be maintained free of accumulations of asbestos fibers if, with their dispersion, there would be an excessive concentration.

(2) **Waste disposal.** Asbestos waste, scrap, debris, bags, containers, equipment, and asbestos-contaminated clothing, consigned for disposal, which may produce in any reasonably foreseeable use, handling, storage, processing, disposal, or transportation airborne concentrations of asbestos fibers in excess of the exposure limits prescribed in paragraph (b) of this section shall be collected and disposed of in sealed impermeable bags, or other closed, impermeable containers.

(i) **Recordkeeping**—(1) **Exposure records.** Every employer shall maintain records of any personal or environmental monitoring required by this section. Records shall be maintained for a period of at least 20 years and shall be made available upon request to the Assistant Secretary of Labor for Occupational Safety and Health, the Director of the National Institute for Occupational Safety and Health, and to authorized representatives of either.

[1910.1001(i)(1) amended at 41 FR 11505, March 19, 1976]

(2) **Access.** Employee exposure records required by this paragraph shall be provided upon request to employees, designated representatives, and the Assistant Secretary in accordance with 29 CFR 1910.20 (a)-(c) and (g)-(i). [Section 1910.1001(i)(2) amended at 45 FR 35212, May 23, 1980, effective August 21, 1980]

**Notification.** After an employee is exposed to asbestos in excess of the limits prescribed in paragraph (b) of this section, the employer shall be notified in writing of the exposure as soon as practicable but not later than 5 days of the finding. The employee shall be notified of the corrective action being taken.

sure as soon as practicable but not later than 5 days of the finding. The employee shall be notified of the corrective action being taken.

(j) **Medical examinations**—(1) **General.** The employer shall provide or make available at his cost, medical examinations relative to exposure to asbestos required by this paragraph.

(2) **Maintenance.** The employer shall provide or make available to each of his employees, within 30 calendar days following his first employment in an occupation exposed to airborne concentrations of asbestos fibers, a comprehensive medical examination, which shall include, as a minimum, a chest roentgenogram (posterior-anterior 14 x 17 inches), a history to elicit symptomatology of respiratory disease, and pulmonary function tests to include forced vital capacity (FVC) and forced expiratory volume at 1 second (FEV<sub>1</sub>).

(3) **Annual examinations.** On or before January 31, 1973, and at least annually thereafter, every employer shall provide or make available, comprehensive medical examinations to each of his employees engaged in occupations exposed to airborne concentrations of asbestos fibers in excess of the limits prescribed in paragraph (b) of this section. The examinations shall include, as a minimum, a chest roentgenogram (posterior-anterior 14 x 17 inches), a history to elicit symptomatology of respiratory disease, and pulmonary function tests to include forced vital capacity (FVC) and forced expiratory volume at 1 second (FEV<sub>1</sub>).

(4) **Termination of employment.** The employer shall provide, or make available, within 30 calendar days before or after the termination of employment of any employee engaged in an occupation exposed to airborne concentrations of asbestos fibers, a comprehensive medical examination which shall include, as a minimum, a chest roentgenogram (posterior-anterior 14 x 17 inches), a history to elicit symptomatology of respiratory disease, and pulmonary function tests to include forced vital capacity (FVC) and forced expiratory volume at 1 second (FEV<sub>1</sub>).

(5) **Record examinations.** If a medical examination is required of any employee, if adequate records show that the employee has been examined in accordance with this paragraph within the past 1-year period.

(6) **Medical records**—(1) **Maintenance.** Employers of employees examined pursuant to this paragraph shall cause to be maintained complete and accurate records of all such medical examinations. Records shall be retained by employers for at least 20 years.

(ii) **Access.** Records of the medical examinations required by this paragraph shall be provided upon request to employees, designated representatives, and the Assistant Secretary in accordance with 29 CFR 1910.20(a)-(c) and (g)-(i). These records shall also be provided upon the request to the Director of NIOSH. Any physician who conducts a medical examination required by this paragraph shall furnish to the employer of the examined employee all the information specifically required by this paragraph, and any other

medical information related to occupational exposure to asbestos fibers.

[Section 1910.1001(j)(6)(ii) amended at 45 FR 35212, May 23, 1980, effective August 21, 1980; corrected by 45 FR 54333, August 15, 1980]

§ 1910.1002 Coal tar pitch volatiles; interpretation of term.

As used in Sec. 1910.1000 (Table Z-1), coal tar pitch volatiles include the fused polycyclic hydrocarbons which volatilize from the distillation residues of coal, petroleum, wood, and other organic matter.

§ 1910.1003 4-Nitrobiphenyl.

(a) **Scope and application.** (1) This section applies to any area in which 4-Nitrobiphenyl, Chemical Abstracts Service Registry Number 92933 is manufactured, processed, repackaged, released, handled, or stored, but shall not apply to transshipment in sealed containers, except for the labeling requirements under paragraphs (e) (2), (3), and (4) of this section.

(2) This section shall not apply to solid or liquid mixtures containing less than 0.1 percent by weight or volume of 4-Nitrobiphenyl.

(b) **Definitions.** For the purposes of this section: (1) "Absolute filter" is one capable of retaining 99.97 percent of a mono disperse aerosol of 0.3  $\mu$ m particles.

(2) "Authorized employee" means an employee whose duties require him to be in the regulated area and who has been specifically assigned by the employer.

(3) "Clean change room" means a room where employees put on clean clothing and/or protective equipment in an environment free of 4-Nitrobiphenyl. The clean change room shall be contiguous to and have an entry from a shower room, when the shower room facilities are otherwise required in this section.

(4) "Closed system" means an operation involving 4-Nitrobiphenyl where containment prevents the release of 4-Nitrobiphenyl into regulated areas, non-regulated areas, or the external environment.

(5) "Decontamination" means the inactivation of 4-Nitrobiphenyl or its safe disposal.

(6) "Director" means the Director, National Institute for Occupational Safety and Health, or any person directed by him or the Secretary of Health, Education, and Welfare to act for the Director.

(7) "Disposal" means the safe removal of 4-Nitrobiphenyl from the work environment.

(8) "Emergency" means an unforeseen circumstance or set of circumstances resulting in the release of 4-Nitrobiphenyl which may result in exposure to or contact with 4-Nitrobiphenyl.

(9) "External environment" means any environment external to regulated and nonregulated areas.

(10) "Isolated system" means a fully enclosed structure other than the vessel of containment of 4-Nitrobiphenyl.

[Sec. 1910.1003(b)(10)]

60

Occupational Safety & Health Reporter