

HOFFMAN "PANELMATIC" HOT WATER SYSTEM CONTROLS



Designed for all Types of Radiant Heating

The Hoffman method vastly improves the ordinary forced hot water system by the application of *Continuous Circulation*. This method permits a smoothly modulated regulation of the heat supply. The Control Valve closes and the circulating stream by-passes the boiler as long as the heat requirements are satisfied.

When the circulating water begins to lose heat, the Control Valve is slowly opened by the Controller, permitting hot boiler water to enter the system. Thus, the delicate precision of the Hoffman Controller smoothly varies the temperature of the *continuously circulating* water so

that the heat supply is always equalized with the heat loss and room temperature remains constant throughout all changes in the weather.

There is no type of building to which Hoffman Hot Water Controlled Heat cannot be applied. The system permits *zoning* of apartments, institutions, large residences and factories, thereby assuring a distribution of heat in direct relation to either personal temperature preference or to the functional activities of the building.

**HEATING COMFORT IS ACHIEVED BY THESE SIX HOFFMAN SPECIALTIES****The Panelmatic Controller**

The brain of the Hoffman system. It automatically maintains a constant comfort condition regardless of the outdoor temperature. Its accurate balancing mechanism electrically opens or closes the Hoffman Hot Water Control Valve as required.

Outdoor Temperature Anticipating Bulb

This Bulb transmits changes in the outdoor temperature to the balancing mechanism of the Comfort Controller.

Hot Water Temperature Bulb

Accurately relays temperature changes of the supply main water to the balancing mechanism of the Hoffman Comfort Controller.

Hoffman Circulator

A centrifugal pump of prescribed capacity and low in power consumption. Usually installed in the return main and continuously circulates the water through the system. Continuous operation puts less strain and wear on the pump motor than intermittent operation as any engineer will attest.

1390

**Hot Water Control Valve**

Opens only sufficiently to supply the correct amount of water to maintain the proper water temperature being circulated through the system.

Thermometer. Should be installed about 6 in. from submerged Water Temp. Bulb.


Balancing Orifice

A calibrated orifice used to balance the circuits through the boiler and through the Hoffman circulating pipe.

HOFFMAN PANEL-FLO VALVES


for adjusting the flow of water through individual Panel Heating Coils

Gives a wide range adjustment of water flow to each coil without affecting the heat output of the other coils—can cut flow through coil as much as 80 per cent. . . WITH NO APPRECIABLE CHANGE IN CIRCULATING PUMP HEAD. Has indicating Dial for accurate setting of each coil—or adjusting any coil without affecting the other coils. 1/2 in. pipe connection.

**HOFFMAN INVERTED BUCKET TRAPS**

Working Pressures to 200 lbs


Simple mechanism assures high operating efficiency. Features include—straight-through pipe connection; simple seat adjustment; all working parts connected to bonnet and easily removed with it; stainless steel seat and pin.




Series 600

Series 710 Max. Press. 250 psi., Low Press. 5 to 80 psi.
Series 700 Max. Press. 200 psi., Low Press. 1 to 25 psi.

Choice of types specifically engineered for your needs—continuous service, or, for tight sealing against low pressure side when there is no demand—and with typical Hoffman features of design.



Series 710

HOFFMAN PRESSURE REDUCING VALVES



Series 1100

HOFFMAN TEMPERATURE REGULATORS

Series 1100—for steam pressure to 150 lb per sq in. Standard temperature range—80 F to 250 F. Other ranges available on special order. Self-motivated. Hydraulically formed bellows of selected material. Rugged construction. For water heaters, convectors, fuel oil preheaters and other similar applications.

HOFFMAN "ZONET" ZONE CONTROL


Series 1200—Zonet systems or packages for Steam and Hot Water consist of heat anticipating Room Thermostat, motor operated Globe Type Valve, Transformer, Fuse Block and fuse, and in the case of steam zoning, a Vacuum Breaker. The motor operated, two position, single seated, packed globe type Valve (illustrated) is available in sizes from 1/2 in. to 6 in. Maximum service pressure: steam 100 lbs per sq in., water 150 lbs per sq in.



Hoffman Room Thermostat

HOFFMAN ELECTRIC CONTROLS

Hoffman offers a comprehensive selection of fine quality electric controls for steam, hot water and warm air heating systems. These controls are especially suited for use with other famous Hoffman heating system specialties and provide one source of supply and one responsibility for satisfactory performance. Illustrated are two popular control units, typical of the complete Hoffman line.



Hot Water Limit Control Immersion Type

1391