

SMU 9806 white 160

P001R71 BF GOODRICH COMPANY MESSAGE SERVICE 12:53:49
FROM: P103R360 TO: ALTCRM DOCUMENT: 090020 88 LINES 03/09/92

ROUTE TO: DIXON, PAM K.

* GEON VINYL RESTRICTED / TECHNICAL DOCUMENT *

CUSTOMER NO / DESC: IBM/LEXMARK

R10 50 GEON VINYL RECIPE 03/09/92 12:53:33

EXP 165 047 137 01 PLT OSHA WARNING LABEL: A
COMMODITY NO.: X1650 471 3701 LOC: 12 DEPT: 5697 ISSUE: 002
SBC NBR: 13ED EFFECTIVE DATE: 03/09/92
LAB REF: 165-47-137-1 DELETE FLAG: NO
BASED ON: EXP 165 047 137 01 PLT, ISSUE 1, 3/4/92 CMPR: M. BALASKO
APPLICATION: KEYBOARD SPACE BAR - SUPER FAST STATIC DECAY

PARTS	INGREDIENTS	SEQ	LOC	PERCENT
100.00000	961 000452 110 X 377	110	12	69.259
20.00000	949 711642 PEBAX MX 1074	120		13.852
3.00000	941 710700 2301 X 36	210		2.078
5.00000	942 710859 BLENDEX 338	220		3.463
2.50000	912 00S086 MARK 1900	310		1.731
5.00000	925 710356 ULTRAFLEX H	610		3.463
4.50000	924 00B123 TI-PURE R-100	620		3.117
.19600	921 00B300 YELLOW V-9118	710		.136
.05000	921 00B296 BROWN #7739	720		.035
.14000	961 000405 87333-000-2102	730		.097
2.00000	943 00L034 CA STEARATE-FUSED	810		1.385
2.00000	943 00L037 WAX E	820		1.385

BFG16507

144.38600 TOTAL 100.000
6-34 Calcium Stearate (1592-23-0) 177.2600; 178.2010; 181.29
B300-USE TXC D RESP, AD VENT
B296-USE TXC D RESP, AD VENT
4-37 Ester of Norton Wax w/ Polyphric 172.886; 178.3770
SPECIFIC GRAVITY: 1.34 HARDNESS: D-75
TYPE SAMPLE: COLOR: 0
ISSUED: TO ADD PAGE 2
MARKETING APPROVAL: R. KROCK

MISC CMNT: DESIGN REQUEST #310
TYPE SAMPLE TAKEN FROM 1ST RUN

452: PVC Resin
(Cas. No. 9002-86-2)

711642: PEBAX MX 1074

710700: Styrene/Acrylonitrile
(Cas. No. 9003-54-7)

710859: ABS Polymer
(Cas. No. 9003-56-9)

S-86: Dimethyl Tin-2-ethylhexyl
thiodiolate (Cas. No. 57583-35-4)

710356: Calcium Carbonate
(Cas. No. 471-34-1)

B-123: Titanium Dioxide
(Cas. No. 13463-67-7)

B-300 V-9118 Bright Golden Yellow

B-296 Chrome Yellow
(Cas. No. 71450-83-9)

87333-000-2102: PVC Resin
(9002-86-2)
Calcium Carbonate
(471-34-1)

Carbon Black
(1333-)

FDA Status
Prior Sanction

None (per attachment)

175.105; 175.300; 175.320; 175.180;
177.1200; 177.1210; 181.32

181.32; 177.2600

None (per attachment)

175.300; 175.390; 177.240; 177.1350;
177.1460; 177.1600; 181.29; 182.90; 182.517;
175.300; 177.2600

None

None
Prior Sanction

175.300; 175.290; 177.120; 177.1350;
177.1350; 177.1460; 177.1600; 181.29;
184.1171

177.2400; 177.2600

21782001