

SECTION VII - Precautions for Safe Handling and Use**Steps to Be Taken in Case Material is Released or Spilled**

Grinding, drilling, milling, etc. can result in the release of airborne dust. Measures as outlined in Section VIII should be followed if this occurs.

Waste Disposal Method

Hazardous ingredients: 40 CFR, Part 261, 262 and applicable State and Local regulations.

Other Precautions

Pre-employment screening for allergies and histories of skin sensitivities may be beneficial in determining persons sensitive to cashew materials.

SECTION VIII - Control Measures

Respiratory Protection (Specify Type) NIOSH approved for pneumoconiosis - fibrosis producing dusts and dusts with TLV not less than 0.05 mg/M³.

Ventilation	Local Exhaust	For dust exposures exceeding TLV.
	Mechanical (General)	Not recommended for dust exposures.
	Special	NK
	Other	Barrier creams for persons with skin sensitive to cashew resins and fiber glass.

Protective Gloves
Recommended.

Eye Protection
Should not be needed for normal handling of product. Eye protection is good practice where dust is propelled by grinding or drilling activities.

Other Protective Clothing or Equipment
Long sleeved shirts or other protective clothing may be beneficial to prevent skin contact of persons sensitive to cashew resins and fiber glass.

Work/Hygienic Practices
Employees should be properly instructed in the use of control measures as indicated above when there is a need for it. If dust from this product is produced, unnecessary exposures should be avoided by using a vacuum in place of dry brooming. Use wet method of cleaning for other surfaces. Proper and adequate personal hygiene should be practiced by exposed workers.

NA - Not Available

NK - Not Known

Warner SBC-25-000054

Form #4