



PAYNE FURNACE COMPANY
(One of the Dresser Industries)
BEVERLY HILLS, CALIFORNIA

PAYNEHEAT
OVER 30 YEARS OF LEADERSHIP



**MODEL "AS" UNIT-TYPE
WARM AIR FURNACE**

Gravity-type circulating unit for space-saving basement installation. Can be used as single unit or in multiples for zoned heating. Six standard sizes; A.G.A. input rating, 30,000 to 180,000 Btu's. Grey, metallized enamel finish.




"SPACESAVER" UNIT

Horizontal, forced air heating system for attic, subfloor or ceiling installation in basement-less homes, shops or industrial plants. All-welded heating element of heavy gauge, die-formed steel. Two sizes: A.G.A. input rating, 75,000 to 100,000 Btu's.


PAYNE FURNACE COMPANY has always specialized in *gas-fired* furnaces. Eight salient points characterize the complete PAYNE "line":

1. 69 A.G.A.-approved styles and sizes.
2. Each unit fully vented.
3. Can use natural, manufactured or LP gas.
4. Adaptable to "Zone-Conditioning" (control by zones or rooms).
5. First-class materials; sound, advanced engineering; rugged construction; long life.
6. Compact, light-weight, attractive, modern designs.
7. Ample filter area in forced air models assures thorough air-cleansing.
8. No gas leakage.



PAYNE "CB" COMMERCIAL BLOWER UNIT

Compactly built commercial blower furnace for theatres, buildings and industrial plants, providing large volume of air at high velocity, with minimum fuel consumption. One-piece combustion chamber and radiator are of heavy gauge, die-formed steel, all-welded construction, preventing gas escape; ideal for high-pressure system. Entire radiation surface is exposed to air-currents traveling at high velocity with rapid heat transfer from element to air stream. "CB" Furnaces may be installed individually or in batteries to provide any capacity up to 1,680,000 Btu input. Shipped completely assembled except for supports and controls. A.G.A.-approved with limit control, current-breaking type, operating on current failure valve and automatic pilot.



**PAYNE FLOOR
FURNACE**

Heavy, cold-rolled, rounded edge steel grille, with wide margin for close floor-fit. (See other details at right, above.)



CONSOLE HEATER

Attractively finished to harmonize with any furnishings or decorative scheme.

FLOOR FURNACE (left) made in eight A.G.A.-approved sizes, shipped completely assembled. Deep-drawing steel heating element, heavy gauge for both combustion chambers and radiators. Single burner is first-quality casting, precision-machined with venturi tube and adjustable primary air shutter. Inner casing is suspended to allow for contraction and expansion. A.G.A. Btu input ratings: 15,000 to 75,000.

PAYNE DUPLEX REGISTER FURNACE (right) includes all Floor Furnace features, plus scientifically-designed register head for heating two rooms or suites from both sides of wall. A.G.A. input ratings: 25,000 to 50,000 Btu's.


PAYNE CONSOLE HEATER (left) Fully-vented, A.G.A.-approved heater for use with natural, manufactured or LP gas. Heavy-gauge heating element with special inner baffles for longer fire-travel and uniform heat distribution. Insulated air passages control cabinet temperature; undershield protects floor. Six sizes: Btu input rating, 15,000 to 60,000.

SENTRY FORCED AIR UNIT (right)—Compact forced air unit for basement-less installations. Fits in any nook or corner. All-welded heating element of deep-drawing steel. All moving parts mounted on rubber blocks. Four sizes with Btu input rating, 60,000 to 160,000. Designed for up-discharge only. (Inquire about the ZONEAIR Forced Air Unit for basement installations.)


PAYNE "AA" VENT—Inner tube of aluminum is surrounded by outer galvanized casing with controlled air space between. Patented. Prevents condensation of water vapor in products of combustion as well as over-heating of outside casing. Quickly installed. Sizes: 3 in. to 6 in.

PAYNE ZONE-CONDITIONING—Time-tested PAYNE "Unit" heating,

PAYNEHEAT
OVER 30 YEARS OF LEADERSHIP



DUPLEX FURNACE



**PAYNE
"SENTRY"
UNIT**

using two or more units, controlled by zones or individual rooms. Many advantages over "central" heating. Write for special booklet.

IMPORTANT—Complete catalog sheets and specifications on these and other PAYNE Furnaces available on request. Please specify type, heating value and specific gravity of gas.