October 4, 1967

Mr. Winn Morris
Tenneco Manufacturing Company
P. O. Box 849
Pasadena, Texas 77501

Dear Mr. Morris:

Our Mr. Tom White has asked me to forward toxicity information for our compressor lubricant Pydraul AC. A summary of the toxicity information may be stated as follows:,

> In animal toxicity studies with Pydraul AC, the oral lethal dose in rats is approximately 40 grams per kilogram and for rabbits, 3.5 to 4.5 grams per kilogram. The greater sensitivity of rabbits is typical of this type of fluid. This lethal dose is of such an order, however, that the fluid may be considered only "slightly toxic" to man from oral doses. The fluid may be absorbed through the unbroken skin of rabbits in doses resulting such that accidental massive skin exposures to man do not present a hazard. Skin and eye irritation studies with rabbits classify the fluid as a mild irritant. Laboratory animals survived six-hour exposures to an atmosphere saturated with the vapors of the fluid. On the basis of this data, it is concluded that Pydraul AC requires no special handling precautions other than avoiding prolonged or repeated skin contact. Accidental splashing in the eyes will result in moderately severe pain and irritation but no permanent damage should result.

I am not sure what your particular application may be that raises the question of toxicity. We have run some rather limited tests on a particular compressor where the air downstream showed no detectable levels of the lubricant nor any decomposition products. It must be pointed out, however, that there are many factors which could affect the

DSW 018753

STLCOPCB4005297

amount, if any, of any lubricant in the compressed air. Some of these include the mechanical condition of the compressor, temperature of compressor cylinder walls, variations in operation, etc. If there were any thermal decomposition, we would expect to find HCl, CO, CO_2, phenols, aldehydes, etc. depending on the degree of decomposition.

It appears appropriate to us that, regardless of the type of lubricant, if the air is to be used for breathing purposes, a filter should be placed in the line to remove not only any possible lubricant, but moisture, rust and any other possible contaminants.

If I can be of any further service, please do not hesitate to let me know.

Very truly yours,

R. Emmet Kelly, M.D.
Medical Director

REK:cjs:EPW

cc: Mr. Charles Crain, Area Superintendent - Tenneco Ammonia Plant

Mr. Randy Nichols, Process Eng. - Tenneco

Mr. Tom White - "C" Bldg.

DSW 018754

STLCOPCB4005298