

Attachment
A

VINYL CHLORIDE

**DANGER! EXTREMELY FLAMMABLE LIQUID AND GAS
UNDER PRESSURE
HARMFUL IF INHALED**

**MAY POLYMERIZE VIOLENTLY UNDER FIRE
CONDITIONS OR LOSS OR REMOVAL
OF INHIBITOR**

Keep away from heat, sparks, and open flame.

Keep container closed.

Use with adequate ventilation.

Avoid breathing vapor.

Avoid contact with skin.

Keep cylinder out of sun and away from heat.

Container should be grounded when being emptied.

Never drop cylinder.

FIRST AID: If inhaled, remove to fresh air. If not breathing give artificial respiration, preferably mouth-to-mouth. If breathing is difficult, give oxygen. Call a physician.

In case of:

Fire — Use water spray, dry chemical, or CO₂.

Spill or Leak — For small spills, evacuate area and permit to evaporate. For large spills or leaks, evacuate area. Dike or flush to ground and let evaporate. Do not flush to sewer because of explosion hazard.

RNW 1992

BAG CODE 0000X

NET 50.0 LBS. 22.7 KG
GROSS 61.0 LBS. 27.1 KG

UNION CARBIDE CORPORATION
CHEMICALS AND PLASTICS
NEW YORK, NEW YORK 10027
U.S. PAT. & TM. OFF.



SOLVENT
Vinyl
FOR INDUSTRY USE ONLY



SOLVENT
Vinyl

SOLVENT
Vinyl



Plate AS

YEAR OF USE 1973 - 1976

NET 50.0 LBS. 22.7 KG
GROSS 61.0 LBS. 27.1 KG


UNION CARBIDE CORPORATION
CHEMICALS AND PLASTICS
NEW YORK, NEW YORK 10027
U.S. PAT. & TM. OFF.

SOLVENT
Vinyl
FOR INDUSTRY USE ONLY



SOLVENT
Vinyl

SOLVENT
Vinyl



7-23-76

BAG CODE 0000X

NET 22.7 KG. 50.0 LBS.

UNION CARBIDE CORPORATION
CHEMICALS AND PLASTICS
NEW YORK, NEW YORK 10007
U.S. PAT. 2,811,111



SOLVENT
Vinyl
FOR INDUSTRY USE ONLY



SOLVENT
Vinyl

SOLVENT
Vinyl



PLATE CB 11

NET 22.7 KG. 50.0 LBS.

UNION CARBIDE CORPORATION
CHEMICALS AND PLASTICS
NEW YORK, NEW YORK 10007
U.S. PAT. 2,811,111

SOLVENT
Vinyl



SOLVENT
Vinyl

SOLVENT
Vinyl



RNW 1995

PLATE CC

UNION
CARBIDE

UNION
CARBIDE

PLASTICS

KEEP DRY
USE NO HOOKS
STOW AWAY
FROM BOILERS

Vinyl

RNW 1996

100% Virgin Polyethylene
Produced from Crude Oil
Manufactured by Union Carbide
Product No. 1000-1000

Vinyl

MADE IN U.S.A.

NET 22.7 KG / 50.0 LBS.

UNION CARBIDE CORPORATION
CHEMICALS AND PLASTICS
NEW YORK, NEW YORK 10017

YEAR OF USE 1970 - PRESENT

Vinyl

UNION
CARBIDE

7-23-76

BAG CODE 100001

- (i) Unknown, or above 8,000 ppm... Open-circuit, self-contained breathing apparatus, pressure demand type, with full facepiece.
- (ii) Not over 8,000 ppm... (A) Combination type C supplied air respirator, pressure demand type, with full or half facepiece, and auxiliary self-contained air supply; or (B) Type C, supplied air respirator continuous flow type, with full or half facepiece, and auxiliary self-contained air supply.
- (iii) Not over 100 ppm... (A) Combination type C supplied air respirator demand type, with full facepiece, and auxiliary self-contained air supply; or (B) Open-circuit self-contained breathing apparatus with full facepiece, in demand mode, or (C) Type C supplied air respirator, demand type, with full facepiece.
- (iv) Not over 25 ppm... (A) A powered air-purifying respirator with hood, helmet, full or half facepiece, and a canister which provides a service life of at least 4 hours for concentrations of vinyl chloride up to 25 ppm, or (B) Gas mask, front- or back-mounted canister which provides a service life of at least 4 hours for concentrations of vinyl chloride up to 25 ppm.
- (v) Not over 10 ppm... (A) Combination type C supplied-air respirator, demand type, with half facepiece, and auxiliary self-contained air supply; or (B) Type C supplied-air respirator, demand type, with half facepiece; or (C) Any chemical cartridge respirator with an organic vapor cartridge which provides a service life of at least 1 hour for concentrations of vinyl chloride up to 10 ppm.

(5) (i) Entry into unknown concentrations or concentrations greater than 25,000 ppm (lower explosive limit) may be made only for purposes of life rescue; and

(ii) Entry into concentrations of less than 25,000 ppm, but greater than 3,600 ppm may be made only for purposes of life rescue, firefighting, or securing equipment so as to prevent a greater hazard from release of vinyl chloride.

(6) Where air-purifying respirators are used:

(i) Air-purifying canisters or cartridges shall be replaced prior to the expiration of their service life or the end of the shift in which they are first used, whichever occurs first, and

(ii) A continuous monitoring and alarm system shall be provided where concentrations of vinyl chloride could reasonably exceed the allowable concentrations for the devices in use. Such system shall be used to alert employees when vinyl chloride concentrations exceed the allowable concentrations for the devices in use.

(7) Apparatus prescribed for higher concentrations may be used for any lower concentration.

(h) Hazardous operations. (1) Employees engaged in hazardous operations, including entry of vessels to clean polyvinyl chloride residue from vessel walls, shall be provided and required to wear and use;

(i) Respiratory protection in accordance with paragraphs (c) and (g) of this section; and

(ii) Protective garments to prevent skin contact with liquid vinyl chloride or with polyvinyl chloride residue from vessel walls. The protective garments shall be selected for the operation and its possible exposure conditions.

(2) Protective garments shall be provided clean and dry for each use.

(i) Emergency situations. A written operational plan for emergency situations shall be developed for each facility storing, handling, or otherwise using vinyl chloride as a liquid or compressed gas. Appropriate portions of the plan shall be implemented in the event of an emergency. The plan shall specifically provide that:

(1) Employees engaged in hazardous operations or correcting situations of existing hazardous releases shall be equipped as required in paragraph (h) of this section;

(2) Other employees not so equipped shall evacuate the area and not return until conditions are controlled by the methods required in paragraph (f) of this section and the emergency is abated.

(j) Training. Each employee engaged in vinyl chloride or polyvinyl chloride operations shall be provided training in a program relating to the hazards of vinyl chloride and precautions for its safe use.

(1) The program shall include:

(i) The nature of the health hazard from chronic exposure to vinyl chloride including specifically the carcinogenic hazard;

(ii) The specific nature of operations which could result in exposure to vinyl chloride in excess of the permissible limit and necessary protective steps;

(iii) The purpose for, proper use, and limitations of respiratory protective devices;

(iv) The fire hazard and acute toxicity of vinyl chloride, and the necessary protective steps;

(v) The purpose for and a description of the monitoring program;

program;

(vii) Emergency procedures;

(viii) Specific information to aid the employee in recognition of conditions which may result in the release of vinyl chloride; and

(ix) A review of this standard at the employee's first training and indoctrination program, and annually thereafter.

(2) All materials relating to the program shall be provided upon request to the Assistant Secretary and the Director.

(k) Medical surveillance. A program of medical surveillance shall be instituted for each employee exposed, without regard to the use of respirators, to vinyl chloride in excess of the action level. The program shall provide each such employee with an opportunity for examinations and tests in accordance with this paragraph. All medical examinations and procedures shall be performed by or under the supervision of a licensed physician, and shall be provided without cost to the employee.

(1) At the time of initial assignment, or upon institution of medical surveillance:

(i) A general physical examination shall be performed, with specific attention to detecting enlargement of liver, spleen or kidneys, or dysfunction in these organs, and for abnormalities in skin, connective tissues and the pulmonary system (See Appendix A).

(ii) A medical history shall be taken, including the following topics:

(A) Alcohol intake;

(B) Past history of hepatitis;

(C) Work history and past exposure to potential hepatotoxic agents, including drugs and chemicals;

(D) Past history of blood transfusions; and

(E) Past history of hospitalizations.

(iii) A serum specimen shall be obtained and determinations made of:

(A) Total bilirubin;

(B) Alkaline phosphatase;

(C) Serum glutamic oxalacetic transaminase (SGOT);

(D) Serum glutamic pyruvic transaminase (SGPT); and

(E) Gamma glutamyl transpeptidase.

(2) Examinations provided in accordance with this paragraph shall be performed at least:

(i) Every 6 months for each employee who has been employed in vinyl chloride or polyvinyl chloride manufacturing for 10 years or longer; and

(ii) Annually for all other employees.

(3) Each employee exposed to an emergency shall be afforded appropriate medical surveillance.

(4) A statement of each employee's suitability for continued exposure to vinyl chloride including use of protective equipment and respirators, shall be obtained from the examining physician promptly after any examination. A copy of the physician's statement shall be provided each employee.

(5) If any employee's health would be materially impaired by continued exposure, such employee shall be with-

drawn from possible contact with vinyl chloride.

(6) Laboratory analyses for all biological specimens included in medical examinations shall be performed in laboratories licensed under 42 CFR Part 74.

(7) If the examining physician determines that alternative medical examinations to those required by paragraph (k)(1) of this section will provide at least equal assurance of detecting medical conditions pertinent to the exposure to vinyl chloride, the employer may accept such alternative examinations as meeting the requirements of paragraph (k)(1) of this section, if the employer obtains a statement from the examining physician setting forth the alternative examinations and the rationale for substitution. This statement shall be available upon request for examination and copying to authorized representatives of the Assistant Secretary and the Director.

(l) Signs and labels. (1) Entrances to regulated areas shall be posted with legible signs bearing the legend:

CANCER-SUSPECT AGENT AREA AUTHORIZED PERSONNEL ONLY

(2) Areas containing hazardous operations or where an emergency currently exists shall be posted with legible signs bearing the legend:

CANCER-SUSPECT AGENT IN THIS AREA PROTECTIVE EQUIPMENT REQUIRED AUTHORIZED PERSONNEL ONLY

(3) Containers of polyvinyl chloride resin waste from reactors or other waste contaminated with vinyl chloride shall be legibly labeled:

**CONTAMINATED WITH
VINYL CHLORIDE CANCER-SUSPECT AGENT**

(4) Containers of polyvinyl chloride shall be legibly labeled:

**POLYVINYL CHLORIDE (OR TRADE NAME)
CONTAINS
VINYL CHLORIDE
VINYL CHLORIDE IS A CANCER-SUSPECT AGENT**

(5) Containers of vinyl chloride shall be legibly labeled either:

(1) **VINYL CHLORIDE
EXTREMELY FLAMMABLE GAS UNDER PRESSURE
CANCER-SUSPECT AGENT**

or (2) In accordance with 49 CFR Part 173, Subpart H, with the additional legends:

**CANCER-SUSPECT AGENT
applied near the label or placard.**

(6) No statement shall appear on or near any required sign, label or instruc-

tion which contradicts or detracts from the effect of, any required warning, information or instruction.

(m) Records. (1) All records maintained in accordance with this section shall include the name and social security number of each employee where relevant.

(2) Records of required monitoring and measuring, medical records, and authorized personnel rosters, shall be made and shall be available upon request for examination and copying to authorized representatives of the Assistant Secretary and the Director.

(i) Monitoring and measuring records shall:

(A) State the date of such monitoring and measuring and the concentrations determined and identify the instruments and methods used;

(B) Include any additional information necessary to determine individual employee exposures where such exposures are determined by means other than individual monitoring of employees; and

(C) Be maintained for not less than 30 years.

(ii) Authorized personnel rosters shall be maintained for not less than 30 years.

(iii) Medical records shall be maintained for the duration of the employment of each employee plus 20 years, or 30 years, whichever is longer.

(3) In the event that the employer ceases to do business and there is no successor to receive and retain his records for the prescribed period, these records shall be transmitted by registered mail to the Director, and each employee individually notified in writing of this transfer.

(4) Employees or their designated representatives shall be provided access to examine and copy records of required monitoring and measuring.

(5) Former employees shall be provided access to examine and copy required monitoring and measuring records reflecting their own exposures.

(6) Upon written request of any employee, a copy of the medical record of that employee shall be furnished to any physician designated by the employee.

(n) Reports. (1) Not later than 1 month after the establishment of a regulated area, the following information shall be reported to the OSHA Area Director. Any changes to such information shall be reported within 15 days.

(i) The address and location of each establishment which has one or more regulated areas; and

(ii) The number of employees in each regulated area during normal operations, including maintenance.

(2) Emergencies, and the facts obtainable at that time, shall be reported within 24 hours to the OSHA Area Director. Upon request of the Area Director, the employer shall submit additional information in writing relevant to the nature and extent of employee exposures and measures taken to prevent future emergencies of similar nature.

(3) Within 10 working days following any monitoring and measuring which discloses that any employee has been exposed, without regard to the use of respirators in excess of the permissible exposure limit, each such employee shall be notified in writing of the results of the exposure measurement and the steps being taken to reduce the exposure to within the permissible exposure limit.

(o) Effective dates. (1) Until January 1, 1975, the provisions currently set forth in § 1910.93q of this Part shall apply.

(2) Effective January 1, 1975, the provisions set forth in § 1910.93q of this Part shall apply.

APPENDIX A—SUPPLEMENTARY MEDICAL INFORMATION

When required tests under paragraph (k)(1) of this section show abnormalities, the tests should be repeated as soon as practicable, preferably within 3 to 4 weeks. If tests remain abnormal, consideration should be given to withdrawal of the employee from contact with vinyl chloride, while a more comprehensive examination is made.

Additional tests which may be useful:

A. For kidney dysfunction: urine examination for albumin, red blood cells, and exfoliative abnormal cells.

B. Pulmonary system: Forced vital capacity, forced expiratory volume at 1 second, and chest roentgenogram (posterior-anterior, 14 x 17 inches).

C. Additional serum tests: Lactic acid dehydrogenase, lactic acid dehydrogenase isoenzyme, protein determination, and protein electrophoresis.

D. For a more comprehensive examination on repeated abnormal serum tests: Hepatitis B antigen, and liver scanning.

(Secs. 6 and 8, 84 Stat. 1598, 1599 (29 U.S.C. 655, 657); Secretary of Labor's Order No. 12-71, 36 FR 8784)

Signed at Washington, D.C., this 1st day of October, 1974.

**JOHN STENDER,
Assistant Secretary of Labor.
[PR Doc.74-23176 Filed 10-1-74; 2:54 pm]**

ATTACHMENT

C

ATTACHMENT D

VINYL CHLORIDE

Compressed, liquefied gas; sweet odor. Gas is heavier than air.

HAZARDS

(CANCER SUSPECT AGENT)

FIRE

Extremely flammable. May be ignited by heat, sparks or open flame. Burning releases hydrogen chloride gas which is extremely irritating and corrosive. Fire may cause violent rupture of tank.

EXPOSURE

Vapor harmful. Liquid may cause skin or eye injury similar to frostbite.

IN CASE OF ACCIDENT

IF THIS HAPPENS



For assistance, phone

CHEMTREC

toll free, day or night

800-424-9300

DO THIS



SPILL or LEAK

Shut off ignition. No smoking or flares. Keep people away. Keep upwind. Shut off leak if without risk. Wear self-contained breathing apparatus and full protective clothing. Flush area with water spray. Run-off to sewer may create explosion hazard; notify authorities.

FIRE

Do not put out fire until leak has been shut off. On small fire use dry chemical or CO₂. On large fire use water spray. Wear self-contained breathing apparatus. Tanks in massive flame contact may rupture violently unless cooled by straight streams of water. Use unmanned monitor nozzle. Apply from side. Keep clear of tank ends. Otherwise, withdraw from area and let fire burn.

EXPOSURE

Remove to fresh air. If unconscious, call a physician. If not breathing, apply artificial respiration, oxygen. In case of contact with liquid, thaw frosted parts with water. In case of exposure to gas from fire, administer oxygen if breathing is difficult.

Published by the Manufacturing Chemists' Association, Inc. in cooperation with the Compressed Gas Association, Inc. While prepared from sources believed reliable, the Associations make no warranty that the information is, in all cases, correct or sufficient.
© Manufacturing Chemists' Association, Inc., 1825 Connecticut Ave., N.W., Washington, D. C. 20009, 1972

Printed in USA

2M-2-76

RNW 1999

ATTACHMENT E


POLYVINYL CHLORIDE
contains
VINYL CHLORIDE
VINYL CHLORIDE IS
A CANCER-SUSPECT AGENT
UCC-6005-3

RNW 2000

POLYVINYL CHLORIDE
contains
VINYL CHLORIDE
VINYL CHLORIDE IS
A CANCER-SUSPECT AGENT

UCC-6003-4

RNW 2001



RNW 2002