

RESULTS

Preliminary tests proved techniques customarily employed in anti-biotic sensitivity testing, not applicable in the quantitation of the inhibitory response of mirex, heptachlor, and the PCBs. These toxicants are insoluble in water and the diffusion rates through the agar were variable, yielding non-quantitative zones of inhibition. A relative inhibitory effect, however, could be distinguished between the bacterial strains and toxicant levels tested by using the method described in Table 1.

Of the 85 bacteria tested, 26 demonstrated zones of inhibition to at least one of the test compounds (Table 1). The PCBs were markedly more inhibitory than the organochlorine pesticides. Only 3% of the strains screened showed inhibition at 0.5mg of mirex and heptachlor. This concentration of Aroclor[®] 1016 and 1242, however, inhibited 31% of the bacterial strains. Further, 0.1mg of Aroclor[®] 1016 inhibited 69% of these strains and Aroclor[®] 1242 inhibited 62%.

We attempted to correlate PCS-sensitivity response with biochemical activity or cell composition (Table 2). PCB-sensitive bacteria were both Gram positive and negative and no morphological correlation was noted. However, a comparison of biochemical activities of sensitive and non-sensitive bacteria tested showed two distinctly different groupings. Amylase and gelatinase ^{produced} production was shown by 76% and 86% respectively, of the sensitive strains; however, of the total bacterial strains screened, only 33% and 42% of the populations showed these activities. No other biochemical activity differed

PLAINTIFF'S
EXHIBIT

1538

NEV 025649

738904

Table 2.

Comparison of Physiological Activities of PCB-sensitive and Non-sensitive Microorganisms

Bacteria	Production of:					Nitrate	Citrate	Gram
<u>Tested</u>	<u>Urease</u>	<u>Amylase</u>	<u>Lipase</u>	<u>Gelatinase</u>	<u>H₂S</u>	<u>Reduction</u>	<u>Utilization</u>	<u>Reaction</u>
Sensitive	19*	76	33	86	5	29	43	50
Non-Sensitive	13	33	23	42	6	37	41	

*Percentage of cultures tested showing positive reaction, 100 cultures tested.

distinctly from the non-sensitive bacterial populations. No characteristic gram reaction was shown by the PCB-sensitive bacteria.

DISCUSSION

The sensitivity disc testing procedure commonly used in clinical bacteriology has been successfully applied here as a rapid method for detecting PCB-sensitive estuarine microorganisms in pure culture. Although the procedure is qualitative only, it can serve to eliminate many hours of tedious experimentation involved in the isolation of suitable test organisms for more detailed examinations.

This method has been used previously by investigators to study the effects of pesticides on growth of bacteria (Widdus, et al. 1971; Trudgill, et al. 1971). However, no significant response has been shown screening estuarine microbes and chlorinated hydrocarbon pesticides in this study. Conversely, PCB sensitivity in estuarine bacteria was quite dramatic (Figure 1) using this method. Keil et al. (1973) demonstrated no sensitivity to 0.02 mg PCB by E. coli using the same method on non-marine medium. ^{These} ~~Our~~ experiments indicated PCB's stimulate growth of E. coli. No explanation for this difference between stimulation in E. coli, ^(Keil et al., 1973) and inhibition in ^(this study) estuarine bacteria, has been determined at this time.

The implications of this inhibition, if wide spread in the environment, are obvious. The sensitivity of a large number of heterotrophic bacteria to PCBs may be of considerable importance in an estuarine environment. PCBs have been shown to persist in estuarine sediments in relatively high concentration (9 ppm). Sediment cores taken in close proximity to another showed markedly different concentrations (0.06-9 ppm) indicating the PCBs are pro-

bably absorbed onto particulate organic matter during transport and deposition in estuarine sediments (Butler, 1974). The aforementioned concentrations, when considered absorbed onto distinct detrital particles, are not unlike those shown to be inhibitory to heterotrophic growth in this study. Consequently, PCBs could inhibit the normal turnover of carbon in estuarine sediments by inhibition of specific heterotrophic bacteria attached to organic detritus.

REFERENCES

Ahmed, M. and D.D. Focht. Bull. Environ. Contam. Toxicol 10, 70-72 (1973).

Boutquin, A. W., In: The Microbial Degrad. of Oil Pollutants, Eds. Ahearn, D.G. and S.P. Meyers, 237-243 (1973).

Butler, P. A. Personal Communication (1974).

Keil, J. E., S. H. Sandifer, C. D. Graber, and L. E. Priester.
Water Research 6: 837-841. 1972

Paris, Doris and David L. Lewis. Residue Reviews 45, 95-124 (1973).

Trudgill, P. W., Widdus, and J. A. Rees, J. of Gen. Microbiol. 69, 1-13 (1971).

Ware, G. W. and C. C. Roan, Residue Reviews 33, 15-45 (1970).

Widdus, R., P. W. Trudgill, and D. C. Turnell, J. of Gen. Microbiol. 69, 22-31 (1971).

INTRODUCTION

Polychlorinated biphenyls (PCB) have been used in a wide variety of industrial and consumer applications over the past 40 years, but it was only recently that evidence began to appear that these materials had been widely dispersed throughout the environment. By letter dated February 18, 1970 the Monsanto Company, sole US producer of PCB's, notified all of its customers of "the potential problem of environmental contamination" by these liquids and recommended "that all possible care should be taken in the application, processing, and effluent disposal of these products to prevent them becoming environmental contaminants." Monsanto has begun a program to discontinue sales of PCB's for use in paints, plasticizers, specialty inks, adhesives, paper coatings and all other open-system applications.

The Monsanto Company has declared, however, that it will continue to sell PCB's for closed-system electrical uses. This decision is a tacit recognition of the important role that PCB's play in the safe, reliable, and efficient delivery of electric power from the generating plant to the user. In the spate of published reports and statements that have appeared in recent years on PCB's there has been no meaningful exposition of this role of PCB's in electrical equipment -- why, where, and how they are used; what alternatives are available; and what the consequences would be to the users of such equipment if PCB's were no longer available. We hope that this report will provide such an

...

NEV 025654

BACKGROUND

PCB's are used by the electrical industry as components of certain types of transformers and capacitors. The nature and function of these devices are described in the separate sections of this report devoted to them. At this point it is sufficient to say:

1. Transformers are devices for converting electrical power from one voltage and current level to another, and the conducting parts of these devices must be separated from each other by a suitable insulating medium.
2. Capacitors are devices for storing electrical energy through the physical separation of charged metal surfaces by an insulating medium.

Prior to 1930 the most commonly used insulating medium was mineral oil. The early 1930's saw the commercial development of insulating liquids that were mixtures of synthetic chlorinated aromatic hydrocarbons, principally various polychlorinated biphenyls. By controlling the composition of these mixtures, the manufacturer could obtain desired combinations of thermal, chemical and dielectric properties that resulted in insulating liquids with much greater oxidation and fire resistance than mineral oils. During the past 40 years these liquids have become widely used in certain types of transformers and capacitors and are recognized as a distinct class of insulating materials designated by the international term "askarel". The definition of the term "askarel", the compositions of the liquid that comprise this class of materials, and the various trademarks by which they are known commercially are described in the following section headed "Askarel".

NEV 025655

738910

The particular askarels used in transformers and capacitors are different; so also are the reasons for, and the extent and consequences of, their use in these two types of electrical equipment. However, certain general comments can be made at this point concerning their use in both types of equipment:

1. Askarel-insulated transformers and capacitors are delivered to customers as sealed units from which there is no escape of askarel under normal operation during their expected lifetimes of 10 to more than 30 years. However, certain types of equipment failures can rupture the case and permit the loss of some askarel to the environment. Such failures occur at a rate of about 0.02% of the units in service per year.
2. PCB's can get into the environment during the manufacture, delivery, improper use, maintenance, repair, and disposal of transformers and capacitors. In addition to specific control measures instituted by individual manufacturers and recommended by them to the equipment users, the American National Standards Institute has established ANSI Committee C107 on Use and Disposal of Askarel Used in Electrical Equipment. Its memberships (see Appendix 1) is divided into separate working groups on transformers and capacitors which will recommend national standards and procedures necessary to prevent the loss of PCB's to the environment at all stages from equipment manufacture through ultimate disposal.
3. The record of reliable and safe performance that askarel-insulated transformers and capacitors have

NEV 025056

compiled during the past four decades is reflected in the various codes, standards, and regulations that now effectively require or encourage the continued use of askarel-insulated equipment in many applications.

9
NEV 025657

738912

Definitions

1. A synthetic nonflammable insulating liquid which, when decomposed by the electric arc, evolves only nonflammable gaseous mixtures.

(From the National Electrical Code 1971 and the American National Standards Institute C-42 series, "Definitions of Electrical Terms.")

2. The term askarel generally describes a widely used, broad class of nonflammable synthetic halogenated hydrocarbon insulating liquids used as electrical insulating media.

Askarels of various compositional types are used. Under arcing conditions the gases produced, while consisting of predominantly non-combustible hydrogen chloride, can yield varying amounts of combustible gases depending upon the askarel type.

Insulation systems incorporating these askarels and cellulosic or other organic materials may, when arced, produce gaseous mixtures which are moderately flammable..

(From ASTM (American Society for Testing and Materials) Method D 2283-71, Part 29, 1971 issue; will also appear in the 1972 issue of the IEEE (Institute of Electronic and Electrical Engineers) "Guide for Acceptance and Maintenance of Transformer Askarels in Equipment." Adoption was also recommended to the International Electrotechnical Commission by its Subcommittee 10B (Insulating Liquids Other than Hydrocarbon Oils) of Committee 10 (Liquid and Gaseous Dielectrics) as reported in item number 9 of minutes

Compositions

Polychlorinated biphenyls are derivatives of the hydrocarbon, biphenyl, which has the chemical formula $C_{12}H_{10}$. From one to ten of the hydrogen atoms in a molecule of biphenyl can be replaced by chlorine atoms, and the chemical identity of the resulting chlorinated compound depends both on the number of chlorine atoms that have been introduced into the molecule and on the specific sites in the molecular structure at which they are introduced.

The commercial material manufactured by Monsanto under its registered trademark Aroclor consists of mixtures of these specific chlorinated compounds. They are usually identified by the weight percent of chlorine in the total mixtures, e.g. Aroclor 1254 contains 54% chlorine. The Aroclors commonly used in the electrical industry are Aroclors 1260, 1254, and 1242.

Aroclor 1242, used primarily in capacitors, contains about 7% of pentachlorobiphenyls and higher. In September 1971 Monsanto introduced a new capacitor-grade askarel, Aroclor MCS-1016, which is essentially Aroclor 1242 that has been specially processed to reduce the content of pentachlorobiphenyls and higher to less than 0.4%.

As a general rule, the nonflammability of liquid PCB's, their vapors, and their arc-formed gaseous products is greater the higher the degree of chlorination of the liquid. Studies by Monsanto suggest that the resistance of PCB's to degradation in the environment may also increase with increasing chlorine content. Analytical methods for low levels of PCB's (reported in parts per million or parts per billion) in marine, aquatic, and wildlife environments do not always identify the specific compounds that are present, but in its letter of February 19, 1970 to its customers, Monsanto

NEV 025659

not been found in the environment and appear to present no potential problem to the environment."

Trademarks

The following trademarks are used by electrical manufacturers to designate the askarels used in their products:

<u>Manufacturer</u>	<u>Trademark</u>
Aerovox	Hyvol
Allis-Chalmers	Chlorextol
American Corp.	Abestol
Cornell Dubilier	Dykanol
General Electric	Pyranol
Kuhlman Electric	Saf-T-Kuhl
McGraw Edison General Electric	Elemex
Sangamo Electric	Diaclor
Wagner Electric	Noflamol
Westinghouse Electric	Inerteen

Toxic and Biological Effects of PCB's

Systematic investigations of the toxic and biological effects of PCB's have been undertaken only within the past few years, and the description and evaluation of the results is beyond the scope of this report. Some investigators suggest that reports of certain toxic reactions may be caused by highly poisonous compounds (e.g. chlorinated dibenzofurans) found to be contaminants in some PCB preparations. In the United States, medical records show that over a nearly 40-year period the only adverse health effects experienced by US workers exposed to PCB's, either during the manufacture of these liquids or of electrical equipment containing these liquids, have been limited to occasional cases of non-chronic chloracne or other temporary skin lesions or irritations.

TRANSFORMERS

Definition

A transformer is a device for transferring electrical energy from one alternating current circuit to another by electromagnetic means. It has no moving parts and performs its function by linking two electric current-carrying circuits (the coils, usually copper wire) via a common magnetic flux carrying-circuit (the core, usually a special grade of iron). A transformer may be designed to effect a change in voltage or current from one circuit to the other or simply to obtain electrical energy from one electrical circuit without making a conductive connection between it and a second electrical circuit.

The transmission of electrical energy from one point to another is essentially the transmission of a required number of kilovolt-amperes (kva). By means of transformers the kva's may be generated at a low voltage suitable for the windings of generators, stepped up to higher voltages and lower currents suitable for transmission of electricity over long distance wires, and then at the desired destination stepped down to a lower voltage and larger current suitable for utilization by electrically powered equipment.

The almost universal use of the alternating current system for the transmission and distribution of electrical energy is largely due to this ability of transformers to link up circuits of different voltages and currents. Thus the generator, the transmission lines, the secondary distribution system, and finally the great variety of ultimate loads can each be operated at the voltage most suitable to its particular function. Without this unique ability of the transformer to adapt the circuit voltage to the individual requirements of the different parts of the system, the enormous development and progress in the transmission and distribution of electrical energy during the past 80 years would not have been possible.

NEV 025661

13
738916

Why Askarels are Used in Transformers

The coils and core of most transformers are enclosed in sealed metal tanks that are filled with an insulating liquid, usually mineral oil. Under certain conditions of sudden power surges high-current electric arcs are produced inside the transformer which can generate and ignite flammable and explosive gas mixtures formed from the mineral oil and other cellulosic insulating components in the transformer.

Because of the nonflammability of liquid askarels, their vapors, and their arc-formed gaseous products, transformers filled with askarels are free of these fire and explosion hazards and may be used in locations where failures of oil-insulated transformers would present a potential danger to life and property. This safety factor is the only advantage that askarel-insulated transformers have over oil-insulated transformers of the same size and rating. The density of askarels is about 1.7 times that of mineral oil, so askarel-insulated transformers are heavier than their oil-filled counterparts. Askarels themselves are more expensive than mineral oils, and their solvent characteristics require the use of more expensive insulation components on the internal parts of the transformer, so the complete units are more expensive.

As a consequence, askarel-insulated transformers have captured only those market applications (less than 5%, but growing) where considerations of safety and reliability are paramount. Their use in such applications is usually required or encouraged by the provisions of electrical codes, fire underwriting policies, or governmental regulations.

Note: Prior to the mid-1950's the liquid used in askarel-insulated transformers was a 50-50 weight mixture of Aroclor 1260 (60% chlorine) with trichlorobenzenes; then the benzene component was changed to a mixture of tri- and tetrachlorobenzenes; and in 1971 the Aroclor component was changed to Aroclor 1254 (54% chlorine).

NEV 025662

14
738917

Types and Applications of Askarel-Insulated Transformers

There are two broad classifications of transformers: power transformers, which are used to step up voltages; and distribution transformers, which are used to step down voltages. The many types of transformers that are included within these two classifications are listed in Appendix 2. The applications that accompany the listing apply only to those units of a given type that are manufactured with askarel as the insulating liquid. Most units of the types listed are still oil-insulated.

We estimate that the total number of askarel-insulated units that have been put into service in the United States since 1932 is 125,000, and virtually all of these units are still in service. The lifetime-before-failure is often longer than 30 years, and almost all units that do fail are rebuilt and returned to service. The current production rate of new askarel-insulated transformers units is about 5,000 per year.

Most of these transformers are located inside public, commercial, or industrial buildings; on the roof tops of such buildings; or in close proximity to such buildings, and require no special enclosures other than what are necessary to prevent accidental hazardous mechanical or electrical contact of persons with the equipment. However, the National Electrical Code does specify vaults for the indoor installation of askarel-insulated transformers rated more than 35,000 volts. Askarel-insulated transformers are limited by the electrical properties of these liquids to ratings below 69,000 volts.

The amount of askarel used in various types of transformers ranges from 40 to 500 gals. (516 to 6,450 lbs.) with an average of about 235 gals. (3,032 lbs.). During 1968, the last complete "normal" year for the electrical industry, the total amount of

NEW 025663

PCB's used in transformers was approximately 1.3 million gallons (8.4 thousand tons).

Present Alternatives to Askarel-Insulated Transformers

If PCB's were to be no longer available for closed-system electrical uses -- as they are no longer available from Monsanto for open-system applications -- what alternatives to askarel-insulated transformers could now be supplied by the electrical industry, and what would be the effect upon the user should askarel-insulated transformers no longer be available either as new or replacement units?

The only present alternatives to askarel-insulated transformers are oil-insulated transformers or dry-type transformers (either those open to the atmosphere or those that are gas-filled and sealed).

A. Oil-insulated transformers

1. If one disregards safety considerations, there are no technical reasons why oil-insulated transformers could not be directly substituted for askarel-insulated transformers. The size of the unit would be unchanged; the weight and cost would be less.
2. There are legal restrictions to such a direct substitution.
 - a. Some local regulations (e.g. Chicago) prohibit the use of oil-insulated units in certain locations where askarel-insulated units are allowed.
 - b. Where oil-insulated transformers would not be specifically prohibited as on-site replacements for askarel-insulated units, the National Electrical Code imposes special restrictions upon their mode of installation. Although

NEV 025664

35,000 volts must be installed in vaults, all oil-insulated transformers require vaults, except that alternative fire protection arrangements are permitted for units rated not over 600 volts. Assuming that space were available inside an existing building to accommodate these special auxiliary safety provisions, the cost of their construction could range from \$5,000 to \$50,000 per transformer.

- c. Oil-insulated units can be installed outdoors if they are suitably isolated from flammable structures or if these structures are suitably safeguarded against fires originating in the transformers. The power output must then be brought to the point of use inside the building via cables or insulated buses, and the cost of cable and bus installation could also range from \$5,000 to \$50,000 per transformer. The outdoor transformer would have to be of a higher rating than the indoor one it would replace because of voltage drop and consequent power losses in the cable or bus runs.

B. Dry-type transformers

In most locations, dry-type transformers (either those open to the atmosphere or those that are gas-filled and sealed) could not be directly substituted for askarel-insulated transformers. There are several restrictions to such a direct substitution:

NEV 025665

1. The provisions of the National Electrical Code are more stringent for certain classes of dry-type transformers than for comparable askarel-insulated units.
2. Present technology is not available for designing and manufacturing reliable dry-type transformers above ~~2500~~²⁵⁰⁰ KVA and/or 15 KV.
3. The reliability of dry-type transformers is less than that of comparably rated liquid-insulated transformers. Oil- and askarel-insulated units show much greater resistance to switching and lightning surges than do dry-type units. An EEI survey of failures in network transformer banks showed a 7% per year failure rate for dry-type units compared to 0.2% for liquid-insulated units. Furthermore, liquid-insulated transformers have a much greater overload capability. Many liquid-insulated units can sustain a 100% overload for 8 hours and a 200% overload for 2 hours. These transformers are able to maintain continuity of electrical service during periods of temporary outage of related equipment.
4. Some dry-type transformers are larger by 10 to 30% than comparably rated liquid-insulated units, and most are more expensive.
5. Dry-type transformers are noisier by 5-10 dB than are liquid-insulated transformers.
6. Because their insides require regular cleaning, the maintenance costs for open dry-type transformers are higher than those for sealed dry-type transformers.

099570
NEN

or for liquid-insulated transformers, which are also sealed.

7. Open dry-type transformers, which are cheaper than sealed dry-type transformers, cannot be used in certain corrosive or hazardous atmospheres, e. g. on furnaces or on electrostatic precipitators near hot stacks.

C. Summary

1. For technical or legal reasons it would be impossible to replace most askarel-insulated transformers now in service by oil-insulated units of equivalent rating and reliability without major construction changes that would be required to compensate for the fire and explosion resistance of the askarel-insulated units.
2. For certain applications and locations, dry-type transformers could replace askarel-insulated transformers, but with a significant reduction in system reliability.

19
NEV 025667

738922

CAPACITORS

Definition

A capacitor is a device that stores electrical energy. It consists of two metal surfaces or electrodes separated by an insulating medium such as air, paper, plastic film, or oil. When a voltage is applied across the electrodes, electrostatic energy is stored in the insulating medium.

In typical industrial capacitors the electrode material is aluminum foil and the insulating medium or dielectric is paper tissue and/or plastic film, which for many applications is impregnated with a liquid dielectric. A liquid impregnant is used to fill the voids within the paper or plastic film structure, to fill the voids between sheets, and to contribute to the capacitance or charge-carrying ability of the composite. Voids must be eliminated within capacitors that are to be used above 200-300 volts, which exceeds the dielectric breakdown strength of air.

In our definition of transformers we emphasized their importance in the transmission and distribution of electrical power (kilovolt-amperes) from the generating plant to the ultimate load. If the load were purely resistive (e.g. an electric heating element) no further modification of the power supply delivered to it would be required. Other loads (e.g. induction motors) may require that a portion of the kilovolt-amperes delivered to them be used to provide a magnetizing current, which does not contribute directly to the useful power output of the load. This portion of the total kva delivered to the load is designated as reactive kilovolt-amperes (kvars). It has been found more economical to produce kvars from total kva's near the point of load rather than near the point of kva generation, and capacitors provide the most efficient way of

NEV 02566b

effecting this transformation at the point of load.

Why Askarels are Used in Capacitors

Prior to 1930 most liquid-filled capacitors were made with mineral oil. The subsequent substitution of askarels for mineral oil made possible significant technical improvements in the size, reliability, and life of these capacitors.

A. Size

The single most important property of a liquid to be used in a capacitor is its dielectric constant (the ratio of its ability to store electrostatic energy relative to air). The dielectric constant of capacitor-grade askarel (Aroclor 1242) is 5.85 while that of mineral oil is 2.25. When capacitor tissue is impregnated with these liquids the dielectric constant of the paper-liquid composite is 6.1 for askarel and 2.9 for mineral oil. Furthermore, because of the relatively close match between the dielectric constants of cellulose, (6.6) and askarel (5.85), it is possible to stress askarel-impregnated paper to 400-500 volts/mil, while the stresses that can be applied to comparable paper-mineral oil capacitors are limited to 300-350 volts/mil. The combined effect of these technical advantages of askarels has been to permit a reduction of capacitor sizes to less than 14% of what they were in 1924. In 1965 a new dielectric system consisting of paper-polypropylene film-askarel was introduced with stress capability up to 900 volts/mil. overall. Because of favorable stress distributions, the ability of askarel to increase the dielectric strength of polypropylene

NEV 025669

is partly responsible for this improvement.

B. Reliability and life

Askarels are thermally and oxidatively more stable than mineral oils, and discharges, which can occur in capacitors, are less likely to generate gases from askarels than from mineral oils. The chemical stability of askarels in the presence of capacitor tissue and plastic films and the favorable stress distributions between solid and liquid referred to above have made it possible to design low-cost capacitors with a life expectancy of more than 10 years life in lighting applications and more than 20 years in electric utility applications. In each application the first-year failure rates are less than 0.2%. This level of life and reliability had not been achieved prior to the introduction of askarels. Furthermore, the non-flammability of askarels is greater than that of mineral oil, which reduces the fire hazard that might otherwise accompany those failures that result in rupture of the case.

Whereas the transformer manufacturer has had to essentially "design around" the properties of askarels in order to be able to take advantage of the safety factor that they impart to his equipment, the capacitor manufacturer has been able to "design with" the properties of askarels and obtain significant technical improvements along with the improved safety factor. As a result askarels have virtually replaced mineral oils in more than 90% of the power and industrial

NEV 025670

Note: Prior to 1952 the liquid used in askarel-impregnated capacitors was Aroclor 1254 (54% chlorine); it was then replaced by Aroclor 1242 (42% chlorine), which has better electrical properties; and as noted in the "Askarel" section, in September 1971 Monsanto introduced a new capacitor-grade askarel, Aroclor MCS-1016, which is a modified Aroclor 1242. Unlike askarel-insulated transformers, the liquid in askarel-impregnated capacitors contains only Aroclors and does not contain added chlorobenzenes.

Types and Applications of Askarel-impregnated Capacitors

The principal types of askarel-impregnated capacitors and their applications are described in Appendix 3. Almost 80 million such capacitors are manufactured annually, most of them for first-time use. Unlike transformers, capacitors are not rebuilt and returned to service after failure. They are disposed of (see "Background" section, item concerning ANSI Committee C107) and replaced by new capacitors.

Capacitors used in lighting and air conditioning applications contain 0.005 to ^{0.09}~~0.009~~ gals. (0.05 to 1.0 lbs.) of askarel per unit. The largest power capacitors contain about 6.7 gals (77 lbs.) of askarel. The most popular size contains about 3.1 (36 lbs.) of askarel. The National Electrical Code requires that any installation of capacitors in which any single unit contains more than 3 gallons of combustible liquid shall be in a vault like that required for transformers. During 1968, the last complete "normal" year for the electrical industry, the total amount of PCB's used in capacitors was approximately 14.4 thousand tons.

NEV 025671

Present Alternatives to Askarel-Impregnated Capacitors

If PCB's were to be no longer available for closed-system electrical uses -- as they are no longer available from Monsanto for open-system applications -- what alternatives to askarel-impregnated capacitors could now be supplied by the electrical industry, and what would be the effect upon the user should askarel-impregnated capacitors no longer be available either as new or replacement units?

Possible alternatives to askarel-impregnated capacitors are capacitors impregnated with mineral oil, or capacitors impregnated with certain other liquids.

A. Mineral Oil

Replacement of askarels by mineral oil would essentially return capacitor technology to its pre-1932 level. Some specific consequences of such a replacement would be:

1. Safety. None of the possible liquid alternatives to askarels are nonflammable, and a fire hazard would be created by any capacitor failures that were accompanied by rupture of the case. Presently the use of capacitors containing flammable liquid is governed by the National Electrical Code Articles 460 and 501.
2. Size and Cost. A few specific examples will illustrate the size and cost penalties associated with a switch from askarel to mineral oil in capacitors. The most popular sized power capacitors today are rated at 200 KVAR. If mineral oil were substituted for askarel the volume of the capacitor would be quadrupled and the direct labor and material costs associated with its manufacture would increase by 70%. Today power capacitors are available in 400 KVAR

REV U25072

KVAR because of increased heat dissipation problems with increased volume. In addition to increases in direct costs, the power capacitor industry would face increased capital expenses estimated at \$2,000,000 to provide the increased volume of material at projected KVAR requirements.

Steel companies faced with increased size, cost and flammability of capacitor banks in induction heating furnaces would probably not install new induction heating capability. Utilities would have difficulty with substation size in crowded urban areas. An increase in the size of capacitors for air conditioning would not be critical.

In lighting applications a 3.75/.075 uf 540 VAC rating for high output applications is typical.

If mineral oil were substituted for askarel, the capacitor would be 71% larger and materials would cost 46% more. Lamp ballast manufacturers would have to increase the size of the ballast to accommodate the larger capacitor. This would change the thermal performance of the unit and require U.L. approval of new ballast designs. Lighting fixture manufacturers would also face redesign costs to take larger ballasts.

- 20-
3. Reliability. Users of capacitors in all application areas have come to expect long life and very low initial failure rates. The present performance standards have been achieved after many years of field testing and accelerated testing by manufacturers and users. The reliability of designs containing

mineral oil in many applications would be uncertain. Available records show that capacitor reliability prior to the availability of askarel was only a fraction of what it is today.

4. Replacement Market. The implications of changes in capacitor size have been discussed in terms of new designs. In each major application area some capacitors are sold for replacement business. Power and induction heating capacitors are generally installed in racks of a few to thousands of capacitors. It would not be possible to make simple substitutions for failed capacitors while maintaining the system rating.

In air conditioners replacement of failed capacitors might be as simple as installation of new brackets. On the other hand, tight designs might not take a larger capacitor at all.

Lighting systems would be seriously affected by increases in capacitor size. Larger replacement ballasts would not fit into existing fixtures without altered mounting arrangements. It is possible that space requirements would force complete replacement of lighting fixtures for the want of a replacement ballast.

5. Material Sources. Mineral oil is currently used in a relatively small number of specialty capacitors. In this country there is a single source of capacitor-grade mineral oil with limited facilities for acid refining of crudes from a single oil field. Increased demand would require

NEV 025674

expanded facilities and investment and considerable development in defining technical requirements for capacitor-grade mineral oil.

Efficient use of mineral oil in capacitor designs would require higher density capacitor tissue than is currently produced in this country. At the least this would require extensive paper machine modification. Capacitor winding techniques and machines would need to be developed for winding tighter rolls.

B. Other Liquids

1. Castor Oil. The dielectric constant of castor oil is 4.5 and this material is useful as an impregnant in D.C. energy storage capacitors. However, A.C. capacitors filled with this liquid have relatively short lives and are not very stable under A.C. discharges and in the presence of water derivable from the cellulosic paper.
2. Dibutyl sebacate. This ester is especially useful in high frequency parallel plate capacitors because of its low, flat loss characteristics over a broad frequency range. In this type of construction the liquid is the sole dielectric material. When used in conjunction with paper, this ester is also unstable.
3. Silicone Fluids. These materials have a dielectric constant of 2.7 and would generally be subject to the same disadvantages as mineral oil.

C. Alternative Designs

In addition to liquid dielectric substitutes, alternatives

NEV 025675

to the paper-liquid dielectric might be considered. These would involve the use of plastic film coated with aluminum foil or vapor-deposited aluminum as electrodes. Since the free volume of the system is less than that of paper the capacitance of the system is less dependent on the dielectric constant of the liquid and the stress distribution between the plastic films and low dielectric constant liquids is more closely balanced. Such dielectric systems are difficult to construct completely free of voids. It is expected that several years will be required to achieve the required level of reliability in such dielectric systems.

28
NEV 025676

738931

POSSIBLE DEVELOPMENT OF NEW INSULATING LIQUIDS

The cost of askarel liquids is about \$2.00 per gallon, compared to about \$0.30 per gallon for mineral oil. Thus, long before there were any environmental concerns about PCB's there was a strong economic incentive to find other less-expensive insulating liquids with the desirable characteristics of askarels. Since the 1930's, at least 10 major chemical or electrical companies have invested large amounts of time and money in this search, all with no success. There are today no fluids that can be used as one-for-one replacements for PCB's.

The continued search for new fluids would probably start with fluorochemicals. Fluorochemicals are nonflammable, nontoxic, and as far as is presently known represent no environmental hazard. High-boiling fluorochemicals might thus be potential replacements for PCB's. Considerable laboratory study, over at least a one-year period, of the physical, chemical, and dielectric properties of these materials would be required in order to identify specific candidate materials.

At least another year would be required to develop a finished product based upon a fluorochemical. On one hand, the physical and dielectric properties would certainly be sufficiently different so that substantial engineering redesign by electrical manufacturers would be required to accommodate a fluorochemical. On the other hand, a one-year lead time is needed to construct a chemical plant to produce the identified fluorochemical in the millions of pounds that would be required per year. Furthermore, a significant program of environmental testing would be needed to ensure that the new material was indeed not an ecological hazard. The foregoing are all highly optimistic time estimates.

The cost of manufacturing fluorochemicals is inherently high. Prices of high-boiling liquids are \$10 - 15 per pound, or higher. At best one would hope

that in sufficient volume the price might approach that of Teflon, currently \$3 - 4 per pound. Even this optimistic figure is approximately twenty times the cost of PCB's, and since the value of PCB in a transformer is roughly one-tenth the total value of the transformer, the total cost of a fluoro-chemical-insulated transformer would be at least three times that of an equivalent askarel unit.

50

NEV 025678

738933

Appendix 1

Membership of ANSI Committee C107 on Use and Disposal of Askarel

Used in Electrical Equipment

<u>Number of Representatives</u>	<u>Organization Represented</u>
2	Department of the Army
2	Environmental Protection Agency
1	U.S. Department of Agriculture
1	Tennessee Valley Authority
1	General Services Administration
1	National Bureau of Standards
2	Certified Ballast Manufacturers Association
1	Edison Electric Institute
1	Institute of Electronic & Electrical Engineers
5	National Electrical Manufacturers Association
2	Monsanto Company
2	Commercial Waste Disposal Companies
1	Engineering Consulting Firm
1	Capacitor Manufacturer Serving as an Independent Member

Appendix 2

Types of Askarel-Insulated Transformers

A. Distribution Transformers

1. Network (up to 2500 KVA)
2. Single- and three-phase (up to 2500 KVA)
3. Pole-mounted and station (up to 500 KVA)

The application of these transformers in power distribution systems places a great premium upon their reliability and high overload capability (which they share with comparable oil-insulated units): such as 100% overload for 8 hours and 200% overload for 2 hours.

4. Precipitation (high voltage DC)

These transformers are part of the power supply for electrostatic precipitators, which are gaining increasing use in preventing air pollution by particulate matter. They are generally installed close to hot gas stacks in an atmosphere that would be a fire hazard to oil-insulated transformers and a corrosion hazard to open dry-type transformers. Sealed dry-type transformers are impractical for high voltage DC.

B. Power Transformers

1. Secondary substation
 - a. Load center units
 - b. Secondary substation generation units
 - c. Switchboard units
 - d. Integral units
 - e. Motor control units

These comprise the largest group of askarel-insulated transformers, and they find widespread application in the automobile, paper,

chemical, textile, steel, nonferrous metal, cement, mining, and petroleum industries. They are used in commercial and public buildings, such as schools and hospitals; in defense and nuclear energy installations; and by private and public utilities.

2. Master unit substation
3. Primary unit substation
4. Limited ampere substation
5. Industrial furnace

These transformers are used in the hot, dirty atmosphere in proximity to glass melting and induction furnaces, which require high current, low voltage power supplies (more than 2500 KVA at no more than 13.8 KV). Existing technology does not permit construction of sealed dry-type transformers for these power ratings.

6. Rectifier

These transformers are used for large rolling mills and DC industrial power supplies, and are covered by the same comments given for industrial furnace transformers.

7. Transportation

- a. Third rail

These transformers are used for rapid transit systems, and are basically serving a rectifier function.

- b. Locomotive

Prior to 1932, all on-board transformers were open dry-type. Because of problems with them, railroads went to askarel-insulated transformers. The changes in locomotive design since the 1930's would not now accommodate open dry-type transformers as replacements

for askarel units. A recent trend has been to replace askarel by oil units, and this will continue unless new DOT regulations require nonflammability.

8. Multiple-unit car (MU)

These transformers are mounted under the flat-bed of passenger cars. They ride along in this location, about 8 inches from the rail, at speeds up to 150 mph. The transformer must be ruggedly built to withstand the impact of flying debris and constant vibration. Power to the cars is brought in through an overhead catenary and is fed to the underside of the car where the transformer, controls, and propulsion equipment are located. Present voltage is 11 KV, but new electrification is expected to be 25 KV.

Space and weight are critical in this application. There are only about 33 inches above the rail. The width of the transformer is limited by the width of the car.

Only oil- or askarel-insulated units would provide the required performance levels in the space available. As with locomotive applications, present DOT regulations do not restrict the use of flammable liquids, and the use of askarel units has been dictated largely by the economic considerations of fire insurance rates.

NEV 025682

34
738937

Appendix 3

Types of Askarel-Insulated Capacitors

A. High Voltage Power

Generally AC capacitors are used to improve the power factor of a circuit. Power factor is the ratio of true power in watts to the apparent power as obtained by multiplying the current flowing to the load by the circuit voltage. The power factor correction can be made directly at the load or at utility substations. In the latter case high voltage units will be designed for 4,800 to 13,800 volt service. To the utility engineer the use of capacitors is purely a matter of economics. The main benefits that result from the use of capacitors are:

1. Reduction of losses associated with the delivery of electrical power to the point of use.
2. Reduction of the investment required in equipment for delivering electrical power to the point of use, which may be broken down into:
 - a. Reduction of current for the same kilowatt load.
 - b. Reduction of the kva rating of equipment required to handle the same kilowatt load.
 - c. Reduction of the voltage drop for a given kilowatt load.
 - d. Control of delivered voltage if the capacitor kva is varied.

Electric utilities also use capacitor banks in series with distribution circuits to improve voltage regulation. High voltage utility capacitors, low voltage power capacitors, and induction heating capacitors are manufactured at the rate of 200,000 per year, about 2 to 3% of which are for replacements; the balance are for new installations.

B. Low Voltage Power

Capacitors installed in industrial plants at the demand site (typically large motors and welders) are designed for 230 to 575 volt service. Capacitors installed near the loads are the most efficient way to supply the magnetizing current to produce the flux necessary for the operation of inductive devices. Rates for the sale of power are generally structured to encourage power factor correction at the site, eliminating the need for the electric utility to transmit both power-producing current and magnetizing current all the way from the generator to the plant site.

The same considerations apply to induction heating applications, the principal difference being that capacitors for this rapidly growing application are designed for operation at 960 to 9600 Hz.

C. Lighting

Capacitors improve the efficiency of lighting systems. A fluorescent or mercury vapor lamp can be ballasted without the use of a capacitor, but the power factor of the lighting system would then be in the range of 50 to 60%. For commercial or industrial lighting with either fluorescent or high intensity discharge lamps, the use of a capacitor in the circuit provides part of the lamp ballasting and brings system power factor into the range of 90 to 95%. The current market for these applications is about 44,000,000 units annually of which about 10% are estimated to be replacement ballasts.

D. Air Conditioning

As in the lighting applications, the capacitor improves system efficiency. Air conditioners could be made to operate without capacitors, as do home refrigerators, but because of the higher capacity required for current air conditioners, the resultant line/would virtually eliminate home "plug-ins" and would still further overburden a seriously threatened national

NEV 025684

3/ 738939

power network. Almost all air conditioner pump motors are of the split-winding type on which the capacitor provides phase differential for the so-called start winding, thus delivering good starting torque. The proper size capacitor permits high (90%) power factor after start-up. The current market for this application is about 12,000,000 units annually, with about 5% of these estimated to be for replacement usage.

E: Industrial Electronics

This market category is a catchall covering many varied applications, two important ones being motor run and power supply applications. Motor run applications are for pumps, fans, and farm fced equipment, and do not differ significantly from air conditioning applications. The power supply market uses capacitors principally to provide high power factor, but through careful design the capacitor can also provide wave shaping where desired. The market is estimated at 23,000,000 units per year with no estimate as to the relative size of the replacement market.

Biodegradation by Semi-Continuous Activated Sludge Treatment
Material: Aroclor 1242

Unit Nos

Sampling Date (After Feeding)	3	8	13	18	23	28	33	38	43	48	53	58	63	68	73	78	83	88	93	98	103	108	113	118	123	128	133	138	143	148	153	158	163	168	173	178	183	188	193	198	203	208	213	218	223	228	233	238	243	248	253	258	263	268	273	278	283	288	293	298	303	308	313	318	323	328	333	338	343	348	353	358	363	368	373	378	383	388	393	398	403	408	413	418	423	428	433	438	443	448	453	458	463	468	473	478	483	488	493	498	503	508	513	518	523	528	533	538	543	548	553	558	563	568	573	578	583	588	593	598	603	608	613	618	623	628	633	638	643	648	653	658	663	668	673	678	683	688	693	698	703	708	713	718	723	728	733	738	743	748	753	758	763	768	773	778	783	788	793	798	803	808	813	818	823	828	833	838	843	848	853	858	863	868	873	878	883	888	893	898	903	908	913	918	923	928	933	938	943	948	953	958	963	968	973	978	983	988	993	998	1003	1008	1013	1018	1023	1028	1033	1038	1043	1048	1053	1058	1063	1068	1073	1078	1083	1088	1093	1098	1103	1108	1113	1118	1123	1128	1133	1138	1143	1148	1153	1158	1163	1168	1173	1178	1183	1188	1193	1198	1203	1208	1213	1218	1223	1228	1233	1238	1243	1248	1253	1258	1263	1268	1273	1278	1283	1288	1293	1298	1303	1308	1313	1318	1323	1328	1333	1338	1343	1348	1353	1358	1363	1368	1373	1378	1383	1388	1393	1398	1403	1408	1413	1418	1423	1428	1433	1438	1443	1448	1453	1458	1463	1468	1473	1478	1483	1488	1493	1498	1503	1508	1513	1518	1523	1528	1533	1538	1543	1548	1553	1558	1563	1568	1573	1578	1583	1588	1593	1598	1603	1608	1613	1618	1623	1628	1633	1638	1643	1648	1653	1658	1663	1668	1673	1678	1683	1688	1693	1698	1703	1708	1713	1718	1723	1728	1733	1738	1743	1748	1753	1758	1763	1768	1773	1778	1783	1788	1793	1798	1803	1808	1813	1818	1823	1828	1833	1838	1843	1848	1853	1858	1863	1868	1873	1878	1883	1888	1893	1898	1903	1908	1913	1918	1923	1928	1933	1938	1943	1948	1953	1958	1963	1968	1973	1978	1983	1988	1993	1998	2003	2008	2013	2018	2023	2028	2033	2038	2043	2048	2053	2058	2063	2068	2073	2078	2083	2088	2093	2098	2103	2108	2113	2118	2123	2128	2133	2138	2143	2148	2153	2158	2163	2168	2173	2178	2183	2188	2193	2198	2203	2208	2213	2218	2223	2228	2233	2238	2243	2248	2253	2258	2263	2268	2273	2278	2283	2288	2293	2298	2303	2308	2313	2318	2323	2328	2333	2338	2343	2348	2353	2358	2363	2368	2373	2378	2383	2388	2393	2398	2403	2408	2413	2418	2423	2428	2433	2438	2443	2448	2453	2458	2463	2468	2473	2478	2483	2488	2493	2498	2503	2508	2513	2518	2523	2528	2533	2538	2543	2548	2553	2558	2563	2568	2573	2578	2583	2588	2593	2598	2603	2608	2613	2618	2623	2628	2633	2638	2643	2648	2653	2658	2663	2668	2673	2678	2683	2688	2693	2698	2703	2708	2713	2718	2723	2728	2733	2738	2743	2748	2753	2758	2763	2768	2773	2778	2783	2788	2793	2798	2803	2808	2813	2818	2823	2828	2833	2838	2843	2848	2853	2858	2863	2868	2873	2878	2883	2888	2893	2898	2903	2908	2913	2918	2923	2928	2933	2938	2943	2948	2953	2958	2963	2968	2973	2978	2983	2988	2993	2998	3003	3008	3013	3018	3023	3028	3033	3038	3043	3048	3053	3058	3063	3068	3073	3078	3083	3088	3093	3098	3103	3108	3113	3118	3123	3128	3133	3138	3143	3148	3153	3158	3163	3168	3173	3178	3183	3188	3193	3198	3203	3208	3213	3218	3223	3228	3233	3238	3243	3248	3253	3258	3263	3268	3273	3278	3283	3288	3293	3298	3303	3308	3313	3318	3323	3328	3333	3338	3343	3348	3353	3358	3363	3368	3373	3378	3383	3388	3393	3398	3403	3408	3413	3418	3423	3428	3433	3438	3443	3448	3453	3458	3463	3468	3473	3478	3483	3488	3493	3498	3503	3508	3513	3518	3523	3528	3533	3538	3543	3548	3553	3558	3563	3568	3573	3578	3583	3588	3593	3598	3603	3608	3613	3618	3623	3628	3633	3638	3643	3648	3653	3658	3663	3668	3673	3678	3683	3688	3693	3698	3703	3708	3713	3718	3723	3728	3733	3738	3743	3748	3753	3758	3763	3768	3773	3778	3783	3788	3793	3798	3803	3808	3813	3818	3823	3828	3833	3838	3843	3848	3853	3858	3863	3868	3873	3878	3883	3888	3893	3898	3903	3908	3913	3918	3923	3928	3933	3938	3943	3948	3953	3958	3963	3968	3973	3978	3983	3988	3993	3998	4003	4008	4013	4018	4023	4028	4033	4038	4043	4048	4053	4058	4063	4068	4073	4078	4083	4088	4093	4098	4103	4108	4113	4118	4123	4128	4133	4138	4143	4148	4153	4158	4163	4168	4173	4178	4183	4188	4193	4198	4203	4208	4213	4218	4223	4228	4233	4238	4243	4248	4253	4258	4263	4268	4273	4278	4283	4288	4293	4298	4303	4308	4313	4318	4323	4328	4333	4338	4343	4348	4353	4358	4363	4368	4373	4378	4383	4388	4393	4398	4403	4408	4413	4418	4423	4428	4433	4438	4443	4448	4453	4458	4463	4468	4473	4478	4483	4488	4493	4498	4503	4508	4513	4518	4523	4528	4533	4538	4543	4548	4553	4558	4563	4568	4573	4578	4583	4588	4593	4598	4603	4608	4613	4618	4623	4628	4633	4638	4643	4648	4653	4658	4663	4668	4673	4678	4683	4688	4693	4698	4703	4708	4713	4718	4723	4728	4733	4738	4743	4748	4753	4758	4763	4768	4773	4778	4783	4788	4793	4798	4803	4808	4813	4818	4823	4828	4833	4838	4843	4848	4853	4858	4863	4868	4873	4878	4883	4888	4893	4898	4903	4908	4913	4918	4923	4928	4933	4938	4943	4948	4953	4958	4963	4968	4973	4978	4983	4988	4993	4998	5003	5008	5013	5018	5023	5028	5033	5038	5043	5048	5053	5058	5063	5068	5073	5078	5083	5088	5093	5098	5103	5108	5113	5118	5123	5128	5133	5138	5143	5148	5153	5158	5163	5168	5173	5178	5183	5188	5193	5198	5203	5208	5213	5218	5223	5228	5233	5238	5243	5248	5253	5258	5263	5268	5273	5278	5283	5288	5293	5298	5303	5308	5313	5318	5323	5328	5333	5338	5343	5348	5353	5358	5363	5368	5373	5378	5383	5388	5393	5398	5403	5408	5413	5418	5423	5428	5433	5438	5443	5448	5453	5458	5463	5468	5473	5478	5483	5488	5493	5498	5503	5508	5513	5518	5523	5528	5533	5538	5543	5548	5553	5558	5563	5568	5573	5578	5583	5588	5593	5598	5603	5608	5613	5618	5623	5628	5633	5638	5643	5648	5653	5658	5663	5668	5673	5678	5683	5688	5693	5698	5703	5708	5713	5718	5723	5728	5733	5738	5743	5748	5753	5758	5763	5768	5773	5778	5783	5788	5793	5798	5803	5808	5813	5818	5823	5828	5833	5838	5843	5848	5853	5858	5863	5868	5873	5878	5883	5888	5893	5898	5903	5908	5913	5918	5923	5928	5933	5938	5943	5948	5953	5958	5963	5968	5973	5978	5983	5988	5993	5998	6003	6008	6013	6018	6023	6028	6033	6038	6043	6048	6053	6058	6063	6068	6073	6078	6083	6088	6093	6098	6103	6108	6113	6118	6123	6128	6133	6138	6143	6148	6153	6158	6163	6168	6173	6178	6183	6188	6193	6198	6203	6208	6213	6218	6223	6228	6233	6238	6243	6248	6253	6258	6263	6268	6273	6278	6283	6288	6293	6298	6303	6308	6313	6318	6323	6328	6333	6338	6343	6348	6353	6358	6363	6368	6373	6378	6383	6388	6393	6398	6403	6408	6413	6418	6423	6428	6433	6438	6443	6448	6453	6458	6463	6468	6473	6478	6483	6488	6493	6498	6503	6508	6513	6518	6523	6528	6533	6538	6543	6548	6553	6558	6563	6568	6573	6578	6583	6588	6593	6598	6603	6608	6613	6618	6623	6628	6633	6638	6643	6648	6653	6658	6663	6668	6673	6678	6683	6688	6693	6698	6703	6708	6713	6718	6723	6728	6733	6738	6743	6748	6753	6758	6763	6768	6773	6778	6783	6788	6793	6798	6803	6808	6813	6818	6823	6828	6833	6838	6843	6848	6853	6858	6863	6868	6873	6878	6883	6888	6893
----------------------------------	---	---	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------

Biodegradation by Semi-Continuous Acidified Sludge Treatment

U.S. 405

Maternal: 4 roci 12.22

[illegible]

Sampling Date (After Feeding)	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20	21	22	23	24	25	26	27	28	29	30	31	32	33	34	35	
M ₁ Aroclor 1242 Fed. Every 24 Hours	1.0	→																																		
M ₂ Aroclor 1242 in Mixed Ligand After Feeding		6.30	3.34	2.24																																
M ₃ Aroclor 1242 in Mard Liquor 21 Hours later		4.08	4.12	2.06																																
Decrease in Aroclor 1242 over 24 Hrs (M ₁)		2.22	-0.78	1.98																																
Disappearance Rate (%)		35	-22	32																																
Std dev. volume, ml	110	110	125	125	120	100	100	120	115	120	125	225	200	210	230	240	240	240	-	250	225	220	260	260												
Suspended solids, mg/l					250																															
Mixed Ligand, Percent		7.51	7.35	7.52	7.50	7.51	-	7.58	7.52	7.52	7.48	7.32	-	-	7.47	7.59	7.48	7.55	7.55	-	7.47															
Disappearance Rate (%)	70.5	→																																		

Bioassay by Semi-Continuous Activated Sludge Treatment
Material: MCS 1016

Unit No. 8

Sampling Date (After Feeding)	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20	21	22	23	24	25	26	27	28	29	30	31
Mg MCS 1016 Fed Every 24 Hours									1.0																				
Mg MCS 1016 in Mixed Liquor After Feeding									1.44	0.91																			
Mg MCS 1016 in Mixed Liquor 21 Hrs Later									1.36	0.38																			
Decrease in MCS 1016 over 21 Hrs (Mg)									0.13	0.53																			
Disappearance Rate (%)									9	58																			
Sludge Volume, ml	170	175	185	190	205	180	175	170	160	160	160	200	170	200	205	210	205	200	210	210	185	200	210	200	200	200	200	200	200
Suspended Solids, mg/liter																													
Mixed Liquor Return, ml																													
PH	7.50	7.40	7.38	7.32	7.37	7.21	7.33	7.40	7.44	7.48	7.49	7.49	7.51	7.48	7.47	7.44	7.40	7.40	7.40	7.46	7.32	7.52	7.52	7.52	7.52	7.52	7.52	7.52	7.52
LAS Disappearance Rate (%)																													
Sampling Date (After Feeding)	26	27	28	29	30	31	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20	21	22	23
Mg MCS 1016 Fed Every 24 Hours	1.0	1.0	1.0	1.0	1.0	1.0	1.0	1.0	1.0	1.0	1.0	1.0	1.0	1.0	1.0	1.0	1.0	1.0	1.0	1.0	1.0	1.0	1.0	1.0	1.0	1.0	1.0	1.0	1.0
Mg MCS 1016 in Mixed Liquor After Feeding	4.32	6.75					5.62	10.25	12.09	15.75																			
Mg MCS 1016 in Mixed Liquor 21 Hrs Later	4.16						10.24	11.87	8.41																				
Decrease in MCS 1016 over 21 Hrs (Mg)	0.06						4.62	1.62	4.68																				
Disappearance Rate (%)	1						92	16	35																				
Sludge Volume, ml	200	200	190	200	175	180	190	190	190	195	145	130	135	150	155	150	130	130	160	140	140	140	140	140	140	140	140	140	140
Suspended Solids, mg/liter	2780																												
Mixed Liquor Return, ml	190	45	130				20	40	40	45	340																		
PH	7.45	7.40	7.53	7.52	7.48	7.41	7.43	7.53	7.48	7.52	7.56	7.62	7.62	7.55	7.48	7.49	7.51	7.60	7.70	7.60	7.53	7.47	7.43						
LAS Disappearance Rate (%)																													

Biodegradation by Semi-Continuous Activated Sludge Treatment
Maternal: MCS 1016

U.S. 2.3

[illegible]