

EAGLE-EPKCHER

Sept. 1, 1978

890183

TABLE 2—
SPECIFICATION INDEX

TABLE 3—CAPITAL
RECOVERY FACTOR

PRICE BOOK

* Ceramic Block and PV Block Laminates. (NOTE: The actual temperature may be limited by the interface temperature between the Ceramic and PV Block. For temperatures above 1500°F., consult Eagle-Picher General Sales or Research Department for specific recommendations.)

Specified Type	1850	1200	1400	1600	1800	2200
Fin Material, "Pachibin"						
Fin Material, "Sand-Rite"						
Fin Material, "Rigid"	MT Board(s)	EPITHERM 1200 Block		Superthin Board	PV Block	Ceramic Block Expansion Joint Board
Pipe Covering		EPITHERM 1200 Molded Pipe Covering	Tab-Lok			
Lease Flow			H-2, H-4 or 7-8			
Specialty Products						MTB

Normal Temperature Limit, °F.

TABLE 1
INSULATION MATERIAL SELECTION GUIDE — SERVICE TEMPERATURE INDEX

SURFACE SENSITIVITY, C. 0.12
(Example — Smooth Aluminum)

TABLE 2—
SPECIFICATION INDEX

TABLE 3—CAPITAL
RECOVERY FACTOR

PRICE BOOK