

MDP 60

Sheet 8 of 8

DATE Oct 5 1983 Dupont 19H

MASTROLIANI & FORMAROLI INC.
CERTIFIED SHORTHAND REPORTERS

Chambers Works Mechanical Department

September 17, 1980

PROCEDURE

ASBESTOS CONTROL

12. ELIMINATION OF ASBESTOS IMPREGNATED MATERIALS

- A. The Mechanical Department will, with the assistance of the Logistics Department, maintain a current listing of all maintenance materials containing asbestos. All new requests for Stores stocking of asbestos-bearing material will be reviewed by the Mechanical Asbestos Compliance Committee.
- B. All Mechanical personnel shall continue to seek asbestos-free substitutes for maintenance materials.

13. IDENTIFICATION PROCEDURE FOR NEW INSTALLATIONS

- A. All new installations which use Du Pont Codes 102 and 102.1 calcium silicate shall be identified according to Standard Engineering Specification SN-218-P (attachment "G"). Careful use of this procedure will eliminate unnecessary "white goods" identification in future years.


The identification tape may be purchased from Miscellaneous Stores. Stores Codes are:

Non-Asbestos (N-A) Tape - 32-48-990
Asbestos (ASB) Tape - 32-48-991

- B. Repairs to pipe or equipment insulation require identification as stated in "A" above. Where braided asbestos covering has been used on steam tracer loops, it should be replaced if practical. If the braided asbestos covering is not replaced, the asbestos identification tape should be used to indicate that it is asbestos. The tape should be applied at each joint or loop that is asbestos on the pipe or equipment.

14. REFERENCES

- A. This MDP is based on:
 - 1. Du Pont Engineering Standard S-4-T.
 - 2. O.S.H.A. Regulations, Section 1910:1001.
 - 3. National Emissions Standard for Asbestos (40 CFR 61.20-61.25); and
 - 4. O.S.H.A. Program Directive #300-16.

AUTHORIZED: 

General Superintendent,
Mechanical

Date: 12/11/80

Approved:

DUP 0905890

121420