PLAINTIFF'S EXHIBIT

USG-1783



NEW! USG® Acoustical Sealant

- for caulking partition perimeters, service cutouts
- long-lasting seal—reduces sound transmission
- exceptional adhesion and flexibility
- non-hardening, non-staining
- easy to apply, easy to clean up.

New USG Acoustical Sealant is a superior sealing compound for reducing sound transmission in partition systems. Can be applied to achieve specific STC values. Seals sound leaks at perimeters of partitions or around cutouts at electrical boxes and telephone installations. Surface dries to a tough film. Sealant remains flexible to form a long-lasting, resilient seal. Can be painted. 1-qt. cartridges and 5-gal. cans. See your U.S.G. man, or write us at 101 S. Wacker Dr., Chicago, Ill. 60606, Dept. 122.

DURABOND 200 Adhesive: Solvent-based. For wallboard application to wood or metal framing. 1-qt. cartridges and 5-gal. cans.

DURABOND 300 Adhesive: Water-based. For wallboard application to wood or metal framing and polystyrene rigid foam insulation. 1-qt. cartridges and 5-gal. cans.

DURABOND 400 Adhesive: Water-based. For application of prefinished wall paneling to wood or metal framing, furring or existing wall surfaces. 1/10-gal. and 1-qt. cartridges and 5-gal. cans.

DURABOND 500 Adhesive: Water-based. For laminating gypsum wallboard to gypsum board, monolithic concrete, concrete block, wood fiber board, expanded polystyrene or urethane rigid foam insulation and most other wall surfaces. 5-gal. cans.

DURABOND 600 Adhesive. Water-based. For contact lamination of gypsum wallboard in double layer systems. 5-gal. cans.

Reg U.S. Pat. Off.

UNITED STATES GYPSUM

BB029 0415

APPROVALS
JC 3/12
BS 3/13

GEYER, OSWALD, INC.
Ad No. 06-2268A-20
1 pg., b/w
Ill. Bldg. News, Apr. 70
Retail Lumberman, Apr. 70
Ia. Lumber Dealer, Apr. 70
Lumber Cooperator, Apr. 70
Lumber Merchant, Apr. 70
Wood Construction, May 70
The Plan, May 70
N.W. Lumber Dealer, May 70
UNITED STATES GYPSUM