



Air Products and Chemicals
INC.

ESCAMBIA PLANT
INTEROFFICE MEMORANDUM

RECEIVED
MAR 17 1975
H. L. WATSON

To: Howard Watson

Date: 12 March 1975

From: Dale H. Francke

Copies:

J. T. Barr
R. E. Jones
E. A. Primeau

Re: Visitor Information Sheet
for PVC Plant Admittance

Attached is a copy of the proposed information sheet which will be given to visitors at the Escambia PVC Plant. Plans are to include this sheet in our unit operating procedure, which is being typed.

Please comment on the attached form. If it is not satisfactory, please supply me with an acceptable form which we can use for our procedures manual.

Dale H. Francke
Dale H. Francke

/ms
Attachment

Handwritten notes:
Xerox to Dale Francke
w/ copies to:
① Kramm
② Speed
③ Primeau
④ Jones
⑤ Schantz
⑥ W. & Willard
⑦ T. C.
⑧ Barr
⑨ H. L. Watson
Your instructions are very well thought out except that, according to our latest legal interpretation, we cannot have anyone entering the area who has not had a year medical exam & has been certified by the phys. to enter the area. We are asking for an interpretation from OSHA but in the meantime, I assume we must have visitors after 1 April 75.
Dale

AP00050157

NOTICE TO ALL VISITORS

You are entering an area that may contain vinyl chloride (VCl). It is a sweet smelling gas that will deaden your sense of smell after breathing it a few times. If you smell this, immediately leave the area, since continued breathing of the fumes will cause unconsciousness.

You have been issued an air mask which will be required in the event area levels of VCl become higher than the OSHA permissible level. All operations and procedures are designed to stay below these levels, but in the event the alarm system does indicate a high level you will be required to use the air mask or leave the area immediately. Follow the procedure below in using the air mask:

HOW TO USE THE AIR MASK:

Putting on the Facepiece:

1. Attach filter body to belt using belt clip.
2. Make sure all head straps are fully extended.
3. Using both hands - Grasp together one temple strap and one cheek strap in each hand.
4. Place the chin into position in the facepiece. (See Figure 1.)
5. Draw the head straps over the head, be sure they all lay flat against the head.
6. Simultaneously draw up and back - both CHEEK (bottom) straps. (See Figure 2.)
7. Simultaneously draw-up and back - both TEMPLE (middle) straps.
8. Place palm of either hand on the junction point where the straps join, push DOWN toward the back of the neck. This exerts a pull on the TOP strap or straps lifting the facepiece into proper position.
9. Repeat steps 6 and 7, taking up any slack or looseness.
10. Adjust TOP strap or straps ONLY if necessary to securely hold the facepiece comfortably and safely in position.

OSHA regulations require that you be instructed that Vinyl Chloride is a cancer-suspect agent.

March 12, 1975

AP00050158

