

8 HERN 8 EMI-CLO 88

Recommended for walls, ceilings, furniture and woodwork in kitchens, bathrooms, breakfast nooks, bedrooms, or any other room in the house where a velvet-like washable finish is desired. Its ability to withstand repeated washing makes it ideal for hospitals, hotels, offices, schools.

DIRECTIONS

Self-Thoroughly With a Lifting Motion

UNION PLASTER SURFACES.—The sure mixture is dry and free from dirt, grease and oil. It is made by mixing one part of the plaster with one part of the water, and one part of the sand. The mixture should be applied in a thin coat, and the surface should be finished with a trowel. The plaster should be allowed to dry for 24 hours before the surface is painted. The plaster should be applied in a thin coat, and the surface should be finished with a trowel. The plaster should be allowed to dry for 24 hours before the surface is painted.

NEAR OVERTAKE AND START ACROSS—On unpaved well made dirt unit all water feeding from washing has dried out. For first coat apply Interior Base Coat. Allow to dry overnight then apply a mixture of one-half Sherwin-Williams and one-half of Interior Base Coat. After this has dried 24 hours apply a finishing coat of Sherwin-Williams. As it comes from the can. On woodwork use Under-Name! (Zinnel Undercoat) in place of Base Coat.

Percent: 41.3% - Thrium Calcium 100%

"DIXIE MADE FOR DIXIE TRADE"

Climatic

SHEEN SEMI-GLOSS

4600 WHITE

THE AMERICAN PAINT WORKS
DIVISION
THE GLIDDEN COMPANY
* NEW ORLEANS, LOUISIANA *

TIME

PAINTS • VARNISHES

SHEEN
Recommended for walls, ceilings, fern
breakfast nooks, bedroom, or any
washable finish is desired. Its ability
for hospital, hotels, offices, schools.
DIR
But Thoroughly With a Lifting Motion.
ON PLASTER SURFACES—Be sure a
new plaster or cement
has been thoroughly
smoothed and
dried. On (UNPAINTED) ZIN
COATED SURFACES—WALLS,
are and repeated washings, apply a co
recommended for New Unpainted Surface
of Sheen Semi-Gloss is often sufficient.
first coat of Sheen Semi-Gloss mixed w
this to dry then apply a coat of Sheen Se
work in place of the first coat. Under
NEW UNPAINTED SURFACES—On fin
is thoroughly smoothed. For fin
evening then apply a mixture of each
Base Coat. After this has dried 24 hour
as it comes from the can. On woodw
in place of Base Coat.