PLAINTIFF'S EXHIBIT

KG-168

KAISER GYPSUM

# PRE-MIX DUAL PURPOSE JOINT COMPOUND

net weight
62 POUNDS

SAB041802A-001

Chron

PANEL 1

KAISER
GYPSUM

5 LB .

3-PURPOSE
JOINT
COMPOUND

FOR DRYWALL TAPING, FINISHING, AND TEXTURING

A PRODUCT OF KAISER GYPSUM COMPANY, INC.
300 LAKESIDE DRIVE, OAKLAND, CALIF. 94604

4-26-73

SAB041802A-002

PANEL 2

CAUTION

CONTAINS ASBESTOS FIBER
AVOID CREATING DUST
BREATHING ASBESTOS DUST MAY CAUSE SERIOUS BODILY HARM

Above label is in compliance with Federal Regulations relating to Occupational, Safety, and Health Standards 29 OFR 1910.93a.

How to mix:

Using a clean container, slowly add contents of this carton to 3 pints of clean water at a temperature of 60 to 80°F. ALLOW MIX TO STAND FOR THIRTY MINUTES. Before using, stir again to insure uniform consistency.

PROPER CONSISTENCY is reached when paste is just plastic enough to be worked and handled easily.

IMPORTANT: Mix with clean, cool or lukewarm water only. Do not use hot or dirty water for mixing.

IMPORTANT NOTE TO PURCHASER: Inasmuch as conditions and methods of use and application of this product are beyond our control, Kaiser Gypsum Company, Inc. will not be liable or responsible for any failure of this product when the same is not used in strict accordance with directions contained hereon.

A PRODUCT OF KAISER GYPSUM COMPANY, INC.
300 LAKESIDE DRIVE, OAKLAND, CALIFORNIA 94604

SAB041802A-003

PANEL 3

How to use:

1. Maintain a minimum of 55°F. with adequate ventilation in the structure during application and drying.
2. Spread joint compound evenly over the joint with a 4" or wider broadknife.
3. Press tape firmly into compound with a broadknife, keeping tape centered over the seam. Avoid air bubbles beneath tape. Wipe off excess compound with broadknife.
4. All nailheads should have been slightly "dimpled" below surface of the board. Fill indentions and cornerbead with a coat of compound.
5. When first coat is dry (at least 24 hours), apply a second coat. Feather edges out beyond the tape until seam is eight to ten inches wide. Give nailheads a second coat.
6. When second coat is dry, apply a final thin layer of compound over the seam, feathering edges until the seam is ten to twelve inches wide. Give all nailheads a final coat of compound. Both joint and nailhead surfaces should now be smooth and flush with surface of board.
7. When completely dry, smooth lightly with sandpaper where necessary.

DECORATION: Allow compound to dry thoroughly before decorating. For best results, apply a water emulsion-type sealer over the entire surface and allow the sealer to dry thoroughly.

TEXTURING: A wide range of texture patterns can be obtained by texturing the sealed surface with one or more of the following tools: (1) Brush. (2) Roller. (3) Sponge. (4) Whisk Broom (5) Wadded newspaper or cloth. (6) Scrub Brush. A celluloid triangle may be lightly drawn over a textured area to flatten high spots and produce a brocade effect. A sand finish can be obtained by adding a few handfuls of white silica sand to the material.

A PRODUCT OF KAISER GYPSUM COMPANY, INC.
300 LAKESIDE DRIVE, OAKLAND, CALIFORNIA 94604

PANEL 4

Contents:

5 POUND
PACKAGE

KAISER 3-PURPOSE JOINT COMPOUND

A PRODUCT OF KAISER GYPSUM COMPANY, INC.
300 LAKESIDE DRIVE, OAKLAND, CALIFORNIA 94604

5

TOP BOX PANEL

KAISER
GYPSUM

3-PURPOSE
JOINT
COMPOUND

SAB041802A-006

CAUTION

## How to mix:

A PRODUCT OF KAISER GYPSUM COMPANY, INC.
300 LAKESIDE DRIVE OAKLAND, CA 94604

## How to use:

APPLICATION:

DECORATION:

TEXTURING:

A PRODUCT OF KAISER GYPSUM COMPANY, INC.
300 LAKESIDE DRIVE OAKLAND, CA 94604

SAB041802A-007

4

**Contents:**

# 5 POUND PACKAGE

5 LBS. OF KAISER 3-PURPOSE JOINT COMPOUND

A [illegible] KAISER GYPSUM COMPANY, INC.
300 LAKESIDE DRIVE, OAKLAND [illegible] 94604

# KAISER GYPSUM

## 5LB 3-PURPOSE JOINT COMPOUND

USED TO ATTACH [illegible] FINISHING, SPOTTING [illegible] TEXTURING

[illegible]

SAB041802A-008

LOGO

PRE-MIX
DUAL-PURPOSE
JOINT
COMPOUND

Recommended for use in gypsum drywall construction to embed reinforcing tape and to finish and conceal joints and nailheads.

DIRECTIONS FOR USE

This compound has been mixed by the manufacturer to a standard consistency. If a thinner mix is desired, thin with clean, cool water only, up to one quart per pail of compound. Re-mix before use if any liquid has separated from compound in storage. Protect from freezing. Store in a warm area for at least 24 hours before use. Allow compound to dry thoroughly between coats. Maintain a minimum temperature of 55° F with adequate ventilation in the structure during application and drying.

DECORATION

Allow compound to dry thoroughly before decorating.

For a skip trowel textured surface, apply Kaiser Cover-Tex wall texture, allow to dry, and then apply an emulsion type sealer prior to painting.

For a spray texture containing aggregate, for other full texture applications, for an enamel finish, or for decoration with wallpaper, apply an emulsion type sealer over entire wall surface, allow to dry and then apply texture.

The sealer application may be omitted on specific recommendation by the paint manufacturer that their paint will produce satisfactory results without the use of a sealer.

IMPORTANT NOTICE TO PURCHASER

Inasmuch as conditions and methods of use and application of this product are beyond our control, Kaiser Gypsum Company, Inc., will not be liable or responsible for any failure of this product when the same is not used in strict accordance with our directions and specifications.

NONFLAMMABLE

KEEP OUT OF REACH OF CHILDREN

A PRODUCT OF KAISER GYPSUM COMPANY, INC.
OAKLAND, CALIFORNIA 94666

SAB041802A-009