

EMPIRE

Super Quality

*Built to endure
severe weather*


*Made for easy
application*

HOUSE PAINT

GLD01822

CAPE COD RED

it on
metal
stone
lasting



EMPIRE SUPER QUALITY HOUSE PAINT

Stir the paint thoroughly before and occasionally while using. When desiring to mix a large container of paint, it is advisable to pour the top liquid in the can into another container—stir the remaining pigment and liquid to a paste, and then gradually while stirring return the removed liquid to this container. Be sure all pigment and liquid is thoroughly mixed.

Remove peeling, loose or blistered paint with a wire brush or sandpaper. Be sure surface is clean and dry. If two or more coats are to be applied, thin the first coat with paint thinner, or turpentine, in proportion of one pint to the gallon of paint. The succeeding coat may be applied full body. Putty nail holes between first and second coat. Shellac all knots and sappy places before painting. Allow ample drying time between coats. On bare or badly weathered wood, prime with Empire Super Quality House Paint Primer.

CAUTION! COMBUSTIBLE—Keep from heat and open flame. Avoid breathing vapor or spray mist and prolonged contact with skin may cause skin irritation. Do not take internally—may contain compounds harmful if eaten. Keep container closed when not in use. Keep Out of the Reach of Children. **USE WITH ADEQUATE VENTILATION.** (1-361)

1060

1 U. S. Gal. or 128 Liq. Oz.

THE A. WILHELM COMPANY

Reading, Pennsylvania, U.S.A.

GLD018259

ANALYSIS		Contains added fungicide to make this paint resistant to the action of Mildew Fungi growing in or on the paint. Resistant to Mildew on the Paint Film Only.	
Iron Oxide	14.1%	Linseed Soya Alkyd Resin	57.7%
Calcium Carbonate	30.1%	Active Ingredient (Tetrachlorephenol)	2.1%
Silica	1.6%	Inert Ingredients	37.9%
Mineral Spirits	19.4%		
Driers			
Mildew Preventive	2.1%		