

LEAD INDUSTRIES ASSOCIATION

480 LEXINGTON AVENUE
NEW YORK 17, N. Y.

Pigments and Chemical Division

May 7, 1954

Subject: Re-run of Project 20

To: Mr. R. F. Bates
Dr. L. L. Carriak
Mr. G. Dishman
Mr. H. Garlock
Mr. C. Lomineka
Mr. C. J. Vander Valk
Mr. P. Whitford

Gentlemen:

The consensus of the committee on the re-run of Project 20 is as follows;

The members of the committee are not in favor of company by company comparisons.

The red lead used for the bulk of the tests should be 97% grade, fumed type.

Additional tests should be made over standard wash primer only with the following:

1. 97% grade, furnace type
2. 95% grade, fumed type
3. 95% grade, furnace type.

I have arbitrarily selected National Lead Co. red lead for all the tests. Mr. Bates has agreed to provide such quantities as Mr. Shobe may not have on hand.

It was further deemed advisable to make the following comparisons at, because of his closeness to the subject, the discretion of Mr. Shobe.

1. Check of different sources of resin to be used in P-10 type formulation.
2. Comparison of the effects of different solvents on blistering.

All of the tests will be carried out in accordance with these suggestions.

Thank you for your comments.

Sincerely,

Charles E. Cherry Jr.
Charles E. Cherry Jr.

