

Utility Fan Corporation

A Division of Utility Appliance Corp.
911 East 59th Street, Los Angeles 1, Calif.


Cable Address: UTILIFAN, Los Angeles

Manufacturers of heavy and standard duty blowers for heating, air conditioning and ventilating installations. Producers of blowers and blower parts for original equipment manufacturers.


Built, tested and rated in accordance with ASHVE and NAFM codes.

Sizes 6 inches to 60 inches.


Write for catalog data.




Heavy duty blower, Type "B" backward curved DWDI.



Enclosed Drive Blower



Four-Way Blower



Silent Direct Drive Blower

HEAVY DUTY BLOWERS, Double Inlet Double Width and Single Inlet Single Width, Forward and Backward Curved Wheels. Wheel diameters range in size from 12 inches to 60 inches. These blowers are of Class I construction, in any of ten drive arrangements and eight discharge positions.


NEW ENCLOSED DRIVE BLOWERS, sizes 10 inches to 36 inches, with fully enclosed drive compartment. Ideal for roof installation. The ED blowers are of the forward curved slow speed type, built for ease of installation and a minimum of maintenance.

UTILITY'S FAMOUS "FOUR WAY" BLOWERS, designed by Utility, available in single width single inlet as well as double width double inlet. A simple change in bearing position makes it possible to obtain discharges in any of four directions. An economy unit for medium duty use, rigidly constructed and factory guaranteed.


NEW SILENT DIRECT DRIVE BLOWER. By using vibration-absorbing Neoprene in the basic hub design, the blower wheel is isolated from the motor shaft. This unique development produces a very quiet blower. The direct drive blower is available in three wheel sizes providing a varied range of capacities, depending on motor horsepower selected.

Union Asbestos & Rubber Company


332 S. Michigan Ave., Chicago 4, Illinois
HEATING AND COOLING PRODUCTS



The UNARCO  **ROYAL-AIRE** (CU series) provides full comfort cooling range. Refrigerant flow through vertical coil is thermostatically controlled, utilizing UNARCO "pump-down" control system. Oversize vari-flow blower and oversize condenser, plus large "fin area" cooling coil, insure full-rated capacity.




The UNARCO  **CEILING SUSPENDED UNIT** (CS series) is a completely self-contained unit available in 2-, 3-, 5- and 7½-ton capacities.




The UNARCO  **COMPLETE AIR CONDITIONING PACKAGE** for stores and industrial plants (series AEC) is available in capacities from 5 to 60 tons. It is of single cabinet construction, with packaged condensing unit, blower coil section and evaporative condenser.



UNARCO  **HORIZONTAL AND DOWNBLOW UNIT HEATERS** (down-blow shown) include die-formed cabinets of not less than 20 gauge steel. Casings are phosphatized and finished in hammer enamel, baked on for permanence.



UNARCO  **WALL RADIATION**. Covers are of 14, 16 and 18 gauge steel in sloping top, flat top and expanded metal styles. Available in 2 ft to 10 ft lengths in 6 in. increments. Elements range from 2 ft to 12 ft in 6 in. increments. Accessories available.



UNARCO  **CONVECTOR RADIATORS**. Cabinets are phosphatized, finished in prime gray paint, and constructed of furniture quality steel. Also available in other models. Elements consist of cast brass headers, aluminum fins, copper tubes and 20 gauge side plates.