Produced in camera under seal by order Judges Paul Riley and Gordon Maag, October 16, 1989, in Jackson v. A P C et al. 87-41230

PLAINTIFF'S EXHIBIT FK-113

OC-42-1-OC 8488

OWENS-CORNING FIBERGLAS

PURCHASE ACCEPTANCE STANDARDS

No. CRM.59.1.4

Date 6/15/62

Supersedes 6/30/6

MATERIAL - Roofing Cement (Flintkote #224 Cutback Asphalt)

SCOPE

This specification covers the necessary data for ordering a lightly fabricated cutback cement for use as an adhesive between plies and to deck.

A. DESCRIPTION

Roofing Cement is composed of lightly fibrated cutback of 25 penetration asphalt designed primarily for spray application.

B. PROPERTIES

	Rutherford	New Orleans	Chicago Heights
Asphalt %	48.6-52.6	47.5-51.5	47.1-51.0
Asbestos %	11.4-12.6	10.0-11.0	10.4-11.4
Ash %	9.4-11.0	8.2-9.6	8.6-10.0
Volatiles %	35.1-39.7	37.6-42.6	37.6-42.4
Weight/Gal., Lbs.	7.9-8.2	7.5-8.3	7.4-7.7

C. CONTAINER SIZES

1 gallon - 6 per carton
5 gallon container
30 gallon drum
55 gallon drum

D. LABELS

Each container shall be neatly labeled with OCF Label No. L.1.214.

E. WARRANTIES

Manufacturer to warrant material meets these specifications and will replace material not in accordance with specification.

01 061 1194