

FROM A. A. DOHMANN

~~TO~~ MR. R. M. ROSE

cc: Mr. N. E. Myers
Mr. L. Morish

November 26, 1975

PLAINTIFF'S
EXHIBIT
AL-871


RE: ROD MILL DRIVE LOCK OUT, BUILDING R-25

As requested, this letter is to confirm the desired procedure to be used when it is necessary to safely immobilize the rod mill. This letter deals only with the rod mill immobilization and does not cover other necessary safety procedures such as blinding of pipe, entry permits, locking of the pan conveyor drive, etc.

Any time maintenance is performed to the rod mill feed chute internally, feed drum, rod mill, rod mill drive, rod mill discharge tube or slurry mixer, a yellow equipment tag, a white personnel danger tag and lock is to be affixed to the open main power switch for the rod mill drive motor. The locking apparatus should provide for installation of multiple locks.

Departmental locks should be provided for each maintenance person who will maintain possession of the key while performing maintenance to the above mentioned mechanical equipment. A master key for all area departments should be provided only to the responsible mechanical maintenance area supervisor.

This procedure was agreed upon at a meeting attended by yourself, N. E. Myers, L. Morish and the writer. This procedure was subsequently reviewed and agreed upon by the area mechanical maintenance personnel at the October area safety meeting.


A. A. DOHMANN

AAD:ga

ALCOA0001586

