


UNITED STATES RADIATOR CORPORATION
OVER 40 YEARS A GREAT NAME IN HEATING

General Office, Detroit 31, Mich.

Branches and Sales Offices in Principal Cities

The United States Radiator Corporation carries a complete line of hand, stoker, gas and oil-fired boilers for steam or hot water heating, warm air furnaces, gas burners and oil burners, radiators, baseboard convectors, controls and heating accessories for residential, commercial and industrial heating.




U.S. Radiant Baseboard

Designed to operate with forced circulating hot water systems, U.S. Radiant Baseboard replaces ordinary baseboard. It is light in weight, of all-steel construction and is roughed-in and installed exactly as standard radiator practice. Radiant surfaces, waterways and finned surfaces of U. S. Radiant Baseboard are copper brazed into a single pressure-tight unit. Exterior surfaces are specially treated, then protected with grey zinc chromate primer.


Packed in individual cartons, distinctly marked, U.S. Radiant Baseboard is shipped in unit lengths of 2 to 12-ft inclusive in increments of 1-ft. Write for catalog AR-29G.

U.S. Solar Flame Oil Burners are available for steam and hot water boilers and warm air furnaces. 3 models. Capacities from 0.6 to 15 gal/hr.



U.S. Gas-fired Boilers

U.S. Gas Boilers include a complete range of sizes and capacities from 480 to 12,480 sq ft for steam heating, and from 240 to 20,000 sq ft for hot water heating. U.S. Gas Boilers are furnished with necessary control equipment and are completely automatic in every operation. All units are A.G.A. approved.



U.S. 12
All-Fuels
Boiler


(Oil ratings shown. For coal-fired ratings, write for Catalog A-399.)

Boiler No.	I = B = R Net Ratings				I = B = R Gross Output 1000 Btu/hr
	D.C.I.R. Sq Ft		1000 Btu/hr		
	Steam	Water	Steam	Water	
12-30	230	430	55	65	86
12-40	310	570	74	86	114
12-60	390	715	94	107	143
12-80	470	855	113	128	171

U.S. Solar Flame Gas Conversion Burners are A.G.A. rated and are available for steam, hot water and warm air systems. 2 models. Capacities from 75,000 to 300,000 Btu's/hr.



U.S. Fin-Ray
Baseboard
Radiation



U.S. Solar Flame
Gas Burners

U.S. Fin-Ray Baseboard Radiation for homes and offices is furnished in 1 in. and 1-1/4 in. pipe sizes. For commercial applications U.S. Fin-Ray Commercial Radiation is furnished 1-1/4 in. and 2 in. pipe sizes. Write for catalogs AR 319B (Baseboard) and AR 318 (Commercial) for data and specifications.

THINTUBE RADIATORS

3-Tube		5-Tube	
Heights In.	Per Section Heating Surface	22	2.1 Sq Ft
25	1.6 Sq Ft	25	2.4 Sq Ft
4-Tube		6-Tube	
22	1.8 Sq Ft	19	2.3 Sq Ft
25	2.0 Sq Ft	25	3.0 Sq Ft
		32	3.7 Sq Ft
1½ in. Centers.			

1 1/4 in. Centers.

UNITED STATES RADIATOR CORPORATION
OVER 40 YEARS A GREAT NAME IN HEATING


General Office, Detroit 31, Mich.

Branches and Sales Offices in Principal Cities

Member
Reg. U. S. Pat. Off.

U.S. 2 Oil-Fired Boilers

Boiler No.	I = B = R Net Ratings				I = B = R Gross Output 1000 Btu/hr
	D.C.I.R. Sq Ft		1000 Btu/hr		
	Steam	Water	Steam	Water	
2-03	350	645	84	97	129
2-04	500	910	120	137	182
2-05	650	1170	156	176	234
2-06	800	1425	192	214	285



U.S. 28 All-Fuels Boiler

(Oil ratings shown. For Stoker and Hand Fired ratings, write for Catalog A-417B)


28-30	850	1510	204	227	302
28-35	1055	1850	253	278	370
28-40	1260	2185	302	328	437
28-45	1470	2530	353	380	506
28-50	1690	2880	406	432	576
28-55	1900	3210	456	482	642
28-60	2120	3560	509	534	712
28-65	2340	3900	562	585	780
28-70	2570	4255	617	638	851
28-75	2800	4600	672	690	920



U.S. 46
Oil-Fired
Boiler

U.S. 46 Oil-Fired Boiler


46-3	310	570	74	85	114
46-4	400	730	96	110	146
46-5	550	995	132	149	199
46-6	700	1255	168	188	251



All Fuels
Boiler

(Oil ratings shown. For Stoker and Hand Fired ratings, write for Catalog A-417B)

21-30	400	730	96	110	146
21-35	500	910	120	137	182
21-40	600	1080	144	162	216
21-45	700	1255	168	188	251
21-50	800	1425	192	214	285
21-55	900	1590	216	239	318



U.S. 25
Oil-Fired
Boiler

U.S. 25 Oil-Fired Boiler

25-3	545	985	131	148	197
25-4	905	1610	217	240	320
25-5	1265	2195	304	329	439
25-6	1625	2775	390	416	555
25-7	1985	3345	476	502	669

U.S. Vertical or Horizontal Unit Heaters



U.S. Vertical or Horizontal Unit Heaters are available with either 60 cycle AC or 25 cycle AC or DC motors in a wide range of sizes and capacities. Optional control equipment for special applications may be obtained at extra cost. Write for catalog.