

SALESMAN'S
HAND BOOK.

0007-SWP-040510

N22012

873
Handbook

0007-SWP-040511

0007-SWP-000123902

Salesman's Hand Book



0007-SWP-040512

0007-SWP-000123903

scrupulous parties have used various other substances, in whole or in part, as a substitute for Linseed Oil. Some of them have seemed at first to serve the purpose, but none have proved equal to the article they are imitating, and only result in reducing the actual value of the paint; therefore we must accept Linseed Oil as the chief vehicle for carrying the "coloring matter" (dry pigment) of the paint, and the only other liquids which should be used in connection with this are such as assist in the proper spreading, drying and hardening, to insure constant consistency, or to adapt a surface especially for subsequent special coats of paint or varnish, and none of the added liquids should be used in proportions larger or smaller than are required to cause in some manner the complete mixture best to fulfill the purpose for which it is intended.

Pigments

Now as to the "coloring matter," which we shall from custom term the pigments, meaning the dry material before uniting to the liquids. Their purpose is to give body or consistency and color to the prepared paint, and it is very important that as far as possible those pigments should be used which remain on the surface to which the paint is applied as long as possible, unharmed by exposure. Some of the principal pigments used are carbonate of lead, oxide

of zinc, oxides of iron (yellow ochre, Venetian Red, umbers, etc.), and several others, of both natural and artificial production. The characteristics of these articles are very imperfectly understood by the public. Unfortunately, works on these subjects have not been published in any great numbers, nor have they been introduced in any of our ordinary schools, and the indiscriminate use of paint pigment has been governed by the mercantile class only. So it is no wonder that the subject of paint in the scientific and chemical relations of its elements are so little known by the public generally. But times are changing, progress is being made in all directions. Quite a revolution has taken place in the last generation in the knowledge and use of the material we are discussing.

Many improvements have been made and are being made in paints. The color of a desired paint being decided upon, to select such materials as are best suited to the ultimate ends and the use of them in such proportions one to the other as also secures the desired results, is where the manufacturer or manipulator finds employment for his best skill. The all important element, Linseed Oil, which has already been quite fully explained, being accepted as the life-giving element of the paint, the object should be to unite with the all such pigments in such pro-

0007-SWP-040513

0007-SWP-000123904

portions as will best withstand the influence brought to bear upon the painted surface, and prevent it from disintegrating and perishing, as every one knows it will, sooner or later.

White Lead

On a surface in the best possible condition it is desired and expected that the pigments and vehicles will remain united so as to wear out together. Now as most single pigments are, from their natural qualities, not best suited to all requirements, practical experience, backed up by scientific and chemical knowledge comes into play in choosing and uniting such pigments as will serve the purpose best. Nearly all the best known pigments have their advantages and disadvantages. Take, for instance, the well known article, white lead. It has this advantage over others of great opacity or covering power, but then it has a disadvantage in that it requires more of it to cover a given surface than it does of some other white pigments, and if used uncolored darkens rapidly. Another great disadvantage is that when used alone on wood or any similar surface, after the linseed oil has lost its elasticity (which might be termed complete drying), it leaves the lead in the form of a dry powder, the nature of the particles of which are so small that they are liable to hold them together and to the surface, the paint is easily rubbed off by storms or otherwise. A common illustra-

tion of this fact is frequent where exteriors of buildings have been covered with pure white lead paint, when say from a few months to two or three years one may, by rubbing the hand over the surface, find the white powdery lead coming off like flour. Almost countless instances of this have come to our notice, where the house owner who had believed that pure white lead was the best paint to use and so had taken pains to have it applied, seeing the result, in his ignorance of the real nature of the article has been ready to blame the manufacturer or the painter, believing the paint was not what was represented.

Now we may speak of the merits and demerits of another white pigment, namely, oxide of zinc. This in its nature is quite the opposite of lead in the matter of its particles, they having an affinity for each other, joining together and forming, as it were, an almost impervious film, so that even after the oil has dried out, if the surface was in good condition the film still remains. Another advantage of this pigment is, in consequence of the shape of its particles, a given quantity will spread over a far greater surface than other white pigments. Now what are the disadvantages of zinc? The only one of importance is not a fault when the surface on which the paint is used is in proper condition, but when applied to porous surfaces after the oil has become

completely dry, heat and cold acting differently on the outside surface and in the structure back of the film of paint something must give way, and naturally the film of paint cracks and peels off in pieces instead of powder, as in the case of lead. The reader should not conclude from this that all instances of paint peeling off result from the use of zinc. Far from it. There are other causes. Comparing the two pigments as above, we have fairly illustrated the characteristics of other pigments, and yet there are others that have certain merits over either the above, but possessing other faults, or being of undesirable color, to derive benefit from them they must be used within certain limits, so that the final result will be a positive advantage. To go on further with illustrations of pigment would carry us into a great variety of color pigments beyond the scope of this article, inasmuch as when certain colors are demanded they must be used, because to change their character would change the color. After the above quite lengthy explanation of cause and effect in the component parts of paint, it must be obvious that we have not overrated the necessary intelligence required to take these materials and from the knowledge of results in their use, put them together in such proportions and in such a manner that the result is the durability and beauty of the painted sur-

face will be all that is possible in human power to accomplish.

There are many reasons why paints prepared by machinery are better than paints prepared by hand. *Machinery vs. hand made*

Remember in paint making, as in every other line of business, the world has progressed, and is progressing. Things have changed; they have advanced; they have improved.

People not so long ago, used to grind their own corn, spin their own yarn. They used to burn candles and travel by stage coach. They don't now. *Candles*

When a woman spun her own yarn, and ground her own corn, she felt she could do this work better than it could be done for her by machinery. She had been doing it so long and had become so accustomed to it, she could not all at once, trust it to anybody else.

It's the same with paint. Painters have been so long mixing their own paint, in their own way, it's hard for them to believe it can be done as well in any other way. *Painters*

Habit is strong. But improvements always make their way. It's the world's habit to progress—it's the survival of the fittest all the time. *Progress*

Paints prepared by machinery are an improvement over paints prepared by hand, and they will make their way—just as sure as the sun rises and sets.

*A comparison with
Lead and
Oil*

THE following comparative table shows the difference between the Lead and Oil process and Perfect Method, and gives number of coats and number of days between each coat of each on bodies.

LEAD AND OIL.		PERFECT METHOD.	
NO.	COPIES.	NO.	COPIES.
1.	Priming	1.	Priming
2.	Putty	2.	Putty
3.	Sand Paper		
4.	Oil Lead		
5.			
6.			
7.			
8.			
9.			
10.			
11.			
12.			
13.	Rub over	13.	Coat Body Filler
14.	Let Stand	14.	Coat Body Filler
15.		15.	Coat Body Filler
16.		16.	Coat Body Filler
17.		17.	Coat Body Filler
18.		18.	Coat Body Filler
19.		19.	Coat Body Filler
20.		20.	Coat Body Filler
21.		21.	Coat Body Filler
22.		22.	Coat Body Filler
23.		23.	Coat Body Filler
24.		24.	Coat Body Filler
25.		25.	Coat Body Filler
26.		26.	Coat Body Filler
27.		27.	Coat Body Filler
28.		28.	Coat Body Filler
29.		29.	Coat Body Filler
30.		30.	Coat Body Filler
31.		31.	Coat Body Filler
32.		32.	Coat Body Filler
33.		33.	Coat Body Filler
34.		34.	Coat Body Filler
35.		35.	Coat Body Filler
36.		36.	Coat Body Filler
37.		37.	Coat Body Filler
38.		38.	Coat Body Filler
39.		39.	Coat Body Filler
40.		40.	Coat Body Filler
41.		41.	Coat Body Filler
42.		42.	Coat Body Filler
43.		43.	Coat Body Filler
44.		44.	Coat Body Filler
45.		45.	Coat Body Filler
46.		46.	Coat Body Filler
47.		47.	Coat Body Filler
48.		48.	Coat Body Filler
49.		49.	Coat Body Filler
50.		50.	Coat Body Filler
51.		51.	Coat Body Filler
52.		52.	Coat Body Filler
53.		53.	Coat Body Filler
54.		54.	Coat Body Filler
55.		55.	Coat Body Filler
56.		56.	Coat Body Filler
57.		57.	Coat Body Filler
58.		58.	Coat Body Filler
59.		59.	Coat Body Filler
60.		60.	Coat Body Filler
61.		61.	Coat Body Filler
62.		62.	Coat Body Filler
63.		63.	Coat Body Filler
64.		64.	Coat Body Filler
65.		65.	Coat Body Filler
66.		66.	Coat Body Filler
67.		67.	Coat Body Filler
68.		68.	Coat Body Filler
69.		69.	Coat Body Filler
70.		70.	Coat Body Filler
71.		71.	Coat Body Filler
72.		72.	Coat Body Filler
73.		73.	Coat Body Filler
74.		74.	Coat Body Filler
75.		75.	Coat Body Filler
76.		76.	Coat Body Filler
77.		77.	Coat Body Filler
78.		78.	Coat Body Filler
79.		79.	Coat Body Filler
80.		80.	Coat Body Filler
81.		81.	Coat Body Filler
82.		82.	Coat Body Filler
83.		83.	Coat Body Filler
84.		84.	Coat Body Filler
85.		85.	Coat Body Filler
86.		86.	Coat Body Filler
87.		87.	Coat Body Filler
88.		88.	Coat Body Filler
89.		89.	Coat Body Filler
90.		90.	Coat Body Filler
91.		91.	Coat Body Filler
92.		92.	Coat Body Filler
93.		93.	Coat Body Filler
94.		94.	Coat Body Filler
95.		95.	Coat Body Filler
96.		96.	Coat Body Filler
97.		97.	Coat Body Filler
98.		98.	Coat Body Filler
99.		99.	Coat Body Filler
100.		100.	Coat Body Filler

Under the Lead and Oil System you will notice (No. 6) half and half. This is a coat of half Lead and half Rough Stuff, which is used by most painters in custom shops, and takes the place of a coat of Rough Stuff. Some painters do not use a guide coat; where they do not it is not necessary to use it with Perfect Method.

It is barely possible that some painters will not give six days for priming to dry

with the Lead and Oil process, but more will give a longer time. You will notice under No. 12, in the Lead and Oil process we say "Rub out, two days"; where they wish to rush the work they may let it stand only one day after the last coat of Rough Stuff is applied before rubbing out, but oftener they would let it stand longer.

We have endeavored in this table to be as conservative as possible, as to the length of time required to do a first-class job in a custom shop with Lead and Oil and we have not shortened the time necessary to do a first-class job with Perfect Method. It is customary in both methods on custom work to give more than one coat of Clear Rubbing for a first-class job, but as the time for these coats should be the same, whether Lead and Oil were used or Perfect Method we have taken no account of it.

We next present a comparative table showing the difference between the Lead and Oil "process" and Perfect Method, and giving the number of coats and number of days between each coat for each, on running parts.

Running
parts

LEAD AND OIL.		PERFECT METHOD.	
NO.	RUNNING PARTS.	NO.	RUNNING PARTS.
1.	Priming 4 days	1.	Priming 1 day
2.	Putty 1 day	2.	Putty or Glaze 1 day
3.	Sand Paper 3 days	3.	Sand Paper
4.	Oil Lead		
5.	Putty		
6.	Sand Paper		
7.	Dead Lead 2 days	4.	Gear Filler 1 day
8.	Sandpaper		
9.	Flat Color 1 day		
10.	Color Varnish 1 day	5.	Solid Rubbing 1 day
11.	Hair off	6.	Hair off
12.	Clear Rubbing 2 days	7.	Clear Rubbing 2 days
13.	Rub Down	8.	Rub Down
14.	Stripes	9.	Stripes
15.	Finish 1 day	10.	Finish 1 day
15 Operations	15 days	10 Operations	7 days

As in the case of the table prepared for body work, we have endeavored to reduce the number of days required for the Lead and Oil process to the lowest possible limit necessary for good painting. Several of these operations would be given longer time ordinarily. Some of them might be shortened slightly on a rush, but we have tried to be as fair as possible. The table is strictly to Brush Lead, which is applied with a brush. Parts, where using Rub Lead, which is applied with a brush and then rubbed in with the hand, might not use both a coat of Oil Lead and a coat of Dead Lead, but would be obliged, in order to produce first-class work, to give the Rub Lead eight or ten days to dry, and the labor of applying one coat of Rub Lead would be equal, and probably cost as much, as to apply a coat of Oil

Lead and Dead Lead with a brush, and the time would be even longer.

We not only save time on each of the undercoats, such as primer and filler, but we save coats, and the labor of applying them, which constitutes our saving in cost.

We do not claim that our Priming costs less than Lead Priming or our Filler less than a coat of Lead; but we do claim that we save coats and labor which causes a vehicle painted with Perfect Method to cost no more, if as much, as though painted with Lead and Oil.

Oil Lead is a Lead containing little Turpentine, or Japan, and while not as elastic as an Oil Priming is more elastic than the Dead Lead, which is generally made from the keg Lead thinned with Turpentine and a little Japan to make it dry. Color Varnish, as employed in the Lead and Oil process, is either made from Clear Rubbing and Japan Color thinned down with Turpentine which causes it to be less elastic than Clear Rubbing Varnish, or else it is manufactured by the Varnish maker from Dry Color and Clear Varnish. It is not so strong as the Solid Rubbing Varnish and must be used over a coat of Flat Color. Solid Rubbing Varnish, as we make it, is made from very strong pigments, especially adapted for this purpose, and a first-class Clear Rubbing Varnish, which we prepare especially for Solid Rubbing,

Where the
saving
comes in

0007-SWP-040517

0007-SWP-000123908

is tougher and more elastic than Color Varnish made from Japan Color or Color Varnish made by the average Varnish maker.

Under Lead and Oil process, No. 11 means that the Color Varnish is rubbed with curled hair, or moss, to clean off any specks that may appear in the Color Varnish, or on it; it also roughens the surface of the Varnish slightly, or rather removes the gloss, and produces a surface over which the Clear Rubbing can be used without crawling.

Under the Lead and Oil process, No. 13 means that the Clear Rubbing Varnish is rubbed with pulverized pumice stone and water so as to produce a perfectly smooth surface.

Perfect Method Gear Filler is ground as fine as any Flat Color and is applied with a camel hair brush. It consequently requires no sanding.

Running parts should be sanded with No. 6 Sand Paper. Coarser Sand Paper cuts too deeply and cuts down rather than smooths the surface.

Samples.

Free samples should never be given except when satisfied by the party's assurance or other circumstances that an honest use will be made of them without delay, and only sufficient given to make the necessary tests or trial, the matter to be fol-

lowed up by inquiry, whether the sample has been used and with what result. Free offering of samples is hurtful and wasteful of our goods.

Complaints regarding matching of special goods may be avoided if samples sent in conform to the following specifications. Disregard of them adds needlessly to the difficulties of the Manufacturing Department, and materially to the possibility of failure.

First: The goods should be taken from bulk, in the form in which the goods are purchased, and should not be in the form in which they are used, unless used without change.

Second: The sample should be of sufficient size to permit of thorough investigation. Never less than one-half pound of paste, or one-half pint of liquid goods.

Third: Samples should be so plainly and distinctly labeled as to be easily identified.

Fourth: A specific statement as to how the goods are used, or what is expected of them, carefully written out in full, should accompany each sample.

Packages.

All goods are put up regularly in sizes of packages indicated in the list. Other sizes are only put up when very large

quantities of one article are ordered for one shipment, and the order must wait the convenience of the factory.

We make no charge for packings or cartage on goods of our own manufacture.

Weights and Measures.

Weight of Linseed Oil, United States Standard, $7\frac{1}{2}$ lbs. to the gallon; Imperial, Canada, 9 lbs.

Weight of Turps, United States Standard, 7 lbs. to the gallon; Imperial, Canada, $8\frac{1}{4}$ lbs.

Size of United States Standard gallon, 231 cubic inches.

Size of Imperial gallon, 277 cubic inches.

Usual method of mixing Strictly Pure White Lead, as described in National Lead Co.'s 1898 circular.

100 lbs. White Lead in Oil	} Makes about 6 3/4 U. S. galls.
4 lbs. Tinting Color	
5 galls. Raw Linseed Oil	
1 pint Turpentine	
1 pint Japan	

As mixed at our 1898 Convention:

100 lbs. White Lead in Oil	} Makes 6.592 U. S. galls.
4 galls. Raw Linseed Oil	
1/2 pint turpentine	
1 pint Japan	

1 gallon of U. S. Lead and Oil as ordinarily mixed by painter will cover 225 square feet, two coats.

0007-SWP-040519

0007-SWP-000123910