



FOSECO MINSEP INC.

AIR SAMPLE/SURVEY DATA SHEET

Survey Date _____

Location Plant Area Bldg. _____ Dept. _____

Sampling Date: _____
Air Sampler: Type 2M S/N 100-1-1510

Sample No. _____ Cassette Face: Open ☒ Closed ☐

Contaminant(s) Sampled ASBESTOS

Sample Type: Area ☐ Personal ☒ Personal

Flow Meter Setting 90 min Time: 11:15 AM to 1:00 PM

Time 1:00 min 30 Sampling Rate 2.3 l/min. Volume 52.7 liters

Description of Sampling Area/Operations: _____

Room 201-30
includes cleaning operation: sweeping of
floor, & removal of waste material.
Employee also uses air hose for personal
cleaning. Given air stream for dust removal

Significance of Sample: This is a very dusty operation

Sampled By AT

Analysis: _____

Weight: Blank _____ Tare _____ Gross _____ Net _____

Results: Asbestos: 10.3 fib./ml TLV: 5.0 fib./ml (10 fib./ml ceiling)

Comments: _____

Notes/Comments: Result is approximately two times "ceiling" limit of 10 fib./ml.

Best control measure should be instituted for this operation. Use of air hose
for personal cleaning should be discontinued; an industrial-type, properly
filtered vacuum line should be considered for this purpose.

Result approved by [Signature] Date 10/31/75