

TABLE 19. HEAT EMITTED BY DIRECT RADIATION—WALL RADIATORS
Room Temperature at 70 deg. fahr.
Steam Temperature at 215 deg. fahr.

No. of Sections	9B—29 in.		7B—22 in.		5A—13 in.	
	Rated Surface sq. ft.	Total B.t.u. per hr.	Rated Surface sq. ft.	Total B.t.u. per hr.	Rated Surface sq. ft.	Total B.t.u. per hr.
1	9	2853	7	2234	5	1658
2	18	5456	14	4281	10	3208
3	27	8059	21	6327	15	4758
4	36	10663	28	8372	20	6308
5	45	13266	35	10420	25	7860
6	54	15869	42	12466	30	9408
7	63	18472	49	14513	35	10959
8	72	21074	56	16559	40	12508
9	81	23676	63	18604	45	14063
10	90	26280	70	20650	50	15610
11	99	28888	77	22700	55	17160
12	108	31493	84	24746	60	18708
13	117	34094	91	26790	65	20261
14	126	36696	98	28832	70	21812
15	135	39299	105	30881	75	23363
16	144	41904	112	32928	80	24913
17	153	44508	119	34974	85	26461
18	162	47110	126	37019	90	28008
19	171	49715	133	39062	95	29560
20	180	52322	140	41118	100	31110

TABLE 20. HEAT EMITTED BY DIRECT RADIATION—WINDOW RADIATORS
Room Temperature at 70 deg. fahr.
Steam Temperature at 215 deg. fahr.

No. of Sections	20 in.		16 in.		13 in.	
	Rated Surface sq. ft.	Total B.t.u. per hr.	Rated Surface sq. ft.	Total B.t.u. per hr.	Rated Surface sq. ft.	Total B.t.u. per hr.
1	5	1708	3.75	1332	3	1082
2	10	2761	7.50	2156	6	1762
3	15	3816	11.25	2979	9	2441
4	20	4872	15.00	3803	12	3119
5	25	5930	18.75	4626	15	3798
6	30	6987	22.50	5450	18	4477
7	35	8043	26.25	6274	21	5156
8	40	9098	30.00	7098	24	5836
9	45	10152	33.75	7921	27	6516
10	50	11210	37.50	8745	30	7194
11	55	12265	41.25	9570	33	7871
12	60	13320	45.00	10395	36	8550
13	65	14378	48.75	11217	39	9227
14	70	15435	52.50	12038	42	9908
15	75	16490	56.25	12864	45	10589
16	80	17544	60.00	13686	60	13986
17	85	18598	63.75	14510	57	13304
18	90	19656	67.50	15336	48	11266
19	95	20710	71.25	16160	54	12625
20	100	21770	75.00	16988	51	11944