

TO: D. R. Neck
FOR: S. E. Richter
FROM: L. K. Burton
RE: PVC Plant EPA Compliance - Carbon Adsorbers

DATE: August 20, 1976

SUMMARY

A study has been made to recommend carbon adsorber requirements for the PVC Plant expansion. This study was made using the existing adsorbers manufactured by Chemical Design, Inc. (CDI). Material and mechanical flow sheets based on the CDI concept were prepared. However, this type of unit has some serious deficiencies which can adversely affect the ability to consistently adsorb VCM to or below 10 ppm.

The findings of this study show that with the CDI design:

- Carbon bed capacity is approximately 8 pounds of organic material per 100 pounds of carbon with inlet organic concentration varying from 2 to 7 wt %.
- The amount of residual moisture in the bed during the adsorption cycle is very important. (This is a major deficiency in the CDI unit). Too much water decreases the carbon capacity. Too little water does not give an adequate "heat sink" for the heat of adsorption and the bed temperature gets too high.
- The drying system requires a very large volume of nitrogen to be recirculated. The existing unit never gets completely dry.

RECOMMENDATIONS

The results of this study show that heat of adsorption and drying are very important. For maximum bed capacity, the bed must be completely dry but must remain cool throughout the adsorption cycle. The existing CDI beds do not meet these requirements. Hence, this writer recommends that they be dropped from further consideration unless CDI can design a system to meet the following recommendations.

To achieve the goal of dry, cool beds, the new adsorbers should incorporate the following:

- Vacuum stripping with simultaneous internal high pressure steam heat via heat exchange.
- Internal cooling during adsorption by circulating refrigerated water through internal heat exchange media.

THOMPSON, SANDSTET, SCHENKE

The adsorbers described by Mr. J. R. Jacob in his memo "VCM Removal Via Carbon Adsorption: Research-Cottrell Design", June 14, 1976, appear to incorporate the above mentioned features. Hence, this writer recommends that Research-Cottrell be considered as a potential supplier of our new adsorbers.

None of the equipment on the existing unit is spared. Also, none of the sequence control valves have been provided with blocks and bypasses. Hence even small repairs require a complete shutdown. To avoid frequent shutdowns in the new unit, all major pieces of equipment should have a spare, and all sequence valves should be blocked with a manual bypass.

DISCUSSION

A three month study was made of the existing PVC Plant carbon adsorbers. During this period, the unit was down almost one-third of the time due to mechanical problems. The unit was off-spec (above 10 ppm VCM in the vent) about one-third of the time, and on-spec the remaining one-third of the time.

Much of the downtime was caused by a bearing problem in the regeneration blower. However, some downtime was for minor repairs which because of the economy design, could not be made without a complete shutdown which requires a day to purge the system prior to opening the equipment, and a day to purge air out of the system prior to putting it back on-line. If appropriate block valves with bypass valves and spare equipment had been installed, much of this downtime could have been prevented.

Problems of high stack analyses were found to have two major causes. One cause was a heavy loading of toluene fed to the adsorbers during nitrogen stripping of the slurry tanks. The other problem is an improper relationship between bed moisture content and bed capacity and/or bed temperature.


When toluene is adsorbed on the beds, it is extremely difficult to remove to a low enough concentration to allow adequate VCM adsorption with the existing regeneration system.¹ This problem, however, can be eliminated by using steam stripping of the slurry as is the current plan.

The relationship between bed moisture content and VCM concentration in the adsorber vent was found to be very important. Under isothermal bed conditions, VCM concentration in the adsorber vent will decrease with a corresponding decrease in moisture content of the bed. However, because of heat of adsorption of VCM on carbon, a bed temperature rise is experienced. The magnitude of this rise can be large enough to be detrimental to the bed efficiency. Because of the high heat capacity of water, any water on the bed acts as a "heat sink" to minimize this temperature rise. Hence, there exists an important balance between moisture content and bed efficiency. Although this optimum moisture content was not evaluated, the studies did indicate that there exists a very narrow range of moisture where 10 ppm VCM in the vent can be met. Based on these findings, a unit which incorporates internal cooling and very dry carbon would appear to be much more reliable than the existing unit.

¹ LKB-5-76 "Removal Of Toluene From Carbon Adsorbers", June 28, 1976.

August 20, 1976

Mechanical and material flow sheets based on the existing CDI system were prepared and are attached. As mentioned in the recommendation section of this report, this design is not recommended. The feed data, however, presented in the material flow sheet can be used for other VCM removal designs. The reader will note that there is a major deviation from the CDI design in that a third bed has been added. This third bed has dual purpose: (1) it will allow changing of the carbon without removing the entire unit from service, and (2) it allows primary and a secondary adsorption bed.


L. K. Burman

LKB/cjm
Attachments

cc: D. C. Coldiron
R. E. Harmond
C. E. Crain
L. L. Bird
A. P. Gutierrez
J. K. Jacob ✓
E. J. Schuetz
P. J. Patel
P. A. Lobo
G. I. Rozand
E. J. Hourihan
S. R. Madan
J. Sandstedt

Getting out the last traces of VCM

Tenneco process uses activated carbon to remove vinyl chloride monomer from PVC plant gas streams. It's one of several methods producers are licensing

More than a year's experience with its carbon adsorption method of controlling vinyl chloride emissions from polyvinyl chloride plants has convinced Tenneco Chemicals (Bridle Brook, N.J.) that it is the best route. So it is setting carbon adsorption as the method to others.

After the carbon-adsorbing properties of activated carbon had been demonstrated by a study by John S. Miller, manager of research and development, the firm had to develop its own technology to control emissions. Now it is marketing the know-how in the U.S. and in European countries that are following the U.S. lead in setting stringent emission standards.

The firm is just one of a number of U.S. producers that have developed licensing packages in an effort to recoup part of the millions they have spent to develop the new technology.

B.F. Goodrich is licensing its steam-stripping process, which removes VCM from PVC suspension resins. Diamond Shamrock has developed a proprietary technique for removing residual VCM from PVC dispersion resins. Monsanto has been licensing its PVC reactor cleaning know-how for more than a year. Lonza (Basle, Switzerland) is offering a procedure for preventing suspension resin polymer buildup on reactor walls. And several others have developed instrumentation to monitor the amount of VCM in the air and in PVC.

Thirsty Carbon: Tenneco's development is aimed at recovering the residual VCM in vent gas streams (*CW*, Sept. 18, 1974, p. 66). A unit built by Chemical Design (Lockport, N.Y.) was installed at Tenneco's PVC plant in Pasadena, Tex., in early 1975.

A year's experience with the equipment, says Roy T. Gottesman, associate director of research and development, shows that less than 4 ppm of vinyl chloride monomer is escaping in the adsorber effluent stream. During that time, the activated carbon in the unit has undergone more than 1,300 adsorption and regeneration cycles. That makes it good enough to meet the proposed Environmental Protection Agency standard of 10 ppm.

Moreover, after 10 months of continuous service, samples of carbon withdrawn from the adsorber showed that it retained 99% of its original adsorptive ca-

pacity. Further, there was no evidence of vinyl chloride polymerization in the adsorber unit or in the carbon.

Trouble Spots: Aside from leaks, which manufacturers try to keep to a minimum, there are several points where VCM can escape to the atmosphere: at the feed to the slurry tanks and during vent purge streams.

PVC is made primarily by either suspension or emulsion polymerization techniques. Generally, in these processes VCM and the polymerization initiator are dispersed in water by the use of suspending or emulsifying agents. The polymerization temperature is selected to obtain the desired molecular weight. But not all of the vinyl chloride is converted into PVC. Usually 17-20% of monomer that does not react remains at the end of the polymerization cycle. Much of that can be recovered and recycled to the front end of the process. But as much as

through the vapor space of the tank, it keeps VCM concentrations down and prevents a flammable mixture from forming. Depending on the level of stripping of the slurry downstream, VCM concentration in the nitrogen purge may reach 15 mol percent.

Various equipment in the process is also purged with inert gas to reduce the explosion hazard and to remove the last traces of VCM. These off-gas purge streams generally contain 10-30 mol percent vinyl chloride.

New Twist: Vinyl chloride has been around a long time and so has activated carbon. But up to now, researchers have worked with pure monomer. Tenneco's contribution has been to make the process work with recovered vinyl chloride, says Gottesman. He explains that this material can contain residual initiators, catalyst fragments, and suspending agents, so that it is prone to polymerize and foul the carbon system.

Making the process work is a matter of selecting the right operating conditions and the right type of activated carbon.

Another method of scrubbing VCM from stack gas, called oxyphotolysis, has been investigated by Robintech of Fort Worth, Tex. (*CW Technology Newsletter* July 9, 1975). The firm says it is still evaluating the economics of installing the unit, which so far has not been used commercially.

Although carbon adsorption is the process that Gottesman believes will attract the widest interest, the company is arming itself with a variety of other technology. "We have filed 15 patent applications on widely differing subjects," says Gottesman. "They include a spray apparatus for cleaning PVC reactors, processes for removing VCM from suspension and emulsion processes, the destruction of VCM by ozonolysis and the removal of monomer from dispersion latex by sparging."

If others' experience is any indication, there is a big demand for the know-how. B.F. Goodrich Chemical says it has signed agreements with six corporations in Sweden, Italy, Japan and the U.S. for its suspension-resin stripping technology.

Diamond Shamrock became a licensor in March, offering its proprietary technique for removing residual VCM from



TENNECO'S GOTTESMAN: New process cuts PVC plants' VCM loss to below 4 ppm.

4% VCM can remain in the PVC slurry from the reactor. That can be removed by specialized stripping techniques, such as the ones Goodrich, Diamond Shamrock and Tenneco now offer.

Residual VCM from that cleanup phase is one of the potential sources of feed for the carbon adsorption step.

Another source is the slurry tanks, where operators flush air or nitrogen

AMINATE

Aminoquaridine Bicarbonate:

You can have plenty;
get it fast!

Aminate reacts with acids to generate carbon dioxide and produce solutions of the corresponding salt. It is used in the manufacture of tetrazene, an ingredient for small arms primers.

Further applications, in photographic emulsions, azo dyes, depilation of animal skins, textile softening agents, flameproofing agents. Also as a blowing agent in manufacture of foam as a vinyl stabilizer, and in the preparation of aminoplast resins.

Let your chemical imagination roam. Find all the uses you want because we have all the Aminate you could want. Available as a fine, white, odorless crystalline powder.

Delivery is fast. The price is right. For full details, write today to the IMC Chemical Group, Inc., Sobin Park, Boston, Mass. 02210.

IMC
CHEMICAL
GROUP, Inc.

A subsidiary of International Minerals & Chemical Corporation

CSC INDUSTRIAL
CHEMICALS DIVISION

dispersion resins. Different techniques are required for the two systems because of differences in particle size.

The company explains that in the suspension process, monomer droplets suspended in water (typically of 500-1,000 PVC particles ranging in size from 90 to 130 microns). In the dispersion or emulsion process, a colloidal dispersion of monomer droplets creates PVC particles averaging 0.5 micron in size. These smaller particles are more sensitive to acid and mechanical disturbance than suspension resins, thus different techniques are required.

Says Diamond Shamrock, "We are doing it ourselves. We have a number of people seriously interested in the technology, some from outside the U.S. We do not at the moment have any licensees, but it is a relatively new offer."

It seems doubtful that anyone will reap a financial bonanza from the new technology. Rather, licensors see their effort as one of trying to recover part of their development cost.

Diamond Shamrock adds "Licensing this kind of technology is not going to be a giant money-maker for anybody, as far as we can see, once you put the income generated up against what it cost to develop it in the first place. We hope we will be able to defray our development costs—that is, spread them out through the industry."

Insight into energy

A new 900-page United Nations study of energy use has turned up extensive data on the use and distribution of commercial energy since 1950. Among the findings:

- The U.S., with 5% of the world's population, used 30% of the world's commercial energy in 1974, compared with 45% in 1950. Its per-capita gasoline consumption was nine times the world average.

- The U.S.S.R., the world's second-largest user, increased its share from 11.5% in 1950 to 16.6% in 1974.

- China and Japan are the third- and fourth-largest consumers, respectively. China still relies mainly on solid fuel. Japan is a leading importer of all types of energy.

The report updates earlier studies on commercial energy production, trade and consumption and includes preliminary data on the production of primary fossil fuels for 1975.

It is available from the UN Sales Section (New York) for \$30.