

VISCOSITY WORK SHEET

Item	3069	P.T.No.		Date	10/7/55
Worker	Agnew	Polymer	Lucite	Solvent	EDC
For	Carman	Charge	1290	Temperature	25°C
Viscometer No.	C	Efflux Time	204.0	Weight:	Gross 5.1895
Viscometer No.	M	Efflux Time	183.3		Tare 5.0643
Viscometer No.	L	Efflux Time	180.4		Net 0.1250

Sample	Flask No.	Visc.	Solution	Efflux Times	Rel. Inh. visc. Visc. or M.W.
1	1	1.0	1.0	1.0	1.0
2	2	1.0	1.0	1.0	1.0
3	3	1.0	1.0	1.0	1.0
4	4	1.0	1.0	1.0	1.0
5	5	1.0	1.0	1.0	1.0
6	6	1.0	1.0	1.0	1.0
7	7	1.0	1.0	1.0	1.0
8	8	1.0	1.0	1.0	1.0
9	9	1.0	1.0	1.0	1.0
10	10	1.0	1.0	1.0	1.0
11	11	1.0	1.0	1.0	1.0
12	12	1.0	1.0	1.0	1.0
13	13	1.0	1.0	1.0	1.0
14	14	1.0	1.0	1.0	1.0
15	15	1.0	1.0	1.0	1.0
16	16	1.0	1.0	1.0	1.0
17	17	1.0	1.0	1.0	1.0
18	18	1.0	1.0	1.0	1.0
19	19	1.0	1.0	1.0	1.0
20	20	1.0	1.0	1.0	1.0
21	21	1.0	1.0	1.0	1.0
22	22	1.0	1.0	1.0	1.0
23	23	1.0	1.0	1.0	1.0
24	24	1.0	1.0	1.0	1.0
25	25	1.0	1.0	1.0	1.0
26	26	1.0	1.0	1.0	1.0
27	27	1.0	1.0	1.0	1.0
28	28	1.0	1.0	1.0	1.0
29	29	1.0	1.0	1.0	1.0
30	30	1.0	1.0	1.0	1.0
31	31	1.0	1.0	1.0	1.0
32	32	1.0	1.0	1.0	1.0
33	33	1.0	1.0	1.0	1.0
34	34	1.0	1.0	1.0	1.0
35	35	1.0	1.0	1.0	1.0
36	36	1.0	1.0	1.0	1.0
37	37	1.0	1.0	1.0	1.0
38	38	1.0	1.0	1.0	1.0
39	39	1.0	1.0	1.0	1.0
40	40	1.0	1.0	1.0	1.0
41	41	1.0	1.0	1.0	1.0
42	42	1.0	1.0	1.0	1.0
43	43	1.0	1.0	1.0	1.0
44	44	1.0	1.0	1.0	1.0
45	45	1.0	1.0	1.0	1.0
46	46	1.0	1.0	1.0	1.0
47	47	1.0	1.0	1.0	1.0
48	48	1.0	1.0	1.0	1.0
49	49	1.0	1.0	1.0	1.0
50	50	1.0	1.0	1.0	1.0
51	51	1.0	1.0	1.0	1.0
52	52	1.0	1.0	1.0	1.0
53	53	1.0	1.0	1.0	1.0
54	54	1.0	1.0	1.0	1.0
55	55	1.0	1.0	1.0	1.0
56	56	1.0	1.0	1.0	1.0
57	57	1.0	1.0	1.0	1.0
58	58	1.0	1.0	1.0	1.0
59	59	1.0	1.0	1.0	1.0
60	60	1.0	1.0	1.0	1.0
61	61	1.0	1.0	1.0	1.0
62	62	1.0	1.0	1.0	1.0
63	63	1.0	1.0	1.0	1.0
64	64	1.0	1.0	1.0	1.0
65	65	1.0	1.0	1.0	1.0
66	66	1.0	1.0	1.0	1.0
67	67	1.0	1.0	1.0	1.0
68	68	1.0	1.0	1.0	1.0
69	69				

4819-153-M	N	C	249.1; 249.2; 249.3	1.222	91,500
"	H-20	M	224.8; 224.1; 224.1	1.222	91,500
-153-N	24	L	220.4; 220.6; 220.3	1.222	91,500
"	J-5	B	204.3; 204.7 204.2	1.222	91,500
-153-P	Ju	10	260.5; 260.2; 260.2	1.230	95,600
"	TP	C	249.8; 250.9; 250.2	1.237	94,000
-153-R	BA	M	225.0; 225.1; 225.2	1.228	94,500
"	H-10	L	221.1; 221.2; 221.1	1.226	93,800
-153-S	L-10	B	204.2; 204.9; 204.5	1.204	92,000
"	BB	10	259.2; 259.3; 259.1	1.225	92,500
-153-T	A	C	257.5; 247.0; <u>250.0</u>	1.225	92,500
"	25	M	223.7; 224.9; <u>224.5</u>	1.225	92,500
-153-U	VI	L	214.7; 214.6; 214.5	1.190	74,000
"	Q	B	<u>198.9</u> ; 198.6; 198.8	1.190	74,000