



Tenneco Polymers
A Tenneco Company

MATERIAL SAFETY DATA

(Approved by U.S. Department of Labor as "essentially similar" to FORM OSHA-20)

SECTION I IDENTIFICATION OF PRODUCT		
MANUFACTURER'S NAME TENNECO POLYMERS, INC., RESEARCH & DEVELOPMENT		EMERGENCY TELEPHONE NO. 609-386-9200
ADDRESS RIVER ROAD, P.O. BOX 129, FLEMINGTON, NEW JERSEY 08822		
TRADE NAME AND SYNONYMS TENNECO PVC COMPOUND, RIGID 3711, 3750, 4703		
CHEMICAL NAME AND SYNONYMS POLY(VINYL CHLORIDE) COMPOUND		
CHEMICAL FAMILY CHLOROHYDROCARBON POLYMER	MOLECULAR FORMULA (CH₂CHCl)_n	MOL. WT.

SECTION II HAZARDOUS COMPONENTS OF MIXTURES					
COMPONENT	%	THRESHOLD LIMIT VALUE	COMPONENT	%	THRESHOLD LIMIT VALUE
(UNITS)			(UNITS)		
Carbon Black	(0-0.6%)	3.5 mg/m ³	Tin Organic Compound	(0-2%)	0.1 mg/m ³
Lead Compounds	(0 - 4%)	0.2 mg/m ³	Titanium Dioxide	(0-1%)	15 mg/m ³
Mineral Oil	(0-0.5%)	5 mg/m ³			

SECTION III PHYSICAL DATA	
APPEARANCE AND ODOR White, Black or Colored Pellets, practically odorless.	
BOILING POINT (DEGREES FAHRENHEIT) Not applicable	MELTING POINT (DEGREES FAHRENHEIT) Not applicable Softens about 160 - 180°F
VAPOR PRESSURE (MM. OF MERCURY) Not applicable	SPECIFIC GRAVITY (WATER = 1) 1.32 - 1.42
VAPOR DENSITY (AIR = 1) Not applicable	PERCENT VOLATILE (BY WEIGHT) Essentially non-volatile
SOLUBILITY IN WATER Negligible	EVAPORATION RATE (BUTYLACETATE = 1) Not applicable

SECTION IV FIRE AND EXPLOSION HAZARD DATA		
FLASH POINT (SPECIFY METHOD) (DEGREES FAHRENHEIT) Ignition about 735°F auto- Ignition about 850°F (ASTM D-1929)	FLAMMABLE LIMITS (PERCENT BY VOLUME)	LOWER Not applicable. UPPER
FIRE EXTINGUISHING MEDIA Water spray, carbon dioxide or dry chemical.		
SPECIAL FIRE-FIGHTING PROCEDURES Water spray or fog may be helpful in reducing flame intensity and absorbing irritating fumes. Shut off current in electrical equipment or wiring.		
UNUSUAL FIRE AND EXPLOSION HAZARDS NFPA lists ignition temperature of 752°F for layer and 1220°F for PVC dust cloud. Produces combustible gases above 570°F. Fire conditions produce hydrogen chloride, requiring protective equipment.		

This information is furnished without warranty, representation, inducement or license of any kind, except that it is accurate to the best of Tenneco Polymers' knowledge or obtained from sources believed by Tenneco Polymers to be accurate and Tenneco Polymers does not assume any legal responsibility for use or reliance upon same. Customers are encouraged to conduct their own tests. Before using any product read its label.

SECTION V HEALTH HAZARD DATA**THRESHOLD LIMIT VALUE**

See Section II

EFFECTS OR OVEREXPOSURE

None expected - inert resin. See Section IX. Prolonged breathing of concentrated dust may be harmful. (Processing at high temperatures produces fumes irritating to eyes and respiratory tract requiring local exhaust).

EMERGENCY AND FIRST AID PROCEDURES

Ordinary measures of personal hygiene.

In case of exposure in hot processing move to fresh air, flush eyes with water.

SECTION VI REACTIVITY DATA

STABILITY	UNSTABLE		CONDITIONS TO AVOID Normal processing temperature, about 350° F causes slow darkening and decomposition. Higher heat increases rate and evolution of HCl.
	STABLE	X	
INCOMPATIBILITY (Materials to avoid) None in ordinary use. Soluble in certain ketones and organic solvents.			
HAZARDOUS DECOMPOSITION PRODUCTS Thermal decomposition produces HCl, and CO and CO ₂ (above 570°F).			
HAZARDOUS POLYMERIZATION	MAY OCCUR		CONDITIONS TO AVOID None in ordinary use.
	WILL NOT OCCUR	X	

SECTION VII SPILL OR LEAK PROCEDURES**STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED**

Sweep up and remove to disposal container.

WASTE DISPOSAL METHOD

Bury in an approved landfill.

SECTION VIII SPECIAL PROTECTION INFORMATION

RESPIRATORY PROTECTION (Specify type) In case of concentrated dust, use Bureau of Mines approved dust respiratory (NIOBM TC-21C-132 or equivalent). See Section II and IX.

VENTILATION	LOCAL EXHAUST For hot processing.	SPECIAL Vent to elevated stack.
	MECHANICAL (General) For ordinary handling.	OTHER Ventilate enclosed spaces.

PROTECTIVE GLOVES Not ordinarily required.	EYE PROTECTION Safety glasses.
---	-----------------------------------

OTHER PROTECTIVE EQUIPMENT None required for ordinary handling. For hot processing local exhaust, safety glasses and gloves are recommended.

SECTION IX SPECIAL PRECAUTIONS

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING OSHA Standard 1910.93q(.1017) requires monitoring and other precautions in storage, handling and use of polyvinyl chloride, and also labeling of PVC "Contains Vinyl Chloride-Vinyl Chloride is a Cancer-Suspect Agent". New PVC resins with a low monomer content make it easier to operate below the OSHA action level of 0.5ppm in a processor's work area, assuming normal conditions and ventilation, simplifying compliance with some of the regulatory requirements. Further developments on resins and on regulations are pending.

TEN0155

DATE

3/12/84

NAME AND TITLE

D. GOODMAN, PRODUCT REGULATIONS

SHEET NUMBER

158