

LEAD INDUSTRIES ASSOCIATION

60 EAST 42ND STREET

NEW YORK 17, N. Y.

April 1, 1960


SUBJECT: TERNE-PLATE ROOFING

To Members of the Lead Industries Association:

We are attaching a copy of a new brochure dealing with terne-plate roofing, a lead-alloy coated product which is enjoying a resurgence in popularity. This is another in our series of fliers dealing with lead products for building construction and is being mailed to a list of approximately 14,000 architects and builders.

Additional copies in quantities up to 25 are available free of charge and in larger quantities at \$3.00 per hundred while the supply lasts.

Very truly yours,


Secretary

Att.


MAILED - 100

This Staten Island residence, by Frank Lloyd Wright, has a Bermuda roof of Terne

A.I.A. 12-4031

SPECIFICATIONS


SEAMLESS TERNE FOR ROOFING



Along Pennsylvania's route 40 — the Uniontown Motel. Roofing was done by Henry J. Copper Roofing Company of Uniontown.

A batten seam roof harmonizes with the style of the Philip F. Howerton residence in Charlotte, N. C.

St. Luke's Chapel at Annapolis, Md. makes use of terne in vaulted roof construction. Architects: Rogers, Talliferro and Lamb, Baltimore.




LEAD INDUSTRIES ASSOCIATION

292 Madison Ave. New York 17, N. Y.

George Tech's Alexander Memorial Arena, designed by Arch Associates, shows seamless terne roofing designed to harmonize with the surrounding campus. The roof, 270 feet in diameter, is set on 32 arched girders.



LOOK AHEAD WITH LEAD



LIA22582

TERNE: *An Architectural Rediscovery*

"...I have furthermore found terne superior
to other roofing materials in economy,
color adherence, heat-reflection, permanence,
workability, and low coefficient of expansion."

— Frank Lloyd Wright

Terne, a two-century-old building material, is making current headlines in architectural and technical journals, and in newspapers. Though it is substantially unchanged from the time of its first popularity in the characteristics which give it such excellent performance, there has been a recent development in terne plate's manufacture which is causing the present focus of attention on it: in place of the time-honored sheets which have been characteristic of terne, it is now being made in 30 feet seamless rolls. In this new form it is easily and economically applied; typical installed costs range from 50 to 75 cents per square foot.

Of unquestioned durability, terne is one of the lightest and strongest roofing materials known. It is thoroughly waterproof and hail-proof and survives windstorms unscathed.

Not the least important of its attributes is terne's ability to accept and hold ordinary exterior paints. Terne will take paint without pretreatment or weathering. The exceptional durability of painted terne surfaces argues for the use of a good grade of exterior paint as the finished coat so that an unmarred appearance can persist throughout its life.

Some of the oldest historic buildings in this country have terne roofs. The present headquarters of the American Institute of Architects in Washington, D. C., is still using the terne roof which replaced the structure's original roof in approximately 1880. One of the most noted historic buildings in Tennessee is the Hermitage, the home to which Andrew Jackson retired when he left the White House. In 1834, after the house had been destroyed by a fire, started when a spark landed on the

original roof, Jackson wrote his son to have it rebuilt and "have a tin roof put on it". The current roof is terne and has been satisfactory since its installation in 1890.

Andrew Jackson's phrase "tin roof" was the nomenclature used for terne well into the 19th century. To eliminate confusion, the material is universally referred to today as terne. The alloy coating contains 20% tin. The balance of this coating is lead. It is the lead which is responsible for the excellent corrosion resistance of terne, in large part. The tin is present principally to "alloy" the sheet steel so that a continuous level film of coating can be built up on the steel and tightly adhered to it. There is, in fact, a tin-iron substrate formed at the interface and thus a chemical bonding exists from the steel base through to the surface of the alloy coating.

CHARACTERISTICS OF SEAMLESS TERNE ROOFING

TENSILE STRENGTH

The mechanical properties of terne are excellent. Not only is it among the highest tensile strength materials—45,000 psi for standard weight terne—but it will not crack under climatic changes. The combined properties of light weight, high tensile strength, and good heat resistance make it an excellent fire retardant construction material. Even in cases where fire originating under the roof has burned away support timbers, terne roofs have been known to remain suspended over the fire in one piece and have acted as a blanket to prevent sparks from spreading the fire to adjacent structures.

The alloy surface produces an excellent bond with the paint and, in the case of lead pigment paints, forms an exceptionally durable combination.

Painted white or a light color, terne will reflect a major portion of the sun's heat. Reflectivity factors show how important this property can be when light colors are used on the roof to reduce the heat load in air conditioning equipment or to provide comfortable temperatures when air conditioning is not used. White paint for example will reflect about 80 per cent of the solar heat falling on it; yellow, two thirds. For reference, a roof painted black may reflect only five per cent or less.

supporting structure can be made. Thirty gauge terne weighs only 62 lb. per 100 sq. ft. as laid; 28 gauge terne weighs 76 lb.

EXPANSION

The coefficient of expansion of terne is quite low—only wood and slate are better, among common roofing materials, in this respect. Expansion seams in terne roof are not required in runs under 30 feet long as both ends are free to move.

Table I—Thermal Expansion

Material	Lineal Expansion per 100 ft. per 100°F
Wood	0.331
Slate	0.496
TERNE	0.825
Galvanized	0.825
Copper	1.064
Zinc	2.076
Lead	1.908
Aluminum	1.534

COLOR

Color adaptability is a valuable asset of terne roofing. Terne can be painted any color at any time without special treatment of the surface.

WEIGHT

Seamless terne is one of the lightest satisfactory roofing materials. It is, in fact, so much lighter than many other common roofing materials that a significant saving in the cost of the

SPECIFICATIONS

STANDARD SPECS

All roof surfaces of the building shall be covered with copper-bearing terne roofing. This shall be laid on rosin sized paper (tar paper and other qualities containing acids prohibited). No nails shall be driven through the strips. All solder used shall be strictly half-and-half. Rosin only shall be used as a flux for soldering, and all rosin must be removed from seams before painting. No acid flux shall be used.

The seamless terne roofing shall be painted one coat on the underside and two coats on the exposed side. The mill-applied coat is sufficient for the underside. The exposed surface shall have two coats of a long oil base paint, any color. Even though the exposed surface should have a top coat, two coats of exterior paint should be applied. All painting shall be done by hand, well brushed in, as part of the roofing contract.

The roofers shall wear rubber shoes and no unnecessary walking over the roof or using the same for storage of other material will be allowed. All workmanship guaranteed for one year.

When pitch of roof is two and one-half inches or less to the foot, it is to be laid flat lock. Cleats to be one and one-half inches wide and carefully hooked over one-half inch edge and nailed to sheathing with two 7/8" roofing nails or stapled with 7/8" diversion point staples to each cleat. The seams are to be thoroughly and smoothly hammered down with a wooden mallet and carefully soldered with large coppers.

When there is sufficient pitch (two and one-half inches or more per foot) the roof is to be laid standing seam, batten seam or Bermuda style.

All valleys and gutters (specify whether 28 gauge or 30 gauge) shall be applied flat lock, of sufficient pitch to prevent any water standing therein.

Flashings: Seamless terne roofing (specify gauge and coating weight) to be turned up not less than six inches at chimneys and fire wall and to be cap-flashed four inches, cap-flashings to extend into brick work one inch and to be firmly wedged in with wedges not over fifteen inches apart. Fill openings in brick work with Portland cement.

BERMUDA ROOF*

Use seamless terne roofing. Specify gauge and coating weight. Paint one side and dry well before applying to roof with painted side down. This shop coat may be applied at the mill.

Specify ridge treatment to be either flat seam or standing seam.) To form Bermuda seams, make a vertical bend along the longer dimension of the sheets or rolls 1/2" higher than the batten. Place first course in position with painted side down. Do not nail through the strips. Use cleats made of the same material. Nail cleats every 8" along the face of the batten. Bend the cleat 1/4" over the top of the upturned edge. Bend the 1/2" which projects above the batten to a horizontal position (right angle bend).

Place the next course in position against the face of the succeeding batten. Bottom edge of this course must extend 1" beyond the lower batten. Bend 1/2" around the edge of the first course and mallet tightly against the face of the batten. Stagger cross seams to avoid extra thickness in malleting against the battens.

* For applications of 2 1/2" per foot max pitch to specify if wanted in 10, or heavier weight 1X. The coating is the same in each gauge; the difference is in the thickness of the Copper Bearing Steel base strip before roofing. Formulated in 10, or 1X, or 10 to 15, or 15 to 20, or 20 to 25, or 25 to 30, or 30 to 35, or 35 to 40, or 40 to 45, or 45 to 50, or 50 to 55, or 55 to 60, or 60 to 65, or 65 to 70, or 70 to 75, or 75 to 80, or 80 to 85, or 85 to 90, or 90 to 95, or 95 to 100, or 100 to 105, or 105 to 110, or 110 to 115, or 115 to 120, or 120 to 125, or 125 to 130, or 130 to 135, or 135 to 140, or 140 to 145, or 145 to 150, or 150 to 155, or 155 to 160, or 160 to 165, or 165 to 170, or 170 to 175, or 175 to 180, or 180 to 185, or 185 to 190, or 190 to 195, or 195 to 200, or 200 to 205, or 205 to 210, or 210 to 215, or 215 to 220, or 220 to 225, or 225 to 230, or 230 to 235, or 235 to 240, or 240 to 245, or 245 to 250, or 250 to 255, or 255 to 260, or 260 to 265, or 265 to 270, or 270 to 275, or 275 to 280, or 280 to 285, or 285 to 290, or 290 to 295, or 295 to 300, or 300 to 305, or 305 to 310, or 310 to 315, or 315 to 320, or 320 to 325, or 325 to 330, or 330 to 335, or 335 to 340, or 340 to 345, or 345 to 350, or 350 to 355, or 355 to 360, or 360 to 365, or 365 to 370, or 370 to 375, or 375 to 380, or 380 to 385, or 385 to 390, or 390 to 395, or 395 to 400, or 400 to 405, or 405 to 410, or 410 to 415, or 415 to 420, or 420 to 425, or 425 to 430, or 430 to 435, or 435 to 440, or 440 to 445, or 445 to 450, or 450 to 455, or 455 to 460, or 460 to 465, or 465 to 470, or 470 to 475, or 475 to 480, or 480 to 485, or 485 to 490, or 490 to 495, or 495 to 500, or 500 to 505, or 505 to 510, or 510 to 515, or 515 to 520, or 520 to 525, or 525 to 530, or 530 to 535, or 535 to 540, or 540 to 545, or 545 to 550, or 550 to 555, or 555 to 560, or 560 to 565, or 565 to 570, or 570 to 575, or 575 to 580, or 580 to 585, or 585 to 590, or 590 to 595, or 595 to 600, or 600 to 605, or 605 to 610, or 610 to 615, or 615 to 620, or 620 to 625, or 625 to 630, or 630 to 635, or 635 to 640, or 640 to 645, or 645 to 650, or 650 to 655, or 655 to 660, or 660 to 665, or 665 to 670, or 670 to 675, or 675 to 680, or 680 to 685, or 685 to 690, or 690 to 695, or 695 to 700, or 700 to 705, or 705 to 710, or 710 to 715, or 715 to 720, or 720 to 725, or 725 to 730, or 730 to 735, or 735 to 740, or 740 to 745, or 745 to 750, or 750 to 755, or 755 to 760, or 760 to 765, or 765 to 770, or 770 to 775, or 775 to 780, or 780 to 785, or 785 to 790, or 790 to 795, or 795 to 800, or 800 to 805, or 805 to 810, or 810 to 815, or 815 to 820, or 820 to 825, or 825 to 830, or 830 to 835, or 835 to 840, or 840 to 845, or 845 to 850, or 850 to 855, or 855 to 860, or 860 to 865, or 865 to 870, or 870 to 875, or 875 to 880, or 880 to 885, or 885 to 890, or 890 to 895, or 895 to 900, or 900 to 905, or 905 to 910, or 910 to 915, or 915 to 920, or 920 to 925, or 925 to 930, or 930 to 935, or 935 to 940, or 940 to 945, or 945 to 950, or 950 to 955, or 955 to 960, or 960 to 965, or 965 to 970, or 970 to 975, or 975 to 980, or 980 to 985, or 985 to 990, or 990 to 995, or 995 to 1000, or 1000 to 1005, or 1005 to 1010, or 1010 to 1015, or 1015 to 1020, or 1020 to 1025, or 1025 to 1030, or 1030 to 1035, or 1035 to 1040, or 1040 to 1045, or 1045 to 1050, or 1050 to 1055, or 1055 to 1060, or 1060 to 1065, or 1065 to 1070, or 1070 to 1075, or 1075 to 1080, or 1080 to 1085, or 1085 to 1090, or 1090 to 1095, or 1095 to 1100, or 1100 to 1105, or 1105 to 1110, or 1110 to 1115, or 1115 to 1120, or 1120 to 1125, or 1125 to 1130, or 1130 to 1135, or 1135 to 1140, or 1140 to 1145, or 1145 to 1150, or 1150 to 1155, or 1155 to 1160, or 1160 to 1165, or 1165 to 1170, or 1170 to 1175, or 1175 to 1180, or 1180 to 1185, or 1185 to 1190, or 1190 to 1195, or 1195 to 1200, or 1200 to 1205, or 1205 to 1210, or 1210 to 1215, or 1215 to 1220, or 1220 to 1225, or 1225 to 1230, or 1230 to 1235, or 1235 to 1240, or 1240 to 1245, or 1245 to 1250, or 1250 to 1255, or 1255 to 1260, or 1260 to 1265, or 1265 to 1270, or 1270 to 1275, or 1275 to 1280, or 1280 to 1285, or 1285 to 1290, or 1290 to 1295, or 1295 to 1300, or 1300 to 1305, or 1305 to 1310, or 1310 to 1315, or 1315 to 1320, or 1320 to 1325, or 1325 to 1330, or 1330 to 1335, or 1335 to 1340, or 1340 to 1345, or 1345 to 1350, or 1350 to 1355, or 1355 to 1360, or 1360 to 1365, or 1365 to 1370, or 1370 to 1375, or 1375 to 1380, or 1380 to 1385, or 1385 to 1390, or 1390 to 1395, or 1395 to 1400, or 1400 to 1405, or 1405 to 1410, or 1410 to 1415, or 1415 to 1420, or 1420 to 1425, or 1425 to 1430, or 1430 to 1435, or 1435 to 1440, or 1440 to 1445, or 1445 to 1450, or 1450 to 1455, or 1455 to 1460, or 1460 to 1465, or 1465 to 1470, or 1470 to 1475, or 1475 to 1480, or 1480 to 1485, or 1485 to 1490, or 1490 to 1495, or 1495 to 1500, or 1500 to 1505, or 1505 to 1510, or 1510 to 1515, or 1515 to 1520, or 1520 to 1525, or 1525 to 1530, or 1530 to 1535, or 1535 to 1540, or 1540 to 1545, or 1545 to 1550, or 1550 to 1555, or 1555 to 1560, or 1560 to 1565, or 1565 to 1570, or 1570 to 1575, or 1575 to 1580, or 1580 to 1585, or 1585 to 1590, or 1590 to 1595, or 1595 to 1600, or 1600 to 1605, or 1605 to 1610, or 1610 to 1615, or 1615 to 1620, or 1620 to 1625, or 1625 to 1630, or 1630 to 1635, or 1635 to 1640, or 1640 to 1645, or 1645 to 1650, or 1650 to 1655, or 1655 to 1660, or 1660 to 1665, or 1665 to 1670, or 1670 to 1675, or 1675 to 1680, or 1680 to 1685, or 1685 to 1690, or 1690 to 1695, or 1695 to 1700, or 1700 to 1705, or 1705 to 1710, or 1710 to 1715, or 1715 to 1720, or 1720 to 1725, or 1725 to 1730, or 1730 to 1735, or 1735 to 1740, or 1740 to 1745, or 1745 to 1750, or 1750 to 1755, or 1755 to 1760, or 1760 to 1765, or 1765 to 1770, or 1770 to 1775, or 1775 to 1780, or 1780 to 1785, or 1785 to 1790, or 1790 to 1795, or 1795 to 1800, or 1800 to 1805, or 1805 to 1810, or 1810 to 1815, or 1815 to 1820, or 1820 to 1825, or 1825 to 1830, or 1830 to 1835, or 1835 to 1840, or 1840 to 1845, or 1845 to 1850, or 1850 to 1855, or 1855 to 1860, or 1860 to 1865, or 1865 to 1870, or 1870 to 1875, or 1875 to 1880, or 1880 to 1885, or 1885 to 1890, or 1890 to 1895, or 1895 to 1900, or 1900 to 1905, or 1905 to 1910, or 1910 to 1915, or 1915 to 1920, or 1920 to 1925, or 1925 to 1930, or 1930 to 1935, or 1935 to 1940, or 1940 to 1945, or 1945 to 1950, or 1950 to 1955, or 1955 to 1960, or 1960 to 1965, or 1965 to 1970, or 1970 to 1975, or 1975 to 1980, or 1980 to 1985, or 1985 to 1990, or 1990 to 1995, or 1995 to 2000, or 2000 to 2005, or 2005 to 2010, or 2010 to 2015, or 2015 to 2020, or 2020 to 2025, or 2025 to 2030, or 2030 to 2035, or 2035 to 2040, or 2040 to 2045, or 2045 to 2050, or 2050 to 2055, or 2055 to 2060, or 2060 to 2065, or 2065 to 2070, or 2070 to 2075, or 2075 to 2080, or 2080 to 2085, or 2085 to 2090, or 2090 to 2095, or 2095 to 2100, or 2100 to 2105, or 2105 to 2110, or 2110 to 2115, or 2115 to 2120, or 2120 to 2125, or 2125 to 2130, or 2130 to 2135, or 2135 to 2140, or 2140 to 2145, or 2145 to 2150, or 2150 to 2155, or 2155 to 2160, or 2160 to 2165, or 2165 to 2170, or 2170 to 2175, or 2175 to 2180, or 2180 to 2185, or 2185 to 2190, or 2190 to 2195, or 2195 to 2200, or 2200 to 2205, or 2205 to 2210, or 2210 to 2215, or 2215 to 2220, or 2220 to 2225, or 2225 to 2230, or 2230 to 2235, or 2235 to 2240, or 2240 to 2245, or 2245 to 2250, or 2250 to 2255, or 2255 to 2260, or 2260 to 2265, or 2265 to 2270, or 2270 to 2275, or 2275 to 2280, or 2280 to 2285, or 2285 to 2290, or 2290 to 2295, or 2295 to 2300, or 2300 to 2305, or 2305 to 2310, or 2310 to 2315, or 2315 to 2320, or 2320 to 2325, or 2325 to 2330, or 2330 to 2335, or 2335 to 2340, or 2340 to 2345, or 2345 to 2350, or 2350 to 2355, or 2355 to 2360, or 2360 to 2365, or 2365 to 2370, or 2370 to 2375, or 2375 to 2380, or 2380 to 2385, or 2385 to 2390, or 2390 to 2395, or 2395 to 2400, or 2400 to 2405, or 2405 to 2410, or 2410 to 2415, or 2415 to 2420, or 2420 to 2425, or 2425 to 2430, or 2430 to 2435, or 2435 to 2440, or 2440 to 2445, or 2445 to 2450, or 2450 to 2455, or 2455 to 2460, or 2460 to 2465, or 2465 to 2470, or 2470 to 2475, or 2475 to 2480, or 2480 to 2485, or 2485 to 2490, or 2490 to 2495, or 2495 to 2500, or 2500 to 2505, or 2505 to 2510, or 2510 to 2515, or 2515 to 2520, or 2520 to 2525, or 2525 to 2530, or 2530 to 2535, or 2535 to 2540, or 2540 to 2545, or 2545 to 2550, or 2550 to 2555, or 2555 to 2560, or 2560 to 2565, or 2565 to 2570, or 2570 to 2575, or 2575 to 2580, or 2580 to 2585, or 2585 to 2590, or 2590 to 2595, or 2595 to 2600, or 2600 to 2605, or 2605 to 2610, or 2610 to 2615, or 2615 to 2620, or 2620 to 2625, or 2625 to 2630, or 2630 to 2635, or 2635 to 2640, or 2640 to 2645, or 2645 to 2650, or 2650 to 2655, or 2655 to 2660, or 2660 to 2665, or 2665 to 2670, or 2670 to 2675, or 2675 to 2680, or 2680 to 2685, or 2685 to 2690, or 2690 to 2695, or 2695 to 2700, or 2700 to 2705, or 2705 to 2710, or 2710 to 2715, or 2715 to 2720, or 2720 to 2725, or 2725 to 2730, or 2730 to 2735, or 2735 to 2740, or 2740 to 2745, or 2745 to 2750, or 2750 to 2755, or 2755 to 2760, or 2760 to 2765, or 2765 to 2770, or 2770 to 2775, or 2775 to 2780, or 2780 to 2785, or 2785 to 2790, or 2790 to 2795, or 2795 to 2800, or 2800 to 2805, or 2805 to 2810, or 2810 to 2815, or 2815 to 2820, or 2820 to 2825, or 2825 to 2830, or 2830 to 2835, or 2835 to 2840, or 2840 to 2845, or 2845 to 2850, or 2850 to 2855, or 2855 to 2860, or 2860 to 2865, or 2865 to 2870, or 2870 to 2875, or 2875 to 2880, or 2880 to 2885, or 2885 to 2890, or 2890 to 2895, or 2895 to 2900, or 2900 to 2905, or 2905 to 2910, or 2910 to 2915, or 2915 to 2920, or 2920 to 2925, or 2925 to 2930, or 2930 to 2935, or 2935 to 2940, or 2940 to 2945, or 2945 to 2950, or 2950 to 2955, or 2955 to 2960, or 2960 to 2965, or 2965 to 2970, or 2970 to 2975, or 2975 to 2980, or 2980 to 2985, or 2985 to 2990, or 2990 to 2995, or 2995 to 3000, or 3000 to 3005, or 3005 to 3010, or 3010 to 3015, or 3015 to 3020, or 3020 to 3025, or 3025 to 3030, or 3030 to 3035, or 3035 to 3040, or 3040 to 3045, or 3045 to 3050, or 3050 to 3055, or 3055 to 3060, or 3060 to 3065, or 3065 to 3070, or 3070 to 3075, or 3075 to 3080, or 3080 to 3085, or 3085 to 3090, or 3090 to 3095, or 3095 to 3100, or 3100 to 3105, or 3105 to 3110, or 3110 to 3115, or 3115 to 3120, or 3120 to 3125, or 3125 to 3130, or 3130 to 3135, or 3135 to 3140, or 3140 to 3145, or 3145 to 3150, or 3150 to 3155, or 3155 to 3160, or 3160 to 3165, or 3165 to 3170, or 3170 to 3175, or 3175 to 3180, or 3180 to 3185, or 3185 to 3190, or 3190 to 3195, or 3195 to 3200, or 3200 to 3205, or 3205 to 3210, or 3210 to 3215, or 3215 to 3220, or 3220 to 3225, or 3225 to 3230, or 3230 to 3235, or 3235 to 3240, or 3240 to 3245, or 3245 to 3250, or 3250 to 3255, or 3255 to 3260, or 3260 to 3265, or 3265 to 3270, or 3270 to 3275, or 3275 to 3280, or 3280 to 3285, or 3285 to 3290, or 3290 to 3295, or 3295 to 3300, or 3300 to 3305, or 3305 to 3310, or 3310 to 3315, or 3315 to 3320, or 3320 to 3325, or 3325 to 3330, or 3330 to 3335, or 3335 to 3340, or 3340 to 3345, or 3345 to 3350, or 3350 to 3355, or 3355 to 3360, or 3360 to 3365, or 3365 to 3370, or 3370 to 3375, or 3375 to 3380, or 3380 to 3385, or 3385 to 3390, or 3390 to 3395, or 3395 to 3400, or 3400 to 3405, or 3405 to 3410, or 3410 to 3415, or 3415 to 3420, or 3420 to 3425, or 3425 to 3430, or 3430 to 3435, or 3435 to 3440, or 3440 to 3445, or 3445 to 3450, or 3450 to 3455, or 3455 to 3460, or 3460 to 3465, or 3465 to 3470, or 3470 to 3475, or 3475 to 3480, or 3480 to 3485, or 3485 to 3490, or 3490 to 3495, or 3495 to 3500, or 3500 to 3505, or 3505 to 3510, or 3510 to 3515, or 3515 to 3520, or 3520 to 3525, or 3525 to 3530, or 3530 to 3535, or 3535 to 3540, or 3540 to 3545, or 3545 to 3550, or 3550 to 3555, or 3555 to 3560, or 3560 to 3565, or 3565 to 3570, or 3570 to 3575, or 3575 to 3580, or 3580 to 3585, or 3585 to 3590, or 3590 to 3595, or 3595 to 3600, or 3600 to 3605, or 3605 to 3610, or 3610 to 3615, or 3615 to 3620, or 3620 to 3625, or 3625 to 3630, or 3630 to 3635, or 3635 to 3640, or 3640 to 3645, or 3645 to 3650, or 3650 to 3655, or 3655 to 3660, or 3660 to 3665, or 3665 to 3670, or 3670 to 3675, or 3675 to 3680, or 3680 to 3685, or 3685 to 3690, or 3690 to 3695, or 3695 to 3700, or 3700 to 3705, or 3705 to 3710, or 3710 to 3715, or 3715 to 3720, or 3720 to 3725, or 3725 to 3730, or 3730 to 3735, or 3735 to 3740, or 3740 to 3745, or 3745 to 3750, or 3750 to 3755, or 3755 to 3760, or 3760 to 3765, or 3765 to 3770, or 3770 to 3775, or 3775 to 3780, or 3780 to 3785, or 3785 to 3790, or 3790 to 3795, or 3795 to 3800, or 3800 to 3805, or 3805 to 3810, or 3810 to 3815, or 3815 to 3820, or 3820 to 3825, or 3825 to 3830, or 3830 to 3835, or 3835 to 3840, or 3840 to 3845, or 3845 to 3850, or 3850 to 3855, or 3855 to 3860, or 3860 to 3865, or 3865 to 3870, or 3870 to 3875, or 3875 to 3880, or 3880 to 3885, or 3885 to 3890, or 3890 to 3895, or 3895 to 3900, or 3900 to 3905, or 3905 to 3910, or 3910 to 3915, or 3915 to 3920, or 3920 to 3925, or 3925 to 3930, or 3930 to 3935, or 3935 to 3940, or 3940 to 3945, or 3945 to 3950, or 3950 to 3955, or 3955 to 3960, or 3960 to 3965, or 3965 to 3970, or 3970 to 3975, or 3975 to 3980, or 3980 to 3985, or 3985 to 3990, or 3990 to 3995, or 3995 to 4000, or 4000 to 4005, or 4005 to 4010, or 4010 to 4015, or 4015 to 4020, or 4020 to 4025, or 4025 to 4030, or 4030 to 4035, or 4035 to 4040, or 4040 to 4045, or 4045 to 4050, or 4050 to 4055, or 4055 to 4060, or 4060 to 4065, or 4065 to 4070, or 4070 to 4075, or 4075 to 4080, or 4080 to 4085, or 4085 to 4090, or 4090 to 4095, or 4095 to 4100, or 4100 to 4105, or 4105 to 4110, or 4110 to 4115, or 4115 to 4120, or 4120 to 4125, or 4125 to 4130, or 4130 to 4135, or 4135 to 4140, or 4140 to 4145, or 4145 to 4150, or 4150 to 4155, or 4155 to 4160, or 4160 to 4165, or 4165 to 4170, or 4170 to 4175, or 4175 to 4180, or 4180 to 4185, or 4185 to 4190, or 4190 to 4195, or 4195 to 4200, or 4200 to 4205, or 4205 to 4210, or 4210 to 4215, or 4215 to 4220, or 4220 to 4225, or 4225 to 4230, or 4230 to 4235, or 4235 to 4240, or 4240 to 4245, or 4245 to 4250, or 4250 to 4255, or 4255 to 4260, or 4260 to 4265, or 4265 to 4270, or 4270 to 4275, or 4275 to 4280, or 4280 to 4285, or 4285 to 4290, or 4290 to 4295, or 4295 to 4300, or 4300 to 4305, or 4305 to 4310, or 4310 to 4315, or 4315 to 4320, or 4320 to 4325, or 4325 to 4330, or 4330 to 4335, or 4335 to 4340, or 4340 to 4345, or 4345 to 4350, or 4350 to 4355, or 4355 to 4360, or 4360 to 4365, or 4365 to 4370, or 4370 to 4375, or 4375 to 4380, or 4380 to 4385, or 4385 to 4390, or 4390 to 4395, or 4395 to 4400, or 4400 to 4405, or 4405 to 4410, or 4410 to 4415, or 4415 to 4420, or 4420 to 4425, or 4425 to 4430, or 4430 to 4435, or 44

Batten Seam—continued

below, showing finished seam and progressive steps in forming and attaching with cleats. Construction of batten seams at ridge and hip and ends of battens are shown in diagram.

- Do not drive nails through strips. Use cleats, space at intervals of 8".
- Stagger the cleats along battens.
- Stagger all flat lock soldered seams to avoid extra thickness.
- All work must be painted with two coats of a long oil base paint immediately.

STANDING SEAM

Use seamless terne roofing. (Specify gauge and coating weight.) Paint one side and dry well before applying to roof with shop painted side down. This coat may be applied at the mill. Before beginning the first course, be governed by proper application at ridge, gutter, valley, drip edge, end or side wall, etc.





Specify ridge treatment to be either flat seam, standing seam, or seamless with continuous cross seams.

To form standing seams, make vertical bend along the longer dimensions of sheets or rolls, on one side $1\frac{1}{2}$ " high and on the other side $\frac{1}{4}$ " upturned edge. Bend the cleat $\frac{1}{4}$ " over top of the upturned edge and bend the other end of cleat over staple or nail head. Place next joint in position with the $1\frac{1}{2}$ " flanged edge adjoining the one attached to the roof. Bend $\frac{1}{4}$ " of the $1\frac{1}{2}$ " flange edge over $1\frac{1}{4}$ " cleated edge, forming a single lock standing seam $1\frac{1}{4}$ " high; continue by turning over $\frac{1}{4}$ " of the standing seam, thereby forming a double locked standing seam $1\frac{1}{2}$ " high. Press the seam tightly together in each operation. Stagger cross seams to avoid extra thickness in pressed standing seams.

All cross seams to be single locked soldered joints excepting expansion joints which must be placed above the high water line of gutters, valleys, walls, etc. Cross seams to be

made according to the flow; that is, the higher strips must always overlap the lower adjoining strips.

All work must be painted immediately after application.

STANDING SEAM**FLAT LOCKED SEAM**

Use seamless terne roofing. Specify gauge and coating weight. For roofing or at end walls, side walls, gutters, drip edges, valleys, flashings, etc., use $14\frac{1}{2}$ ", 20", 24" or 28" wide seamless rolls (specify preference). Paint one side and dry well before applying to roof with painted side down. The shop applied coat is sufficient for the under side. Do not nail through the strips. Attach strips to roof with cleats made of the same material. Place cleats at 8" intervals.

Notch corners of the strips and turn $\frac{1}{2}$ " edges, top and one end turned up and bottom and one end turned under, to form $\frac{1}{2}$ " flat seam.

Before beginning the first course, be governed by proper application at ridge, drip edge, end or side wall, gutters, valleys, etc.

Nail cleats to sheathing board. Bend one end of cleat over nail heads and hook the other end of the cleat into the $\frac{1}{2}$ " edge formed on strip. Lay strips according to the flow, i.e., placing the strip higher on the roof over the upper edge of the lower adjoining strip. Sufficient pitch must be provided for proper drainage to prevent any water from standing thereon.

Stagger all joints. Seams to be malletted down to form flat overlapping surface. Carefully mallet the seams to avoid buckling. Sock the seams well with half and half solder, using rosin as a flux. Remove all excess rosin before painting. Never use acid flux.

All work must be painted with two coats of a long oil base paint immediately after application.

For more detailed information or answers to specific queries, write to:

Architectural Department

LEAD INDUSTRIES ASSOCIATION
292 MADISON AVE. NEW YORK 17, N. Y.