

Test 1977

Name Willie J. WilsonDepartment DRYERDate 10-3-77

- 5- 1- The VCM Standard that we now comply with has limits for VCM of 1 ppm time-weighted-average and excursions of 5 ppm for 15 minutes.
- 2- Respiratory Protection devices (gas masks, continuous flow airline, Scott Air Pak) are required above:
- A- 1 ppm ✓
 - B- 10 ppm
 - C- 32 ppm
- 3- Our continuous Honeywell monitors sound an alarm when 10 ppm is reached in an area.
- A- 1
 - B- 10
 - C- 32
- 4- All respirators masks are cleaned:
- A- Weekly
 - B- Monthly
 - C- Daily ✓
- 5- We monitor you on a regular basis to:
- A- Minimize your exposure to VCM
 - B- Monitor our progress in reducing VCM concentrations in our plant
 - C- Both A and B ✓
 - D- Neither A or B
- 6- The VCM regulation does not apply to products made from PVC.
- True ✓
False
- 7- The two regulated areas in our plant are:
- A- Dry Blend basement and Q C Lab
 - B- P-1 building and Boiler House
 - C- VCM Tankfarm and Large Reactors ✓
- 8- Our Plant Emergency Procedures are outlined in the:
- A- Collective Bargaining Agreement
 - B- Make Safety A Habit Booklet
 - C- PVC Plant Safety and Health Manual ✓

VCM TRAINING CLASS

Test 1977

page 2

9- Does non-Conoco personnel have to sign the Regulated Area Log before entering the area?

Yes ✓

No

10- Our plant is continuously monitored for VCM at 40 different points 24 hrs. aday year round.

True ✓

False