


Hirschman-Pohle Co., Inc.

Since 1908

200 Lent Ave. . . . LeRoy, N. Y.

Sales Representatives in Principal Cities

Manufacturers of all types of Power and Gravity Roof Ventilators




Minimum Overall Height

(So Desirable for Modern One-Story School Buildings)

Roof opening "A"	10"	12"	15"	18"	20"	24"	30"	36"	42"
Cowl height "C"	5 1/4"	6"	7"	8"	9 1/4"	11"	12"	14"	16"

The Hirschman Type "CAF" Electric ventilator shown has been designed in response to a demand for the absolute minimum in overall height above the roof line, and as standard construction uses our INSULATED DOUBLE SHELL STEEL CURB of any of the several types for any kind of roof deck. Fan and motor assembly available for a wide range of capacities at the lower static pressures. The companion Type "CA" gravity or pressure relief ventilator (not shown) uses the same general construction minus the fan and motor. Either type subject to numerous modifications to meet the needs of any building project.



Our Type "LA" STATICK Power ventilator designed for efficient exhaust at either low or high static pressure, using non-overloading backward curved blade centrifugal fan, available in many sizes for almost any required capacity within reason. Note the damper housing above the top of the curb providing ready access to whatever type of damper is used. The Type "LB" STATICK Power ventilator (not shown) uses a similar construction minus the damper housing.


See Sweet's Architectural, Engineering, or Industrial Construction Files.
Complete data on any or all types gladly furnished on request.

Muckle Manufacturing Co.


666 Belford Road

Owatonna, Minn.


Sales Engineering Representatives in Principal Cities




MUCKLE VENTS—are ideal for moisture laden applications or corrosive conditions. Motor is located out of the air stream, and housing is hot dipped galvanized after fabrication for maximum protection. Capacities 254 to 10280 cfm. Units very efficient at low static pressures. Constructed from heavy gauge steel, electrically welded.



MUCKLE LO-SIL—designed for low silhouette appearance. Largest unit only 25 1/2 in. high. Capacities from 225 to 17,600 cfm. Automatic back draft dampers built in on all models. Vibration separators are provided to eliminate vibration and hum. Totally enclosed, ball bearing motors are directly connected to propeller.



MUCKLE BC VENT—Centrifugal backward curved wheel is ideal for operation where static pressures are encountered. Non-overloading, dynamically balanced wheel, directly connected to totally enclosed motor. No maintenance of belts, pulleys, or bearings. Motor is out of air stream for protection. Capacities from 280 to 7650 cfm. Heavy gauge construction.



MUCKLE BELTED VENT—offers over 100 different capacities for any specific requirement. High exhaust capacity utilizes low fan tip speed to make unit very quiet in operation. Low in height, compact and symmetrical design, blends well with modern architecture. Heavy duty, ball bearing motors and non-overloading backwardly curved wheels used on all units.

MANUFACTURERS OF POWER ROOF VENTILATORS FOR OVER 15 YEARS
SEE SWEETS ARCHITECTURAL OR INDUSTRIAL FILE, OR COMPLETE DATA
FURNISHED UPON REQUEST.