

Internal ^{EE&PC}
USE Copy

FATE OF FLUOROCHEMICALS - PHASE II

Prepared by:

Environmental Laboratory (EE & PC)

E. A. Reiner, Editor

May 20, 1983

**Exhibit
1282**

State of Minnesota v. 3M Co.,
Court File No. 27-CV-10-28862

ACKNOWLEDGMENTS

This proposal represents the combined efforts of many persons throughout 3M, particularly past and present members of the Environmental Laboratory Staff.

Special thanks are extended to Commercial Chemicals, Agricultural Products, Riker Laboratories, Central Research Analytical Services, and 3M Toxicology for sharing with us pertinent information from their experience on selected fluorochemicals. We apologize for any misquoted information or incorrect interpretations which may have crept into the final proposal.

TABLE OF CONTENTS

	<u>Page</u>
ABSTRACT	1
ORGANIZATION OF REPORT	1
I. INTRODUCTION	3
A. Background	3
B. Remaining Environmental Concerns	4
C. Timing	6
D. Costs	6
II. FLUOROCHEMICAL RISK ASSESSMENT	7
III. COMMON CONCERNS WITH 3M FLUOROCHEMICALS	10
A. Structure Activity Relationships	10
B. Field Studies	20
C. Incineration	27
IV. ENVIRONMENTAL PROPERTIES OF FLUOROCHEMICAL CLASSES	29
A. Inert Liquids	29
B. Low MW Acids and Their Salts	34
C. Surfactants	36
D. Phosphates	55
E. Alcohols	58
F. Acrylates	69
G. Urethanes	77
H. FLUOREL® and KEL-F® Polymers	81
I. Catalysts	82
V. SUMMARY	83
REFERENCES	93
APPENDIX I - AQUATIC TOXICITY RANKING SYSTEM	A-1
APPENDIX II - KEY TO CHEMICAL PRODUCTS DISCUSSED IN REPORT	A-2
APPENDIX III - NEEDS FOR ¹⁴ C-RADIOLABELED FLUOROCHEMICALS	A-6

FATE OF FLUOROCHEMICALS - PHASE II

ABSTRACT

This report reviews the Environmental Laboratory's knowledge through the end of 1982 of the environmental behavior of 3M fluorochemicals and proposes areas of further study necessary to resolve important unanswered questions.

ORGANIZATION OF REPORT

The arrangement of the report is as follows:

- I. INTRODUCTION. This section covers four areas:
A) Background, B) Remaining Environmental Concerns,
C) Time, and D) Cost requirements of the proposal.
- II. FLUOROCHEMICAL RISK ASSESSMENT. The reader is introduced to the basic approach and thought processes used by the Environmental Laboratory in assessing the environmental risks of fluorochemicals and the need for such study.
- III. COMMON CONCERNS WITH 3M FLUOROCHEMICALS. This section is divided into 3 parts:
 - A. Structure-Activity Relationship. This part addresses the need to develop capabilities which will enable prediction of the environmental behavior of fluorochemicals from structure and physical properties measurements rather than expensive laboratory and field testing.
 - B. Field Studies. This part discusses a proposal to perform on-site studies to evaluate actual environmental concentration and fate of selected fluorochemicals. The section emphasizes the need to compare field study data with laboratory data predictions.
 - C. Incineration. This part describes the need to determine experimentally whether fluorochemicals produce toxic combustion by-products at levels that could have significant effects on the surrounding environment.
- IV. ENVIRONMENTAL PROPERTIES OF FLUOROCHEMICAL CLASSES. This extensive section reviews existing environmental data and assessment needs for each of the following fluorochemical groups: A. Inert Liquids; B. Low Molecular Weight Acids and Their Salts; C. Surfactants; D. Phosphates; E. Alcohols; F. Acrylates; G. Urethanes; H. the FLUOREL® and Kel-F® polymers; and I. Catalysts.

Each of the above fluorochemical groups (A through I) are further divided into two parts entitled:

1. Background: An examination of current understanding of physical properties, degradability, and bio-effects for each fluorochemical group.
 2. Recommended Testing: Proposals for further studies needed in order to fill important gaps in present knowledge. Decision points, expected test output, and priorities are included.
- V. SUMMARY. This section reviews in tabular form the proposed work and cost for this Part II of the Fate of Fluorochemicals Study.
- VI. REFERENCES. A list of cited 3M internal reports and published literature reports.

Four appendixes follow the report:

Appendix I: The NIOSH Aquatic Toxicity Ranking System.

Appendix II: "Key to Chemical Products Discussed in the Report." This appendix provides the class, chemical code name, and structure or formulation of chemical products mentioned in the report text.

Appendix III: "Needs For ^{14}C -Radiolabeled Fluorochemicals." It lists the proposed tests which require, or would be simplified by, using radiolabeled fluorochemicals. The section addresses test priorities, the preferred placement of the radiolabel on the fluorochemical, and the importance of having radiolabeled material for each recommended test. The appendix also references the location of the proposed test in the report.

Appendix IV: Article from the Chemical Regulation Reporter showing the importance of structure activity relationships to the U.S. EPA chemical assessment program.

I. INTRODUCTION

A. Background

The Environmental Laboratory has a considerable amount of environmental test data on 3M fluorochemicals. This work consists primarily of environmental screening tests on Commercial Chemicals Division products and a previous (Part I) "Fate of Fluorochemicals" study*.

Nearly all Commercial Chemicals Division liquid and low molecular weight fluorochemical products have been subjected to environmental screening studies. In most cases, these studies determined 1) the concentrations of fluorochemicals which cause acute lethality to fish (96-hr. LC50); 2) laboratory BOD/COD tests determined the portion of the product that microorganisms can degrade readily; and 3) for sewerage fluorochemical products, microbial bioassays determined the levels which inhibit waste treatment microorganisms.

In the Part I study, more extensive laboratory studies were done to further evaluate the environmental effects of selected fluorochemicals (1,2,3). Data from this study are summarized in Table 1, and the main body of this present report references and discusses these data in greater detail as background information for the Fate of Fluorochemicals Study Part II.

The major general findings of the Fate of Fluorochemicals Program Part I and other field and laboratory studies on fluorochemicals performed over the last three years are:

1. Fluorochemicals have some common characteristics. The most environmentally significant is their greater resistance, compared to their hydrogen or other halogen analogs, to degradation through chemical, biochemical, and photochemical mechanisms. Some of this stability appears to extend to the nonfluorinated portions of fluorochemical molecules. This stability is due to the inherent strength of the

* The Environmental Laboratory conducted the Fate of Fluorochemicals Study Part I from 1976 through 1979. Four fluorochemical products (FC-95, FC-143, FC-807, and FM-3422) were examined in some detail and several 3M technical reports were written. The present proposal references many of these earlier technical studies. The Environmental Laboratory wrote comprehensive reports on three of the four chemical products (1,2,3). Analytical difficulties--which now have been solved (4,5)--stymied the work on FC-807.

carbon-fluorine bond and is probably enhanced by the hydrophobicity of the perfluorinated portions of 3M fluorochemicals. This hydrophobicity would be expected to repel water from the fluorochemical molecules so that hydrolysis and degradation by enzymes is minimized.

2. Most 3M fluorochemicals exhibit low orders of toxicity to aquatic organisms in both acute and subchronic tests. Some fluorochemical surfactants, however, have been found to be exceptions.
EC-95 EAL-80021, for example, was moderately toxic to fathead minnows in critical life-stage studies(6). It should be noted, however, that a majority of commonly used nonfluorinated surfactants are also moderately toxic in acute aquatic tests (7).
3. The fluorochemical alcohol, FM-3422, has very low water solubility, a high octanol-water partition coefficient, and tends to concentrate in the lipid portions of fish(8,9).
4. Regression analysis of experimental soil sorption coefficients and water solubilities of four 3M fluorochemicals shows that these two parameters correlate well with the same regression equation derived for nonfluorinated organics(10). This suggests that some of the classic structure-activity relationships for physical properties also may be applicable to fluorochemicals.
5. Preliminary field studies at Decatur demonstrated that the soil environmental compartment receives the highest concentration of fluorochemicals from the application of wastewater treatment sludge. A laboratory analysis showed sludge to contain 730 ppm of organic fluorine(11,12). In comparison, fluorochemicals entering the Tennessee River in wastewater effluent were present at 10.9 ppm organic fluorine, but the volume of the effluent is 200 times that of the sludge (13).

B. Remaining Environmental Concerns

Major environmental questions which were not addressed during the Fate of Fluorochemicals Study Part I or which have surfaced since 1979, include:

1. What are the environmental fate and effects of fluorochemical polymers?
2. What is the applicability of SAR (Structure Activity Relationship) estimation techniques to fluorochemicals?

TABLE 1

DATA ON FLUOROCEMICALS INCLUDED IN
FATE OF FLUOROCEMICALS STUDY PART I

3M "CONFIDENTIAL"

PRODUCT	EA1 80021	LR 5625	LR 3844-4	cc 795-23
STRUCTURE	$C_8F_{17}SO_3^-K^+$	$C_7F_{15}CO_2^-NH_4^+$	$C_8F_{17}SO_2N(Et)C_2H_4OH$	$IC_8F_{17}SO_2N(Et)C_2H_4O_1_2P_2O_7NH_4^+$
MW	538	431	571	1221
PHYSICAL PROPERTIES (Room Temp)				
Aqueous solub., mg/l:	1080	$>5 \times 10^5$	0.05, 0.16	--
Octanol-Water Part., log K_{ow} :			6-7	--
Vapor Press.:	--	Unknown (a)	Unknown (a)	--
Soil Adsorp., K_{oc} :	45	17	1500	--
Soil TLC:	Inconclusive	Inconclusive	No mobility	--
DEGRADATION				
Chemical Hydrolysis: detected	--	--	Hydr. to EA1 80021 in alcoholic KOH ($T_{1/2}$ =77 hrs.)	No reaction at pH 3-12.3 and 45°C for 24 hrs.
Photochemical, in solution: adsorbed to soil:	None (b)	None (b)	None (b) Inconclusive results	--
Biological, Shake flask: Warburg:	None (2 1/2 month) None-3 hrs.	None (2 1/2 month)	None (3-month)(c) Probably none	Inconclusive
SCAS (d): BOD ₂₀ :	-- None	-- None	None (7-day)	-- Probably none (e)
EFFECTS				
Fish, 96-Hr. LC ₅₀ , mg/l, Fathead: Bluegill: Trout:	38 68 11	766 569 --	>0.1 (f) -- --	>3600 mg/l -- --
30-Day Subchronic MTC ₉ , mg/l, Fathead egg-fry	1.9	>100	$>.0013$	--
Bioconcentration,	Residue detected qualitatively in fish placed in Decatur effluent.	--	In lab studies fish accumulated 200-600 times aqueous conc. Fish placed in Decatur effluent accumulated 7 ppm.	--
Daphnia 48-Hr. LC ₅₀ , mg/l:	50	632	>0.1 (d)	--
Algal 14-day EC ₅₀ , mg/l, cell weight:	146	73	>0.1 (d)	--
cell count:	95	43	--	--
Microbial, mg/l:	No inhibition of activated sludge respiration rate at 4000 mg/l	No inhibition of act. sludge res- piration rate at 1000 mg/l	No effect on wastewater treatment at 0.1 mg/l (d)	No effect on wastewater treat- ment at 1200 mg/l

Footnote:

- (a) Steam distills.
 (b) Study done in DI water at >300 nm
 (c) Slight O_2 uptake was observed but no degradation products found.
 (d) SCAS - Semicontinuous Activated Sludge.
 (e) Masked by degradation of isopropanol.
 (f) The limit of compounds solubility.
 (g) MTC - Minimum Threshold Concentration

3. What is the fate of fluorochemicals in soil systems?
4. What are the chronic effects on biota from exposure to realistic environmental concentrations?

This proposal explores areas where further study is needed and outlines a three-year systematic testing program to address these issues within a modest budget. These further studies are needed so that 3M can continue to ensure the long-term environmental safety of its fluorochemical-containing products.

The refractory nature (i.e., persistence) of fluorochemicals identifies them as potential candidates for environmental regulations, including further testing requirements under laws such as the Toxic Substances Control Act, the European Communities' Sixth Amendment, or Japan's Chemical Control Law.

C. Timing

The study will be conducted over a three-year period, with field studies requiring the greatest amount of elapsed time. Specific items are given priority ratings from I to III indicating importance and the order in which the program will progress.

D. Costs

The total cost of the study over the three-year period is estimated to be three to four man years (approx. \$300,000). For a summary listing of projected costs by test type and priority, see Table 14 in the summary section (V). Table 15, also in the summary, is a schedule by quarter of proposed work and costs.

3M "CONFIDENTIAL"

II. FLUOROCHEMICAL RISK ASSESSMENT

This section introduces the reader to the processes used in assessing the environmental risk of chemicals in general and 3M fluorochemicals in particular.

The evaluation of the environmental impact of a chemical starts with basic questions on what a chemical will do in the environment. These basic questions lead to more specific questions about the chemical's environmental impact based on our understanding of the properties and ecological interactions of this chemical and chemicals in general.

The most important basic question is: Will a chemical harm any life? This question leads to two others: What concentration of a chemical causes harm; and to what concentration will various plants and animals be exposed in the environment? Laboratory tests (bioassays) can be performed to determine what levels cause harm to selected species, but in order to answer how much exposure will occur, many additional questions must be answered. How much will be produced? How much will be disposed and how? Is the chemical sorbed by sediment? Do animals or plants bioconcentrate the chemical? Does the chemical partition mainly into air, water, or soil? Does the chemical degrade readily? and so on. The answers to these questions sometimes lead to yet other questions that can be answered experimentally. For instance, one may know that a chemical degrades in the environment but not know the major routes of degradation. Does it photodegrade? Is it chemically oxidized? Can it biodegrade, or can it hydrolyze? There are laboratory tests to evaluate the probability of each of these possibilities.

A full list of possible questions is quite long, but the length can be shortened in two ways. First, testing is done in an orderly progression so that the results of the first tests performed indicate which tests are not appropriate in the next round of tests (i.e., tier or sequential testing schemes). As properties of a chemical are elucidated, we can see that certain other tests are inappropriate. For instance, if we find that a chemical will rapidly and completely degrade, there is likely no need to perform bioaccumulation tests.

The second way of thinning a list of chemical questions or tests is by using "structure activity relationships" (SAR). This is a technique scientists use to say that chemical, physical, and biological properties depend, in a predictable way, upon the molecular structure. If we understand these relationships, we can predict relevant properties from the structure. This science is being used more and more frequently by both industry and regulatory bodies in environmental risk analysis.

Structure activity relationships are derived from empirical observations or theoretical concepts. Equations written to describe these observations or theories are then used to predict properties of untested chemicals falling within the structural limits of the system. Additional chemicals are then tested to validate and refine the relationships.

Tests and observations used in environmental studies range from simple laboratory measurements to field tests and observations. Field studies are a real-world luxury for environmental scientists, but in the case of fluorochemicals, an important opportunity exists to back up laboratory tests and predictions with field observations on a unique class of proprietary chemicals. The combination of field and laboratory measurements gives a much more convincing appraisal of what the environmental impact really is--or is not. *rich* ✓

Importantly, prudent testing of new chemicals as they evolve can help minimize, but never entirely eliminate, future testing of structurally related chemicals. Careful planning can yield a proper and complete testing program that will answer basic questions about the chemical of immediate concern and build a basis to make predictions about the behavior of similar chemicals produced in the future.

In the case of fluorochemicals, structural considerations and test results to date give rise to concern for environmental safety. For example:

- Fluorochemicals are halogenated organics and for this reason may be linked in the minds of regulators with chlorinated and brominated compounds that have caused problems in the past (e.g., PCB, PBB, DDT, etc.).
- Fluorochemicals are even more resistant to degradation than chlorinated and brominated chemicals.

These concerns give rise to legitimate questions about the persistence, accumulation potential, and ecotoxicity of fluorochemicals in the environment.

These questions and concerns should be answered for at least two reasons. First, where there is "smoke" (structural and stability similarities with known hazardous chemicals) there eventually will be a high level of concern from regulators and the public. 3M needs to have sound answers at hand with which we can respond to these concerns, questions, and possibly inaccurate accusations. *quickly respond* ✓

Second, the properties of fluorocarbons appear to be unique. They often do not act as other halocarbons do. In other words, the current structure activity relationships may or may not apply. In fact, it appears that 3M fluorochemicals pose very little problem compared with other halocarbons, and are environmentally "sound." But since these observations are contrary to many predictions, the hard data needed to support such a contention must be of the highest quality and more extensive than normal. Proper testing can strengthen the contention that our products are environmentally sound, or it can enable us to identify problems as soon as possible. Showing that our products are environmentally sound could have a beneficial marketing effect, and finding problems early can help 3M avoid potentially costly environmental problems and adverse publicity.

The potential application to new products or manufacturing process of reliable property values and relationships should not be overlooked as a by-product of this type of characterization program.

III. COMMON CONCERNS WITH 3M FLUOROCHEMICALS

This section deals with concerns that apply to all 3M fluorochemicals. It is divided into 3 parts: A. Structure-Activity Relationships. Presents use of SAR and proposes the development of further capabilities with fluorochemicals; B. Field studies. This subsection describes the minimal field data now available on 3M fluorochemicals and proposes further study at and surrounding the Decatur plant site; and C. Incineration. Gives existing information and questions concerning the incineration of 3M fluorochemicals.

A. Structure Activity Relationships

1. Background

State-of-the-art environmental risk assessment procedures use models to predict the mobility of chemicals and their concentrations in various environmental compartments. Most of these models are mathematical simulations of representative environmental systems and scenarios which require inputs of physical, chemical, and biochemical properties, which include aqueous solubility, octanol-water partition coefficient, vapor pressure, soil organic matter adsorption coefficient, and chemical, biochemical, and photolytic degradation rates. Figure 1 illustrates the types of movement between environmental compartments which are frequently modeled in risk assessment procedures.

In the absence of laboratory data, these chemodynamic properties can be estimated by structure activity relationships (SAR). While SAR provides a quick and economical method of estimating the chemical properties needed for environmental modeling, the applicability of existing SAR methods to the 3M line of fluorochemicals has not been validated. The current literature does not have sufficient information to defend using existing SAR approaches with perfluorinated chemicals, so SAR applications to 3M fluorochemicals are suspect.

The U.S. EPA is actively engaged in developing SAR estimation-mathematical modeling for the purpose of predicting the environmental behavior of chemicals. The extent of EPA commitment to SAR was clearly illustrated in a letter from the EPA's Assistant Administrator for Pesticides and Toxic Substances to the Department of State. In this letter, he states that physicochemical information is more readily and more accurately developed by existing Office of Toxic

Substances QSAR (Quantitative Structure Activity Relationship) methodologies than by the MPD (Minimum Premarket Data Base) measurements prescribed by the EEC 6th Amendment (14). Additional information on the importance of SAR to the U.S. EPA can be found in Appendix IV.

Since EPA can be expected to be concerned eventually with the risk and hazard of fluorochemicals, they are likely to apply data generated by these SAR methods to mathematical models to predict the environmental fate and effects of 3M (and other) fluorochemicals. Since the applicability of this approach to fluorochemicals is not validated, development of sufficient scientific knowledge is necessary to identify the true risks and to refute any inaccurate risk assessment which could affect 3M fluorochemicals.

The development of SAR predictive capabilities for fluorochemicals should also have utility to 3M in areas other than environmental, e.g., the design of perfluorinated structures with unique properties required for processing, product formulation, or new product development.

2. Objective

The objective of this proposed work will be to determine the applicability of SAR methods to 3M fluorochemicals, and, if necessary, obtain new data for SAR development. In this respect, two stages of structure activity analysis are of primary interest:

- 1) The use of equations interrelating properties; and
- 2) The estimation of physical properties from molecular structure.

475 SAR studies on fluorochemicals are complicated by the remarkable differences in physical-chemical properties between the fluorochemicals and other organic chemicals. The simplest method for aqueous solubility measurement^(15,16) uses HPLC quantitation, which will not be effective for the fluorochemicals, since most 3M fluorochemicals have no strong chromophores for UV detection. Alternative analytical methods, such as GC or total fluorine analysis, will require an extraction step. A more important potential problem involves the expected difficulty in getting pure samples of fluorochemicals.

The two-phase proposal has been designed to most rapidly and efficiently examine SAR application to fluorochemicals. The phases are:

Phase I: Evaluate existing, empirically derived SAR application to fluorochemicals.

Phase II: Derive new SAR for fluorochemicals

3. Phase I

Phase I will permit us to test the validity of applying existing SAR to 3M fluorochemicals without requiring method development or getting pure fluorochemical samples.

SAR procedures are most commonly derived as empirical relationships, which are applied to estimating properties of unknown substances. Extrapolation of an SAR to a new series of substances remains highly suspect until it can be validated. Such validation can be achieved by empirical methods, which requires physical property measurement by theoretical arguments or by a combination of the two.

This first phase will test application of the well-known SAR between octanol/water partition coefficient, K_{ow} , and aqueous solubility, S_w , for non-electrolyte solutes (10,15,16,17,18,19). This relationship is given by Equation 1a for pure liquids and by Equation 1b as a general expression for pure crystalline solids as well as liquids.

$$\begin{array}{ll} \log K_{ow} = A \log S_w + C & 1a \\ \log K_{ow} = A \log S_w + B (mp-25) + C & 1b \end{array}$$

In these equations, mp is the melting point in °C of a crystalline solid or 25 for a liquid, and A, B, and C are constants derived from linear regression analysis.

These equations were empirically developed using linear regression analysis on K_{ow} and S_w data. The data base from which the equations were derived did not include any good analogs of 3M fluorochemicals. Subsequent publications (15,16,17,20,21) have demonstrated a thermodynamic basis for this SAR, in which Equation 1 is explained by the activity coefficients for the solutes in octanol (o) and water (w). For this description, we have selected the Mackay treatment⁽²⁰⁾, Equations 2 and 3, in which o and w are expressed on a molar basis.

$$K_{ow} = 0.115 \frac{w}{o} \quad (2)$$

$$S_w = 55.5 \frac{(f/f_R)}{w} \quad (3)$$

In these equations, f/f_R is the fugacity ratio for the pure solute to the liquid reference state ($f/f_R = 1$ for liquids). The fugacity of crystalline solids is less than 1. Its f/f_R ratio can be estimated by means of its melting point. Combining Equations 2 and 3 yields Equation 4 for pure liquid solutes.

$$\log K_{ow} = -\log S_w - \log o + \log M_o \quad (4)$$

The M_o in this equation is the molarity of octanol in itself (6.36 moles/liter).

If o remains constant, then a $\log K_{ow}$ vs. $\log S_w$ correlation, as given by Equation 1a, will have a slope, A , equal to -1 , which empirical regression analysis on nonfluorochemicals confirms. The melting point term in Equation 1b accounts for the difference in fugacities of the solute as a solid and as a liquid (the defined reference state). Any series of solutes where o varies will not yield the linear regression expressions of Equation 1. Since 3M fluorochemicals are not miscible with octanol, nonideal behavior and a wide variation in their octanol activity coefficients, o , can be expected. These arguments ultimately predict that the existing SAR defined by Equation 1 will not apply to 3M fluorochemicals.

Amidon and Williams offered Equation 4a as a general relationship for relating aqueous solubility to octanol/water partition coefficient (22). They derived this equation from thermodynamic relationships for the following sequence: solid melted to supercooled liquid; supercooled liquid dissolved to yield an octanol solution; solute partitioned from octanol solution into aqueous solution. This equation uses the solubility parameter, δ , for the organic solute as a means of estimating its activity in octanol. Since this equation might be valid for nonionic fluorochemicals, it should be tested.

$$\log K_{ow} = -\log S_w - 7.3 \times 10^{-4} S_f (mp-25) - 7.3 \times 10^{-4} (V_2 (10.3 - \delta)^2 + 0.8) \quad (4a)$$

In this equation, S_f is the entropy of fusion, V_2 is the molar volume and δ is the Hildebrand solubility parameter for the substitute.

To avoid the need for pure fluorochemical isomers and methods development that are prerequisite to the direct study of the relationship between K_{ow} and S_w for fluorochemicals, an alternative approach is proposed. This approach will examine aromatic hydrocarbon partitioning between water and fluorochemical solvents by means of Equation 5, which can be derived by the Mackay approach(20,21).

$$\log K_{FW} = -\log (f/f_R)S_w - \log f + \log M_F \quad (5)$$

Here, K_{FW} is the fluorochemical solvent-water partition coefficient, f is the solute activity coefficient in the fluorochemical solvent, and M_F is the molarity of the fluorochemical solvent in itself. A nonlinear relationship for K_{FW} vs. S_w regression would be evidence that f for aromatic hydrocarbons would not be constant. If f varies for a series of hydrocarbon solutes, then f for a perfluorochemical series analogous to the fluorochemical solvent is expected to also vary. This would support the concept that Equation 1 will not be valid for 3M fluorochemicals(23).

Reference to Table 2

Two procedures for K_{FW} measurement are being considered. They are the standard shake flask method or preferably the new column generator technique developed by the National Bureau of Standards (15,16,17). The fluorochemical solvents selected should provide a reasonable estimate of the behavior of 3M fluorochemical types ranging from fluorochemical inert liquids to fluorochemical alcohols. We have selected as the preliminary candidate solvents: 1) perfluorooctane; 2) 1,1,2,2-tetrahydroperfluorooctanol from DuPont ($C_6F_{13}C_2H_4OH$); and 3) N-Et FOSE alcohol (FM-3422), which is a solid. This series of fluorochemicals, however, does not cover fluorochemicals which ionize in water, such as EAI 80021. Either measurement technique (shake flask or generator column) could be applied to the liquid fluorochemicals, but the solid, FM-3422, would require the generator column approach. We will select aromatic hydrocarbons from Table 2. This table comes from the National Bureau of Standards studies of octanol-water partitioning and aqueous solubility. We expect to choose about 10 solutes, based upon statistical needs.

The following table summarizes the anticipated scheduling and manpower for the work proposed in Phase I:

<u>Function</u>	<u>Man-hours</u>
Setup time	50-80
Analytical method development	50-70
System testing and range finding	50-70
Partition measurements using approximately ten solutes for each solvent:	
1) Perfluorooctane	125-200
2) 1,1,2,2-tetrahydro-perfluorooctanol	100-150
3) FM-3422	70-100
Total Phase I	445-670

*Renowned?
No. 100-150-100
solute?*

4. Phase II

As described above, SAR refers to both molecular substituent factor analysis for estimating physical-chemical properties (24,25,26,27) and correlation equations which relate two or more physical-chemical properties (18,19,21,28-37). Both approaches will require a data base of laboratory measurements to which standard regression analyses are applied to yield the SAR.

The objectives of this phase will depend upon the observations in Phase I and a literature review. It is anticipated that the SAR development will include estimating perfluorochemical fragment substituent constants for one or more key physical-chemical properties, such as K_{OW} , S_W , and vapor pressure, and making interproperty correlations, such as K_{OW} vs. S_W or soil organic matter sorption coefficient, K_{OC} vs. S_W .

The study will gather available data in the literature and from within 3M on the aqueous solubility, vapor pressure, octanol-water partition coefficient, and soil-water partition coefficient of fluorochemicals. When necessary, laboratory measurements will be made to fill in the gaps. It is anticipated that such measurements will be more accurate than in previous studies since attempts will be made to use test chemicals which exist as single isomers rather than products which are mixtures of structural and molecular weight isomers.

Correlations will then be made between measured fluorochemical properties, comparing them with those published in the literature for other types of organic compounds. Examples of relevant published correlations are those of vapor pressure and water solubility by Amidon and Anik (28); of aqueous solubility and partition coefficient by Banerjee et al (21); and of partition coefficient and biosorption partition coefficient developed by Steen and Karickhoff (37).

If correlations between the physical chemical and chemodynamic properties of fluorochemicals are strong, the developed estimation approach will be applied to existing literature data and to actual 3M fluorochemicals. Attempts will also be made to derive substituent constants for important 3M fluorochemical groups such as C_8F_{17} . Values of properties estimated by this approach will be compared with measured properties for validation.

The following is an estimated work load for Phase II. It anticipates the derivation of C_8F_{17} , CF_3 and CF_2 fragment constants for the Hansch and Leo approach to K_{ow} estimation and the derivation of correlation equations between K_{ow} vs. S_w and K_{oc} vs. K_{ow} or S_w .

<u>Function</u>	<u>Man-hours</u>
Substituent constants, K_{ow}	
Literature review	35-50
Property measurement	300-400
Statistical analysis	20-25
Correlation equations	
Literature review	5-10
Property measurements	250-350
Statistical analysis	20-25
K_{oc} vs. K_{ow} or S_w	
Method development for K_{oc} measurement	200-300
K_{oc} measurements	250-350
Statistical analysis	20-25
Total Phase 2	1100-1535

B. Field Studies

1. Background

The purpose of field studies is to determine what happens to chemicals in the real world. The results often confirm, but sometimes refute, laboratory predictions, and they often uncover unpredictable phenomena. In other words, field studies determine where in the environment chemicals accumulate, how they move in the environment, and whether or not they cause any adverse effects.

In evaluating the fate and effects of substances, a field study is extremely valuable but rarely practical. Such studies are frequently too costly to be justified for low volume chemicals. Release may be too widespread to allow for easy monitoring, or in the case of new chemicals, sufficient field release to allow detection may not have occurred.

The uncontrolled nature of field studies also presents potential problems. Unrelated natural or man caused factors may complicate data interpretation. For example, toxic discharges from nearby industrial or agricultural activities may mask the effects of the chemicals of interest.

For the fluorochemicals, though, a field study is possible since there has been known production and limited environmental release for years at a few facilities. By designing the proper studies, one can use these sites to evaluate the real-world fate and effects of fluorochemicals. This, in turn, will allow evaluation of the validity and the utility of predictions based only on laboratory observations. Such comparisons will also enable the Environmental Laboratory to make better estimates of the fate and effects of similar substances in the future with much less data and hence for less cost.

Table 3 summarizes results of past field studies on fluorochemical residues at the Decatur plant (11,12). The distribution of organic and inorganic fluorine was measured in the plant's wastewater treatment sludge and effluent, as well as in the soil where sludge had been applied. Some fluorochemical components were identified. Because these were only preliminary quantitative evaluations, it cannot yet be concluded that high fluorochemical concentrations have not accumulated near the plant site.

TABLE 3
FLUORIDE MEASUREMENTS AT THE DECATUR PLANT

	Measured Fluorine		
	<u>Total</u>	<u>Inorganic</u>	<u>Organic</u>
Sludge		223	730a
Effluent		23.7	10.9b, 0.096
Soil (Sludge Treated)	300c	440c	
Decatur Soil (untreated)	24.4	8.9	

a Major volatile fluorochemical was FM-3422. FC-143 and C₈F₁₇SO₂NH₂Et were also identified.

b Identified FC-143.

c Apparent analytical error (CRL Anal. #6937).

Fish placed in the Decatur effluent bioconcentrated those fluorochemicals with low water solubility (38). Residue concentrations in the fish were measured at 10 ppm for the FOSE amide (C₈F₁₇SO₂NH₂Et) and 7 ppm* for FM-3422 (C₈F₁₇SO₂NEtC₂H₄OH). Neither FC-128 nor FC-143 was detected. FC-95 was detected but not quantified.

This greater bioaccumulation of low water soluble fluorochemicals agrees with SAR relationships between bioaccumulation and water solubility or octanol-water partition coefficient derived for nonfluorinated organic chemicals (24,39).

*For perspective, FDA allows PCB concentrations up to 2 ppm in edible portions of fish.

2. Field Study at Decatur Plant

A field study is recommended to measure distribution, biological uptake, and effects of fluorochemicals near the Decatur plant. In this study, we want to determine: 1) if fluorochemicals are long lived as predicted; 2) if they concentrate near the point of entry or are diluted throughout the environment; 3) if they concentrate in one compartment of the environment such as air, water, soil, sediment or biota; 4) if they cause any ecological effects.

Fluorochemicals have been produced at the Decatur plant for about thirty years. Since then, they have been entering the environment through landfilling of tars and other by-products, through water discharges, both before and after the installation of a modern wastewater treatment facility, through vapor discharges from manufacturing processes and wastewater aeration basins, and more recently through the field incorporation of wastewater sludge containing fluorochemicals.

Analytical capabilities will be tested and evaluated prior to study initiation. While there is concern about all fluorochemicals produced at Decatur, we plan to monitor only three (perfluorooctanoic acid, perfluorooctyl sulfonate, and FM-3422). Specific analyses, however, will only be made after first determining the need by looking at the levels of total organic fluorine. This preliminary screening for total organic fluorine will eliminate an unnecessarily large number of costly specific fluorochemical analyses. We can obtain estimations on how these chemicals and other fluorinated chemicals move and act in the environment by looking at just organic fluorine.

A comparison of the difference between the total organic fluorine concentration and the concentration of the three specific monitored chemicals would indicate whether other fluorinated chemicals may be important as environmental contaminants, and thus whether they should also be identified. Other fluorochemicals found in significant quantities in Decatur soil, sludge, biota, wastewater, and receiving water by methods such as capillary GLC may also be identified and quantitatively determined in the study.

The analytical techniques selected must have adequate specificity for 3M fluorochemicals to ensure accurate identification in order to avoid false alarms. *POST 10.5*
Analytical work, done to determine if Tennessee River fish bioconcentrated 3M fluorochemicals, has clearly illustrated the potential for incorrect results with nonspecific analytical techniques (40,41). In this study, preliminary GLC analysis with electron capture detection separated three peaks from fish extracts that moved identically to those of three 3M fluorochemical controls (40). Had analysis stopped here, it would have appeared that 3M fluorochemicals were bioconcentrating into fish from ambient concentrations. However, confirmational analytical work using microwave sustained helium plasma detection showed that the peaks from the fish tissue extracts were not due to fluorochemicals (41).

✓ Before sampling, conceptual modeling will be conducted in an attempt to predict the field study findings. These predictions will be based on old and new laboratory data, available discharge records, and maps of the site. When possible, widely used environmental models such as the EPA's EXAMS System will also be applied. This exercise will help to ensure a meaningful interpretation of the field study results and will immediately draw attention to unexpected results. It will also help in evaluating the applicability of existing models, which are based mostly on hydrocarbon data, in predicting the environmental behavior of fluorochemicals. *as I will Resample Friday C*
SLSA
in appen. give sig of parent
Validate

The following is a list of proposed sampling sites and procedures. These procedures and sites may be adjusted as other information on the properties of the chemicals and nature of the sampling sites become available. At the time of sampling, complete details of the sampling sites, including pictures, will be recorded.

a) Sludge

A series of grab sludge samples will be taken to compare with other samples previously taken. Sludge should be sampled when it is being pumped from storage to be applied to fields. The results will be used to estimate quantities and variability of fluorochemicals entering the soil environment through sludge incorporation. (7 samples, 96 hrs.)

b) Effluent

Effluent will be collected at the outflow of the biological treatment system before mixing with cooling water. Concentrations entering the reservoir will also be calculated based on relative flow rates and the assumption that no fluorochemicals are present in cooling water. One 5-liter sample will be taken during each of four different weeks so that the variation in the effluent characteristics can be evaluated. Single controls will also be taken from two waste treatment systems not treating fluorochemicals. The results of the analysis will give an estimation of the quantities of fluorochemicals entering the lake. The values will be compared with those from sediment and biota. (6 samples, 84 hrs.) ✓

c) Soil

Soil from the fields where sludge has been incorporated will be collected in accordance with accepted methods (42) and analyzed for total organic fluorine and, if this is found in high quantities, for the three fluorochemicals specified above. Approximately ten samples will be collected from the fields in different locations. Sampling depth will be between the surface and 12". *n=3/field*

In addition to these samples, approximately six soil samples from the ditches that collect runoff water from the field will be taken at points outside the sludge application area.

Two controls will be taken from a location with the same soil type at least 10 miles from the manufacturing facility. The exact locations of the sampling sites will be set after review of the sludge incorporate rates in the fields and the runoff patterns of the fields. ✓

??
hydrocarbons (not)
The results from the analysis of these samples will be used to estimate how much of the applied fluorochemical stays in the soil at the site and how much of the fluorinated sludge is washed from the field, possibly to the adjacent reservoir. (18 samples, 252 hrs.)

d) Field Vegetation

Six crop samples will be collected at harvest time from fields receiving sludge and two from control fields. *n=3/field*

These samples will first be analyzed for total organic fluorine. Then if there are high levels, the crops will be analyzed for FC-143, FC-95, and FM-3422, and a rat feeding study using the crop will be initiated. The purpose of the feeding study will be to determine the uptake kinetics of the fluorocarbons from the crop. The details of the feeding study will be set if or when it is appropriate. (8 samples, 108 hrs not including possible feeding studies)

e) Fallout

One important possible mode of entry of the fluorochemicals into the environment is through air emissions from plant manufacturing processes or volatilization due to aeration of the waste treatment system. Chemicals entering the environment through the air are usually either diluted into the air and therefore carried off or they precipitate out, usually locally. When there is such fallout, the concentration is usually greatest closest to the source and falls off with distance from the source.

*10 miles
down road
July*

Thus, we propose sampling the soil close to the plant and at increasing distances from the plant. Two sampling vectors would be set up. The first would follow the predominant downwind trajectory and the other upwind. Four soil core samples would be collected along each vector at intervals of 100M, 200M, 400M, and 800M. Two control samples will be taken several miles from the plant. The location is yet to be determined. Samples will not be taken from those points where sampling vectors intersect waste disposal sites or the river (10 samples, 144 hrs).

f) Sediment

Previous studies have shown that several of the fluorochemicals bind to soil and thus would be expected to also bind to aquatic sediments. For this reason there is a need to look at aquatic sediment to see how much fluorochemical does bind. Chemicals that bind to sediment and are in water tend to fractionate into the sediment very rapidly, and are usually found in higher concentrations where effluent waters enter a lake or pond. The concentration decreases with distance away from the entry point. (1) For this reason, we propose to sample sediment at the effluent entry point and at the middle and mouth of the cove into which the discharge flows. Since the flow of the effluent after entering the reservoir can vary, additional sampling will follow three vectors:

one up the shore line: one down the shore line, and one perpendicular to the shore line. Sampling depth will be determined on-site and will depend on the bottom topography along each vector. Control samples will also be taken from points on the river well above and below the plant site. Only the top 1-2 centimeters of sediment would be sampled. The sampling method has not been determined yet, but it could be either done by diving and scraping the top 1-2 centimeters or by using a Vanbean sampler with a removable top to obtain the top 1-2 centimeters. (9 samples, 132 hrs.)

g) Biota *Benthos* *n=5*

There will be two types of biotic sampling. First, to estimate possible effects and second, to determine if biota accumulate fluorochemicals. The sampling points will be the same as for the sediment samples for the same reason and so that the concentrations in the sediment can be directly compared with the concentration in the biota. If there is an effect on biota, then either species diversity or populations will likely decrease with increasing concentration of the chemical causing the effect. The clam, Corbicula, will be sampled in order to determine the concentration of fluorochemicals in biota. (43) (18 samples, 204 hrs.)

h) Water Column

The concentration of fluorochemicals in the water column will be measured at each of the sites where the biota and sediment are sampled in order to directly compare the concentration of fluorochemicals in the water versus the sediment and the biota. The parts of the water column that will be sampled will depend on the mixing pattern of the water, the flow of the effluent, and topography of sampling sites. One possibility is to sample water close to the bottom, at the middle of the water column, and close to the surface. (12 samples, 168 hrs.)

Dye study

n=3/part

water col.

3. Priority

This field work is needed for three reasons: 1) very little data now exists on the actual environmental concentration and (impact) of fluorochemicals; 2) the study will assist in clarifying those physical, chemical, and biochemical properties of fluorochemicals that are most important in determining their environmental fate; 3) it will provide the necessary data for validation or correction of our present estimated environmental concentrations from our modeling studies.

effects

n.d.p. reference

The primary objective of the field study, however, is to determine if unanticipated or unreasonably high fluorochemical concentration exists in any site near the Decatur manufacturing plant and to extend such information to predictions at other manufacturing and use sites.

The phases of this study are given the following priority:

- Phase 1 (confirm analytical capabilities) -
Priority I - 150 hours
 - Phase 2 (modeling to predict findings) -
Priority I - 20 hours
 - Phase 3 (field samples and sample analysis) -
Priority III - 1200 hours
- in some cases of
modeling
time ??*

C. Incineration

1. Background

Incomplete combustion of fluorochemicals can lead to the formation of acutely toxic by-products such as carbonyl fluoride and perfluoroisobutylene in addition to the HF normally formed. *ref*

Incineration studies conducted by EE&PC at a pilot scale incineration facility looked for possible toxic by-products (such as CF_2O , OF_2 , perfluoroolefins or NF_3) from FC-78 (100 ml) combustion (with 5 gallons #2 fuel oil) at 2185°F . None of these components were detected at 1 and 5 ppm in condensable and volatile components, respectively. However, literature sources describing other fluorochemical combustion studies have observed some of these toxic components (44). *cc*

2. Approval and Decision Points

A test burn of fluorochemicals at the Decatur incinerator is recommended. The Decatur incinerator has been selected for this study because it is more likely to allow the formation of incomplete combustion products than the more sophisticated Chemolite incinerator. Thus, if the Decatur incinerator does not produce significant levels of toxic by-products, we would assume that the similar Cordova or more modern Chemolite incinerators are at least as effective in destroying fluorochemicals without producing toxic by-products.

Samples of the material to be incinerated will be analyzed for HF and Total Organic Fluorine. Suggested stack gas analytical parameters include HF, CF₂O (carbonyl fluoride), perfluoroisobutylene, total organic carbon (TOC), total organic fluoride, and CO.

Analytical capabilities and sample handling, stability, and preservation requirements will be evaluated prior to the test. As some of these possible by-products are quite reactive, sample handling difficulties are anticipated and could cause cancellation or changes to portions of this proposal.

modification

*necessary
to say
cancellation*

3. Priority

The study is a confirmatory test planned to tell us if the Decatur incinerator does or does not emit unreasonable amounts or concentrations of hazardous degradation products.

A Priority III is assigned to this proposal.

IV. ENVIRONMENTAL PROPERTIES OF FLUORO-CHEMICAL CLASSES

This section reviews our present knowledge of the following classes of 3M fluorochemicals: A. Inert Liquids; B. Low MW Acids and Their Salts; C. Surfactants; D. Phosphates; E. Alcohols; F. Acrylates; G. Urethanes; H. FLUOREL® and Kel-F® Polymers; and I. Catalysts.

The section on each fluorochemical class is further divided into a "Background" section and a "Recommended Testing" section. The Background sections outline our present understanding of the environmentally significant aspects of the fluorochemical class' physical properties, degradability, and effects. The "Recommended Testing" section proposes additional work and gives decision points and expected test output. Each study is given a priority rating of I, II, or III in which the numbers indicate both the need and the order in which the proposed studies should be done.

The proposed physical properties measurements will broaden profiles on individual fluorochemicals which are representative of these important fluorochemical classes. These data will be used both to model their environmental fate and as a data base for SAR development.

Degradations studies will determine which, if any, of the possible environmental degradation mechanisms (chemical, biochemical or photochemical) are important in the environmental fate of the fluorochemical classes.

and persistence

Effects testing will determine the concentration of fluorochemicals that could adversely affect ecological systems.

These three types of data, when used in combination with modeling and field data, will yield a good indication of the likelihood of adverse environmental effects from these 3M fluorochemical classes.

with assessment

A. Inert Liquids

1. Background

a) Physical Properties

Commercial Chemicals Division Technical brochure Y-ITPB-1(21.3)JR summarizes the physical properties of Fluorinert Electronic Liquids. These data indicate that all FLUORINERT liquids have sufficient volatility to enable them to eventually evaporate and disperse into the atmosphere.

Calculations based on models developed by Cupitt (45) show that, once in the atmosphere, the FLUORINERT liquids are not likely to be removed by dissolving in rain water or by adsorbing to and settling with particulates. In any case, because of their high volatility, any of these inert fluorochemicals removed from the atmosphere by these processes will likely eventually reevaporate to the atmosphere.

Some unanswered questions do exist concerning the physical properties of the inert fluorochemicals. For example, how strongly do they adsorb to soil? Soil sorption data allows us to predict mobility and determine if they, like some chlorinated solvents, are likely to move from spill and land disposal sites and contaminate groundwater sources. The Environmental Laboratory should be able to evaluate this possibility after development of structure activity relationships (SAR) capabilities. The low toxicity of FLUORINERT® Liquids, discussed below, makes this potential problem noncritical, but even if completely innocuous, the presence of man-made chemicals in groundwater is a sensitive and high profile subject.

on work

negot

b) Degradation

Fluorochemical inert liquids are very stable, resisting degradation under both extreme chemical and physical conditions. In addition, these liquids show no susceptibility to biodegradation in BOD and other biodegradation tests.

Their stability suggests that they will persist in the atmosphere for very long times. This hypothesis is substantiated by analytical findings of Dietz and co-workers (46,47,48). They found that perfluoromethylcyclohexane and perfluorodimethylcyclohexane have remained in the atmosphere near the concentration expected from their total worldwide production. The great majority of these two perfluorochemicals were released to the atmosphere in the 1940's at Oak Ridge, and eighty percent, or possibly all, of this fluorochemical is still in the atmosphere.

Due to the transparency of perfluoroparaffins and amines above 280 nm (49,50,51,52), the FLUORINERT products are not expected to degrade in the troposphere or lower stratosphere. Nitrogen-containing FLUORINERT products, which have the longest wavelength UV absorption, may

photodegrade in the mid-stratosphere, but other FLUORINERT chemicals will probably only photodegrade in the upper stratosphere and above. *higher*

Unlike other organic materials, degradation of inert liquids through reaction with OH radical is also unlikely to provide a significant sink for perfluorocarbons (53). Reactions with O(¹D) (which occurs primarily in the stratosphere) may have some significance (53).

The lifetime of these products is probably determined by the extremely long time required for molecules to diffuse into the upper regions of the atmosphere where photolysis, photooxidation or significant reaction with singlet oxygen can occur (54). Estimated atmospheric lifetimes of perfluorocarbons due to these reactions are on the order of hundreds of years (53).

Preliminary literature findings on chlorofluoromethanes and ethanes suggest that FLUORINERTS, unlike chlorofluorocarbons, are unlikely candidates to photodegrade after adsorbing to sand in spite of the strength of SiF bonds (55). The literature shows that increasing the number of fluorines in a chlorofluorocarbon greatly decreases its rate of photodegradation when adsorbed to sand (39,55). Thus, one would expect that these completely fluorinated compounds would degrade even more slowly than chlorofluoromethanes. In addition, these experiments have shown no detectable C-F bond breakage.

Kanno has reported on the sensitized photodegradation of Freon 12 with very high concentrations of nitrogen oxides in air. This study, which used a xenon lamp, shows the formation of HF indicating breakage of the C-F bond (56). Similar sensitized photodegradation could possibly occur with the FLUORINERTS but would likely be at an extremely slow rate.

c) Effects

As a class, FLUORINERT liquids show little toxicity. A summary of the environmental effects data on this class of compounds is shown in Table 4. No significant toxicity has been found. All of the thirteen FLUORINERT liquid products which have been subjected to acute fish bioassays have had 96-hr. LC₅₀ values greater than 1,000 mg/l and are classified as insignificant hazard*.

*Appendix 1 gives a scale rating aquatic toxicity data from highly toxic to insignificant hazard.

In addition, one FLUORINERT liquid (FC-77) was found to be nontoxic to Daphnia (LC₅₀ >1500 mg/l), and four were found not to adversely affect activated sludge microorganisms.

TABLE 4

SUMMARY OF ENVIRONMENTAL EFFECTS OF
FLUORINERT® LIQUIDS

Product	Typical Boiling Range (°C)	Major Components	96-Hr. LC ₅₀ (a,b) (mg/l)	Other Data and Lab Request or Reference
FC-40	138-189	(C ₄ F ₉) ₃ N	>1,000 >5,000	5120 2455
L-4380 (c)	139-185	$\begin{array}{c} \text{F}_2\text{C}-\text{CF}_2 \\ \\ (\text{C}_8\text{F}_{17})\text{FC}-\text{CF}_2 \\ \\ \text{C}_{11}\text{F}_{24} \\ \\ \text{O} \end{array}$	1,686 1,893	4894
FC-43	165-185	(C ₄ F ₉) ₃ N	>5,000	Did not support fungal growth(d). 2455
FC-48	139-180	$\begin{array}{c} \text{C}_{12}\text{F}_{24} \\ (\text{cyclic, 8 isomers}) \end{array}$	>1,500 >5,000	Retarded activated sludge O ₂ depletion rate(e). (57), 2465
FC-70	207-225	(C ₅ F ₁₁) ₃ N	>1,000	7981
FC-70 , L-4308(g)	203-211	$\begin{array}{c} \text{C}_{13}\text{F}_{28}; \\ \text{F}_2\text{C}-\text{CF}_2 \\ \\ (\text{C}_{10}\text{F}_{21})\text{FC}-\text{CF}_2 \\ \\ \text{O} \end{array}$	>1,000(h)	No adverse effect on lab scale treatment system(f) (57). No effect on activated sludge O ₂ depletion rate. EAI 79215, 79213, 6589
FC-71, L-4308	244-262	(C ₆ F ₁₃) ₃ N	>1,000	6589
FC-72	50-60	C ₆ F ₁₄	>1,000	7842
FC-75	99-107	$\begin{array}{c} \text{C}_8\text{F}_{18}; \\ \text{F}_2\text{C}-\text{CF}_2 \\ \\ (\text{C}_4\text{F}_9)\text{FC}-\text{CF}_2 \\ \\ \text{O} \end{array}$	>5,000	Did not support fungal growth(d). 2455
FC-77	90-107	$\begin{array}{c} \text{C}_8\text{F}_{18}; \\ \text{F}_2\text{C}-\text{CF}_2 \\ \\ (\text{C}_4\text{F}_9)\text{FC}-\text{CF}_2 \\ \\ \text{O} \end{array}$	>5,000 >1,000	>1,500 mg/l, 48-Hr. LC ₅₀ Daphnia. 2455

LR 7843

(Table 4 continued)

Product	Typical Boiling Range(°C)	Major Components	96-Hr. LC ₅₀ (a,b) mg/l	Other Data and Lab Request or Reference
FC-78	50-60	$ \begin{array}{c} \text{O} \\ \diagup \quad \diagdown \\ \text{F}_2\text{C} \quad \text{CF}_2 \\ \quad \\ \text{F}_2\text{C} \quad \text{CF}_2 \\ \\ \text{N} \\ \\ \text{CF}_3 \end{array} $	>5,000	Retarded activated sludge O ₂ depletion rate(e). No adverse effect on lab scale treatment system(f). 2455, 5713(57)
FC-82	90-107	Cyclic C ₈ F ₁₆	>1000h	4913
FC-84	75-90	C ₇ F ₁₆	>1,000	No effect on activated sludge O ₂ depletion rate. 6262

Footnotes:

- (a) All 96-hr. LC₅₀ tests were on Fathead minnows (Pimephales promelas) unless indicated.
- (b) All 96-hr. LC₅₀ values are for nonmiscible mixtures.
- (c) L-4380 is a possible FC-40 component. It is a mixture of various isomers of perfluoro-octyl tetrahydrofuran.
- (d) ASTM G-21-70 growth rating was 1 indicating sparse and scattered growth. The analyst felt this growth was due to a mass of spores in the inoculum and not to growth on product.
- (e) Activated sludge mixed liquor with a dissolved oxygen concentration of 7 mg/l had a slightly longer oxygen depletion time than the control.
This was probably not due to toxicity but to the fact that perfluorinated organic liquids dissolve large quantities of oxygen which they can transfer to the aqueous phase. Thus, since more O₂ was present, a longer time was needed for its utilization.
- (f) FC-48 and FC-78, even at unreasonably high concentrations (13 g/l nonmiscible mixtures), had no adverse effect on lab scale semicontinuous activated sludge systems operated for 11 days.
- (g) L-4308 is a possible FC-70 component.
- (h) Bluegill sunfish (Lepomis macrochirus).

The low toxicity of FLUORINERT® liquids, indicates that this group of chemicals presents an insignificant risk of causing adverse environmental effects to aquatic organisms. The low aquatic exposure resulting from their low water solubility and high volatility further reduces the risk.

2. Recommended Testing

No laboratory studies on FLUORINERT® Liquids are recommended at this time. However, an ongoing literature study has been established. This study is enabling the Environmental Laboratory to continually increase its understanding of the fate and effects of these chemicals.

B. Low MW Acids and Their Salts

1. Background

a) Physical Properties

Commercial Chemicals Division products in this class consist of two fluorochemical acids (FC-23 and FC-24) and some of their salts. In the unneutralized form, the fluorochemical acids are very strongly acidic and corrosive, making them hazardous materials. However, except in the case of large spills or discharges, they would be neutralized in the environment. *0002*

Calculated Henry's Law constants for these products suggest that they will ultimately migrate to and disperse in the aquatic environment(58). Unlike the inert fluorochemical liquids, the atmosphere will not be a significant sink. The high water solubility of these products also makes them unlikely to bioconcentrate in living systems or to bond strongly to soil or sediments. *changed water*

b) Degradation

FC-24 showed no biochemical oxygen demand (BOD) in a 20-day test and no dichromate chemical oxygen demand (COD) (LR 5695). Similar results would be expected for FC-23. The lack of a chemical oxygen demand suggests extreme resistance to chemical degradation in the environment.

c) Effects

Environmental screening data on the neutralized products shows them to have very little toxicity (insignificant hazard) (see Table 5 and Appendix I). Neutralized FC-24 caused no acute lethality or other toxic effects to fish in 96 hrs. at 2000 mg/l. At this same concentration, FC-23 caused minimum lethality: only two of 60 fish died.

Table 5 also shows that the neutralized acids have no significant acute toxicity to activated sludge microorganisms at concentrations much higher than would normally occur in a waste treatment system.

The low toxicity of these chemicals, the fact that they are likely to dilute in the aquatic environment and not concentrate in either living or nonliving systems, and their low production volumes makes the probability of significant adverse effects from this group of chemicals remote. Nevertheless, some concern exists about the apparent extreme resistance of these products to degradation.

result also

2. Recommended Testing

No further environmental testing is recommended on these products at this time.

TABLE 5

TOXICITY OF NaOH NEUTRALIZED FLUORO-CHEMICAL ACIDS AND OTHER SALTS OF THESE ACIDS

<u>Product</u>	<u>Formula</u>	<u>96-Hr. LC50 (mg/l) (a)</u>	<u>Microbial Inhibition Concentration(b) (mg/l)</u>	<u>Lab Request No.</u>
FC-23	C ₃ F ₇ COOH	-	-	-
Neutralized	C ₃ F ₇ COONa	>2000	>1000	7364
FC-24	CF ₃ SO ₃ H	-	-	-
Neutralized	CF ₃ SO ₃ Na	>2000	>1000	5696
FC-124	CF ₃ SO ₃ Li	>1000(c)	-	4388
FC-520	[CF ₃ SO ₃ ⁻] [H ₂ N(C ₂ H ₅) ₂] ⁺	>1000	-	4740

(a) Bioassays used Fathead minnows (Pimephales promelas) unless indicated.

(b) Concentration causing an immediate reduction of activated sludge oxygen uptake rate.

(c) Bluegill sunfish (Lepomis macrochirus).

C. Surfactants

1. Background

a) Physical Properties

Water Solubility - FC-143 ($C_7F_{15}COONH_4$) and FC-95 ($C_8F_{17}SO_3K$) were studied as representative FC surfactants in the Fate of Fluorochemicals Program Part I (2,3). From an environmental perspective, both products have high water solubility. Since this study, FC-95 solubility has been more accurately measured, and determined to be about 1,080 mg/l (59). This solubility measurement was subsequently confirmed by the analysis of a water saturated sample of FC-95 sent to Dohrmann during the Environmental Laboratory's evaluation of their TOC equipment (60).

FC-143 is very soluble. Its actual solubility limit was not determined. Solubility work on this compound was terminated after a sample was found to totally dissolve in a volume of water of equal weight (61). Solubility data on other 3M fluorochemical surfactants are given in Table 6.

These high water solubilities suggest that FC-95, FC-143, and other 3M fluorochemical surfactants will dilute in aquatic environments with little partitioning from the water phase into sediment, lipid tissues, or suspended organic matter. These data also indicate that these fluorochemicals are likely to remain in the aqueous phase during wastewater treatment and not to concentrate into wastewater sludge.

✓ 110

TABLE 6
SOLUBILITY AND OCTANOL/WATER PARTITION COEFFICIENTS
OF FLUORO-CHEMICAL SURFACTANT PRODUCTS

	Water Solubility at Room Temp.	Reference
FC-90	>250 g/l	(62,63)
FC-93	(a)	
FC-95	1 g/l	(59,60)
FC-98	10 g/l	(64)
FC-99	>500 g/l	(65)
FC-100 (hydroxy foamer)	(a)	
FC-120	(a)	
FC-128	200 g/l (gel)	(66)
cc 773-588	50 g/l (gel)	(66)
FC-143	>500 g/l	(61)
FC-170	300 g/l (gel)	(66)
FC-170C	1 g/l	(67)
FC-171	1 g/l (b)	(68)

Footnotes:

(a) Solubility is unknown but probably high (>1%) because it is sold at 25% solids in a water-organic solvent solution.

(b) Cloudy solution.

Octanol/Water Partition Coefficient - An octanol/water partition coefficient (K_{ow}), or more accurately, an octanol/water distribution coefficient, is available for only one fluorochemical surfactant, FC-90 ($K_{ow}=0.65$). Since FC-90 is an ionic material and thus does not exist as the same solute species in the two immiscible solvents*, this is not a true partition coefficient. Quantitative SAR methods have not been fully developed for ionic species (24).

The applicability of this distribution ratio value for FC-90 to existing regression equations correlating physical-chemical and chemodynamic properties is questionable. Nevertheless, the regression equation of Banerjee et al (21), which correlates K_{ow} with water solubility (S), appears to make a reasonable prediction. Using the midpoint of the melting range as the melting point (69), this equation predicts the solubility of FC-90 to be 250 g/l.

*FC-90 will exist in the dissociated state in the aqueous phase and primarily in the associated state in n-octanol.

Soil Adsorption Coefficients - Soil organic matter adsorption coefficients, K_{oc} , of 17 for FC-143 and 45 for FC-95 (70) indicate very high mobility in soil. This is congruent with their high water solubility. A regression analysis based on data for FC-95, FC-143, FM-3422, and FM-3925 showed the following relationship between solubility (S) and soil organic matter adsorption coefficient (K_{oc}):

$$\log K_{oc} = 3.58 - 0.513 (\log S).$$

*on Sw as
solubility*

This regression equation is nearly identical to the correlation reported by Kenaga and Goring (10) for 106 organic compounds:

$$\log K_{oc} = 3.64 - 0.55 (\log S).$$

This preliminary correlation again supports the prospect that some currently described structure relationships may be applicable to fluorochemical surfactants and alcohols.

Developing soil thin-layer chromatography (TLC) plates with water is another method of measuring the affinity of chemicals for soil. Procedures have been proposed by the USEPA to measure mobility in soil by this method (71), and preliminary measurements by a very similar method have been made on FC-95 and FC-143 (72). Unfortunately, the amount of FC-95 spotted was too small to allow visualization. FC-143, however, showed low mobility. This finding seems to contradict both the soil adsorption coefficient measurements given above and the predictions of low soil sorption based on the high water solubility of 3M fluorochemical surfactants. These adsorption (K_{oc}) and TLC measurements were conducted in two different soil types, but while edaphic factors* can cause

*The following are edaphic factors which can affect chemical mobility in soil (73):

- 1) Complexation with organics
 - a) Cation exchange with organics
 - b) Organic anion fixation
 - c) Nonpolar organic reactions
- 2) Adsorption by mineral species (e.g., clay)
- 3) Chemical oxidation-reduction effects
- 4) Precipitation reactions and pH effects
- 5) Ion exchange reactions
 - a) With layered silicates
 - b) With hydroxy oxides of Fe and Mn
 - c) With organic matter
 - d) With lime materials (agricultural or natural)

AMS

differences in chemical mobility, differences of this magnitude are unlikely with these fluorochemical surfactants. Clarification of these data is needed.

Biosorption - A biosorption study has been conducted on FC-90, the diethanolamine salt of perfluoroethylcyclohexyl sulfonic acid (74). The fluorochemical portion of this material was found not to bind strongly to activated sludge. The results of this study indicate that the fluorochemical portion of FC-90 is likely to remain in the aqueous phase during passage through a wastewater treatment system. The behavior of this water soluble fluorochemical is thus similar to that predicted for FC-95 and FC-143, and because of its similarity to FC-95 (the perfluorinated portion is also a saturated, C₈ sulfonic acid), the finding adds credence to this prediction.

Studies with rats done by Riker have shown that perfluorooctane sulfonate is very difficult to recover quantitatively from tissues and feces even when extracted by a series of nonpolar to polar organic solvents. Perfluorooctane sulfonate in the blood was also found to be essentially completely bound to soluble proteins (75). These two findings suggest that perfluorooctane sulfonate may bind strongly to nonsoluble proteinaceous materials, both in animal tissues and in soils or sediments of the aquatic or terrestrial environment. These findings and the predictions based on them are contrary to the prediction of the Environmental Laboratory based on water solubility measurements.

*if environmental
not a true VP
necessary*

Vapor Pressure - No actual vapor pressure measurements were made on FC-95, FC-143, or any other 3M fluorochemicals in the Fate of Fluorochemical Study Part I. The parameter can be very useful, however, in predicting the rate of movement and distribution of a chemical between the atmosphere and terrestrial and aquatic environments (45), e.g., vapor pressure approximates the rate of volatilization from aqueous solution or from the adsorbed state on soil (76).

FC-143 can be sublimed completely and recovered unchanged (by IR) at 178°C and atmospheric pressure (77). Most FC-143 probably enters the environment through volatilization from its use in PTFE manufacture. On the other hand, our experience in handling FC-95 and trying to analyze it by TOC and GLC indicates that its

vapor pressure is probably quite low. These data indicate the need for quantitative measurement of vapor pressure and volatilization from aqueous systems that will enable predictions of environmental distribution.

b) Degradation

One 3M fluorochemical surfactant, FC-143, is a perfluorocarboxylic salt. Several of these surfactants, like FC-95, are perfluorosulfonic acid salts, and the remainder, such as FC-128 and the hydroxy foamer, are organic-amide derivatives of fluorochemical sulfonic acids. Degradability assessments on this latter group must separately consider the perfluorinated and nonfluorinated portions.

Biodegradation - Neither FC-95 nor FC-143 degraded in 2 1/2-month shake flask biodegradation studies using inocula from three separate treatment systems (78). Two of these inocula were from systems treating 3M fluorochemical wastes, and thus more likely than nonacclimated inocula to have microorganisms capable of growing on these fluorochemicals. This was the most rigorous laboratory biodegradation test ever done on these fluorochemical surfactants. Other biodegradation tests, including a (3-hr. Warburg study on FC-95 (79) and BOD₂₀ tests on both FC-95 and FC-143 (LR #3844), also showed no degradation. No testing has been done under anaerobic conditions.

These data are adequate to demonstrate that biodegradation of FC-95 and FC-143 cannot be depended on to occur in an aquatic environment. This resistance to degradation is consistent with their perfluorinated structure. However, to more substantially rule out the possibility of biotransformation and the concomitant formation of daughter products of unknown toxicity, tests more rigorously favoring biodegradation should be performed.

Table 7 shows biodegradation data on other fluorochemical surfactant products. The products in this table do not contain biodegradable solvents which tend to mask the biodegradability of the fluorochemical surfactants in nonspecific tests, such as BOD.

These data show that fluorochemical surfactants with no nonfluorinated organic portions, e.g., FC-98, FC-95, and FC-143, have essentially no biochemical oxygen demand. Those with ionically bonded organics, i.e., FC-98 and FC-99, have BOD's close to that which would be - - - - - ✓
- - - - - ✓

TABLE 7

BIODEGRADATION DATA ON NONSOLVENT-CONTAINING
FLUORO-CHEMICAL SURFACTANTS

<u>Product(a)</u>	<u>Test Results</u>	<u>Reference or Lab Request</u>
FC-90	BOD ₂₀ 0.28 g/g(b)	6260
FC-98	BOD ₂₀ <3800 mg/kg BOD ₂₀ Nil	3844 1231
FC-99	BOD ₂₀ 82,000 mg/kg(c)	4895
FC-128	7-Hr. Warburg BOD=70% of ThOD _{NH₃} (d) of the organic portion.	(79)
FC-134	BOD ₂₀ Nil	1870
FC-170C	BOD ₂₀ = 0.107 g/g(e)	4197
FC-171	BOD ₂₀ = 0.17 g/g(f)	4951
FM-3555 (MCL Emulsifier)	BOD ₂₀ 9600 mg/l	5062
F-6422 (Hydroxy Foamer)	BOD ₂₀ <9300 mg/kg	8139

- (a) Structures for these products are in Table 9.
- (b) The BOD₂₀ of FC-90 is approximately 90% of the theoretical oxygen demand of the diethanolamine portion of this chemical.
- (c) FC99 is a 25% aqueous solution of a diethanolamine salt. The fluorochemical portion of this salt is the same as that of FC-95.
- (d) ThOD_{NH₃} is the theoretical oxygen demand assuming no oxidation of the nitrogen. This ThOD also assumes no degradation of the perfluorinated portion of the molecule.
- (e) BOD₂₀ = 10% of COD
- (f) BOD₂₀ = 25% of COD

expected from their organic portion (diethanolamine) alone. Fluorochemical surfactants with covalently bonded organic portions gave mixed results. Those with quaternary ammonium organic portions, i.e., MCL, hydroxy foamer, and FC-134, had no BOD. This is not unexpected since even nonfluorinated quaternary ammonium surfactants are frequently difficult to biodegrade. Those surfactants with polyethylene glycol components, i.e., FC-170C and FC-171, had BOD₂₀ values equal to 10-20% of their COD's. This indicates some partial degradation of the nonfluorinated organic portions of FC-170C and FC-171 since the observed BOD is greater than would be expected from organic by-products. One of these, FC-170C, did not biodegrade at all in the first 7 days. Slight biodegradation was seen at 10 days with the rate increasing at the 14-day observation and continuing at 20 days with no indication of plateauing. *- biocidal*

These data suggest that longer biodegradation test periods, using acclimated organisms, might lead to more complete degradation of the nonfluorinated portion of polyethylene glycol adduct fluorochemical surfactants.

not in FC-128 has the highest BOD₂₀/COD (77%) of those surfactants with covalently bound organics, but it was tested by a somewhat more rigorous biodegradation test method (79). Attempts to confirm this biodegradability have been made with FC-129 (LR 6300), a product containing the FC-128 surfactant, but samples from this study are still awaiting analysis in the Commercial Chemicals Division Laboratory.

Photodegradation - Both FC-95 and FC-143 have been tested for photodegradation in aqueous solutions using an artificial light source (wavelength >300 nm) (80,81). No photodegradation was observed. These photodegradation studies did not contain sensitizing agents. No photodegradation studies have been done on surfactants with covalently bonded nonfluorinated portions or when adsorbed onto solid surfaces such as sand or silica gel.

c) Bioconcentration

No bioconcentration studies have been done on fluorochemical surfactants in the Environmental Laboratory. Studies in Riker have shown that male rats excrete prefluorooctane sulfonate and perfluorooctanoate very slowly (75). Perfluorooctane sulfonate is strongly protein-bound which prevents excretion through the kidney. ✓
Perfluorooctanoate is less strongly protein bound (approx. 97.5%), but the small fraction of free material that filters through the glomerulus seems to be actively reabsorbed by male rat kidneys. Researchers at DuPont have made similar findings on hamsters (75). Female rats can excrete perfluorooctanoate, but both male and female people appear to behave more like male rats and only very slowly clear their bodies of this material.

d) Effects

Table 8 summarizes the current set of bioassay data on FC-95 and FC-143. FC-95 was about a factor of ten more toxic to fish and daphnia than FC-143. On the other hand, FC-143 retarded algae growth by approximately twice as much as FC-95. Based on the NIOSH aquatic toxicity scale (see Appendix I), FC-95 would be considered to have slight to moderate toxicity to fish, while FC-143 would be classified as practically nontoxic to fish and slightly toxic to algae.

Screening tests Environmental screening tests have also been run on other surfactant products (Table 9). In some of these products, e.g., FC-93 and FC-100, the fluorochemical surfactants are sold in solvent systems containing water and isopropanol or butyl Carbitol®. Bioassays were run on these products as sold. Since these solvents have very little toxicity to fish, it is assumed that all the toxicity observed was due to the fluorochemical and not the solvents. Synergistic or antagonistic effects, however, are possible. Based on our limited experience, antagonism, which would make the surfactants appear somewhat less toxic, is more likely.

TABLE 8
AQUATIC BIOASSAY DATA ON FC-143 AND FC-95

<u>Species</u>	<u>Parameter</u>	<u>Concentration mg/l</u>		<u>Lab Request or Reference</u>
		<u>FC-95</u>	<u>FC-143</u>	
Fathead	96-Hr. LC ₅₀	32,29,38	766	1429,2340,5625,(c)
Bluegill	96-Hr. LC ₅₀	68	569	(d),3844
Trout	96-Hr. LC ₅₀	11	—	(e)
Daphnia	48-Hr. LC ₅₀	50	632	
Fathead	30-Day Egg-Fry	1.9(a)	100(b)	(82,83)
Green algae	Cell weight 14-Day EC ₅₀	146	73	(84,85)
Green algae	Cell count 14-Day EC ₅₀	95	43	(84,85)

- (a) Color and behavioral changes observed at 1.0 mg/l while egg-fry survivability was decreased at 1.9 mg/l.
- (b) No effect noted during this study at doses up to and including 100 mg/l.
- (c) Environmental Laboratory Aquatic Toxicity Worksheet on FC-95 Lot 583, Fathead minnow, started 8/22/77.
- (d) M. T. Elnabarawy, Environmental Laboratory Aquatic Toxicity Data Sheet on FC-95 Lot 583, Bluegill sunfish, started 5/23/78.
- (e) M. T. Elnabarawy, Environmental Laboratory Aquatic Toxicity Data Sheet on FC-95, Lot 583, Rainbow trout, started 2/21/78.

TABLE 9

FISH 96-HR. LC₅₀ DATA FOR FLUORO-CHEMICAL SURFACTANTS

Product	Chemical Structure	Fathead minnow 96-Hr. LC ₅₀ (mg/l)	Lab Request Number
FC-90	$C_2F_5 \text{ (benzene ring) } SO_3^- H_2N^+ (C_2H_4CH)_2$	43	6260
FC-93	$C_8F_{17}SO_3^- NH_4^+$	20-25(a)	2318, 2456
FC-98	$C_2F_5 \text{ (benzene ring) } SO_3^- K^+$	155, 200	3844, 2563
FC-99	$C_8F_{17}SO_3^- H_2N^+ (CH_2CH_2CH)_2$	8(b)	(86)
FC-100 (Hydroxy Foamex)	$C_6F_{13}SO_2N^+C_3H_6N^+(CH_3)_2C_2H_4CH_2CH(OH)CH_2SO_3^-$	20-25(a)	5720, 4950
FC-120	$C_{10}F_{21}SO_3^- NH_4^+$	4(a)	2318, 2456
FC-127	$C_8F_{17}SO_2N(C_2H_5)CH_2COO^- K^+$	430(c)	7009
FC-128	$C_8F_{17}SO_2N(C_2H_5)CH_2COO^- K^+$	34, 30(c)	2254, 2340
FC-129	$C_8F_{17}SO_2N(C_2H_5)CH_2COO^- K^+$	260(c)	6300
FC-134	$C_8F_{17}SO_2NHC_3H_6N^+(CH_3)_3I^-$	20, 31	2340, 1955
FC-170C	$C_8F_{17}SO_2N(C_2H_5)(CH_2CH_2O)_{14}H$	285(b)	4197
FC-171	>90% $C_8F_{17}SO_2N(C_2H_5)(CH_2CH_2O)_7.2CH_3$ <10% $C_8F_{17}SO_2NH(CH_2CH_3)$	208	4951
FM-3555	$C_8F_{17}SO_2NHC_3H_6N^+(CH_3)_3Cl^-$	30	5408

(a) Product had much more impurity

Footnotes:

- LC₅₀ values reported are those calculated for the surfactant solids. This calculation assumes neither synergism nor antagonism from solvent systems.
- Blugill sunfish.
- This fluorochemical was tested both as a 100% solids material (FC-128) and as water-isopropanol and water-butyl Cellosolve-ethanol solutions (FC-127, FC-129). The solvent appears to have an antagonistic effect on toxicity, but it's also possible that differences in by-product concentration could have caused the observed toxicity differences.

(1)

Other environmental effects data on fluorochemical surfactants are shown in Table 10. These tests showed that the surfactants have little or no immediate toxicity to activated sludge at concentrations much greater than those normally expected to reach a wastewater treatment system.

While most sludge toxicity tests were run for 5-10 minutes, the test with ~~EAI 80021~~ showed no inhibition even when exposure of the sludge to the fluorochemical was continued for four hrs. The data does not show whether fluorochemical surfactants have a delayed or chronic effect on sludge, i.e., by inhibiting growth or causing population shifts, but due to their low acute toxicity, this seems unlikely.

One unusual result was that cc ~~7711-18~~ is more than two orders of magnitude more toxic to Daphnia than to fish. Large differences between Daphnia and fish toxicity were not seen with cc ~~8011-23~~, ~~EAI 80021~~, nor ~~LB 5625~~.

FC-170C cc ~~7711-18~~ is the only fluorochemical surfactant which has undergone testing to determine its chronic effects on Daphnia (87) and its acute effects on vascular plants. While the product showed chronic toxic effects at very low concentration exposures, 0.1 mg/l, to daphnids, it was found not to be very toxic to vascular plants. It had no effect on germination, root growth, or hypocotyl growth of soybeans, ryegrass, or corn at concentrations ranging from 1000-1800 mg/l.

TABLE 10
OTHER ENVIRONMENTAL EFFECTS DATA(a)
ON FLUORO-CHEMICAL SURFACTANTS

<u>Product</u>	<u>Immediate Inhibition of Activated Sludge</u>	<u>48-Hr. LC50 Daphnia magna</u>	<u>Other Effects</u>	<u>Lab Request No. or Reference</u>
FC-90	None at 250 mg/l	18 mg/l		6260S 6457S
FC-95	None at 4000 mg/l(b)			(79)
FC-98	None at 100 mg/l			5428
FC-99	None at 250 mg/l			4895
FC-100 (c)	None at 150 mg/l			4950S
FC-127	None at 500 mg/l			7009
FC-128			No inhibition of microbial activity at low mg/l(d)	2174
FC-129	None at 500 mg/l			6003
FC-134			No inhibition of microbial activity at low mg/l(d)	2174
FC-170C		1.5 mg/l 1.0 mg/l	No effect on soy- bean, rye, and corn growth and germination at 1800 mg/l(e)	4197 (87)
FC-171	None at 1000 mg/l		0.15 mg/l caused reduced survivability, number of broods, and brood size in 28-day daphnid life cycle study. Later generations were less sensitive.	5951
FM-3555(e)	30% inhibition at 1000 mg/l None at 100 mg/l			5062

Footnotes:

- (a) All values based on surfactant solids.
- (b) Exposure to FC-95 continued for 4 hrs. as opposed to 5 to 10 min. sludge exposures in other tests.
- (c) Hydroxy foamer.
- (d) Measured by TTC (2,3,5-Triphenyltetrazolium chloride) test for dehydrogenase activity re: "Dehydrogenase Enzyme as a Parameter of Activated Sludge Activities," Ford, et al. Proceedings of the 21st Industrial Waste Conference, Purdue, May 3, 4, and 5, 1966.
- (e) The no effect level for soybean root length was 1000 mg/l.

2. Recommended Testing

a) Physical Chemical

Solubility - Water solubility data on 3M fluorochemical surfactants is adequate for use in estimating the environmental mobility of these compounds. Further water solubility measurements on 3M fluorochemical surfactants are not specifically recommended, but some may be included as part of efforts to develop structure activity relationships for fluorochemicals.

Partition Coefficients - Octanol/water partition coefficient measurements on fluorochemical surfactants FC-95 and FC-143 are recommended. True "partition coefficients" can't be made on these ionic materials, but octanol/water distribution coefficients can be measured. The usefulness of such distribution coefficients in predicting chemodynamic properties from octanol/water partition coefficients is now uncertain, but these measurements will be helpful in determining their utility in this area. FC-95 and FC-143 are appropriate choices for this testing since they represent the range of fluorochemical surfactant solubility: FC-95 is one of the least soluble FC surfactants, and likely to have one of the highest octanol/water distribution coefficients among this class of fluorochemicals, while FC-143 has one of the highest solubilities.

Distribution coefficients will be measured, if possible, by standard procedures such as those approved by the OECD (88) and the USEPA (89). The separated phases will be analyzed for total organic fluorine, for the specific fluorochemical by capillary GLC following methylation, or by using radiolabeled materials. Standard samples prepared in water-saturated octanol and octanol-saturated water will be used as controls.

These distribution coefficient measurements are given the following priority:

- FC-95 - Priority I
- FC-143 - Priority I

Soil TLC - Since preliminary soil TLC tests on FC-95 and FC-143 gave ambiguous results, we recommend repeating these tests. The standard USEPA soil TLC procedure will be followed (71). The procedure requires a ^{14}C -labeled substrate and produces a standard TLC R_f value that characterizes the mobility of the fluorochemical in soil systems.

Soil TLC testing of fluorochemical surfactants is given the following priority.

FC-95 - Priority II
FC-143 - Priority II

Bioadsorption - As FC-143 and FC-95 have been found to bind to protein in rats, it seems probably that they would also bind to the microbial proteins in activated sludge. It is recommended that Bioadsorption Studies be run using the Environmental Laboratory protocol (74) and radiolabeled materials. Such studies would be useful in determining whether these compounds would be most likely to pass through a wastewater treatment system in the aqueous phase or bind strongly and be disposed of with activated sludge.

Biosorption testing of fluorochemical surfactants.

FC-143 - Priority III
FC-95 - Priority III

Vapor Pressure - Vapor pressure measurements are necessary to estimate the volatilization of fluorochemicals and to make quantitative predictions of environmental distribution. Measurements will be made following standard USEPA (90) or OECD procedures (91) and will most probably be performed by Analytical and Properties Research at CRL.

EAI 80021 - Priority III
FC-143 - Priority III

Greater priority is given to work on FC-143 since this material will typically enter the atmosphere through its use in PTFE manufacture. It is also a higher volume product.

b) Degradation

Biodegradation - FC-171 and FC-170C have both given indications of partial biodegradation in a 20-day BOD test, suggesting possible degradation of the Carbowax portion of these molecules. Studies on FC-171 under more rigorous conditions are recommended to substantiate these partial degradation findings and to identify degradation products.

The recommended test approach involves using preacclimated microorganisms as inocula for a 28-day BOD (92). If biodegradation tests are positive, an attempt will be made to identify major degradation products. This testing is important to substantiate the previous inconclusive findings of partial microbial degradation of 3M fluorochemicals with covalently bonded nonfluorinated moieties and to determine if perfluorooctane sulfonic acid (the FC-95 fluorochemical) is the major degradation product. Analytical methods could involve techniques such as methylation and capillary GC or TLC of radio-labeled FC-171 degradation products. The ¹⁴C label should be on the perfluorinated portion of the FC-171 molecule.

28-Day BOD:

FC-171 - Priority I

Degradation Product Identification -
Priority II

No degradation has been observed in BOD tests on the hydroxy foamer, F-6422, or on any other quaternary ammonium fluorochemical surfactant. Since the hydroxy foamer is an important component of "LIGHT WATER" products and is also finding a significant use in copper mining, rigorous biodegradation tests such as the SCAS* test or soil respirometric tests are recommended. This testing would be greatly facilitated by the use of radiolabeled hydroxy foamer with the radiocarbon tag placed on the hydrocarbon portion of the molecule.

If results indicate significant degradation, an attempt will be made to identify degradation products.

Soil Respirometry or SCAS:

Hydroxy foamer - Priority II

Degradation product identification -
Priority III

*Semicontinuous activated sludge

While the structure of FC-95 and FC-143 suggests they will have extreme resistance to biodegradation, testing to date is only sufficiently rigorous to show that their degradation cannot be depended upon to occur in an aquatic environment. More rigorous aerobic biodegradation tests are recommended to further substantiate the expected complete resistance of FC-95 and FC-143 to biodegradation. Conditions rigorously favoring biodegradation will be used such as mixing the products with garden soil and compost further inoculated with sludge that has been acclimated to these chemicals. Such studies could be extended up to 1 year depending on results, and would be periodically primed with fresh decaying materials. Analytical methods will involve testing for fluoride release using the fluoride electrode, measurement of $^{14}\text{CO}_2$, absorbed in base, or searching for other degradation products of radiolabeled fluorochemicals by TLC autoradiography.

Rigorous (soil) aerobic biodegradation:
FC-95 - Priority II
FC-143 - Priority II

Rigorous anaerobic biodegradation tests involving long-term (i.e., weeks-months) burial of FC-143 as a representative perfluorinated surfactant in water-saturated soil are also recommended. Analytical methods will be the same as for the rigorous aerobic tests.

Rigorous anaerobic biodegradation:
FC-143 - Priority III

not primary

Photodegradation - Since no photochemical degradation of a 3M fluorochemical surfactant has yet been demonstrated in aqueous solution (71,72), exploratory photodegradation studies are suggested to test possible activation by surfaces such as silica sand or "sensitizing agents" like the organic components of natural water.

Candidate fluorochemical surfactants, preferably radiotagged, will be both coated onto sand or silica gel and also dissolved in water containing sensitizing agents. Both the coated silica and aqueous samples will then be irradiated in Vycor tubes by sunlight for 3, 6, and 12-month periods. After irradiation, the samples will be extracted, analyzed for initial fluorocarbon and/or daughter products by TLC autoradiograph, or GLC following methylation, and for fluoride release using the fluoride electrode.

FC-143 and FC-95 Photodegradation:

On silica - Priority III

Sensitized - Priority III

Hydroxy foamer* photodegradation:

Sensitized - Priority III

c) Bioconcentration

Because an active mode of concentrating perfluorooctanoic acid exists in rats (75), it seems possible that fish or other organisms could actively concentrate this or other fluorochemical surfactants from the environment. Laboratory studies should be done to prove or disprove this possibility. Whole body fish bioconcentration studies using EPA-approved techniques (93) and radiolabeled materials are recommended.

Fish bioconcentration studies on fluorochemical surfactants.

Perfluorooctanoate (FC-143) - Priority I

Perfluorooctane sulfonic acid (FC-95) -
Priority I

d) Effects

Aquatic bioassays are proposed to complete the aquatic toxicity profiles of several selected fluorochemical surfactants. These bioassays will employ standard Environmental Laboratory procedures (87,94,95).

Environmental screening tests have been done on the hydroxy foamer in two mixtures, FM-3974 and FC-100 (LR Nos. 4950 and 5720). Assuming that all of the toxicity of these mixtures is due to the FC solids, the hydroxy foamer has a 96-hr. LC₅₀ for Fathead minnow of 20-25 mg/l. Tests on the surfactant alone to confirm this toxicity level are desirable.

Fish - 96-hr. LC₅₀ on Solvent-free Hydroxy
Foamer - Priority III

* Photodegradation tests on hydroxy foamer are recommended only if it does not biodegrade under rigorous conditions.

Fish bioassays on FC-127, FC-128, and FC-129, which all contain the same fluorochemical surfactant, suggest that solvents found in FC-127 and FC-129 may have a significant antagonistic effect on the toxicity of this fluorochemical. Acute fish bioassays on an FC-128 sample both in the presence and absence of isopropanol would clarify if the great differences in toxicity observed (Table 9) were due to antagonistic effects or differences in toxicity of different lots of this surfactant.

Testing is currently underway (LR #8442) on L-6778, F-6873, a product similar to FC-127, that may partially answer this question. As an addendum to the routine screening, the Environmental Laboratory is also looking at the toxicity of this product after evaporating off the solvent. The need for further testing will depend on the results of this testing.

Fish 96-hr. LC₅₀ on FC-128 with and without solvent - Priority III

Since most fluorochemical surfactants find their way into aquatic environments, 28-day Daphnia bioassays similar to that done on FC-170C (87), and 14-day multigeneration algal bioassays similar to those done on FC-143 and FC-95 are recommended for all of the major fluorochemical surfactants.

Toxicity tests on those organisms, which represent 2 major components of the aquatic community, plants and invertebrates, will give a broader perspective of the toxic potential of fluorochemical surfactants to the aquatic environment. This broader perspective is needed because the minimal daphnid and algal test data presently available has shown that toxicity to these organisms cannot be predicted reliably from fish bioassay data. For example, FC-170C is practically nontoxic to fish but moderately to highly toxic to daphnids, and FC-95 when compared with FC-143 is more toxic to fish but less toxic to algae.

These tests should be done on the neat fluorochemicals to avoid synergistic effects from solvents in which they are sold. Chronic Daphnia studies will be done only on products with LC₅₀ values less than 100 mg/l or which show a delayed onset of toxicity in preliminary acute bioassays on this organism.

14-Day Algae Bioassays on the neat
fluorochemicals contained in:

FC-128	Priority II
FC-100	Priority II
GC-773-58 FC-133	Priority II
FC-171	Priority II

28-Day Daphnia Bioassay on the neat fluoro-
chemicals contained in:

FC-143	Priority II
FC-128	Priority II
FC-100	Priority II
GC-773-58 FC-133	Priority II
FC-171	Priority II

D. Phosphates

1. Background

The Environmental Laboratory has generated data on FC-807, which is one of the highest volume products in the FC product line. It is a mixture containing mostly the ammonium salt of the di-phosphate ester of the ethyl FOSE alcohol, FM-3422 but also containing some of the mono- and tri-phosphate ester salts.

a) Physical Properties

The Environmental Lab has generated no physical-chemical data on the fluorochemical component of FC-807.

b) Degradation

Hydrolysis - The results of a hydrolysis study on FC-807 (NB 46269 p. 22, 24) show that incubation at 45°C for 24 hours at pH 3, 6, 9, 10, 12, and 12.3 did not increase the FM-3422 concentration above that initially present as an unreacted chemical precursor of FC-807. This work is significant because it suggests that rapid chemical hydrolysis of FC-807 to FM-3422 is unlikely in the environment.

Biodegradation - Biodegradation testing on FC-807 involved both biochemical oxygen demand (BOD) tests (96, LR #3488) and inconclusive shake flask tests from the Fate of Fluorochemicals Study Part I.

The BOD test results lead to the conclusion that the FC-807 fluorochemical component is not easily biodegraded. The 20-day BOD of FC-807 is only about half of the chemical oxygen demand (LR 3844). Since isopropanol, which makes up 40% of the organics, should have been nearly completely degraded in this test, very little, if any, degradation could have occurred to the remaining 60%, which is the fluorochemical component.

The shake flask biodegradation studies are inconclusive because no analytical technique for FC-807 was available at the time. A nonspecific analytical technique (TOC) also did not work because material precipitated from solution, possibly due to calcium in the culture medium.

c) Effects

The available data demonstrate three environmental effects properties of FC-807: 1) it has minimal acute toxicity to aquatic organisms (96-hr. LC₅₀ Fathead minnow (*Pimephales promelas*) >3600 mg/l) (96, LR 1204, LR 2191, LR 2256); 2) it does not significantly affect waste treatment system operation at <1200 mg/l (96), and 3) it does not retard the biodegradability of treated cardboard (97).

2. Recommended Testing

a) Physical Properties

To enable the evaluation of FC-807 environmental mobility, measurement of water solubility, partition coefficient, soil sorption, soil TLC, and vapor pressure of FC-807 fluorochemical components* are recommended. Of these, solubility and partition are most important since they can most easily be used to predict other chemodynamic properties.

Water Solubility - The Environmental Laboratory will measure fluorochemical solubility in water using current recommended methodology (98). Analysis of the saturated water samples could involve GLC of the methylated samples, allowing determination of the relative solubility of the mono- and di- esters. Alternatively, or for confirmation purposes, radiolabeled FC-807 could be used.

Water Solubility of FC-807 - Priority I

Octanol/Water Partition Coefficient - K_{ow} will be measured by standard procedures (88,89). The analytical procedures will be the same as those described above for measuring FC-807 water solubility.

Distribution Coefficient of FC-807 -
Priority I

*"fluorochemical components" refers to the mono-, di-, and tri-phosphate ester salts of ethyl FOSE alcohol.

*due to volume,
necessary
process
↑
HC - needed*

Soil/Organic Matter Adsorption Coefficient (K_{oc})
Soil sorption measurements are proposed to aid in evaluating the mobility of FC-807 in the soil environment. For example, these data will aid in predicting the rate and extent of leaching from landfills to groundwater. This work will follow standard procedures (98,99,100). The analytical methods will be the same as used for water solubility and K_{ow}, but because of possible interferences caused by soil, the need for radiolabeled material is greater.

K_{oc} of FC-807 - Priority III

Soil TLC - This procedure will confirm K_{oc} measurements. USEPA recommended procedures will again be followed (71). These EPA procedures require radiolabeled materials.

Soil TLC of FC-807 - Priority III

Vapor Pressure - Vapor pressure measurement for FC-807 is proposed to complete its physical property profile. This measurement is necessary to estimate the extent and rate of its movement into the atmosphere (101). Analytical and Properties Research at CRL is probably the most appropriate laboratory for this testing.

Vapor Pressure of FC-807 - Priority III

b) Degradation

Degradation studies on FC-807 will allow estimation of its persistence in the environment and identification of degradation products.

Proposed biodegradation studies, as a first stage, will simply involve looking for an increased concentration of FM-3422, the most likely degradation product, by GLC as was done in the above described FC-807 hydrolysis experiment. In this case, extraction with ethyl ether or dioxane will be necessary to insure complete extraction of FM-3422 which we have found binds strongly to biological sludge and soil.

If studies give an indication of FC-807 biodegradation, further work will be done involving specific analysis for FC-807 components and other possible degradation products such as FC-95. As described above, these specific analytical methods will consist of gas-liquid chromatography of methylated extracts, or, if possible, thin-layer chromatography of radiolabeled FC-807.

All proposed testing will be done under conditions rigorously favoring biodegradation. FC-807 will be incubated for extended periods in a mixture of compost and soil.

Rigorous Soil Biodegradation Tests on FC-807
- Priority III

c) Effects

A 28-day Daphnia bioassay (87) and a 14-day algae test (84) are needed to complete the environmental effects profile on this important fluorochemical. Procedures and decision points will be the same as those recommended for fluorochemical surfactants.

FC-807:

14-day Algae Bioassay - Priority II
28-day Daphnia Bioassay - Priority II

E. Alcohols

1. Background

a) Usage

Only a few relatively small-volume products, FC-10, PPA-790, PPA-791, contain the free fluorochemical alcohols as other than an uncompletely reacted raw material. Thus, the importance of the alcohols (FM-3422 and FM-3925) from an environmental assessment perspective is mainly a concern with wastes from manufacture and the possible release of these alcohols from the degradation of other products such as the fluorochemical acrylates and the phosphates (FC-807) in which the alcohols are chemically bound.

b) Physical Properties

Water Solubility - Water solubility measurements have been made on FM-3422 (102,103) and FM-3925 (104) by the Veith technique (105). This process saturates water by recirculating it through a column of sand or glass beads coated with a low solubility material. Unfortunately, the technique preferentially leaches the more soluble components of impure materials from the column.

This defect of the procedure can be significant with this class of products since both alcohols are actually mixtures of several isomers which likely have different solubilities but were undifferentiated by the analytical method used. This lack of purity makes it impossible to accurately and reproducibly measure solubility and partition coefficient by any standard method, but the Veith technique is particularly deficient in this respect. For example, the two solubility values given for FM-3925 (2.3 mg/l and 0.82 mg/l) resulted from two sequential recirculations through the same coated column. From these data, it appears that the more soluble components came off in the first washings. Thus, the 0.82 mg/l value probably more closely represents the solubility of the major FM-3925 component.

Proof items

The lack of chemical purity may also be the cause of variability in FM-3422 solubility measurements. Early, apparently repeatable results showed an FM-3422 water solubility of 0.05 mg/l (102), but our latest set of measurements consistently showed a value of about 0.16 mg/l (103).

Octanol/Water Partition Coefficient - The partition coefficient for the ethyl FOSE alcohol is also not accurately known, but the ratio of the product's water solubility and octanol solubility (106) indicates that the partition coefficient is high (possibly between 10^6 and 10^7). On the other hand, using the average measured solubility of FM-3422, 0.1 mg/l (0.18 μ M), the regression equation of Chiou et al (19) predicts an octanol/water partition coefficient for FM-3422 of 3×10^5 . The distribution coefficient of FM-3925 has been measured by the standard Environmental Laboratory procedure and was determined to be 5.7×10^4 (107).

These water solubility and partition coefficient data suggest that the two fluorochemical alcohols would tend to partition from water into sediments, lipid tissues of aquatic organisms, and suspended organic matter, such as activated sludge.

Label numbers

Soil Sorption - FM-3925 and FM-3422 were found to have soil organic carbon adsorption coefficients, K_{oc} , of 3,500 and 15,000 (108,109), respectively, which indicates very low mobility in soil and is in agreement with the low water solubilities of these compounds. Preliminary soil TLC measurements were also made on FM-3422 (72). In this test, the FM-3422 remained at the origin, which is consistent with its K_{oc} and water solubility data. Together, the water solubility, soil sorption, and soil TLC measurements indicate that FM-3422 will have very low mobility in the soil environment.

Vapor Pressure - From nonquantitative observations, the volatility of FM-3422 was found to be substantial (102,106). FM-3422 steam distills or coevaporates appreciably with water. These observations suggest that FM-3422 has a significant vapor pressure. Due to its structural similarity, FM-3925 likely behaves in a similar manner.

H

c) Degradation

Chemical Degradation - Lab tests have shown that FM-3422, when treated with 5% KOH in absolute ethanol at 50-53°C, hydrolyzes to form FC-95 with a half-life of 77 hours (106). These results, however, cannot be extrapolated to estimate environmentally relevant alkaline hydrolysis rates in water. Alkoxides formed in alcohol are much stronger bases than hydroxyls in water. This stronger activity can cause reactions to take place in alcohol that may not occur in water.

Our present understanding is that FM-3422 would not hydrolyze at a significant rate in the environment since sulfonamides are stable in water at normal pH, only hydrolyzing in strong acid or caustic solutions (110).

Photodegradation - Photolysis studies by the Agrichemical Group on FM-3422 in DI water have given negative results (111). In addition, the Environmental Laboratory has done two photodegradation studies on FM-3925. The first involved exposing a saturated aqueous solution of FM-3925 for 30 days to a 40 W fluorescent black light (112). The second involved exposing supersaturated aqueous solutions of FM-3925 to natural sunlight for 7 months both in the presence and absence of acetophenone, a photochemical "sensitizing" agent (113). Neither study showed any significant photodegradation. Aquatic photolysis doesn't appear likely to cause significant degradation of these compounds.

A photolysis study on FM-3422 adsorbed to soil (114) has given slight positive, yet inconclusive, results. In this study, adsorption to silica could have lowered energy requirements for photodegradation.

Biodegradation - No biodegradation of either FM-3422 or FM-3925 has been substantiated by analytical means in any of several biodegradation tests conducted in the Environmental Lab. The tests conducted on FM-3422 include a Warburg (79), a 10-day semicontinuous activated sludge (115), and a 6-month shake flask study which used inocula from a number of sources, including soil and sludge that had been exposed to fluorochemicals (115). These studies show that rapid aerobic, microbial conversion of FM-3422 to other products is unlikely.

In contrast, perfluorooctane sulfonic acid (FC-95) has been identified in rat and monkey serum following 30 and 90-day FM-3422 feeding studies (116). Its concentration was 300-750 times greater than that of residual FM-3422, suggesting that it is a major metabolite of FM-3422 in mammalian systems. Due to the great diversity of catabolic capabilities in microorganisms, this finding increases the probability that microbial systems may eventually be found that are also capable of this conversion. It also suggests that biotransformation could occur in other organisms, such as fish or food crops grown on soil in which fluorochemical-containing wastewater sludge has been incorporated.

d) Bioconcentration

It has been demonstrated that fish will bioconcentrate FM-3422 in their tissues, with whole fish values ranging from 200-600 times the concentration of this material in the water (8,9). These bioconcentration factors (BCF) values were independent of species. BCF data of similar orders of magnitude were found for both bluegill sunfish or channel catfish. Muscle samples had a BCF value of approximately 200, whereas relatively more fatty tissues bioconcentrated FM-3422 to a much greater degree, e.g., BCF = 1000 in brain tissue. This finding that FM-3422 tends to concentrate in lipophilic material qualitatively agrees with predictions of the regression equation developed by Neely (117) relating octanol/water partition coefficient (K_{ow}) to BCF. Quantitatively the equation predicts whole fish BCF's about one order of magnitude higher than that observed.

Fish cleared accumulated FM-3422 upon return to clean water. Experiments with both channel catfish and bluegill sunfish showed clearance to be about 95% complete in 14 days (8). A second study, using only channel catfish, showed 70% whole body clearance in five days (9). Muscle, the major edible component of fish, cleared 50% of the FM-3422 in the same five-day period.

A major question remains about this bioconcentration work since a review of the raw data (NB #41947, p. 21, 23, 24, 25, 41, and NB #46269, p. 35) shows that no tests were done to demonstrate that the solvents used (octanol and ethyl acetate) would quantitatively extract FM-3422 from fish tissue. Work on microorganisms suggests that some binding to cellular material is irreversible (115).

e) Effects

Bioassay data on the fluorochemical alcohols, which include acute fish and daphnia studies on both FM-3422 and LR-3925, and algal studies on FM-3422, indicate a lack of toxicity of these compounds at or near their solubility limits, ca, 0.1 and 1 mg/l, respectively (Table 11). Egg-fry studies on FM-3422 indicated no toxicity at 2 ug/l or approximately 1/3 water saturation. This was the highest concentration used in this study. This lack of toxicity has also been indirectly substantiated by other tests. For example, a semicontinuous activated sludge system operated for 10 days with 500 mg/l

of emulsified FM-3422 and produced no apparent toxicity to the sludge microorganisms (115). In bioconcentration studies on bluegill sunfish and channel catfish (8,9), FM-3422 showed no toxic effect despite the fact that the fish concentrated FM-3422 to whole body concentrations of up to approximately 300 mg/kg (9).

TABLE 11

BIOASSAY DATA ON FM-3422 AND FM-3925

<u>Test</u>	<u>FM-3422</u>	<u>FM-3925</u>	<u>References</u>
48-Hr. LC50 <u>Daphnia magna</u>	exceeds water solubility	(1350 mg/l)(c)	(1,118)
96-Hr. LC50 <u>Bluegill sunfish</u>	exceeds water solubility	exceeds water solubility >100 mg/l)(c)	(1,118)
30-day egg-fry(a) exposure	MTC(b) >20 ug/l		(119)
Algae(d)14-day EC50 cell count	>1,800 mg/l(c)		(120)

Footnotes:

- (a) Fry were Fathead minnow (Pimephales promelas).
- (b) MTC - Minimum Threshold Concentration (20 ug/l was the highest concentration used).
- (c) This concentration is greatly above maximum water solubility.
- (d) The green algae used in these studies was Selenastrum capricornutum.

2. Recommended Testing

a) Physical Properties

Water Solubility and K_{OW} - More accurate measurements of FM-3422 water solubility, FM-3422 octanol/water partition coefficient (K_{OC}), and FM-3925 water solubility are needed for structure activity work. These measurements preferably should be made on individually isolated isomers. Work will be done using EPA-approved protocols and, if available, radiolabeled fluorochemicals to simplify analysis and cut analytical costs.

Water Solubility:

FM-3422 - Priority III
FM-3925 - Priority III

Distribution coefficient (K_{ow}):

FM-3422 - Priority I

*Low priority -
Biology*

Soil Sorption - Soil Thin-Layer Chromatography (TLC), using the U.S. EPA protocol (79), is recommended to substantiate the prediction that fluorochemical alcohols have low soil mobility. Adsorption data obtained using this procedure may show differences among various fluorochemical alcohol isomers. These studies will aid in determining the rate and extent of movement of these alcohols in soil environments such as landfills and sludge incorporative sites. Soil TLC measurements on FM-3422 are of lower priority since this type of work has already been done, although prior to the availability of a standard procedure. Soil TLC requires radiolabeled materials.

Soil TLC:

FM-3925 - Priority II
FM-3422 - Priority III

Vapor Pressure - Since preliminary laboratory observations indicate that FM-3422 readily volatilizes from water, quantitative measurements of vapor pressure and aqueous volatility are needed to model the movement of this compound and FM-3925 between various environmental compartments and the atmosphere. Measurements may be most efficiently performed by Analytical and Properties Research, CRL.

Vapor pressure and volatilization measurements are proposed for:

FM-3422 - Priority I
FM-3925 - Priority II

b) Degradation

Low priority

Chemical Degradation - Chemical hydrolysis of FM-3422 has only been measured in the presence of alcoholic KOH. These findings cannot be extrapolated to estimate environmental half-lives. Therefore, tests more directly applicable to the environment are needed.

Testing under high temperatures (up to 60°C) and pH's (up to pH 11) may be necessary to observe hydrolysis within a reasonable time frame. Knowledge of the hydrolysis rate of FM-3422 is important because it is likely to be the most significant mode of environmental degradation for this chemical. To date, neither microbial nor photodegradation tests have shown them to be important. If hydrolysis is observed, attempts will be made to extrapolate findings to predict half-lives under normal environmental conditions and to identify hydrolysis products.

This testing can give only an upper limit to half-life since other mechanisms of hydrolysis may play a more dominant role at neutral pH. For example, mechanisms such as hydrolysis by H₂O alone or general acid-base hydrolysis catalyzed by metals or other materials in the environment would not be speeded up by increasing the pH. Radiolabeled material will facilitate this testing.

Proposed hydrolysis tests:

FM-3422 - Priority III
FM-3925 - Priority III

Photolysis - A previous study has given an indication that some photodegradation of FM-3422 may occur when adsorbed to soil. Testing to measure the photolysis of FM-3422 adsorbed to silica sand or silica gel is recommended to confirm this finding.

Testing will involve placing a thin coating of FM-3422 on silica sand or preferably silica gel from a solvent, spreading a thin layer of the coated substrate on the bottom of an airtight Vycor® container, and exposing to sunlight for up to one year. The container used will be transparent to sunlight down to 290 nm to permit the maximum environmental degradation rate.

Photolysis of FM-3422 on Silica Gel or Sand -
Priority III

Biodegradation - Hydrolysis, photolysis, and biodegradation studies under moderately rigorous conditions have not shown degradation of environmental significance in previous testing. A need exists to run aerobic microbial biodegradation studies under the most rigorous conditions conceivable at moderate cost. Such studies would allow us to determine whether measurable biolysis might be occurring in the environment, but was undetectable under the milder laboratory conditions of previous tests. ✓

The proposed biodegradation study will modify standard soil burial methods by simultaneously composting organic material with the soil. This approach, which increases microbial activity in the soil, has been found to greatly increase the degradation rate of organic compounds very resistant to degradation(121).

This study would be greatly facilitated by the use of radiotagged FM-3925 and FC-3422. This would allow detection of ^{14}C -FC-95 or other degradation products by TLC if the label were on the perfluorinated portion. If the label were on the hydrocarbon portion of the fluorochemical alcohol, $^{14}\text{CO}_2$ evolution would be measured, and if results indicated significant degradation, the program would be expanded to identify degradation products.

Proposed rigorous soil aerobic biodegradation testing:

FM-3422 - Priority I
FM-3925 - Priority II

No study of FM-3422 biodegradation under anaerobic condition has been done. Rigorous anaerobic tests are also recommended such as mixing ^{14}C -FM-3422 in river sediments or water-saturated soil supplemented with digester sludge and adequate nutrients. Such testing would provide optimal conditions for anaerobic degradation. It is relevant to the fluorochemical alcohols since water solubility, octanol/water partition coefficient, and soil sorption data all suggest that the alcohols are likely to accumulate in sediments or soil. This testing would preferably be done with the ^{14}C label on the perfluorinated portion of FM-3422.

Proposed Anaerobic Testing:

FM-3422 - Priority II

Biotransformation - The metabolism of FM-3422 by fish has not been investigated in our previous studies. Indications have appeared in the internal 3M literature (122,123) that this process is operative in mammalian systems. It is, therefore, recommended that similar studies be done on fish and plants. Fish studies could be performed alone or in conjunction with other long-term studies such as fish chronic tests.

Accumulation in plants is of significance since food crops are grown in areas in which FM-3422-containing sludge is applied. A preliminary study of accumulation of FC's, including the methyl and ethyl FOSE alcohols, into crops grown at Decatur is now underway. Samples are awaiting analysis in the Commercial Chemicals Division Analytical Laboratory (124). Proposed laboratory studies will examine roots and aboveground portions of corn and soybeans grown to maturity. Again, radiolabeled FM-3422 should be used in future studies and plant tissue assayed for parent and degradation compounds.

Information from this study will be used to estimate environmental risk of sludge soil incorporation practices. It will allow determination of whether vegetation grown at these sites could uptake, accumulate, and pass fluorochemicals into the human food chain. Abnormalities in plant growth and development will also be checked. The study will follow proposed standard procedures for vegetation uptake measurement (125).

Proposed fish biotransformation studies:

FM-3422 - Priority III

Proposed plant ^{uptake} and biotransformation studies:

FM-3422 - Priority II

c) Bioconcentration

Fish bioconcentration data are suspect because, as indicated above, no checks were done to show quantitative extraction of FM-3422 from fish tissue. It is recommended that such checks be done at this time. Testing would involve adding FM-3422 to fish tissue homogenized in water, mixing for 1 hr. and 8 hrs. This would be followed by extracting with ethyl acetate and n-octanol, the solvents used in the fish bioconcentration studies, as well as ethyl ether, a solvent which unlike the other two solvents extracted FM-3422 quantitatively from microorganisms. Analysis will be by GLC with electron capture detection or by the use of radiolabeled material.

Confirmation of fish bioconcentration study extraction procedure:

FM-3422 - Priority I

d) Effects

We recommend expanding the bioassay data on FM-3422 with a 28-day daphnia bioassay. This data will allow a more complete evaluation of the environmental safety of the important fluorochemical alcohols. This testing is needed to determine if this apparently long-lived environmental contaminant causes any long-term toxic effects. Tests on daphnids, a representative of the invertebrates, are particularly useful since they are generally more sensitive to toxicants than fish and algae. These tests are also much less costly than other chronic studies. Daphnia magna life cycle studies are completed in 28 days as opposed to nine months for fish.

28-Day Daphnia Bioassay FM-3422 - Priority II

F. Acrylates

1. Background

a) Chemical Characteristics

The 3M fluorochemical acrylate products are all formulated products. They contain components such as solvents and emulsifying agents, in addition to fluorochemical-containing acrylate polymers.

The acrylate polymers are made from fluorochemical acrylate and common hydrocarbon acrylate monomers. MeFOSEA ($\text{C}_8\text{F}_{17}\text{SO}_2\text{N}(\text{CH}_3)\text{C}_2\text{H}_5\text{-O-C(O)CH:CH}_2$) is the most important fluorochemical monomer(126).

There are two types of acrylate fluorochemical polymers: emulsion and solution polymers. The emulsion polymers (those polymerized as emulsions in water) have molecular weights (MW) ranging from 200,000 to greater than a million. The solution polymers (those polymerized in organic solvents) have molecular weights ranging from 20,000 to 200,000. The MW ranges are estimates since there are really little hard data on MW (126).

These acrylate products may also contain some unreacted fluorochemical alcohol (approx. 1%), and this low level contaminant may be the most environmentally significant aspect of these products. Low molecular weight components are of more environmental concern than polymers because they are likely to be more mobile, having higher solubility and vapor pressure, and they are more likely to pass through or into biological membranes, possibly causing toxic effects. Thus, because of their high MW and their inertness, the acrylate polymers, per se, are not likely to cause significant adverse effects.

b) Physical Properties

The Environmental Lab has generated no physical properties data on acrylate polymers. Based on their chemical structure, these products are likely to have low water solubility, and based on their MW, they are expected to have negligible volatility and little mobility in a soil environment.

c) Degradation

The only significant question with acrylate polymers is whether they will break down under environmental conditions to release more environmentally significant low MW FC components. As a general rule, FC acrylates are more stable (they depolymerize less readily) than their hydrocarbon analogs (126).

Chemical Degradation - Due to their known chemical stability, it seems unlikely that the acrylate products would undergo rapid chemical degradation in lab tests simulating normal environmental conditions. The products, however, are known to degrade in strong base (pH 11-12) but are not easily acid hydrolyzed (126). This suggests that the acrylates will undergo some slow basic hydrolysis in the environment.

Photodegradation - The acrylates (e.g., MeFOSEA/BA) do not discolor when exposed to light (126) which suggests resistance to photodegradation, but some such degradation is possible on sunlight exposed fabrics. Both waterborne and solid manufacturing wastes containing fluorochemical acrylates are not likely to be exposed for long period to solar radiation since the high MW of these polymers suggests that they will not volatilize and that they will move into sediments or be buried in soils where little solar exposure is possible.

Biodegradation - The likelihood of rapid biodegradation is low. Evaluation of biodegradation tests done by the Environmental Laboratory, however, is complicated by the presence of biodegradable surfactants and solvents in the tested acrylate products. In all cases, though, the extent of biodegradation can be explained as being solely due to the nonacrylate components. The lack of ready biodegradation is substantiated by the fact that hydrocarbon acrylates are generally not biodegradable (127,128), and FC acrylates are likely to be even more resistant.

d) Effects

Environmental effects tests have been done on a large number of acrylate products. Some of these data are summarized in Table 12. This table groups products containing the same acrylate polymer together. It gives the weight percentages of the specified acrylate polymers in the nonaqueous component of each product. As these data are for formulated products, they do not directly represent the toxicity of the fluorochemical acrylate polymers. In fact, the solvents and surfactants in these products are the major cause of product toxicity. The data only allow one to set minimum LC₅₀ values for the fluorochemical acrylate polymers.

Only one acrylate product family (cc 805-14) has an aquatic LC₅₀ value low enough to be classified as moderately toxic (see Appendix I). This causes little concern since these products are unlikely to reach the aquatic environment in significant concentrations. cc 805-14 is now being assessed (LR 8185) and an attempt will be made to determine the likely cause of this toxicity.

Tests to determine the acute toxic effects to activated sludge have also been done on a number of fluorochemical-acrylate products. In all cases, the products were found not to inhibit sludge respiration rates at product concentrations likely to reach waste treatment systems.

Only one fluorochemical acrylate monomer N-BuFOSEA, is sold alone as a product. This material, sold as FC-189 and cc 8111-16, is practically nontoxic. Its acute 96-Hr. LC₅₀ fathead minnow is 235 mg/l.

TABLE 12

TOXICITY OF ACRYLATE PRODUCTS TO AQUATIC ORGANISMS^a

<u>Product</u>	<u>% this Polymer in Nonaqueous Components</u>	<u>96-Hr. LC50 of Acrylate Assuming it caused all the Toxicity (mg/l)^b</u>	<u>96-Hr. LC50 of Total Product (mg/l)</u>	<u>Lab Request No. or (Reference)</u>
Products Containing the Emulsion Polymer: 95/5 MeFOSEA/BA				
FC-214, FC-214A	19	40 125	400 1250	2485 1204
FC-214-30	33	20 51c 38d 43e	131 339c 249d 284e	(129)
FC-232 CC-8110-92	42	34 34c 22d 34e	180 179c 118e 180d	(130)
FC-245 CC-805-15 FC-247 CC-805-17	27	25	170	(131)
FC-252	55	46	233	5785
FC-254	38	78	527	(132)
FC-270 CC-8010-32	47	66	575	6363
FC-353	54	71	440	6671
FC-452-30	20	12c 26d	132c 283d	4068
Products containing the emulsion polymer: 49/29/16/6 MeFOSEA/Vinylidene chloride/ODMA/N methylol acrylamide				
FC-461	59	>295	>1000	4625
Products containing the emulsion polymer: Chloroprene/EtFOSEA				
FC-208	50	167 487	600 1750	2563 1204

TABLE 12 (continued)

<u>Product</u>	<u>% this Polymer in Nonaqueous Components</u>	<u>96-Hr. LC₅₀ of Acrylate Assuming it caused all the Toxicity (mg/l)^b</u>	<u>96-Hr. LC₅₀ of Total Product (mg/l)</u>	<u>Lab Request No. or (Reference)</u>
Products containing the solution polymer: 50/50 MeFOSEA/C.W. 4000 DMA				
FC-218	67	>600 1132 1695	>2000 3762 5630	8021 (133) 1204
cc 813-17	9	9.5	286	6888
Products containing the solution polymer: 70/20/10 MeFOSEA/Polymeg - 2000 DMA/Butyl Acrylate				
cc 805-15	27	25	170	(131)
cc 805-16	77	>300	>1000	
cc 805-16	77	28	96 ^f	5884
FC-836	48	130	328	4200
Products containing: 35/35/20/10 MeFOSBA/MeFOSEA/Polmeg -2000 DMA/BA				
FC-324-40	36	>360	>1000	5546
Products containing: 70/30 MeFOSEA/CW 750A				
FC-808	00	1800	9000	2256
Products containing: 50/50 EtFOSEMA/ODMA				
FC-740	50	45 ^d	180 ^d	(134)
Products containing: 65/35 N-MeFOSEMA/ODMA				
cc 8011-235	10		140	2485
FC-3029	10	>1009	184	7820
Products containing: 75/25 MeFOSEA/Alfol 1620A				
FC-835	80	95 ^d 38 ^e	238 ^d 94 ^e	4197
Products containing MeFOSEA/Alfol-1620A				
FC-824	95	479 400	1200 1000	2456 2256

TABLE 12 (continued)

<u>Product</u>	<u>% this Polymer in Nonaqueous Components</u>	<u>96-Hr. LC50 of Acrylate Assuming it caused all the Toxicity (mg/l)^b</u>	<u>96-Hr. LC50 of Total Product (mg/l)</u>	<u>Lab Request No. or (Reference)</u>
Products containing 70/15/5/10 MeFOSEA/Alfol 6120A/IOA/CW 750A				
cc 805-14	35	3.5	21	8185
Products containing 50/50 chloroprene/EtFOSEMA				
FC-208	50	167	600	2563
		487	1750	1204
		362	1300	2485
Products containing 56.7/28.3/15 MeFOSEA/(EtFOSE/TDI/HOPMA)/BA				
FC-134	93	179	480	5508
Products containing 25/25/50 MeFOSEA/(EtFOSE/TDI/HOEMA)/Alfol 1620A				
FC-300	40	>800	>2000	7461
N Bu FOSEA Monomer				
FC-189	00	235	235	6813

Footnotes:

- a Organism is Fathead minnow, unless noted.
- b Assuming no synergistic or antagonistic effects, this represents a minimum 96-Hr. LC₅₀ for the polymer. The actual LC₅₀ for the acrylate, however, is likely to be much higher.
- c Rainbow trout (*Salmo gairdneri*)
- d Bluegill sunfish (*Lepomis macrochirus*)
- e *Daphnia magna* 48-Hr. LC₅₀
- f The emulsifiers Tween 80 and Span 80 which make up 1.5% of the product were replaced by Siponic L-4. This small change made the product 10 times as toxic.
- g Toxicity measured after solvent evaporation

2. Recommended Testing

a) Physical Properties

No physical properties tests are recommended on fluorochemical acrylate polymers.

b) Degradation

100 Mar 20 2
4 1000
why not
Chemical Degradation - Measurements of the alkaline hydrolysis rate of two representative acrylates are recommended. These data will enable us to estimate upper limits on the hydrolysis rates of these products at environmental pH's. The acrylates recommended for this testing are 95/5 MeFOSEA/BA and 50/50 MeFOSEA/C.W. 4000 DMA. MeFOSEA/BA is a high molecular weight emulsion polymer used in FC-214, FC-214A, FC-353, and several other products. It is likely to be one of the most resistant to hydrolysis. MeFOSEA/CW 4000 DMA is a much lower MW solution polymer used in FC-220, FC-393, and other products. The Carbowax® portion of the product may increase the affinity of this product to water, possibly increasing its susceptibility to hydrolysis. This is expected to be one of the most readily hydrolyzed of the fluorochemical acrylate polymers.

Laboratory procedures will be modeled after standard methods (e.g., 135). Products containing the emulsified fluorochemical acrylate polymer will be hydrolyzed first within environmentally relevant pH (4-9) and temperature (20°-45°C) ranges. Low molecular weight fluorochemical hydrolysis products will be searched for using thin-layer chromatography, if ¹⁴C-tagged fluorochemical acrylates are available, or gas liquid chromatography, otherwise. If no low molecular weight fluorochemicals are detected in the pH 4-9 range, hydrolysis rate will be determined at high pH and extrapolations made to estimate hydrolysis rates under normal environmental conditions.

Hydrolysis of fluorochemical acrylates:

FC-220 - Priority II

FC-214, FC-214A - Priority III

Photochemical Degradation - The susceptibility of the same two fluorochemical acrylates to photolysis should be simply checked by coating the products on silica gel, coating this on the inside of a sealed high silica glass container (Vycor®), and exposing to sunlight for one year. Following such exposure, the product could be compared with dark controls, using analytical methods described above, for the amount of extractable low MW fluorochemical.

Fluorochemical acrylates are used as a soil resistant coating for carpeting and textiles. In this use, some of the acrylates will be exposed to sunlight, and it is possible that the textile dyes might act as photochemical "sensitizer" for the fluorochemical degradation, capable of absorbing and transferring solar energy to the acrylate polymers. For this reason, it is also proposed that dyed textile fibers coated with the candidate fluoroacrylates be sealed in Vycor® containers, exposed to sunlight, and analyzed for low MW fluorochemicals as described above.

Photolysis of fluorochemical acrylates:

- A. On silica gel
 - FC-220 - Priority III
 - FC-214, FC-214A - Priority III
- B. On dyed textile fibers
 - FC-220 - Priority III
 - FC-214, FC-214A - Priority III

Biodegradation - Rigorous biodegradation tests are recommended to see if depolymerization of the fluorochemical acrylates will occur. Testing will be similar to that recommended for FM-3422 involving burial with composting organic material in garden soil and analyzed for the release of low MW fluorochemical degradation products. Such tests should be run for at least one year. The use of radiolabeled acrylates would greatly improve the sensitivity of such tests and would allow monitoring of degradation by capturing radiolabeled CO₂ or by isolating radiolabeled fluorochemical degradation products. Radiolabeling could be achieved by incorporating either radiolabeled HC or FC acrylate monomers into the polymers.

Preliminary tests will be done to determine if low MW fluorochemical species that are possible degradation products can be retrieved from the soil system. These preliminary tests will also be used to determine whether loss of fluorochemical monomers from the soil system through volatilization is likely.

Rigorous soil biodegradation tests on fluorochemical acrylates:

FC-220 - Priority III
FC-214, FC-214A - Priority III

c) Effects

Acute fish bioassays are needed on the acrylate polymers alone, separated from the solvents and surfactants which keep them in emulsion or solution. Such separation could probably be made by dialysis. This method would probably remove monomers and low MW oligomers as well. Such bioassays on the dialyzed material would be useful in supporting the existing evidence that the fluorochemical acrylate polymers themselves are nontoxic.

Acute fish bioassays of dialyzed:

FC-220 - Priority II
FC-214, FC-214A - Priority II

G. Urethanes

1. Background

a) Composition

Unlike the acrylates, the fluorochemical urethanes are not polymeric materials, but are trimers, tetramers, or other small oligomers of fluorochemical alcohols, diisocyanates and sometimes hydrocarbon alcohols. Their molecular weights are in the range of one to two thousand.

b) Physical Properties

The Environmental Laboratory has no physical properties data on the fluorochemical urethanes. These materials have low water solubility, but their solubility in lipid materials is unknown (126). Based on their MW, they are expected to have low volatility.

c) Degradation

The fluorochemical urethanes are more stable than their hydrocarbon analogs, but they are less stable than the fluorochemical acrylates. These materials are more likely than the acrylates to degrade through hydrolysis; photolysis, or biochemical mechanisms, releasing low MW fluorochemical monomers to the environment.

d) Effects

Environmental effects data on these products are shown in Table 13. Like the acrylates, the fluorochemical urethanes are sold in mixtures with other materials, including solvents, surfactants, and polymers that can mask the toxicity of the urethane. The table shows, however, that some of these products have high concentrations of fluorochemical urethane and little toxicity. These data indicate that at least two of the three urethanes are at worst practically nontoxic assuming no antagonistic effects on toxicity from other product components.

2. Recommended Testing

a) Physical Properties

The possibility of bioconcentration of urethane products should be further investigated. One possibility is that their molecular size may limit their capacity to bioconcentrate. Further literature study is needed on the effects of molecular size or molecular weight on the bioconcentration potential of fluorochemicals.

Most SAR methods predict bioconcentration from octanol/water partition coefficient. It is recommended that the octanol/water partition coefficient of the EtFOSE/TDI urethane be determined as a representative of this group of fluorochemicals. The most appropriate method of making this measurement appears to be the use of reverse-phase high-pressure liquid chromatograph (136). This method will prevent possible interference from other components of the product mixture. The TDI component of the molecule should facilitate UV detection.

n-Octanol/water partition coefficient of:

2 EtFOSE/TDI - Priority III

b) Degradation

Tests similar to those for the acrylates are recommended to check susceptibility of the urethane products to biodegradation, photodegradation, and chemical hydrolysis. As with the acrylates, hydrolysis tests will be run on the product as sold. Photodegradation tests will be done on the product residue left on silica gel and on dyed textile fabrics. Biodegradation tests will be done on the product residue in soil.

It is recommended that testing be done on FC-352-20. This product contains 20% solids, and 98% of their solids are EtFOSE/MDI. The remaining 2% is MCL emulsifier, a 3M fluorochemical surfactant. The presence of this surfactant could cause some confusion in interpreting results if only very low levels of degradation occur. The use of radiolabeled urethanes would simplify analytical work and prevent such confusion.

Degradation tests on fluorochemical urethane FC-325-20 (EtFOSE/MDI):

Hydrolysis - Priority II
Rigorous soil biodegradation - Priority III
Photodegradation on silica gel - Priority III
Photodegradation on dyed fabric -
Priority III

c) Effects

Although no bioassays have been done on the fluorochemical urethane alone, bioassays on the formulated products can allow a determination of the worst case or lowest possible toxicity due to the urethane. Such predictions assume that all the toxicity of the product is due to the fluorochemical, and also assume no toxicity or antagonistic effects from other product components. Using this technique, present environmental data shows that EtFOSE/MDI and EtFOSE/ODA/PAPI urethanes have little toxicity. But similar data on EtFOSE/TDI urethanes allow us only to say that its 96-hr. fish LC₅₀ >15 mg/l (LR #5493). Its LC₅₀ is probably much higher (less toxic) than this. To complete the data base, bioassays are needed on products with high levels of this urethane. FC-376M is one

possible product for use in such testing since it contains 20% EtFOSE/TDI as its only fluorochemical component. A sample of the urethane alone would be even better to demonstrate its probable lack of significant toxicity.

96-Hr. Fish LC50:

EtFOSE/TDI - Priority II

H. FLUOREL® and KEL-F® Polymers

1. Background

These products are high MW polymers made from one or more of the following monomers: vinylidene fluoride, hexafluoropropane, and chloro-or bromo-trifluoroethylene. Some also have curative systems. After being fully cured, these polymers are nontoxic, insoluble, nonvolatile, and extremely inert.

FLUOREL®-FLUOREL® Brand fluoroelastomer FC-2174 has been found to leach small amounts of fluoride (0.43 mg/g) and small amounts of COD (0.74 mg/g) (Lab request 3270). A later study under different conditions leached 0.26 mg of COD per gram of FC-2174 (137). The leachate from FC-2174 was found to be toxic to fish and daphnids (137,138), but after curing at 350°F for 15 minutes, no toxic material leached (138).

Toxicity was also not found after longer curing periods. FC-2175, an identical FLUOREL® fluoroelastomer, except that it does not contain a curative system, leached only .01 mg of COD/g, and the leachate was not toxic to fish or daphnids (138). These results indicate that the curative system, and not residual fluorochemical monomers or the fluorochemical polymers themselves, are the cause of the toxicity from uncured FLUOREL® fluoroelastomers.

Kel-F® - No environmental testing has been done on the Kel-F® polymers.

2. Recommended Testing

No environmental testing is recommended for the FLUOREL® and Kel-F® polymers.

I. Catalysts

1. Background

3M makes two hexafluorophosphate salts which are used as catalysts for the curing of epoxy resins. At this time, these are used in low volume products (FC-508 and FC-509) and their prospect for significantly increased volume do not seem great.

2. Recommended Testing

No recommendations to include these products in the Part II Fate of Fluorochemicals program are made at this time.

TABLE 13

AQUATIC TOXICITY DATA ON URETHANE-CONTAINING PRODUCTS^a

<u>Product</u>	<u>Wt. % Urethane in Product</u>	<u>96-Hr. LC₅₀ (mg/l)</u>	<u>Lab Request Number or (Reference)</u>
Products containing EtFOSE/MDI			
cc 8110-92	10.5	180 179 ^c 118 ^d 180 ^e	(130)
FC-252	10.5	233	5785
FC-270	6.2	575	6363
FC-324-40	4	>1000	5546
FC-351-25	9	440	6671
FC-352-20	20 (98% of solids)	>2000 mg/l	6672
Products containing EtFOSE/TDI			
FC-383	15	102	5493
FC-388	15	56	4369
FC-391	14	65	5055
Products containing 2 EtFOSE/ODAb/PAPI			
FC-214	10	400 1250	2485 1204
FC-214-30	15	131 339 ^c 249 ^d 284 ^e	(129)
cc 8110-93B	30	1148	5511
cc 8110-96B	30	1306	5983
FC-247	5	689	6814
FC-254	15	527	(132)

Footnotes:

- ^a All data on Fathead minnows unless otherwise noted.
- ^b ODA = Stearyl alcohol.
- ^c Rainbow trout.
- ^d Bluegill sunfish.
- ^e Daphnia magna, 48-Hr. LC₅₀

TABLE 14

SUMMARY OF RECOMMENDED STUDIES ON FLUOROCHEMICALS

<u>Test or Measurement</u>	<u>Product Category</u>	<u>Product(a)</u>	<u>Priority of Work</u>	<u>Testing Time Requirements (Hrs)</u>	<u>Cost (\$)</u>
<u>SAR(b)</u>	All 3M fluorochemicals				
1) Application of existing SAR to Fluorochemicals			I	650	29,250
2) Derive new SAR for fluorochemicals			II	1,300	58,500
<u>Field Studies</u>	All 3M fluorochemicals				
1) Confirm analytical			I	150	6,750
2) Predictive modeling			I	20	900
3) Field Sampling and analysis			II	1,200	54,000
<u>Incineration</u>	All 3M fluorochemicals		III	200	9,000

Footnotes:

- (a) Chemistry of Products is shown in Appendix II
 (b) SAR = Structure Activity Relationships
 (c) Hydroxy Foamer

Table 14 (continued)

<u>Test or Measurement</u>	<u>Product Category</u>	<u>Product (a)</u>	<u>Priority of Work</u>	<u>Testing Time Requirements (Hrs)</u>	<u>Cost (\$)</u>
<u>Physical Properties</u>					
1) Water Solubility	Phosphates	FC-807	I	35	1,575
	Alcohols	FM-3422	III	50	2,250
		FM-3925	III	50	2,250
2) n-Octanol-Water distribution coefficient					
a) Shaking	Surfactants	FC-95	I	25	1,125
		FC-143	I	25	1,125
	Phosphates	FC-807	I	40	1,800
	Alcohols	FM-3422	I	25	1,125
b) HPLC	Urethane	2 EtFOSE/TDI	III	25	1,125
3) Soil Sorption					
a) K _{oc}	Phosphates	FC-807	III	90	4,050
b) TLC	Surfactants	FC-95	II	15	675
		FC-143	II	15	675
	Phosphates	FC-807	III	15	675
	Alcohols	FM-3422	III	15	675
		FM-3925	II	15	675
4) Vapor Pressure	Surfactants	FC-95	III	15	675
		FC-143	III	15	675
	Phosphates	FC-807	III	15	675
	Alcohols	FM-3422	I	15	675
		FM-3925	II	15	675
5) Bioadsorption					
	Surfactants	FC-95	III	15	675
		FC-143	III	15	675
<u>Degradation</u>					
1) Alkaline Hydrolysis	Alcohols	FM-3422	III	40	1,800
		FM-3925	III	40	1,800
	Acrylates	FC-220	II	60	2,700
		FC-214, FC-214A	III	60	2,700
	Urethane	FC-352	II	60	2,700
2) Photolysis					
a) on Silica	Surfactants	FC-95	III	100	4,500
		FC-143	III	100	4,500
	alcohols	FM-3422	III	100	4,500

Table 14 (continued)

	Acrylates	FC-220	III	100	4,500
		FC-214, FC-214A	III	100	4,500
	Urethanes	FC-352-20	III	100	4,500
b) on dyed fabrics	Acrylates	FC-220	III	100	4,500
		FC-214, FC-214A	III	100	4,500
		FC-352-20	III	100	4,500
	Urethanes				
c) sensitized in water	Surfactants	FC-95	III	100	4,500
		FC-143	III	100	4,500
		F-6422C	III	100	4,500
3) Biodegradation					
a) Acclimated Seed BOD28	Surfactants	FC-171	I	20	900
		Daughter Products I.D.	II	25	1,125
b) Soil Respirometry	Surfactants	F-6422C	II	20	900
		Prod. I.D.	III	25	1,125
c) Rigorous Aerobic	Surfactants	FC-95	II	45	2,025
		FC-143	II	45	2,025
	Phosphates	FC-807	III	45	2,025
	Alcohols	FM-3422	II	45	2,025
		FM-3925	II	45	2,025
	Acrylates	FC-220	III	45	2,025
		FC-214	III	45	2,025
	Urethanes	FC-352-20	III	45	2,025
D) Rigorous Anaerobic	Surfactants	FC-143	III	45	2,025
	Alcohols	FM-3422	II	45	2,025
4) Biotransformation					
a) Plants	Alcohol	FM-3422	II	50	2,250
b) Fish	Alcohol	FM-3422	III	25	1,125
<u>Bioconcentration</u>					
a) Fish	Surfactants	FC-95	I	55	2,475
		FC-143	I	55	2,475
b) Confirm ex- traction method	Alcohol	FM-3422	I	25	1,125
1) 96-Hr. Fish Tox.					
	Surfactants	F-6422C	III	10	450
		FC-128 (with & without solvent)	III	20	900
	Acrylate	Dialyzed	II	25	1,125
		FC-220			
		Dialyzed	II	25	1,125
		FC-214, FC-214A			
	Urethane	EtFOSE/TDI	II	10	450

Table 14 (continued)

2) 14-Day Algae	Surfactants	FC-128	II	35	1,575
		cc 773-58 solids	II	35	1,575
		FC-171	II	35	1,575
		F-6422C	II	35	1,575
		FC-807	II	35	1,575
3) 28-Day Daphnia	Phosphates	FC-143	II	50	2,250
	Surfactants	FC-128	II	50	2,250
		cc 773-58 solids	II	50	2,250
		FC-171	II	50	2,250
		F-6422	II	50	2,250
		FC-807	II	50	2,250
	Phosphates	FM-3422	II	50	2,250
	Alcohol				
Total Priority I				1,140	51,300
Total Priority II				2,285	102,825
Total Priority III				3,465	155,925
Total Project				6,890	310,050

TABLE 15

SCHEDULE OF PROPOSED WORK

This table prioritizes work and schedules it by quarter following program approval. The schedule assumes a 1-1 1/2 man rate of expenditure and availability of the radiolabeled materials listed in Appendix III.

Year 1, Quarter 1

<u>Priority</u>	<u>Category</u>	<u>Description</u>	<u>Time in hrs.</u>
I	<u>SAR</u>	- Begin study on applicability of existing SAR methods	150
I	<u>Field</u>	- Confirm analytical capabilities for TOF, FC-95, FC-143, and FM-3422 in spiked soil, sediment, sludge, tissue and water samples.	150
I		- Predictive modeling for proposed field study.	20
I	<u>Physical Properties</u>	- Water solubility of FC-807	35
I		- n-octanol/water distribution coefficient of FC-95, FC-143, FC-807, and FM-3422.	115
I		- vapor pressure of FM-3422	15
I	<u>Biodegradation</u>	- Acclimated seed BOD or Shake flask study on FC-171 (save products)	20
I	<u>Bioconcentration</u>	- Determine if extraction procedures used in past FM-3422 fish bioconcentration studies were quantitative	25
		Time quarter 1 -	530 hrs.
		Cost quarter 1 -	\$23,850

Year 1, Quarter 2

<u>Priority</u>	<u>Category</u>	<u>Description</u>	<u>Time in hrs.</u>
I	<u>SAR</u>	- Continue study on existing SAR applicability.	125
II	<u>Field</u>	- Begin field sampling and analysis.	300
II	<u>Biodegradation</u>	- Identify biodegradation products of FC-171	25
I	<u>Bioconcentration</u>	- Fish bioconcentration studies on FC-95 and FC-143	<u>110</u>
		Time quarter 2 -	560 hrs.
		Cost quarter 2 -	\$25,200

Year 1, Quarter 3

I	<u>SAR</u>	- Continue study on existing SAR applicability.	125
II	<u>Field</u>	- Continue field sampling and analysis.	300
II	<u>Biodegradation</u>	- Rigorous aerobic on FC-95, FC-143, FM-3422, and FM-3925.	<u>180</u>
		Time quarter 3 -	605 hrs.
		Cost quarter 3 -	\$27,225

Year 1, Quarter 4

I	<u>SAR</u>	- Continue SAR applicability	125
II	<u>Field</u>	- Continue field sampling and analysis	300
II, III	<u>Physical Properties</u>	- Soil TLC of FC-95, FC-143, FC-807, FM-3422, and FM-3925	75
II	<u>Effects</u>	- 14-day algae FC-128, FC-135 Solids, and FC-171	105
		- 96-hr. LC ₅₀ fish on dialyzed acrylate polyers FC-220, and FC-214A	<u>50</u>
		Time quarter 4 -	655 hrs.
		Cost quarter 4 -	\$29,475

Year 2, Quarter 1

<u>Priority</u>	<u>Category</u>	<u>Description</u>	<u>Time in hrs.</u>
I	<u>SAR</u>	- Finish SAR applicability	125
II	<u>Field</u>	- Finish field sampling and analysis	300
II, III	<u>Physical Properties</u>	- Vapor pressure of FC-95, FC-143, FC-807, and FM-3925	60
II	<u>Effects</u>	- 14-day algae F-6422 and FC-807	70
		- 28-day Daphnia FC-143 and FC-128	<u>100</u>
		Time quarter 5 -	655 hrs.
		Cost quarter 5 -	\$29,475

Year 2, Quarter 2

III	<u>SAR</u>	- Start to derive new SAR for fluorochemicals	300
II, III	<u>Degradation</u>	- Alkaline hydrolysis of representative acrylates and urethanes	180
II		- Biotransformation of FM-3422 in plants	50
II	<u>Effects</u>	- 28-day Daphnia on FC-135 solids, FC-171, and F-6422	<u>150</u>
		Time quarter 6 -	680 hrs.
		Cost quarter 6 -	\$30,600

Year 2, Quarter 3

III	<u>SAR</u>	- Continue new SAR for fluorochemicals	250
III	<u>Physical Properties</u>	- Water solubility of fluorochemical alcohols FM-3422 and FM-3925	100
II, III	<u>Biodegradation</u>	- Soil respirometry on hydroxy foamer with product identification	45

<u>Priority</u>	<u>Category</u>	<u>Description</u>	<u>Time in hrs.</u>
II, III		- Rigorous anaerobic biodegradation of FC-143, FM-3422	90
III		- Biotransformation of FM-3422 in fish	25
II	<u>Effects</u>	- 28-day Daphnia FC-807 and FM-3422	<u>100</u>
		Time quarter 7 -	610 hrs.
		Cost quarter 7 -	\$27,450

Year 2, Quarter 4

III	<u>SAR</u>	- Continue new SAR for fluorochemicals	250
III	<u>Incineration</u>	- Look for toxic fluorochemical by-products in Decatur Incinerator emissions	200
III	<u>Bioadsorption</u>	- Determine adsorption of surfactants FC-95 and FC-143 to activated sludge	30
	<u>Degradation</u>	- Sensitized photolysis of surfactants in water on FC-143 and F-6422	<u>200</u>
		Time quarter 8 -	680 hrs.
		Cost quarter 8 -	\$30,600

Year 3, Quarter 1

III	<u>SAR</u>	- Continue new SAR for fluorochemicals	250
III	<u>Physical Properties</u>	- Octanol/water distribution coefficient of urethane by HPLC	25
III	<u>Degradation</u>	- Sensitized photodegradation surfactant FC-95	100
		- Photodegradation of alcohol, FM-3422, and urethane, FC-352-20, on silica	200
III	<u>Effects</u>	- 96-hr. fish tox on F-6422 F-128 solids, and EtFOSE/TDI	<u>40</u>
		Time quarter 9 -	615 hrs.
		Cost quarter 9 -	\$27,675

Year 3, Quarter 2

<u>Priority</u>	<u>Category</u>	<u>Description</u>	<u>Time in hrs.</u>
III	<u>SAR</u>	- Complete new SAR for fluoro-chemicals	250
III	<u>Physical Properties</u>	- Measure K _{OC} for FC-807	90
III	<u>Degradation</u>	- Photolysis of acrylates FC-220 and FC-214A on silica	200
III		- Rigorous aerobic biodegradation of phosphate FC-807 and urethane FC-352-20	<u>90</u>
		Time quarter 10 -	630 hrs.
		Cost quarter 10 -	\$28,350

Year 3, Quarter 3

III	<u>Degradation</u>	- Alkaline hydrolysis of alcohols FM-3422 and FM-3925	80
		- Photolysis on silica of surfactants FC-95 and FC-143	200
		- Photolysis of acrylates and urethanes on dyed fabrics	300
		- Rigorous aerobic biodegradation of acrylates FC-220 and FC-214	<u>90</u>
		Time quarter 11 -	670 hrs.
		Cost quarter 11 -	\$30,150

VI. REFERENCES

1. A. N. Welter, "Final Comprehensive Report: FM 3422," 3M Technical Report, 2/7/79.
2. A. N. Welter, "Final Comprehensive Report: FC-143" 3M Technical Report, 3/23/79.
3. A. N. Welter, "Final Comprehensive Report: FC-95," 3M Technical Report, 3/15/79.
4. D. F. Hagen, Personal Communication, May 11, 1981.
5. V. Pothapragada, Personal Communication, May 5, 1982.
6. J. Dean, "The Effects of Continuous Aqueous Exposure to 14C-78.02 (FC-95) on Hatchability of Eggs and Growth and Survival of Fry of Fathead Minnow (Pimephales promelas)," Report #BW-78-8-263, EG&G Bionomics, Wareham, MA, August 1978.
7. M. M. Goyer et al, Human Safety and Environmental Aspects of Major Surfactants. A report by Arthur D. Little, Inc., To The Soap and Detergent Association, May 31, 1977.
8. M. T. Elnabarawy, "Bioconcentration of FM-3422 in Bluegill Sunfish and in Channel Catfish," 3M Technical Report, 5/17/77 (Dept. 0222).
9. A. N. Welter, "Evaluation of the Bioconcentration Potential of FM-3422," 3M Technical Report, 8/16/78 (Dept. 0222).
10. E. E. Kenaga and C.A.I. Goring, "Relationship Between Water Solubility, Soil Sorption, Octanol-Water Partitioning, and Concentration of Chemicals in Biota," Published in Aquatic Toxicology. ASTM STP 707. J. G. Eaton, P. R. Parrish, and A. C. Hendricks, Eds., American Society for Testing and Materials, 1980, pp. 78-115.
11. A. Mendel, "Progress Report on Fate of Fluorochemicals Project," 3M Technical Report, 8/30/78 (Dept. 0535).
12. J. W. Belisle, "Analysis of Decatur, Alabama, Soil for Fluorine Content," 3M Technical Report, 6/6/78 (Dept. 0502).
13. T. F. Baltutis Personal Communication, October 26, 1982. This ratio was calculated from data from the 1981 report to the State of Alabama on Wastewater Sludge application and from data in the four quarterly NPDES Reports to the State of Alabama.

14. J. A. Todhunter, Assistant Administrator for Pesticides and Toxic Substances, USEPA, Letter to M. R. Rose, Deputy Assistant Secretary for Environmental Health and Natural Resources, U.S. Department of State, Sept. 30, 1982.
15. S. P. Wasik, Y. B. Tewari, M. M. Miller, and D. E. Martire, Octanol/Water Partition Coefficients and Aqueous Solubilities of Organic Compounds, NBSIR 81-2406, 1981.
16. Y. B. Tewari, M. M. Miller, S. P. Wasik, and D. E. Martire, "Aqueous Solubility and Octanol/Water Partition Coefficient of Organic Compounds at 25.0°C," J. Chem. Eng. Data, 27: 451-454, 1982.
17. Y. B. Tewari, M. M. Miller, And S. P. Wasik, "Calculation of Aqueous Solubility of Organic Compounds," J. Research NBS, 87: 155-158, 1982.
18. W. B. Neely, "Estimated Rate Constants for the Uptake and Clearance of Chemicals by Fish," Environ. Sci. Technol. 13:1506-1510, 1979.
19. C. T. Chiou et al., "Partition Coefficient and Bioaccumulation of Selected Organic Chemicals," Environmental Science & Technology, 11(5), 1977.
20. D. Mackay, Untitled note, Environ. Sci. Technol. 11: 1219-1220, 1977.
21. S. Banerjee, S. H. Yalkowsky, and S. C. Valvani; "Water Solubility and Octanol-Water Partition Coefficients of Organics. Limitations of the Solubility-Partition Coefficient Correlation," Environmental Science and Technology Vol. 14(10), p. 1227-1229, 1980.
22. G. L. Amidon & N. A. Williams, A Solubility Equation for Nonelectrolytes in Water, Intl. J. Pharm. 11:249-256 (1982).
23. P. W. Carr, D. F. Hagen, L. D. Winter, and S. S. Lande, personal communication, February 24, 1983.
24. C. Hansch and A. J. Leo, Substituent Constants for Correlation Analysis in Chemistry and Biology, Wiley-Interscience, New York, 1979.
25. J. M. Prausnitz, et al., Computer Calculations for Multicomponent Vapor-Liquid and Liquid-Liquid Equilibria, Prentice-Hall, Englewood Cliffs, NJ, 1980.

26. J. M. Mayer, H. van de Waterbeemd, and B. Testa, "A comparison between the Hydrophobic Fragmental Methods of Rekker and Leo," Eur J. Med. Chem., V17 N1, pp. 17-25, 1982.
27. D. S. Abrams and J. M. Prausnitz, "Statistical Thermodynamics of Liquid Mixtures: A New Expression for the Excess Gibbs Energy of Partly or Completely Miscible Systems," AIChE J., 21,116 (1975).
28. G. L. Amidon and S. T. Anik, "Application of the Surface Area Approach to the Correlation and Estimation of Aqueous Solubility and Vapor Pressure, Alkyl Aromatic Hydrocarbons," J. Chem. Eng. Data, 26:28-33, 1981.
29. G. L. Amidon, S. H. Yalkowsky, and S. Leung, Solubility of Nonelectrolytes in Polar Solvents II: Solubility of Aliphatic Alcohols in Water, Journal of Pharmaceutical Sciences, 63(12), p. 1858, 1974.
30. L. H. Hall, "The Relation of Molecular Connectivity to Molecular Volume and Biological Activity," Eur. J. Med. Chem.-Chemica Therapeutica, 16(5), pp. 399-407, 1981.
31. C. T. Chiou et al, "Partition Equilibria of Nonionic Organic Compounds Between Soil Organic Matter and Water," Environmental Science & Technology, 17(4), 1983.
32. S. S. Lande and S. Banerjee, Predicting Aqueous Solubility of Organic Nonelectrolytes from Molar Volume, Chemosphere Vol. 10, pp. 751-759, 1981.
33. G. G. Briggs, Theoretical and Experimental Relationships Between Soil Adsorption, Octanol-Water Partition Coefficients, Water Solubilities, Bioconcentration Factors, and the Parachlor, J. Agric. Food Chem. Vol. 29, pp. 1050-1059, 1981.
34. C. F. Grain, "Vapor Pressure," Chapter 14, pp. 14-7, Handbook of Chemical Property Estimation Methods Environmental Behavior of Organic Compounds, W. J. Lyman, W. F. Rechl, and D. H. Rosenblett, Eds., McGraw-Hill, 1982.
35. S. H. Yalkowsky, R. J. Orr, and S. C. Valvani, "Solubility and Partitioning. 3. The Solubility of Halobenzenes in Water," Ind. Eng. Chem. Fundam. 18:351, 1979.
36. D. Mackay, R. Mascarenhas, and W. Y. Shiu, "Aqueous Solubility of Polychlorinated Biphenyls, Chemosphere 9:257, 1980.
37. W. C. Steen and S. W. Karickhoff, "Biosorption of Hydrophobic Organic Pollutants by Mixed Microbial Populations," Chemosphere Vol. 10, pp. 27-32, 1981.

38. G. A. Vraspir, A. Mendel; "Analysis for Fluorochemicals in Bluegill Fish," 3M Technical Report, 5/1/79 (Dept. 0535).
39. H. Parlar, 1980, "Photochemistry at Surfaces and Interphases," in O. Hutzinger (ed.), The Handbook of Environmental Chemistry, Vol. 2, Part A, Springer-Verlag, New York, pp. 145-160.
40. J. E. Gagnon, "Bioaccumulation of Fluorochemicals in Tenn. River Fish," 3M Technical Report, 5/22/79 (Dept. 0222).
41. J. E. Gagnon, "Fluorochemicals in Tenn. River Fish," 3M Technical Report, 12/28/79 (Dept. 0222).
42. On-Site Sampling of Sediments and Soil, Handbook for Sampling and Sample Preservation of Water and Wastewater. Edward Berg, Editor, EPA 600/4-82-0209, September, 1982.
43. Biological Field and Laboratory Methods for Measuring the Quality of Surface Water and Effluents, Cornelius Weber, Editor. EPA-670/4-73-001. July, 1973.
44. Y. Alarie et al., Toxicity of Plastic Combustion Products, NTIS #PB-267 233, Springfield, VA, 1977.
45. L. T. Cupitt, Fate of Toxic and Hazardous Materials in the Air Environment. EPA 600/3-80-084, August, 1980, NTIS #PB80-221948.
46. R. N. Dietz, R. W. Goodrich, and E. A. Coate; "Detection of Perfluorinated Taggants in Electric Blasting Caps by Electron Capture Monitors." In Proceedings - Symposium and Workshop on Detection and Identification of Explosives, October 30, 31, and November 1, 1978, Reston Virginia.
47. R. N. Dietz, Brookhaven National Laboratory. Personnel communication 7/24/81.
48. G. J. Ferber, NOAA Air Resources Laboratory. Personal communication 4/28/82.
49. L. D. Winter, UV/Vis Spectra of CS 81210 (LR 6589), Commercial Chemicals Analytical Report #240, July 17, 1981.
50. G. Belanger, P. Sauvageau, and C. Sandorfy, "The Far-Ultraviolet Spectra of Perfluoro-Normal-Paraffins," Chem. Phys. Letters 3, 649, 1969.
51. A. R. Calloway, M. A. Stamps, and G. L. Loper; Vacuum Ultraviolet and Ultraviolet Absorption Spectra of Various Candidate Vapor Taggants for Blasting Caps, Prepared by the Aerospace Corporation for the U.S. Dept. of the Treasury, March, 1979, NTIS #PB 81-15531 9.

52. C. Sandorfy, "UV Absorption of Fluorocarbons," Atmospheric Environment, Vol. 10, pp. 343-351, 1976.
53. M. B. McElroy, et al., "Potential Atmospheric Impact of Explosive Vapor Taggant Molecules," Atmospheric and Environmental Research, Inc., NTIS #PB81-187189 1979.
54. National Academy of Sciences - Committee on Impact of Stratospheric Change, Halocarbons: Environmental Effects of Chlorofluoromethane Release, p. 28, 1976.
55. P. Ausloos et al., "Photodecomposition of Chloromethanes Adsorbed on Silica Surfaces," Journal of Research of the National Bureau of Standards 82(1): 1-8, 1977.
56. S. Kanno, T. Ito, and T. Omura, "Studies on the Photochemistry of Aliphatic Halogenated Hydrocarbons I." Chemosphere 6(8), pp. 583-508, 1977.
57. E. A. Reiner, "Environmental Effects of Fluorinert Electronic Liquids FC-48 and FC-78," 3M Technical Report, Project 9970010100, Report 002, Dept. 0535, 12/27/78.
58. R. G. Thomas, "Volatilization from Water," Chapter 15, pp. 15-1 - 15-34, Handbook of Chemical Property Estimation Methods - Environmental Behavior of Organic Compounds, W. J. Lyman, W. F. Reehl, and D. H. Rosenblatt, Eds., McGraw-Hill, Inc., 1982.
59. E. A. Reiner, and W. A. Scheil, "Solubility Measurements on FC-95," 3M Technical Report, 2/6/81.
60. Anonymous, XERTEX, Dohrmann Division, Application Project Report No. 1653, June 29, 1982. Dohrmann found that, after filtration through a Whatman GF/F glass fiber filter, a 0.25% FC-95 mixture in water had a TOC of 195 ppm C. This TOC concentration is equivalent to a FC-95 concentration of 1090 mg/l.
61. M. T. Elnabarawy, Measurements on the Solubility of FC-143 Lot 37, 3M Technical Notebook 50012, page 28, 11/17/81.
62. L. D. Winter, CS-2070/CS-2151 (FC-90) Solubility, Commercial Chemicals Analytical Report #242, August 3, 1981.
63. L. D. Winter, CS-2070/CS-2151 (FC-90) Partition Coefficient, Commercial Chemicals Analytical Report #245, August 3, 1981.
64. Commercial Chemicals Division Technical Information Brochure Y-ISTDI (75-2) NPI, FLUORAD® Brand Fluorochemical Surfactants FC-95 and FC-98.

65. J. D. Lazerte, Memo Subject: Change in Formulation-Fluorochemical Code Number, June 29, 1979. Memo indicates that FC-99 had been sold as a 50% Solids Solution.
66. Commercial Chemicals Division Technical Information Brochure Y-ISTDJ (75-2) NPI, FLUORAD® Brand Fluorochemical Surfactants FC-128, FC-134, and FC-170.
67. Commercial Chemicals Division Technical Information Brochure Y-ITD170C (41.1) R1, "FLUORAD®" Fluorochemical Surfactant FC-170C, 1981.
68. Commercial Chemicals Division Technical Information Brochure Y-ITD171 (41.1) R1, "FLUORAD®" Fluorochemical Surfactant FC-171, 1981.
69. L. D. Winter, CS-270/CS 2151 (FC-90) Thermal Analysis, Commercial Chemicals Analytical Report #244, July 29, 1981.
70. S. K. Welsh, "Adsorption of FC-95 and FC-143 on Soil," 3M Technical Report, 2/27/78.
71. U. S. EPA, Draft Proposed Environmental Test Standard for TSCA Test Rules, Soil TLC Standard for Test Data Development, Proposed Rule Section 4 TSCA, Part 772, Subpart L, Section 122-5, Federal Register Vol. 44, No. 53. pp. 16257-16264, March 16, 1979.
72. A. Mendel, "Analytical Methodology and Support for Fate of Fluorochemicals Project," 3M Technical Report, 1/17/79 (Dept. 0535). Also see 3M Technical Notebook No. 48277 page 30.
73. W. H. Fuller, Movement of Selected Chemicals in Soil - Applications to Waste Disposal Problems, 1977, EPA-600/2-77-020.
74. E. A. Reiner, "Biosorption of CS-2070 (FC-90)," 3M Technical Report, Project 9970012600, Report No. 61, Dept. 0535, 8/25/81.
75. R. D. Johnson, Personal Communications, 3/22/83.
76. W. Klopffer, G. Rippen, and R. Frische, "Physicochemical Properties as Useful Tools for Predicting the Environmental Fate of Organic Chemicals," Ecotoxicology and Environmental Safety, Vol. 6(3), 294-301, 1982.
77. M. T. Pike, Phone report with Mr. J. Kolcun of ICI, November 11, 1981.

78. E. A. Reiner, "Biodegradation Studies of Fluorocarbons III," 3M Technical Report, Project 9970612613, No. 5, Dept. 0535, 7/19/78.
79. E. A. Reiner, "Biodegradation Studies of Fluorochemicals," 3M Technical Report, Project 75-6398-29, Dept. 0222, 8/12/76.
80. J. W. Todd, "FC-95/Photolysis Study using Simulated Sunlight," 3M Technical Report, Project 9976750202, No. 001, Dept. 3068, 1/9/79.
81. J. W. Todd, "FC-143 Photolysis Study using Simulated Sunlight," 3M Technical Report, Project 9976750202, No. 002, Dept. 3068, 2/2/79.
82. J. Dean, "The Effects of Continuous Aqueous Exposure to 14C-78.02 (FC-95) on Hatchability of Eggs and Growth and Survival of Fry of Fathead Minnow (Pimephales promelas)," Report #BW-78-8-263, EG&G, Bionomics, Wareham, MA, August 1978.
83. B. F. Wilson, "The Effects of Continuous Aqueous Exposure to 78.03 (FC-143) on Hatchability of Eggs and Growth and Survival of Fry of Fathead Minnow (Pimephales promelas)," Report #BW-78-6-175, EG&G Bionomics, Wareham, MA, June, 1978.
84. M. T. Elnabarawy, "Multi-phase Exposure/Recovery Algae Assay Test Methods, FC-95, Lot 583," 3M Technical Report, Project No. 9970030000, No. 007, Dept. No. 0535, 12/16/81.
85. M. T. Elnabarawy, "Multi-phase Exposure/Recovery Algae Assay Test Method, FC-143, Lot 37," 3M Technical Report, Project No. 9970030000, No. 006, Dept. No. 0535, 11/16/81.
86. C. M. Thompson, "Acute Toxicity of 3M Sample No. 2 (FC-99) to Bluegill Sunfish (Lepomis macrochirus)," Static Acute Bioassay Report #23893, ABC Analytical Biochemistry Laboratories, Columbia, MO, June 18, 1979.
87. A. N. Welter, "Multigeneration Daphnid Life Cycle Test," 3M Technical Report, Project No. 9970030000, Report #5, Dept. 0535, 7/17/81.
88. Anonymous, "Partition Coefficient (n-otanol/water)" (Flask-shaking Method), OECD Guidelines for Testing Chemicals, No. 107, p. 1-9, 1981.

89. U.S. EPA, Draft Proposed Environmental Test Standard for TSCA Test Rules, Octanol/Water Partition Coefficient, Proposed Rule Section 4 TSCA, Part 772, Subpart L, Section 722-122-4, FR Vol. 44, No. 53, pp. 16254-16256, March 16, 1979.
90. U.S. EPA, Draft Proposed Environmental Test Standard for TSCA Test Rules, Vapor Pressure, Proposed Rule Section 4 TSCA, Part 772, Subpart L, Section 772-122-3, Federal Register, Vol. 44, No. 53, pp. 16256-16257, March 16, 1979.
91. Anonymous, "Vapor Pressure Curve", OECD Guidelines for Testing Chemicals No. 104, p. 1-20, 1981.
92. Anonymous, U.S. EPA Notice of Proposed Environmental Test Standards for TSCA Test Rules, Biodegradation, Federal Register 44, No. 53, 16272, 1979.
93. Anonymous, Fish Bioconcentration Test, Environmental Effects Test Guidelines, EPA 560/6-82-002, 1982.
94. ASTM-Standard Practice E729-80. Standard Practice for Conducting Acute Toxicity Tests with Fishes, Macroinvertebrates, and Amphibians. American Society for Testing and Materials, Philadelphia, PA 1980.
95. W. E. Miller, J. C. Greene, and T. Shiroyama. "The Selenastrum capricornutum Printz Algal Assay Bottle Test: Experimental design, application, and data interpretation." U.S. Environmental Protection Agency, Corvallis, Oregon. EPA-600/9-78-018. 125 p., July, 1978.
96. R. L. Bohon, "Environmental Aspects of Scotchban® Brand Paper Protector FC-807," 5/12/77. This paper was approved for an outside presentation by Mr. P. Salomon (Hilden) 1977.
97. E. A. Reiner, "Biodegradation of FC-807 Treated Cardboard," 3M Technical Report, Project 9970012600, Dept. 0535, 4/22/80.
98. Anonymous, OECD Guidelines for Testing of Chemicals, Sections I, Physical Chemical Properties, Water Solubility Method 105, 1981.
99. P. J. McCall, and D. A. Laskowski, Standard Practice for the determination of sorption constants of organic chemicals in soil and sediments. Draft #9, Oct. 7, 1981, under consideration by ASTM.
100. Anonymous, OECD Guidelines for Testing of Chemicals, No. 106, Adsorption/Desorption pp. 1-23, 1981.

101. D. Mackay and P. J. Leinonen, "Rate of Evaporation of Low-Solubility Contaminants From Water Bodies to Atmosphere," Environ. Sci. Technol. 9:1178, 1975.
102. A. Mendel, "Analytical Methodology on FM-3422," 3M Technical Report, 11/15/77.
103. M. T. Elnabarawy, 3M Technical Notebook No. 42669, p. 33, 12/28/77.
104. E. A. Reiner and A. N. Welter, "Solubility of FM-3925," 3M Technical Report, 1/8/79.
105. G. D. Veith and V. M. Comstock, "Apparatus for Continuously Saturating Water with Hydrophobic Organic Chemicals," J. Fish, Res. Board Can. Vol. 32(10), pp. 1845-1851, 1975.
106. A. Mendel, "Analytical Methodology and Support," 3M Technical Report, 1/17/79.
107. E. A. Reiner, "Distribution Coefficient of FM-3925, in n-Octanol/Water," 3M Technical Report, Project No. 9970012600, Report No. 015, Dept. 0535, 1/10/79.
108. S. K. Welsh and C. H. Schrandt, "Adsorption of FM-3925 on Soil," 3M Technical Report, 3/22/79.
109. S. K. Welsh, "Adsorption of FM-3422 on Soil," 3M Technical Report, 9/1/78.
110. J. March, 1968, Advanced Organic Chemistry, McGraw-Hill Book Company, New York, p. 313-316.
111. J. W. Todd, "FM-3422 Photolysis Using Simulated Sunlight," 3M Technical Report, 8/11/81 (Dept. 3068).
112. Arthur Mendel and Connie H. Schrandt, "Photodegradation Study on FM-3925," 3M Technical Report, 8/6/80 (Dept. 0535).
113. J. E. Gagnon, C. H. Schrandt, "Photolysis of FM-3925 in Aqueous Solutions," 3M Technical Report, 11/7/80 (Dept. 0535).
114. J. E. Gagnon and Arthur Mendel, "Photolysis of FM-3422 on Soil," 3M Technical Report, 12/10/81.
115. E. A. Reiner, "Biodegradation Studies of Fluorocarbons II," 3M Technical Report, 1/9/78, (Dept. 0222).
116. J. Belisle, Study Numbers: IRDC 137-086 and IRDC 137-088.

117. W. B. Neely et al., "Partition Coefficient to Measure Bioconcentration Potential of Organic Chemicals in Fish," Environmental Science and Technology Vol. 8, p. 1113, 1974.
118. A. N. Welter, "Aquatic Toxicity Studies: FM-2935," 3M Technical Report, Project 9970012600 Report No. 018, Dept. No. 0535, 1/8/79 (See also Lab Request 4197).
119. J. W. Dean, "The Effects of Continuous Aqueous Exposure to 78.01 (FM-3422) on Hatchability of Eggs and Growth and Survival of Fry of Fathead Minnow (Pimephales promelas)," EG&G, Bionomics Report #BW-78-6-175, June, 1978.
120. M. T. Elnabaraway, "Multi-phase Algae Assay Test Method. FM-3422," 3M Technical Report, Project 9970030000, Report No. 008, Dept. 0535, 12/30/81.
121. J. L. Osmon and C. C. Andrews, "The Biodegradation of TNT in Enhanced Soil and Compost Systems," Science Div., Weapons Quality Engineering Center, Naval Weapons Support Center, Crane, Indiana, Report No. ARLCD-TR-77032, 1978 NTIS No. AD-A054375.
122. CRL, First Trimester Report, 1978.
123. J. D. Johnson, "First Trimester Report, 1981," Riker Laboratories, Inc., April 29, 1981.
124. E. A. Reiner, Sampling Vegetation for Fluorochemical Uptake, Memo to F. J. Blackwell, March 17, 1981.
125. US EPA, Plant Uptake and Translocation Test Standard. Draft Proposed Section 4 Test Guidelines, Sections #48 and #49, January 15, 1981.
126. D. P. Landucci, Personal Communication, May 5, 1981.
127. J. Suzuki et al., "Effect of Ozone Treatment upon Biodegradation of Water-Soluble Polymers." Environmental Science and Technology 12(10), p. 1180-1183, 1978.
128. D. L. Kaplan et al., "Biodegradation of Polystyrene, Poly (methyl metacrylate) and Phenol Formaldehyde," Applied and Environmental Microbiology, 38(3), pp. 55-535, 1979.
129. A. N. Welter, "Aquatic Toxicity Studies: FC-214-30," 3M Technical Report, Project 9970012600, Report Number 007, Dept. 0535, 2/16/79.

130. A. N. Welter, "Aquatic Toxicity Studies: ~~cc 8110-92~~ Lot 610," 3M Technical Report, Project 9970012600, Report No. 008, Dept. 0535, 1/17/79. FC-232
131. A. N. Welter, "~~cc 805-15~~ Aquatic Testing Results," 3M Technical Report, Project 9970012600, Report No. 018, Dept. 0535, 6/29/79. FC-245
132. M. T. Elnabarawy, "Aquatic Toxicity Testing: FC-254 (F-6461-1) L.R. 57495," 3M Technical Report, Project 9970012600, Report No. 038 Dept. 0535, 6/30/80.
133. Env. Lab. Aquatic Toxicity Work Sheet FC-218 Completed 9/10/77.
134. C. M. Tompson, A. D. Forbis, "Acute Toxicity of 3M Sample No. 5 (FC-740) to Bluegill Sunfish (Lepomis macrochirus), Static Acute Bioassay Report #23896, ABC Analytical Bio Chemistry Laboratories, Inc., Columbia, MO, June 19, 1979.
135. Anonymous, OECD Guidelines for Testing Chemicals, No. 111, Hydrolysis as a Function of pH, pp. 1-24, 1981.
136. G. D. Veith and R. T. Morris, A Rapid Method of Estimating Log P for Organic Chemicals, EPA-6003-78-049, May, 1978.
137. E. A. Reiner and A. N. Welter, "Bioassay on Leachate of FC-2174," 3M Technical Report, Project #9970012600, Report No. 47, 11/17/80.
138. E. A. Reiner, "Bioassays on Cured and Uncured Fluoroelastomer Leachate," 3M Technical Report, Project #9970012600 Report No. 62, 11/17/81.

APPENDIX I

AQUATIC TOXICITY RANKING SYSTEM

NIOSH adopted the following toxicity scale to aid in interpreting aquatic toxicity data listed in the Registry of Toxic Effects of Chemical Substances:

<u>Description</u>	<u>LC₅₀ Concentration</u>
Insignificant hazard	>1,000 mg/l
Practically nontoxic	100-1,000 mg/l
Slightly toxic	10-100 mg/l
Moderately toxic	1-10 mg/l
Highly toxic	<1 mg/l

This scale, which was developed based on published data from studies on adult and juvenile aquatic organisms, provides a basis on which acute aquatic toxicity data can be put in some perspective. In using this scale, one should be aware that many other factors, in addition to acute aquatic toxicity, contribute to determining the impact of a chemical on an aquatic environment. Important among these other factors are solubility, volatility, environmental entry concentration, bioconcentration potential, persistence, and the size and mixing rate of the receiving aquatic environment.

Reference:

Registry of Toxic Effects of Chemical Substances, '75 Edition, Christensen, H. E., and E. J. Fairchild, Eds., p. XV and CI, U.S. Department of Health, Education and Welfare; National Institute for Occupational Safety and Health, Washington, DC (June, 1976).

APPENDIX II

This Appendix is a cross-reference between report code numbers, product identification FC numbers, and product chemical composition. The alphanumeric codes used in the report are primarily those assigned by Commercial Chemicals Division to keep track of work requests to the Environmental Laboratory. These numbers begin with "cc". Although many products have more than one cc number because more than one request for work on the product has been made to the Environmental Lab, only one cc number was selected. Thus each product has only one cc number in this report. In those cases where a cc number could not be found, Envir. Assess. Inq. (EAI) numbers or Lab Request (LR) numbers were used.

KEY TO CHEMICAL CODES USED IN REPORT

<u>CODE</u>	<u>PRODUCT NUMBER</u>	<u>CODE</u>	<u>PRODUCT NUMBER</u>	<u>CODE</u>	<u>PRODUCT NUMBER</u>
cc 742-7	FC-77	cc 798-21	FC-393	EAI 80021	FC-95
cc 7512-25	FC-376M	cc 802-23	FC-98	LR 2256-3	FC-808
cc 766-29	FC-452-30	cc 803-3	FC-383	LR 2318-2	FC-120
cc 773-53	FC-135	cc 803-15	FC-324-40	LR 2337-1	FC-170
cc 775-27	FC-326	cc 805-1	FC-24	LR 2456-1	FC-93
cc 777-3	FC-171	cc 805-10	FC-100	LR 2465-1	FC-48
cc 777-4A & B	FC-760	cc 805-10S	FC-6422	LR 2455-3	FC-75
cc 777-4B	F-6580	cc 805-15	FC-243	LR 2485-2	FC-214,
cc 7711-18	FC-170C	cc 805-24	FC-254		FC-214A
cc 7711-27	FC-134	cc 806-6	FC-252		
cc 782-5	FC-388	cc 809-21	FC-84	LR 2543-4	FC-824
cc 782-14	FC-835	cc 8010-11A	FC-2174	LR 2563-3	FC-208
cc 782-43	FC-836	cc 8010-11B	FC-2175	LR 2929	FC-128
cc 783-1	PPA-790	cc 8010-32	FC-270	LR 2929-1	F-6873
cc 783-38	FC-244	cc 8011-10	FC-129	LR 3844-1	FC-43
cc 786-6	FC-124	cc 8011-23	FC-90	LR 3844-4	FM-3422
cc 788-19	FC-78	cc 8011-24A	FC-220	LR 4197-2	FM-3925
cc 7811-1	FC-461	cc 8012-41	FC-3029	LR 4894	L-4380
cc 791-17	FC-520	cc 811-17	FC-353	LR 4913	FC-82
cc 792-8	FC-508	cc 811-18	FC-352-20	LR 5062	FM-3555
cc 794-2	FC-740	cc 812-35	FC-247	LR 5120	FC-40
cc 794-6	FC-509	cc 813-26	FC-189	LR 5625	FC-143
cc 795-7	FC-99	cc 815-1	FC-214-30	LR 6589	FC-71,
cc 795-19	FC-391	cc 815-11	FC-10		L-4308
cc 795-23	FC-807	cc 816-27	FC-127	LR 7842	FC-72
cc 796-3	FM-3974	cc 8110-9	FC-23	LR 7981	FC-70
cc 796-10	PPA-791	cc 8111-4	FC-300		
		cc 824-32	FC-218		

KEY TO CHEMICAL PRODUCTS DISCUSSED IN REPORT

This table includes those products which are discussed within the report.

<u>Product Number</u>	<u>Class</u>	<u>Chemical Name (3M Synonym)</u>	<u>Chemical Formulation</u>
FC-10 (cc 815-11)	Alcohol	(Wide range N-EtFOSE alcohol)	See FM-3422
FC-23 (cc 8110-9)	Low MW Acid	Perfluorobutyric acid	C_3F_7COOH
FC-24 (cc 805-1)	Low MW Acid	Trifluoromethane sulfonic acid (Triflate)	CF_3SO_3H
FC-40 (LR 5120)			
FC-43 (LR 3844-1)			
FC-48 (LR 2465-1)			
L-4380 (LR 4894)			
FC-70 (LR 7981)			
FC-71 (LR 6589)			
FC-72 (LR 7842)			
FC-75 (LR 2455-3)			
FC-77 (cc 742-7)	Inert liquid	Perfluorinated alkanes and cyclic ethers boiling range 90-107°C	e.g., $(C_4F_9)_2O$, C_4F_7O , C_8F_{18}
FC-78 (cc 788-19)	Inert liquid	N-perfluoromethyl perfluoromorpholine	$C_5F_{11}NO$
FC-82 (LR 4913)			
FC-84 (cc 809-21)			
FC-90 (cc 8011-23)	Surfactant	Perfluoroethyl cyclohexyl sulfonic acid, diethanolamine salt	$C_2F_5 F SO_3^{--}H_2N^+(C_2H_4OH)_2$

<u>Product Number</u>	<u>Class</u>	<u>Chemical Name (3M Synonym)</u>	<u>Chemical Formulation</u>
FC-93 (LR 2456-1)			
FC-95 (EAI 80021)	Surfactant	Perfluorooctanesulfonic acid, potassium salt	$C_8F_{17}SO_3K$
FC-98 (cc 802-23)	Surfactant	Perfluoroethyl cyclohexyl sulfonic acid, potassium salt	$C_2F_5 \quad F \quad SO_3^-K^+$
FC-99 (cc 795-7)	Surfactant	Perfluorooctanesulfonic acid, diethanolamine salt	$C_8F_{17}SO_3^-H_2N^+(CH_2CH_2OH)_2$
FC-100 (cc 805-10)	Surfactant	Product containing 25% FC Hydroxy Foamer, 25% solvent and 50% H ₂ O	$ \begin{array}{c} C_2H_4OH \\ \\ C_6F_{13}SO_2N-C_3H_6N^+(CH_3)_2 \\ \\ CH_2CHCH_2SO_3^- \\ \\ OH \end{array} $
FC-120 (LR 2318-2)			
FC-128 (LR 2929) FC-127 (cc 816-27) FC-129 (cc 8011-10) F-6873	Surfactant	N-ethyl-n-[(perfluorooctyl) sulfonyl] glycine, potassium salt	$C_8F_{17}SO_2N(C_2H_5)CH_2COOK$
FC-134 (cc 7711-27) FC-135 (cc 773-53)	Surfactant	3(((perfluorooctyl) sulfonyl) amino)-N,N,N-trimethyl-1-propanaminium iodide	$ \begin{array}{c} H \\ \\ C_8F_{17}SO_2NC_3H_6N^+(CH_3)_3I^- \end{array} $
FC-143 (LR 5625)	Surfactant	Perfluorooctanoic acid ammonium salt	$C_7F_{15}COO^-NH_4^+$
FC-170 (LR 2337-1)			
FC-170C (cc 7711-18)	Surfactant	(N-EtFOSE alcohol-ethylene oxide adduct)	$C_8F_{17}SO_2N(C_2H_5)(CH_2CH_2O)_{14}OH$
FC-124 (cc 786-6)			
FC-171 (cc 777-3)	Surfactant	See FC-760	
FC-189 (cc 813-26)	Acrylate	2-Propenoic acid-4-(((heptadecafluorooctyl) sulfonyl)methylamino)-butyl ester (N-butyl FOSE acrylate)	$ \begin{array}{c} C_8F_{17}SO_2N(C_3H_7)C_2H_4O \\ C(O)CHCH_2 \end{array} $

<u>Product Number</u>	<u>Class</u>	<u>Chemical Name (3M Synonym)</u>	<u>Chemical Formulation</u>
FC-208 (LR 2563-3)			
FC-214 (LR 2485-2)			
FC-214A (LR 2485-2)	Acrylate	A polymer of 95% MeFOSEA = $C_8F_{17}SO_2N(CH_3)CH_2CH_2OC(O)CHCH_2$ and 5% butyl acrylate = $CH_3(CH_2)_3OC(O)CHCH_2$ Emulsifier is 5% Ethoquad 18/25 based on solids	
FC-214-30 (CC 815-1)			
FC-218 (cc 824-32)			
FC-220 (cc 8011-24A)	Acrylate	30% 50/50 copolymer of N-MeFOSEA/Carbowax 4000 55% water 8% solvent 7% Carbowax 4000	
FC-232 (cc 8110-9L)			
FC-244 (cc 783-38)	Acrylate	17% 70/15/5/10 MeFOSEA/ Alfol-1620A/IOA/CW 750A 11% other acrylate polymer 52% water 20% solvent	
FC-247 (cc 812-35)			
FC-252 (cc 806-6)			
FC-254 (cc 805-24)			
FC-270 (cc 8010-32)			
FC-300 (cc 8111-4)			
FC-324-40 (cc 803-15)			
FC-326 (cc 775-27)			
FC-351-25 (cc 811-17)			

<u>Product Number</u>	<u>Class</u>	<u>Chemical Name (3M Synonym)</u>	<u>Chemical Formulation</u>
FC-352-20 (cc 811-18)	Urethane	20%: 98% EtFOSE/MDI 2% MCL emulsifier 80%: water Trace: ethyl acetate	
FC-353 (cc 813-17)			
FC-376M (cc 7512-25)	Urethane	20% 2-EtFOSE/TDI 12.5% alumina Dispai .75 sulfamic acid 66.75 solvents and water	
FC-383 (cc 803-3)			
FC-388 (cc 782-5)			
FC-391 (cc 795-19)			
FC-393 (cc 798-21)			
FC-452-30 (cc 766-29)			
FC-461 (cc 7811-1)			
FC-508 (cc 792-8)	Catalyst	50% $\text{O}_3\text{S}^+\text{PF}_6^-$ 50% dimethoxyethyl phthalate	
FC-509 (cc 794-6)	Catalyst	45% $\text{O}_3\text{I}^+\text{PF}_6^-$ 45% dimethylphthalate 10% ERL-4221 epoxy resin	
FC-520 (cc 791-17)			
FC-740 (cc 794-2)			
FC-760 (cc 777-4A & B)	Surfactant	>90% <10%	$\text{C}_8\text{F}_{17}\text{SO}_2\text{NH}(\text{Et})$ $(\text{CH}_2\text{CH}_2\text{O})_{7.2}\text{CH}_3$ $\text{C}_8\text{F}_{17}\text{SO}_2\text{NH}(\text{Et})$
PPA-790 (cc 783-1)	Alcohol	(90 - 100% N-MeFOSE alcohol + 0 - 10% N-EtFOSE Alcohol)	See FM-3925 See FM-3422

<u>Product Number</u>	<u>Class</u>	<u>Chemical Name (3M Synonym)</u>	<u>Chemical Formulation</u>
PPA-791 (cc 796-10)	Alcohol	(MeFOSE alcohol)	See FM-3925
FC-807 (cc 795-23)	Phosphate	33% solids: N,N'-(phosphinicobis (oxy-2,1-ethanediyl)) bis(N-ethyl perfluoro-1-octane sulfonamide) (ammonium salt of diphosphate ester of N ethyl FOSE alcohol) Note some mono and tri-esters are also present +49% water, 18% alcohol.	$[C_8F_{17}SO_2N(C_2H_5)CH_2CH_2O]_2PO(OH_4)$
FC-808 (LR 2256-6)			
FC-824 (LR 2543-4)			
FC-835 (cc 782-14)			
FC-836 (cc 782-43)			
FC-2174 (cc 8010-11A)	FLUOREL® Polymer	96% fluoroelastomer: 1% dichlorodiphenyl sulfone 2% bisphenol AF 0.5% triphenyl benzyl phosphonium chloride 0.45% tetramethylene sulfone 0.05% sodium methylate	78 mole % CH_2CF_2 and 22 mole % C_3F_6
FC-2175 (cc 8010-11B)	FLUOREL® Polymer	100% fluoroelastomer	76/24 CF_2CH_2/CF_3CFCF_2
FC-3029 (cc 8012-41)			
FM-3422 (LR 3844-4)	Alcohol	N-ethyl-N(2-hydroxy ethyl)-1-perfluoro-octanesulfonamide (N-ethyl FOSE alcohol)	$C_8F_{17}SO_2N(C_2H_5)C_2H_4OH$

<u>Product Number</u>	<u>Class</u>	<u>Chemical Name (3M Synonym)</u>	<u>Chemical Formulation</u>
FM-3555 (LR 5062)	Surfactant	3-(((heptadecafluoro-octyl) sulfonyl) amino)-N,N,N-trimethyl-1-propanamium chloride (MCL emulsifier)	$C_8F_{17}SO_2NHC_3H_6N^+(CH_3)_3Cl^-$
FM-3925 (LR 4197-2)	Alcohol	N-ethyl-N(hydroxymethyl)-1-perfluorooctane sulfonamide (N-methyl FOSE alcohol)	$C_8F_{17}SO_2N(CH_3)C_2H_4OH$
FM-3974 (cc 796-3)			
F-6422 (cc 805-10S)	Surfactant	100% FC Hydroxy Foamer solids	See FC-100
F-6580 (cc 777-4B)	--	N-ethyl-1-perfluorooctane sulfonamid (FOSE amide)	$C_8F_{17}SO_2N^H-C_2H_5$
F-6873 (LR 2929-1)			See FC-128

This article from the BNA Chemical Regulation Reporter shows the importance that Structure-Activity relationships will take in future U.S. EPA Chemical Assessment.

CURRENT REPORT

993

*Research***EVALUATION OF BIOLOGICAL PESTICIDES,
STRUCTURE-ACTIVITY RELATIONSHIPS PLANNED**

New research on "key" environmental issues, including the role of structure-analysis in evaluating chemical hazards and the effects of biological pesticides on non-target organisms, is planned during 1983, according to a draft of the Environmental Protection Agency's 1983 research outlook.

Discussed Nov. 29 at a Science Advisory Board meeting, the draft said structure-activity relationships (SAR) currently used to assess chemicals are based upon limited data and often are speculative. "Often the SAR information is essentially the product of prevailing but unverified toxicological opinion," the report said. EPA currently uses structure-activity assessments in its evaluation of chemicals submitted for premanufacture review.

Now research by the agency's Office of Research and Development would seek to "make decisions based on SAR more independent than they are now and of greater use in assuring that toxic chemicals and pesticides are adequately regulated," the report said.

The outlook paper's sections on toxics and pesticides said research also is planned on:

- ▶ Key methods of meeting the agency's monitoring, data collection, and data analysis requirements under the Toxic Substances Control Act;
- ▶ The most important environmental parameters that should be used in the physical and biological mathematical models that the agency uses to predict exposure, hazard effects, and risks;
- ▶ The primary environmental endpoint responses for toxic substances and pesticides;
- ▶ New tests needed to assess chemical hazards and evaluate risk;
- ▶ Use of field information to verify models used to predict pesticide exposure;
- ▶ Improvements needed on mathematical models of pesticide transport, fate, and exposure; and
- ▶ Registration criteria and environmental measurements needed to register biological pesticides.

Structure-Activity Relationships

The agency plans research into development of reliable structure-activity analyses because the SAR is "an attractive and potentially useful method which, if valid, can produce rapid, timely, inexpensive, scientifically acceptable data for evaluating the biological effects of chemicals and pesticides and for better assessing the risks," the draft report said.

Specifically, the agency would develop a data base of existing information and correlations and would seek data on the causal relationship between molecular structure and chemical, physical, and biological behavior.

By 1985, the agency hopes to produce models for evaluating environmental fate and toxicity of several chemical classes in a variety of media. By 1986, a working system is expected to be completed using molecular structure descriptions and combinations to predict genetic and carcinogenic activity in humans, according to the draft.

Biological Control Agents

Environmental research to evaluate the effects of biological control agents on non-target organisms also will begin in 1983, the agency said. Initially, EPA plans to develop hazard evaluation protocols to determine effects from microbial agents and for some biochemicals in estuarine, freshwater, and terrestrial ecosystems.

The organisms, both biochemical and microbial pest control agents, are registered for use under the Federal Insecticide, Fungicide, and Rodenticide Act. "These microorganisms are known to attack targeted pests, but their transport, persistence, and fate in the environment and their effects on non-target species are not clearly understood," the report said.

Specific research planned by the agency includes:

- ▶ Determining the scope of the biological control agents' effects in terrestrial environment, 1983;
- ▶ Testing protocols for estimating hazards to non-target terrestrial species, 1984;
- ▶ Testing with non-target freshwater organisms under field conditions, 1985; and
- ▶ Studying exposure of aquatic animals to insect viruses, 1984.

Research Milestones

EPA also set a variety of research milestones for the next five years. These include the development of methodologies for several short-term tests, such as identifying the effects of toxicants upon the nervous system. A short-term methodology for identifying the teratogenic potential of chemicals

994

also will be sought in an effort "to support or eliminate the need for extensive animal tests," the draft said.

The agency also aims to develop methods "capable of evaluating the responses of entire systems, systemic disease processes, and specific target organisms to acute, sub-chronic, and chronic toxicant insult," according to the report.

TABLES AND FIGURES

	<u>Page</u>
TABLE 1 - DATA ON FLUOROchemicals INCLUDED IN FATE OF FLUOROchemicals STUDY PART I	5
FIGURE 11- IMPORTANT PATHWAYS OF AN ORGANIC CHEMICAL IN THE ENVIRONMENT	12
TABLE 2 - AQUEOUS SOLUBILITIES AND OCTANOL/WATER PARTITION COEFFICIENTS OF ORGANIC COMPOUNDS	16
TABLE 3 - FLUORIDE MEASUREMENTS AT THE DECATUR PLANT	21
TABLE 4 - SUMMARY OF ENVIRONMENTAL EFFECTS OF FLUORINERT LIQUIDS	32
TABLE 5 - TOXICITY OF NaOH NEUTRALIZED FLUOROchemical ACIDS AND OTHER SALTS OF THESE ACIDS	35
TABLE 6 - SOLUBILITY AND OCTANOL/WATER PARTITION COEFFICIENTS OF FLUOROchemical SURFACTANT PRODUCTS	37
TABLE 7 - BIODEGRADATION DATA ON NONSOLVENT-CONTAINING FLUOROchemical SURFACTANTS	41
TABLE 8 - AQUATIC BIOASSAY DATA ON ^{FC 143} LR 5625 AND ^{FC-55} EAT 80021	44
TABLE 9 - FISH 96-HR. LC ₅₀ DATA FOR FLUOROchemical SURFACTANTS	45
TABLE 10 - OTHER ENVIRONMENTAL EFFECTS DATA ON FLUOROchemical SURFACTANTS	47
TABLE 11 - BIOASSAY DATA ON ^{FM 3422} LR 3844-4 AND ^{FM-3923} LR 4197-2	63
TABLE 12 - TOXICITY OF ACRYLATE PRODUCTS TO AQUATIC ORGANISMS	72
TABLE 13 - AQUATIC TOXICITY DATA ON URETHANE CONTAINING PRODUCTS	79
TABLE 14 - SUMMARY OF RECOMMENDED STUDIES ON FLUOROchemical	84
TABLE 15 - SCHEDULE OF PROPOSED WORK	88

APPENDIX III
CAPS

Needs for ^{14}C -Radiolabeled Fluorochemicals

<u>Report Section</u>	<u>Test</u>	<u>Priority</u>	<u>Placement of ^{14}C Label</u>	<u>Importance of Having Label^(a)</u>
IV.C.2.a.	Distribution coef. of FC-95 and FC-143	I	anywhere	Low
IV.C.2.a.	Soil TLC of FC-95 and FC-143	II	anywhere	Necessary
IV.C.2.a.	Bioadsorption of FC-95 and FC-143	III	anywhere	high
IV.C.2.b.	Acclimated seed BOD of FC-171	II	on perfluorinated portion	Moderate
IV.C.2.b.	respirometry Soil biometry on Hydroxy Foamer, F-6422	II	on Hydrocarbon portion	High
IV.C.2.b.	Aerobic soil biodegradation tests on FC-143, FC-95	II	anywhere	High
IV.C.2.b.	Anaerobic soil biodegradation tests on FC-143	III	anywhere	High
IV.C.2.b.	Photodegradation of FC-143, FC-95, F-6422	III	on perfluorinated portion	Moderate
IV.C.2.c.	Bioconcentration of FC-95 and FC-143	I	anywhere	High
IV.D.2.a.	Water solubility of FC-807	I	anywhere	Low
IV.D.2.a.	Octanol/water partition coefficient of FC-807	I	anywhere	Low
IV.D.2.a.	Soil adsorption of FC-807	III	anywhere	Moderate
IV.D.2.a.	Soil TLC of FC-807	III	anywhere	Necessary
IV.D.2.b.	Aerobic soil biodegradation of FC-807	III	on perfluorinated portion	High
IV.E.2.a.	Water Solubility of FM-3422 and FM-3925	III	anywhere	Low
IV.E.2.a.	Octanol/water partition coef. of FM-3422	I	anywhere	Low
IV.E.2.a.	Soil TLC of FM-3422	III	anywhere	Necessary
IV.E.2.a.	Soil TLC of FM-3925	II	anywhere	Necessary
IV.E.2.b.	Alkaline hydrolysis of FM-3422 and FM-3925	III	on perfluorinated portion	Moderate

IV.E.2.b.	Photolysis of FM-3422 on sand	III	on perfluorinated portion	Moderate
IV.E.2.b.	Soil biodegradation of FM-3422 and FM-3925	I for FM-3422 II for FM-3925	preferably on perfluorinated portion	High
IV.E.2.b.	Anaerobic soil biodegradation of FM-3422	II	on perfluorinated portion	High
IV.E.2.b.	Biotransformation in fish and plants of FM-3422	III-fish II-plants	on perfluorinated portion	Moderate
IV.E.2.c	Extraction of FM-3422 from fish tissue	I	anywhere	Moderate
IV.F.2.b.	Hydrolysis of FC-220 and FC-214A	FC-220-II FC-214AIII	preferably anywhere on MeFOSEA monomer	Moderate
IV.F.2.b.	Photolysis of FC-220 and FC-214A	III	preferably anywhere on MeFOSEA monomer	Moderate
IV.F.2.b.	Soil biodegradation of FC-220 and FC-214A	III	preferably anywhere on MeFOSEA monomer	High
IV.G.2.b.	Hydrolysis of EtFOSE/MDI (FC-352-20)	II	on EtFOSE monomer	Moderate
IV.G.2.b.	Rigorous soil biodegradation of EtFOSE/MDI	III	on EtFOSE monomer	High
IV.G.2.b.	Photolysis of EtFOSE/MDI	III	on EtFOSE Monomer	Moderate

Footnotes:

(a) Terms in this column are defined as followed:

Low = radiolabeled material is preferred but testing could readily be done without it;

Moderate = The use of radiolabeled material would greatly facilitate testing;

High = Testing would be difficult, possibly impossible, without radiolabeled materials;


Necessary = Testing could not be done without radiolabeled material.

Fat

Liver

(2)

100



2


100

Fat

Liver

2

(100)



2

0

(102)