

U.S. DEPARTMENT OF LABOR

Form No. OSHA-20
May, 1971

81104-246

1- S.D. File
1- R. McCutchan

MATERIAL SAFETY DATA SHEET

SECTION I				
MANUFACTURER'S NAME MONSANTO COMPANY		EMERGENCY TELEPHONE NO. (314) 694-1000		
ADDRESS (Number, Street, City, State, and ZIP Code) 800 North Lindbergh Boulevard, St. Louis, Missouri 63166				
CHEMICAL NAME AND SYNONYMS Mixture		TRADE NAME AND SYNONYMS Aroclor 1016, MCS 1016		
CHEMICAL FAMILY Chlorinated aromatic		FORMULA Mixture		
SECTION II HAZARDOUS INGREDIENTS				
PAINTS, PRESERVATIVES, & SOLVENTS	%	TLV (Units)	ALLOYS AND METALLIC COATINGS	% TLV (Units)
PIGMENTS			BASE METAL	
CATALYST			ALLOYS	
VEHICLE			METALLIC COATINGS	
SOLVENTS			FILLER METAL PLUS COATING OR CORE FLUX	
ADDITIVES			OTHERS	
OTHERS				
HAZARDOUS MIXTURES OF OTHER LIQUIDS, SOLIDS, OR GASES				% TLV (Units)
SECTION III PHYSICAL DATA				
BOILING POINT (P.F.) 760 mm	325°C	SPECIFIC GRAVITY (H ₂ O = 1) (25/15.5°C)		1.367
VAPOR PRESSURE (mm Hg.) (155-195°C)	3 mm	PERCENT VOLATILE BY VOLUME (%)		N.A.
VAPOR DENSITY (AIR = 1)	Not Avail	EVAPORATION RATE (BuAc = 1)		<1
SOLUBILITY IN WATER 20°C negligible	<0.01%			
APPEARANCE AND ODOR colorless oil		slight aromatic odor		
SECTION IV FIRE AND EXPLOSION HAZARD DATA				
FLASH POINT (Method used) C.O.C. 180°C		FLAMMABLE LIMITS	Lel	Uel
			N.A.	N.A.
EXTINGUISHING MEDIA Water, foam, CO₂ or dry chemical				
SPECIAL FIRE FIGHTING PROCEDURES Respiratory protection when fighting fires where exposure to vapors or gases is possible.				
UNUSUAL FIRE AND EXPLOSION HAZARDS Highly toxic gases (chlorides and chlorine) can be evolved in fires of this product.				

DSW 267536

STLCOPCB4062797

Aroclor MCS 1016 SECTION V HEALTH HAZARD DATA

THRESHOLD LIMIT VALUE
EFFECTS OF OVEREXPOSURE Skin irritation in the form of chloracne, systematic intoxication leads to nausea, vomiting, loss of weight, edema and abdominal pain.
EMERGENCY AND FIRST AID PROCEDURES

SECTION VI REACTIVITY DATA

STABILITY	UNSTABLE		CONDITIONS TO AVOID
	STABLE	X	
INCOMPATIBILITY (Materials to avoid)			
HAZARDOUS DECOMPOSITION PRODUCTS CO, CO ₂ , smoke, soot, chlorides and chlorine			
HAZARDOUS POLYMERIZATION	MAY OCCUR		CONDITIONS TO AVOID
	WILL NOT OCCUR	X	

SECTION VII SPILL OR LEAK PROCEDURES

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED Absorb on clay, sawdust or other absorbant material. Place in drums. Bury in approved chemical landfill in accordance with local and state regulations.
WASTE DISPOSAL METHOD Burn in an approved incinerator in accordance with local and state regulations.

SECTION VIII SPECIAL PROTECTION INFORMATION

RESPIRATORY PROTECTION (Specify type) Bureau of Mines approved respirator for organic vapors.		
VENTILATION	LOCAL EXHAUST Yes - for vapors	SPECIAL
	MECHANICAL (General)	OTHER
PROTECTIVE GLOVES rubber	EYE PROTECTION chemical goggles	
OTHER PROTECTIVE EQUIPMENT		

SECTION IX SPECIAL PRECAUTIONS

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING Avoid skin and eye contact. Avoid inhalation of vapors.
OTHER PRECAUTIONS

DSW 267537

While the information and recommendations set forth herein are believed to be accurate as of the date hereof, MONSANTO COMPANY MAKES NO WARRANTY WITH RESPECT THERETO AND DISCLAIMS ALL LIABILITY FROM RELIANCE THEREON.

JAG:HOH:JTG:WBP

1/25/72

STLCOPCB4062798