

Branches
ST. LOUIS
MEMPHIS
OMAHA
MINNEAPOLIS
SALT LAKE CITY
CHICAGO

L. J. Mueller Furnace Co.


ESTABLISHED 1857

2009 W. Oklahoma Ave., Milwaukee, Wis.

Branches
LOS ANGELES
KANSAS CITY
BALTIMORE
PHILADELPHIA
PITTSBURGH
WASHINGTON


SERIES 50 OIL-FIRED AIR CONDITIONING UNIT

Designed and constructed to meet the needs and purse of the moderate-sized home, this unit automatically heats, filters, humidifies and circulates the air within the home—efficiently and economically. The heating drum and radiator are made of heavy gauge steel, all electric welded, with no joints. Uniform distribution of the conditioned air is secured by the quiet, efficient Mueller fan. Filters furnished are of ample area, and with large dirt-holding capacity. Series 50 unit is available with a Mueller Vaporizing or Pressure Atomizing type oil burner. If desired, any standard burner may be used. Three sizes, from 100,000 to 225,000 Btu per hour.




MUELLER CLIMATOR FAN-FILTER UNITS

For positive distribution of air in old or new construction, wherever air is to be moved, there is a Mueller Climator Fan-filter unit available. These units are designed to provide better, cleaner, and healthier home heating. Fans are designed in accordance with latest aerodynamic principles, providing uniform air distribution from top to bottom of the fan outlet. Filter area is adequate to handle the air requirements. Fans have ample air delivery capacity for the addition of cooling, if desired. Smaller size fans are equipped with top-mounted motors. Motor mounting is designed and cushioned so as to absorb motor vibration, thereby eliminating possibility of transmission of sound to the duct work. These units are available in a range of sizes capable of handling practically any requirement.



SERIES "EPS" GAS-FIRED AIR CONDITIONING UNIT




Designed and styled for the modern home, this Mueller unit meets every requirement for an automatic Winter air conditioning unit. Provides balanced distribution of filtered, humidified warm air in ample volume to every room. Heating unit consists of Mueller steel Heatspreader sections, providing quick heat in desired volume. The fan operates quietly and efficiently, with ample capacity for any requirement. Filters thoroughly clean the air. Humidity is supplied automatically. Available in three sizes with AGA input ratings from 90,000 to 180,000 Btu per hour.

Mueller Heaters For All Fuels


A Complete Line for All Purposes




Return Flue all-cast Furnace. 18 in. to 30 in. fire-pots, single and double fire-door styles. Available in round, galvanized or square, lacquered casings.




Series P-400 Steel coal-fired fan-filter-furnace unit. Also available with round casing for gravity operation. Four sizes, 20 in. to 27 in. drums.



Series "200" Steel coal-fired furnace. Sizes, 20 in. to 34 in. drums. Available also with square lacquered casings for forced air installations.




Gas Era Cast Iron air conditioning furnace. AGA input rating, 65,000 Btu per hour, per section. Wide range of sizes and air delivery capacities.




Gas-fired air conditioning furnace. A.G.A. input ratings from 60,000 to 100,000 Btu per hour. Wide range of air deliveries.




Muelleraire unit. Gas-fired with fan, filters, and humidifier. 5 sizes—AGA input ratings, 72,000 to 180,000 Btu per hour.




Series "AE" Gas Boiler. AGA ratings, 180 to 1,260 sq ft steam; 290 to 2,015 sq ft hot water.



Gas Era Unit Heater. Sizes from six to twenty sections, with A.G.A. ratings from 216,000 to 720,000 Btu per hour.



Series "SA" stoker-fired furnace, with fan-filter unit. Any stoker may be used. Capacities, 110,000 and 175,000 Btu.



Horizontal Tubular Heaters, for schools, churches and other large buildings. Three sizes, with capacity range from 1,188,000 to 1,390,000 Btu per hour.

Complete catalogs on each of above units available upon request.