A guide to fire-resistant hydraulic fluids.



Monsanto

0019800

TOWOLDMON0020891
WATER_PCB-00005360

Contents

Page No.

SECTION I

Pydraul® "E" Series
Straight Phosphate Ester Hydraulic Fluids 1-12

SECTION II

Pydraul® "C" Series
Phosphate Ester Base Hydraulic Fluids 1-12

SECTION III

Santosafe® W/G Series
Water/Glycol Hydraulic Fluids 1-6

POCKET

Santosafe W/G Maintenance Guide
Pydraul Air Compressor Fact Finder

NOTICE: "Nothing contained herein is to be construed as a recommendation to use any product in conflict with any patent. MONSANTO MAKES NO WARRANTIES AS TO THE FITNESS FOR A PARTICULAR PURPOSE OR MERCHANTABILITY OF ANY PRODUCT REFERRED TO, no guarantee of satisfactory results from reliance upon contained information or recommendations, and disclaims all liability for any resulting loss or damage."

Bulletin number IC/FF-30

0019801

TOWOLDMON0020892
WATER_PCB-00005361

Pydraul "E" series

STRAIGHT PHOSPHATE ESTER HYDRAULIC FLUIDS

Development

Fire protection for industrial hydraulic operations began with Pydraul in 1951. Pydraul® fluids have since provided industry with millions of machine hours of safe operation.

New ways are continuously being explored to improve the excellent performance records of Pydraul fluids. From the first Pydraul fluid, (Pydraul F-9) the family has grown to ten specially tailored, fire-resistant* safety fluids. Each answers a major but specific hydraulic fluid need for industrial use. In addition to guarding against fire, each Pydraul fluid lubricates as well as premium grade oil. Pydraul fluids have answered the need of virtually every industrial operation, indoors and out—from the sub-zero, outdoor hydraulic lift operations for refineries and blast furnaces to the low-viscosity fluid demands of high-speed, precision machine tools.

The Pydraul Fluids in this Selector were reformulated in 1971 to remove all chlorinated components. Monsanto has developed a series of ALL PHOSPHATE ESTER fluids known as the Pydraul E Series which exhibit performance superior to presently available phosphate ester hydraulic fluids.

Pydraul E Series fluids are named for their viscosity at 100° F in centistokes (e.g. Pydraul 30E has 100° F viscosity of 30 centistokes). The E designation for these Pydraul fluids denotes straight phosphate ester—with no chlorinated components.

Pydraul 30E, Pydraul 50E, Pydraul 65E, Pydraul 90E (for air compressors) and Pydraul 115E are a unique family of fluids. They offer improved thermal and oxidative stability with corresponding long service life compared to present competitive products.

With unique low temperature fluids Pydraul 10E and Pydraul 29E LT added to the above line, the Pydraul E Series is the most complete line of phosphate ester fluids offered for industrial hydraulic service.

***NOTE:** Fluids designated "fire resistant" generally are more difficult to ignite, or once ignited burn at a slower rate than corresponding conventional fluids. This does not mean that fire-resistant fluids will not burn.

Performance

Pydraul fluids offer a wide range of viscosities from which you can select the proper range specified by your hydraulic equipment manufacturer. Whichever Pydraul fluid you select, each provides the same protection against fire, premium lubricity, ease of maintenance, and freedom from corrosive action and foam. Pydraul hydraulic fluids also offer several additional benefits—

Reduced Fire Insurance Rates

Pydraul substantially reduces fire hazards from hydraulic operations and fire threats to surrounding structure and equipment. Insurance premiums for plants using Pydraul are often lower than premiums for operations using petroleum oil.

Longer Pump Life

Machines which operate on water-based fluids frequently require pump repair or replacement as often as every two or three months. Machines which use Pydraul hydraulic fluids can operate on the same pump for several years. Pydraul hydraulic fluids give the same long pump life as the finest grade petroleum oil.

No Corrosion Problems

Any metal hydraulic system component in contact with Pydraul will not rust. Pydraul hydraulic fluids do not lose anti-rust properties even after extended use.

Maximum Equipment Response

Pydraul never produces excessive froth or foam during normal operations to interfere with hydraulic equipment response. Because Pydraul hydraulic fluids lubricate as well as premium petroleum oils, Pydraul permits equipment to operate at optimum response capability.

Inspection and Replacement Down-Time Are Virtually Eliminated

Pydraul hydraulic fluids are designed to be permanent. Pydraul fluids do not wear out. Except for normal "make-up" requirements, you never have to add new Pydraul to hydraulic systems. Pydraul eliminates "drain and change" periods; it does not have to be inspected in your system from month to month—or replaced from year to year.

0019802

TOWOLDMON0020893
WATER_PCB-00005362

Pydraul "E" series 2

	PYDRAUL® 10-E	PYDRAUL 29-E-LT
PHYSICAL PROPERTIES		
Appearance	Clear Blue Liquid	Clear Blue Liquid
Spec. Gravity 25/25°C.	1.085–1.095	1.090–1.110
Neutralization No. (mg KOH/g) max.	0.25	0.35
Moisture (max.) %	0.10	0.15
VISCOSITY		
Centistokes @ 100°F.	10.0 cs	30.9 cs
@ 210°F.	2.4 cs	7.9 cs
SSU @ 100°F.	60 SSU	145 SSU
@ 210°F.	35 SSU	52 SSU
Absolute SSU @ 100°F.	60.5 SSU	158 SSU
(SSU x Density) @ 210°F.	35 SSU	54 SSU
Pour Point	−70°F.	−45 °F.
Bulk Temp. Max. (continuous operation)	175°F.	175 °F.
Boiling Point °F. at 760 mm Hg	707°F.	500 °F.
Coefficient of Thermal Expansion per °F.	0.00044	0.00040
Specific Heat BTU/lb./°F. @ 77°F.	0.42	0.39
Thermal Conductivity BTU/hr./ft./°F.	0.047	0.0757
Vapor Pressure mm Hg @ 200°F.	0.002	0.002
Bulk Modulus (Room Temp. 1000-6000 psi)	328,000	370,000
Rust Test ASTM D-665	Pass	Pass
Foam Test ASTM D-892	Pass	Pass
Solubility in Water	Negligible	Negligible
FIRE RESISTANCE TESTS		
Factory Mutual Spray Test. Test fluid sprayed at 1000 psi through orifice, passing through flame of propane torch.	Fail	Pass
Factory Mutual Channel Iron Test. Test fluid sprayed at 1000 psi through orifice, onto hot channel iron at 1300°F.	Fail	Pass
Hot Manifold Test (Federal Test Method Std. 791). Test fluid dripped on at 1300°F.	Intermittent flashing but does not propagate to pan below.	Intermittent flashing but does not propagate to pan below.
Factory Mutual Approval. FM	No	Yes

Fire-resistance Advantages of Pydraul
Pydraul fluids protect hydraulic equipment and personnel with *permanent* fire protection. Pydraul fluids contain no water to evaporate and do not leave a flammable residue. During their many millions of machine hours of use, Pydraul fluids have been accidentally sprayed over molten metal, through electrical arcs, into flames and sparks. They pass all of the important ignition tests for fire-resistance.

0019803

TOWOLDMON0020894
WATER_PCB-00005363

PYDRAUL 30-E	PYDRAUL 50-E	PYDRAUL 65-E	PYDRAUL 115-E
Clear Blue Liquid	Clear Blue Liquid	Clear Blue Liquid	Clear Blue Liquid
1.155–1.175	1.145–1.165	1.142–1.162	1.145–1.165
0.15	0.15	0.15	0.15
0.10	0.10	0.10	0.10
32 cs 4.8 cs 150 SSU 42 SSU *174 SSU* 47 SSU	49 cs 5.9 cs 231 SSU 46 SSU *262 SSU* 50 SSU	67.3 cs 7.1 cs 312 SSU 50 SSU *349 SSU* 54 SSU	122 cs 9.1 cs 565 SSU 56 SSU *644 SSU* 61 SSU
−15 °F.	−5 °F.	0 °F.	+10 °F.
225°F.	225 °F.	225 °F.	225 °F.
725 °F.	750 °F.	780 °F.	820 °F.
0.00035	0.00035	0.00035	0.00035
0.36	0.37	0.38	0.38
0.0737	0.0730	0.0726	0.0721
0.002	0.002	0.001	<0.001
390,000	392,000	395,000	397,000
Pass	Pass	Pass	Pass
Pass	Pass	Pass	Pass
Negligible	Negligible	Negligible	Negligible
Pass	Pass	Pass	Pass
Pass	Pass	Pass	Pass
Intermittent flashing but does not propagate to pan below.	*Intermittent flashing but does not* propagate to pan below.	*Intermittent flashing* but does not propagate to pan below.	Intermittent flashing but does not propagate to pan below.
Yes	Yes	Yes	Yes

FOLLOWING IS A PARTIAL LIST OF APPLICATIONS FOR THE PYDRAUL FLUIDS:

STEEL INDUSTRY
continuous casters
rolling mills
furnaces
scrap chargers
stripper cranes
arc welders
combustion controls
mobile equipment

ALUMINUM INDUSTRY
stripper cranes
direct chill casters
furnaces
rolling mills
shearers
combustion controls
mobile equipment

FORGING AND EXTRUSION
forge presses
extrusion presses
billet manipulators

FOUNDRIES
furnaces
molding lines

DIECASTING
diecast machines
trim presses

FABRICATION
forming presses
welders
furnaces

0019804

TOWOLDMON0020895
WATER_PCB-00005364

Pydraul "E" series 4



0019805

TOWOLDMON0020896
WATER_PCB-00005365



908100

TOWOLDMON0020897
WATER_PCB-00005366

Pydraul "E" series 6

In a more severe Vickers hydraulic pump test (V-105-C pump), the Pydraul fluids performed as well as commercial antiwear oils and proved far superior to premium R & O oil (rust and oxidation inhibited).



0019807

TOWOLDMON0020898
WATER_PCB-00005367

MIXING COMPATIBILITY

Pydraul® With Other Pydraul Fluids

	10-E	29-E LT	30-E	50-E	65-E	115-E
10-E	—	YES	YES	YES	YES	YES
29-E LT	YES	—	YES	YES	YES	YES
30-E	YES	YES	—	YES	YES	YES
50-E	YES	YES	YES	—	YES	YES
65-E	YES	YES	YES	YES	—	YES
115-E	YES	YES	YES	YES	YES	—
230-C	YES	YES	YES	YES	YES	YES
312-C	YES	YES	NO	YES	YES	YES
540-C	YES	YES	NO	YES	YES	YES

Pydraul® With Other Hydraulic Fluids

	10-E	29-E LT	30-E	50-E	65-E	115-E
FYRQUEL*						
90	YES	YES	YES	YES	YES	YES
150	YES	YES	YES	YES	YES	YES
220	YES	YES	YES	YES	YES	YES
300	YES	YES	YES	YES	YES	YES
550	YES	YES	YES	YES	YES	YES
HOUGHTO-SAFE**						
1010	YES	YES	YES	YES	YES	YES
1115	YES	YES	YES	YES	YES	YES
1120	YES	YES	YES	YES	YES	YES
1130	YES	YES	YES	YES	YES	YES
1055	YES	YES	YES	YES	YES	YES

*Fyrquel is a registered trademark of Stauffer Chemical Company.
**Houghto-Safe is a registered trademark of E. F. Houghton Company.

0019808

TOWOLDMON0020899
WATER_PCB-00005368

Pydraul "E" series 8

CONVERTING TO PYDRAUL IS EASY

Regardless of the type hydraulic fluid being used, converting a system to low-cost Pydraul fluids is easy. Virtually every type of equipment which uses fire-resistant hydraulic fluid has been converted to Pydraul fluids. Most equipment manufacturers are experienced in Pydraul fluid conversions and should be consulted.

If changing seals is necessary, equipment manufacturers can recommend what seals to change, and many carry a supply of correct seals. Laboratory tests and operational experience show Viton*, Teflon*, and silicone the preferred elastomers for compatible seals. Please refer to the following section on seal and packing information for compatibility of Pydraul with other elastomers.

To replace other fluids which are compatible with Pydraul and where compatible seals are in the system, it is only necessary to add Pydraul as make-up fluid. It is not necessary to drain or clean. When converting from petroleum oils, non-compatible synthetic fluids, water-glycol fluids, or water-in-oil emulsions, the following steps are recommended. These conform to USA Standard B93.5—1966.

Please ask the Monsanto fluids specialist for recommendations and assistance. He may be reached by phoning the nearest sales office, listed on the inside back cover of this brochure.

Change-Over Procedures

Changing from Petroleum Oil

1. Completely drain and clean the system. Small amounts of oil will not interfere with the performance of Pydraul, but resistance to fire is reduced by the amount of oil left in the system.
2. Drain and blow out pipelines. Manually clean valves and reservoirs.
3. Open or remove and drain valves. Replace gaskets, packings, and seals with those compatible with Pydraul. It is particularly important to change dynamic seals. Static seals do not necessarily have to be changed if they are not leaking. Non-compatible static seals will have to be replaced when the part is disassembled for maintenance.
4. Remove pumps, accumulators, and cylinders, if necessary, for draining. Replace packings, seals, gaskets, and bladders with those compatible with Pydraul.
5. Check component functions before the system is closed and fluid is added.
6. If your system cannot be completely drained, you may have to flush it with a small amount of Pydraul.

Changing from Water-Glycol or Water-in-Oil Emulsion

1. Drain and clean system thoroughly. Remove all traces of water. Empty all lines and low points or dead pockets in components.
2. Clean with steam or warm water. Follow by blowing with dry air.
3. Check sealing materials, hoses, and accumulator bags. Replace if necessary with compatible materials.
4. Install a minimum charge of Pydraul and operate the system from 16 to 24 hours. During this period, inspect the reservoir. If water or other contaminants float to the top, skim them off.
5. Drain the flushing charge immediately after shut-down while the fluid is warm. Drain all isolated points or parts which do not drain back to the reservoir. If water is apparent in fluid clinging to walls, wipe down all accessible parts.

Changing from Phosphate Esters (Other Than Pydraul)

The Pydraul E Series fluids are compatible in all proportions with competitive phosphate esters and may be added as make-up to these fluids.

*Registered trademark of E. I. Du Pont de Nemours & Co., Inc.

0019809

TOWOLDMON0020900
WATER_PCB-00005369

SEALS AND PACKINGS INFORMATION

Materials compatible with Pydraul hydraulic fluid are necessary for dynamic or moving seals. For static seals they are preferred, but not essential. The following table indicates materials recommended, depending on the Pydraul fluid selected.

PYDRAUL® FLUID	BUTYL	EPR	VITON	TEFLON	NYLON	SILICONE	BUNA N	NEOPRENE	NATURAL RUBBER
10-E	R	R	U	R	R	S	U	U	U
29-E LT	R	R	R	R	R	R	U	U	U
30-E	R	R	R	R	R	R	U	U	U
50-E	R	R	R	R	R	R	U	U	U
65-E	R	R	R	R	R	R	U	U	U
115-E	R	R	R	R	R	R	U	U	U

R—Recommended S—Satisfactory U—Unsatisfactory

This list of component manufacturers is a guide to obtaining seals compatible with Pydraul fluids. Please contact your equipment manufacturer or seal supplier for their most current recommendations.

Acushnet Process Company
776 Belleville Avenue
New Bedford, Massachusetts 02745

Anchor Packing Company
401 North Broad Street
Philadelphia, Pennsylvania 19108

Bearings, Inc.
3634 Euclid Avenue
Cleveland, Ohio 44115

A. W. Chesterton Company
Everett
Massachusetts 02149

Chicago Rawhide Manufacturing Company
1311 Elston Avenue
Chicago, Illinois 60622

C. E. Conover & Company, Inc.
333 Passaic Avenue
Fairfield, New Jersey 07006

Crane Packing Company
6400 Dakton Street
Morton Grove, Illinois 60053

Garlock Packing Company
Palmyra
New York 14522

Goshen Rubber Company, Inc.
P. O. Box 416
Goshen, Indiana 46526

Greene, Tweed & Company
North Wales
Pennsylvania 19454

Hercules Packing Corporation
11061 Walden Road
Alden, New York 14004

International Packing Corporation
Bristol
New Hampshire 03104

Johns-Manville
22 East 40th Street
New York, New York 10016

C. W. Marsh Company
36 Hudson Street
Muskegon, Michigan 49441

Minnesota Rubber Company
3630 Wooddale Avenue
Minneapolis, Minnesota 55416

Parker Seal Company
10567 Jefferson Boulevard
Culver City, California 90230

Plastic & Rubber Engineering, Inc.
756 East Florence Avenue
Los Angeles, California 90001

Plastic & Rubber Products Company
2100 Hyde Park Boulevard
Los Angeles, California 90047

Precision Rubber Products Corporation
Hartmann Drive
Lebanon, Tennessee 37087

Raybestos-Manhattan, Inc.
Packing Division
Passaic, New Jersey

Reliable Rubber Products
Eddyington
Pennsylvania 19020

Rockwell Mechanical Packing Company, Inc.
1634 Long Beach Avenue
Los Angeles, California 90021

W. S. Shamban Company
11617 West Jefferson Boulevard
Culver City, California 90230

Vellumoid Company
Rockdale Street and Beaman Avenue
Worchester, Massachusetts 01606

The James Walker Packing Company, Inc.
P. O. Box 75
Chicago Heights, Illinois 60411

0019810

TOWOLDMON0020901
WATER_PCB-00005370

Pydraul "E" series 10

FILTERS AND HOSES

Filters/ Most standard oil filters are satisfactory. You can use active earth or clay types. Filter manufacturers include:

Briggs Filtration Division
Bowser Corporation
Cookeville, Tennessee

Capital Engineering Company
5839 S. Ashland Avenue
Chicago, Illinois

Commercial Filters Corporation
(Honan-Crane)
Lebanon, Indiana

Cuno Engineering Corporation
Sub. of American Machine
& Foundry
4627 S. Vine Street
Meriden, Connecticut

Dollinger Corporation
20 Centre Park
Rochester 3, New York

Fulflo Specialties Company, Inc.
410 Fancy Avenue
Blanchester, Ohio

Hilliard Corporation
98 W. Fourth Street
Elmira, New York

Marvel Engineering Company
7227 North Hamlin Avenue
Chicago 45, Illinois

Pall Corporation
32 Sea Cliff Avenue
Glen Cove, L. I., New York

Purolator Products
1000 New Brunswick Avenue
Rahway, New Jersey

Rosaen Filter Corporation
1776 E. Nine Mile Road
Hazel Park, Michigan

Schroeder Bros. Corporation
101 Nichol Avenue
McKees Rocks, Pennsylvania

Serfilco Division
Service Filtration Corporation
7408 North Milwaukee
Niles, Illinois 60648



Hoses/ Although both neoprene and buna elastomers swell somewhat in Pydraul, hose of these materials have given satisfactory service when made of a reinforced braid construction. Butyl, nylon or Viton are preferred when new hoses are installed. Suppliers include:

Anchor Coupling Company
3600 N. Fourth Street
Libertyville, Illinois

Eastman Mfg. Company
(See Imperial-Eastman Corp.)
Department T. R.
6300 West Howard Street
Chicago 48, Illinois

Electric Hose & Rubber Co.
1201 Duro Street
Wilmington, Delaware

Gates Rubber Company
999 South Broadway
Denver, Colorado 80217

Imperial-Eastman Corp.
6300 W. Howard Street
Chicago, Illinois

Lewis Products
Hohenwald, Tennessee 38462

Samuel Moore Co.
Mantua, Ohio

Resistoflex Corp.
Roseland, New Jersey

Stratoflex, Inc.
222 Roberts Cutoff Rd.
Fort Worth, Texas

Weatherhead Corp.
302 E. 131st Street
Cleveland, Ohio 44108

0019811

TOWOLDMON0020902
WATER_PCB-00005371

OTHER COMPONENTS

Swivel Couplings
Systems for Pydraul fluids often contain swivel couplings. Some suppliers are:

Chiksan Division
FMC Corporation
332 N. Brea Boulevard
Brea, California

Pipe Joint Sealers
. . . can be bought from:

American Sealants Company
(See Loctite Corporation)
115 N. Mountain Road
Hartford 11, Connecticut

Crane Packing Company
6410 Oakton Street
Morton Grove, Illinois

Dow Corning Corporation
Midland, Michigan

Friesland Plastics Company
Friesland, Wisconsin

General Electric Company
Insulating Materials Department
1 Campbell Road
Schenectady 6, New York

Permatex Company
Department T. R.
Flagler Court Building
West Palm Beach, Florida

W. S. Shamban & Company
11617 W. Jefferson Boulevard
Culver City, California

Shell Chemical Company
110 W. 51st Street
New York, New York



Accumulators
. . . many hydraulic systems for Pydraul contain an accumulator which uses a bladder to separate the fluid from air or nitrogen pressure. For these, a rubber compatible with the fluid is necessary. Suppliers include:

Greer Hydraulics, Inc.
5930 W. Jefferson Boulevard
Los Angeles, California

Paints
. . . resistant to Pydraul are supplied by:

Amercoat Corporation
Department T
Brea, California

Andrew Brown Paint Company
5413 S. District Boulevard
Los Angeles, California

Carboline Company
32-R Hanley Industrial Court
St. Louis, Missouri

Carrol Products
148 Marine Street
Farmingdale, New York

Finch Paint & Chemical Company
Torrence, California

W. P. Fuller & Company
1645 W. Valencia Drive
Fullerton, California

The Glidden Company
900 Union Commerce Building
Cleveland, Ohio

Interchemical Corporation
Finishes Division
1255-T Broad Street
Clifton, New Jersey

Lowe Brothers Company
Third & Madison Streets
Dayton, Ohio

Magna Coatings & Chemical Corporation
1785 N. Eastern Avenue
Los Angeles, California

Nycote Laboratories
15002 Delano Street
Van Nuys, California

Pittsburgh Plate Glass Company
One Gateway Center
Pittsburgh 22, Pennsylvania

Rinshed-Mason Company
5935 Milford
Detroit, Michigan

Royalty Paint & Varnish Company
Pasadena, California

Saran Protective Coatings Company
2415 Burdette at Reed
Ferndale, Michigan

Sherwin-Williams Company
101 Prospect Avenue, N. W.
Cleveland, Ohio

Titanine, Inc.
Seagrave Corporation
Elmwood & Morris Avenues
Union, New Jersey

U. S. Paint, Lacquer & Chemical Company
2101 Singleton
St. Louis, Missouri

0019812

TOWOLDMON0020903
WATER_PCB-00005372

Pydraul "E" series 12

RECLAIMING PYDRAUL FLUIDS

Pydraul hydraulic fluid lost from leaks and spills can be reclaimed because it is exceptionally stable and resistant to water and other contaminates. If fluid losses are appreciable—fluid recovery can result in considerable savings. Simply placing a container beneath leaks until they can be repaired will save some fluid. Where drip pans have been used beneath hydraulic machinery, more than half of the total Pydraul leakage has been reclaimed.

This dollar-saving recovery appears especially advantageous because it isn't practical to reclaim either water glycol or water-oil emulsions except to filter out large dirt particles. Reclaiming Pydraul fluid helps make it the most economical fire-resistant fluid available.

Reclaiming Pydraul consists of two steps: removing water, and filtering dirt or other solid particles.

Water Removal . . . Water does not mix with Pydraul and will, therefore, form a layer on top. A drum reserved for contaminated fluid with a side and end bung, placed horizontally on a cradle about two feet off the floor, is a simple and effective settling chamber. Salvaged fluid can be added through a large funnel in the top opening and Pydraul periodically drained off through the lower opening.

For a more elaborate system, permanently installed settling tanks, or a commercial installation can be used.

A second method is centrifuging. Suitable units are made by DeLaval and Sharples Co. Centrifuges operate swiftly . . . will separate water from large volumes of fluid in a short time.

Final Filtration . . . A number of filtration units are available complete with filter pump and motor. Other systems use filter media such as cotton linters, felt or metal screens. Attapulgus clay and Fuller's earth may be used to help keep the fluid clean, reduce moisture and lower neutralization number. Diatomaceous earth filtration is recommended for solid particles removal only. Paper and fiber type filters are recommended for water and particle removal but are ineffective for lowering neutralization number (acidity) values.

TOXICITY AND SAFE HANDLING

Acute animal studies indicate that the Pydraul E Series Fluids can be classed as practically non-toxic when considered as an industrial fluid. They are non-irritating when the skin is exposed to the fluid.
However, this product should not contact or in any way contaminate food, animal feed, food products, food packaging materials, pharmaceuticals or any items which may directly or indirectly be ultimately ingested by humans. Any contact may contaminate these items to the extent that their destruction may be required.

Due to their low order of toxicity, the Pydraul E Series require no special handling precautions. However, as in handling any chemical, good hygienic procedures should be followed. In case of skin contact, wash off with soap and water. In the case of eye contact, flush with copious amounts of water.

While Pydraul E Series (Pydraul C Series, also AC Series, Santosafe W/G) fluids pose no serious problems with respect to the environment, as a concerned supplier to industry, Monsanto urges the user to maintain a tight system, to correct leakage promptly and to exercise care in the handling and disposal of this and all other such products.

FLUID PURIFICATION SYSTEM



CENTRIFUGE SYSTEM FOR PURIFICATION

Filters in the 3 to 5 micron range are recommended for Pydraul filtration and reclamation. Such filter media will not affect the basic Pydraul formulation.



TOWOLDMON0020904
WATER_PCB-00005373

Pydraul "C" series 1

SECTION 2

PHOSPHATE ESTER BASE HYDRAULIC FLUIDS

Development

Fire protection for industrial hydraulic operations began with Pydraul in 1951. Pydraul fluids have since provided industry with millions of machine hours of safe operation.

New ways are continuously being explored to improve the excellent performance records of Pydraul fluids. From the first Pydraul fluid, (Pydraul F-9) the family has grown to ten specially tailored, fire-resistant safety fluids. Each answers a major but specific hydraulic fluid need for industrial use. In addition to guarding against fire, each Pydraul fluid lubricates as well as premium grade oil. Pydraul fluids have answered the need of virtually every industrial hydraulic operation, indoors and out—from the sub-zero, outdoor hydraulic lift operations for refineries and blast furnaces to the low-viscosity fluid demands of high-speed, precision machine tools.

Reformulation

The Pydraul fluids in this Selector were reformulated in 1971 to remove all chlorinated components. Monsanto has developed a series of phosphate ester base fluids known as the Pydraul C Series which exhibit performance superior to other phosphate ester base products.

The Pydraul C Series products, as with the Pydraul E Series straight phosphate ester line, are based on a unique phosphate ester. This gives the Pydraul C Series improved thermal and oxidative stability with corresponding long service life compared to competitive products.

Performance

Pydraul fluids offer a wide range of viscosities from which to select the proper range specified by the hydraulic equipment manufacturer. Whichever Pydraul fluid selected, each provides safety, premium lubricity, ease of maintenance, and freedom from corrosive action and foam. These Pydraul fluids have positive viscosity index values and are shear stable.

Introduction of Low Cost Series of Pydraul Safety Fluids

Pydraul 312 (now Pydraul 312-C) was the first of Monsanto's new series of low cost high performance fire-resistant hydraulic fluids. Introduced to the market in 1965, this chemistry was the latest innovation in synthetic safety hydraulic fluids. Pydraul 312-C is augmented with two other viscosity grade fluids which combine proved high performance with low cost.

Besides providing safe hydraulic operations, these Pydraul fluids offer lubrication equal to or even better than premium grade oils; freedom from corrosive action and foam; ease of maintenance; permanence—they don't "wear out."

These new lower cost Pydraul fluids are unique formulations of synthetic fluids blended with selected high viscosity low volatility petroleum fractions. The results are a series of fire-resistant hydraulic fluids which match or excel existing hydraulic fluids—including synthetics, premium grade petroleum oils, and water base fluids—but which sell in the price range of water-glycol fluids.

Reduced Fire Insurance Rates

Pydraul substantially reduces fire hazards from hydraulic operations and fire threats to surrounding structure and equipment. Insurance premiums for plants using Pydraul are often lower than premiums for operations using petroleum oil.

Longer Pump Life

Machines which operate on water-based fluids frequently require pump repair or replacement as often as every two or three months. Machines which use Pydraul hydraulic fluids can operate on the same pump for several years. Pydraul hydraulic fluids give the same long pump life as the finest grade petroleum oil.

No Corrosion Problems

Any metal hydraulic system component in contact with Pydraul will not rust. Pydraul hydraulic fluids do not lose anti-rust properties even after extended use.

Maximum Equipment Response

Pydraul never produces excessive froth or foam during normal operations to interfere with hydraulic equipment response. Because Pydraul hydraulic fluids lubricate as well as premium petroleum oils, Pydraul permits equipment to operate at optimum response capability.

Inspection and Replacement Down-Time Are Virtually Eliminated

Pydraul hydraulic fluids are designed to be permanent—they do not wear out. Normal "make-up" requirements are usually all that is needed for new Pydraul. Pydraul eliminates "drain and change" periods; it does not have to be inspected in your system from month to month—or replaced from year to year.

0019814

TOWOLDMON0020905
WATER_PCB-00005374

Pydraul "C" series 2

PHYSICAL PROPERTIES	
Appearance	
Spec. Gravity 25/25°C.	
Neutralization No. (mg KOH/g) max.	
Moisture (max.) %	
VISCOSITY	
Centistokes @ 100°F. @ 210°F. SSU @ 100°F. @ 210°F. Absolute SSU @ 100°F. (SSU x Density) @ 210°F.	
Pour Point	
Bulk Temp. Max. (continuous operation)	
Boiling Point °F. at 760 mm Hg	
Coefficient of Thermal Expansion per °F.	
Specific Heat BTU/lb./°F. @ 77°F.	
Thermal Conductivity BTU/hr./ft./°F.	
Vapor Pressure mm Hg @ 200°F.	
Bulk Modulus (Room Temp. 1000-6000 psi)	
Rust Test ASTM D-665	
Foam Test ASTM D-892	
Solubility in Water	
FIRE RESISTANCE TESTS	
Factory Mutual Spray Test. Test fluid sprayed at 1000 psi through orifice, passing through flame of propane torch.	
Factory Mutual Channel Iron Test. Test fluid sprayed at 1000 psi through orifice, onto hot channel iron at 1300°F.	
Hot Manifold Test (Federal Test Method Std. 791). Test fluid dripped on at 1300°F.	
Factory Mutual Approval. FM.	**FM**

Fire-resistance Advantages of Pydraul
Pydraul fluids protect hydraulic equipment and personnel with *permanent* fire protection. Pydraul fluids contain no water to evaporate and do not leave a flammable residue. During their many millions of machine hours of use, Pydraul fluids have been accidentally sprayed over molten metal, through electrical arcs, into flames and sparks. They pass all of the important ignition tests for fire-resistance.

0019815

TOWOLDMON0020906
WATER_PCB-00005375

PYDRAUL® 230-C	PYDRAUL 312-C	PYDRAUL 540-C
Clear Green Liquid	Clear Green Liquid	Clear Green Liquid
1.040—1.060	1.030—1.050	1.030—1.050
0.30	0.30	0.30
0.15	0.15	0.15
46.2 cs 6.9 cs 215 SSU 49 SSU 224 SSU 49 SSU	66 cs 8.4 cs 309 SSU 54 SSU 311 SSU 52 SSU	106 cs 10.5 cs 491 SSU 61 SSU 498 SSU 59 SSU
−20 °F.	−10°F.	0°F.
200°F.	200°F.	200°F.
500°F.	540°F.	545°F.
0.00038	0.00036	0.00036
0.41	0.41	0.40
0.0755	0.0760	0.0749
0.24	0.20	0.22
332,000	330,000	336,000
Pass	Pass	Pass
Pass	Pass	Pass
Negligible	Negligible	Negligible
Pass	Pass	Pass
Pass	Pass	Pass
Intermittent flashing but does not propagate to pan below.	Intermittent flashing but does not propagate to pan below.	Intermittent flashing but does not propagate to pan below.
Yes	Yes	Yes

FOLLOWING IS A PARTIAL LIST OF APPLICATIONS FOR THE PYDRAUL FLUIDS:

STEEL INDUSTRY
continuous casters
rolling mills
furnaces
scrap chargers
stripper cranes
arc welders
combustion controls
mobile equipment

DIECASTING
diecast machines
trim presses

ALUMINUM INDUSTRY
stripper cranes
direct chill casters
furnaces
rolling mills
shearers
combustion controls
mobile equipment

FABRICATION
forming presses
welders
furnaces

FORGING AND EXTRUSION
forge presses
extrusion presses
billet manipulators

FOUNDRIES
furnaces
molding lines

0019816

TOWOLDMON0020907
WATER_PCB-00005376

Pydraul "C" series 4



0019817

TOWOLDMON0020908
WATER_PCB-00005377



0019818

TOWOLDMON0020909
WATER_PCB-00005378

Pydraul "C" series 6

In a more severe Vickers hydraulic pump test (V-105-C pump), the Pydraul fluids performed as well as commercial antiwear oils and proved far superior to premium R & O oil (rust and oxidation inhibited).



0019819

TOWOLDMON0020910
WATER_PCB-00005379

MIXING COMPATIBILITY

Pydraul® With Other Pydraul Fluids

	230-C	312-C	540-C
230-C	—	YES	YES
312-C	YES	—	YES
540-C	YES	YES	—
10-E	YES	YES	YES
29-E LT	YES	YES	YES
30-E	YES	NO	NO
50-E	YES	YES	YES
65-E	YES	YES	YES
115-E	YES	YES	YES

Pydraul® With Other Hydraulic Fluids

FYRQUEL*	230-C	312-C	540-C
90	NO	NO	NO
150	YES	NO	NO
220	YES	YES	YES
300	YES	YES	YES
550	YES	YES	YES
HOUGHTOSAFE**			
1010	NO	NO	NO
1115	YES	NO	NO
1120	YES	YES	YES
1130	YES	YES	YES
1055	YES	YES	YES

*Fyrquel is a registered T.M. of Stauffer Chem. Co.
**Houghtosafe is a registered T.M. of E. F. Houghton Co.

0019820

TOWOLDMON0020911
WATER_PCB-00005380

Pydraul "C" series 8

CONVERTING TO PYDRAUL IS EASY

Regardless of the type hydraulic fluid being used, converting a system to low-cost Pydraul fluids is easy. Virtually every type of equipment which uses fire-resistant hydraulic fluid has been converted to Pydraul fluids. Most equipment manufacturers are experienced in Pydraul fluid conversions and should be consulted.

If changing seals is necessary, equipment manufacturers can recommend what seals to change, and many carry a supply of correct seals. Laboratory tests and operational experience show Viton*, Teflon*, and silicone the preferred elastomers for compatible seals. Please refer to the following section on seal and packing information for compatibility of Pydraul with other elastomers.

To replace other fluids which are compatible with Pydraul and where compatible seals are in the system, it is only necessary to add Pydraul as make-up fluid. It is not necessary to drain or clean. When converting from petroleum oils, non-compatible synthetic fluids, water-glycol fluids, or water-in-oil emulsions, the following steps are recommended. These conform to USA Standard B93.5—1966.

Please ask the Monsanto fluids specialist for recommendations and assistance. He may be reached by phoning the nearest sales office, listed on the inside back cover of this brochure.

Change-Over Procedures

Changing from Petroleum Oil

1. Completely drain and clean the system. Small amounts of oil will not interfere with the performance of Pydraul, but resistance to fire is reduced by the amount of oil left in the system.
2. Drain and blow out pipelines. Manually clean valves and reservoirs.
3. Open or remove and drain valves. Replace gaskets, packings, and seals with those compatible with Pydraul. It is particularly important to change dynamic seals. Static seals do not necessarily have to be changed if they are not leaking. Non-compatible static seals will have to be replaced when the part is disassembled for maintenance.
4. Remove pumps, accumulators, and cylinders, if necessary, for draining. Replace packings, seals, gaskets, and bladders with those compatible with Pydraul.
5. Check component functions before the system is closed and fluid is added.
6. If your system cannot be completely drained, you may have to flush it with a small amount of Pydraul.

Changing from Water-Glycol or Water-in-Oil Emulsion

1. Drain and clean system thoroughly. Remove all traces of water. Empty all lines and low points or dead pockets in components.
2. Clean with steam or warm water. Follow by blowing with dry air.
3. Check sealing materials, hoses, and accumulator bags. Replace if necessary with compatible materials.
4. Install a minimum charge of Pydraul and operate the system from 16 to 24 hours. During this period, inspect the reservoir. If water or other contaminants float to the top, skim them off.
5. Drain the flushing charge immediately after shut-down while the fluid is warm. Drain all isolated points or parts which do not drain back to the reservoir. If water is apparent in fluid clinging to walls, wipe down all accessible parts.

Changing from Phosphate Esters (Other Than Pydraul)

The Pydraul C Series fluids are compatible in all proportions with most competitive phosphate esters and may be added as make-up to these fluids. Refer to the compatibility table on page 7 of this section for specific fluid combinations.

*Registered trademark of E. I. Du Pont de Nemours & Co., Inc.

0019821

TOWOLDMON0020912
WATER_PCB-00005381

SEALS AND PACKINGS INFORMATION

Materials compatible with Pydraul hydraulic fluid are necessary for dynamic or moving seals. For static seals they are preferred, but not essential. The following table indicates materials recommended, depending on the Pydraul fluid selected.

PYDRAUL® FLUID	BUTYL*	EPR	VITON*	NYLON	TEFLON*	SILICONE	BUNA-N	NEOPRENE	NATURAL RUBBER
230-C	M	M	R	R	R	R	U	U	U
312-C	M	M	R	R	R	R	U	U	U
540-C	M	M	R	R	R	R	U	U	U

R—RECOMMENDED M—MARGINAL U—UNSATISFACTORY

*Although generally classified as marginal with these Pydraul fluids, butyl and EPR (ethylene propylene rubber) have proved satisfactory in equipment operating under certain conditions of temperature, fluid cleanliness, maintenance, etc. For best service under general all-around operating conditions, elastomers of Viton, Fluorel, Teflon, and silicone are recommended.

This list of component manufacturers is a guide to obtaining seals compatible with Pydraul fluids. Please contact your equipment manufacturer or seal supplier for their most current recommendations.

Acushnet Process Company
776 Belleville Avenue
New Bedford, Massachusetts 02745

Anchor Packing Company
401 North Broad Street
Philadelphia, Pennsylvania 19108

Bearings, Inc.
3634 Euclid Avenue
Cleveland, Ohio 44115

A. W. Chesterton Company
Everett
Massachusetts 02149

Chicago Rawhide Manufacturing Company
1311 Elston Avenue
Chicago, Illinois 60622

C. E. Conover & Company, Inc.
333 Passaic Avenue
Fairfield, New Jersey 07006

Crane Packing Company
6400 Dakton Street
Morton Grove, Illinois 60053

Garlock Packing Company
Palmyra
New York 14522

Goshen Rubber Company, Inc.
P. O. Box 416
Goshen, Indiana 46526

Greene, Tweed & Company
North Wales
Pennsylvania 19454

Hercules Packing Corporation
11061 Walden Road
Alden, New York 14004

International Packing Corporation
Bristol
New Hampshire 03104

Johns-Manville
22 East 40th Street
New York, New York 10016

C. W. Marsh Company
36 Hudson Street
Muskegon, Michigan 49441

Minnesota Rubber Company
3630 Wooddale Avenue
Minneapolis, Minnesota 55416

Parker Seal Company
10567 Jefferson Boulevard
Culver City, California 90230

Plastic & Rubber Engineering, Inc.
756 East Florence Avenue
Los Angeles, California 90001

Plastic & Rubber Products Company
2100 Hyde Park Boulevard
Los Angeles, California 90047

Precision Rubber Products Corporation
Hartmann Drive
Lebanon, Tennessee 37087

Raybestos-Manhattan, Inc.
Packing Division
Passaic, New Jersey

Reliable Rubber Products
Eddyington
Pennsylvania 19020

Rockwell Mechanical Packing Company, Inc.
1634 Long Beach Avenue
Los Angeles, California 90021

W. S. Shamban Company
11617 West Jefferson Boulevard
Culver City, California 90230

Vellumoid Company
Rockdale Street and Beaman Avenue
Worchester, Massachusetts 01606

The James Walker Packing Company, Inc.
P. O. Box 75
Chicago Heights, Illinois 60411

0019822

*Registered trademarks of E. I. Du Pont de Nemours & Co., Inc.

TOWOLDMON0020913
WATER_PCB-00005382

Pydraul "C" series 10

FILTERS AND HOSES

Filters/ Most standard oil filters are satisfactory. You can use active earth or clay types. Filter manufacturers include:

Briggs Filtration Division
Bowser Corporation
Cookeville, Tennessee

Capital Engineering Company
5839 S. Ashland Avenue
Chicago, Illinois

Commercial Filters Corporation
(Honan-Crane)
Lebanon, Indiana

Cuno Engineering Corporation
Sub. of American Machine
& Foundry
4627 S. Vine Street
Meriden, Connecticut

Dollinger Corporation
20 Centre Park
Rochester 3, New York

Fulflo Specialties Company, Inc.
410 Fancy Avenue
Blanchester, Ohio

Hilliard Corporation
98 W. Fourth Street
Elmira, New York

Marvel Engineering Company
7227 North Hamlin Avenue
Chicago 45, Illinois

Pall Corporation
32 Sea Cliff Avenue
Glen Cove, L. I., New York

Purolator Products
1000 New Brunswick Avenue
Rahway, New Jersey

Rosaen Filter Corporation
1776 E. Nine Mile Road
Hazel Park, Michigan

Schroeder Bros. Corporation
101 Nichol Avenue
McKees Rocks, Pennsylvania

Serfilco Division
Service Filtration Corporation
7408 North Milwaukee
Niles, Illinois 60648



Hoses/ Although both neoprene and buna elastomers swell somewhat in Pydraul, hose of these materials have given satisfactory service when made of a reinforced braid construction. Butyl, nylon or Viton are preferred when new hoses are installed. Suppliers include:

Anchor Coupling Company
3600 N. Fourth Street
Libertyville, Illinois

Eastman Mfg. Company
(See Imperial-Eastman Corp.)
Department T. R.
6300 West Howard Street
Chicago 48, Illinois

Electric Hose & Rubber Co.
1201 Duro Street
Wilmington, Delaware

Gates Rubber Company
999 South Broadway
Denver, Colorado 80217

Imperial-Eastman Corp.
6300 W. Howard Street
Chicago, Illinois

Lewis Products
Hohenwald, Tennessee 38462

Samuel Moore Co.
Mantua, Ohio

Resistoflex Corp.
Roseland, New Jersey

Stratoflex, Inc.
222 Roberts Cutoff Rd.
Fort Worth, Texas

Weatherhead Corp.
302 E. 131st Street
Cleveland, Ohio 44108

0019823

TOWOLDMON0020914
WATER_PCB-00005383

OTHER COMPONENTS

Swivel Couplings
Systems for Pydraul fluids often contain swivel couplings. Some suppliers are:

Chiksan Division
FMC Corporation
332 N. Brea Boulevard
Brea, California

Pipe Joint Sealers
. . . can be bought from:

American Sealants Company
(See Loctite Corporation)
115 N. Mountain Road
Hartford 11, Connecticut

Crane Packing Company
6410 Oakton Street
Morton Grove, Illinois

Dow Corning Corporation
Midland, Michigan

Friesland Plastics Company
Friesland, Wisconsin

General Electric Company
Insulating Materials Department
1 Campbell Road
Schenectady 6, New York

Permatex Company
Department T. R.
Flagler Court Building
West Palm Beach, Florida

W. S. Shamban & Company
11617 W. Jefferson Boulevard
Culver City, California

Shell Chemical Company
110 W. 51st Street
New York, New York



Accumulators
. . . many hydraulic systems for Pydraul contain an accumulator which uses a bladder to separate the fluid from air or nitrogen pressure. For these, a rubber compatible with the fluid is necessary. Suppliers include:

Greer Hydraulics, Inc.
5930 W. Jefferson Boulevard
Los Angeles, California

Paints
. . . resistant to Pydraul are supplied by:

Amercoat Corporation
Department T
Brea, California

Andrew Brown Paint Company
5413 S. District Boulevard
Los Angeles, California

Carboline Company
32-R Hanley Industrial Court
St. Louis, Missouri

Carrol Products
148 Marine Street
Farmingdale, New York

Finch Paint & Chemical Company
Torrence, California

W. P. Fuller & Company
1645 W. Valencia Drive
Fullerton, California

The Glidden Company
900 Union Commerce Building
Cleveland, Ohio

Interchemical Corporation
Finishes Division
1255-T Broad Street
Clifton, New Jersey

Lowe Brothers Company
Third & Madison Streets
Dayton, Ohio

Magna Coatings & Chemical Corporation
1785 N. Eastern Avenue
Los Angeles, California

Nycote Laboratories
15002 Delano Street
Van Nuys, California

Pittsburgh Plate Glass Company
One Gateway Center
Pittsburgh 22, Pennsylvania

Rinshed-Mason Company
5935 Milford
Detroit, Michigan

Royalty Paint & Varnish Company
Pasadena, California

Saran Protective Coatings Company
2415 Burdette at Reed
Ferndale, Michigan

Sherwin-Williams Company
101 Prospect Avenue, N. W.
Cleveland, Ohio

Titanine, Inc.
Seagrave Corporation
Elmwood & Morris Avenues
Union, New Jersey

U. S. Paint, Lacquer & Chemical Company
2101 Singleton
St. Louis, Missouri

TOWOLDMON0020915
WATER_PCB-00005384

Pydraul "C" series 12

RECLAIMING PYDRAUL FLUIDS

Pydraul hydraulic fluid lost from leaks and spills can be reclaimed because it is exceptionally stable and resistant to water and other contaminates. If fluid losses are appreciable—fluid recovery can result in considerable savings. Simply placing a container beneath leaks until they can be repaired will save some fluid. Where drip pans have been used beneath hydraulic machinery, more than half of the total Pydraul leakage has been reclaimed.

This dollar-saving recovery appears especially advantageous because it isn't practical to reclaim either water glycol or water-oil emulsions except to filter out large dirt particles. Reclaiming Pydraul fluid helps make it the most economical fire-resistant fluid available.

Reclaiming Pydraul consists of two steps: removing water, and filtering dirt or other solid particles.

Water Removal . . . Water does not mix with Pydraul and will, therefore, form a layer on top. A drum reserved for contaminated fluid with a side and end bung, placed horizontally on a cradle about two feet off the floor, is a simple and effective settling chamber. Salvaged fluid can be added through a large funnel in the top opening and Pydraul periodically drained off through the lower opening.

For a more elaborate system, permanently installed settling tanks, or a commercial installation can be used.

A second method is centrifuging. Suitable units are made by DeLaval and Sharples Co. Centrifuges operate swiftly . . . will separate water from large volumes of fluid in a short time.

Final Filtration . . . A number of filtration units are available complete with filter pump and motor. Other systems use filter media such as cotton linters, felt or metal screens. Attapulgus clay and Fuller's earth may be used to help keep the fluid clean, reduce moisture and lower neutralization number. Diatomaceous earth filtration is recommended for solid particles removal only. Paper and fiber type filters are recommended for water and particle removal but are ineffective for lowering neutralization number (acidity) values.

TOXICITY AND SAFE HANDLING

Animal studies indicate that the Pydraul C Series Fluids can be classed as practically non-toxic when considered as an industrial fluid. They are non-irritating when the skin is exposed to the fluid.

However, this product should not contact or in any way contaminate food, animal feed, food products, food packaging materials, pharmaceuticals or any items which may directly or indirectly be ultimately ingested by humans. Any contact may contaminate these items to the extent that their destruction may be required.

Due to their low order of toxicity, the Pydraul C Series require no special handling precautions. However, as in handling any chemical, good hygienic procedures should be followed. In case of skin contact, wash off with soap and water. In the case of eye contact, flush with copious amounts of water.

While Pydraul E Series (Pydraul C Series, also AC Series, Santosafe W/G) fluids pose no serious problems with respect to the environment, as a concerned supplier to industry, Monsanto urges the user to maintain a tight system, to correct leakage promptly and to exercise care in the handling and disposal of this and all other such products.

FLUID PURIFICATION SYSTEM



CENTRIFUGE SYSTEM FOR PURIFICATION

Filters in the 3 to 5 micron range are recommended for Pydraul filtration and reclamation. Such filter media will not affect the basic Pydraul formulation.



0019825

TOWOLDMON0020916
WATER_PCB-00005385

Santosafe® W/G

WATER/GLYCOL HYDRAULIC FLUIDS

The new Santosafe® W/G series of fire resistant water/glycol hydraulic fluids are designed for use in hydraulic systems working in areas with a source of heat or ignition that creates a potential fire hazard if petroleum oils are used.

Santosafe W/G fluids are mixtures of water, ethylene glycol, a high viscosity lubricating and thickening agent and selective additives for corrosion protection.

When compared to other commercial water/glycol fluids, Santosafe W/G fluids show improved pump performance and lubricity, meaning significantly longer component life and less maintenance costs.

Santosafe W/G fluids also exhibit excellent corrosion protection to metals, high VI, low pour points and excellent heat transfer properties that make the fluids acceptable for a wide range of operating temperatures.

Fire Resistance

The fire resistance of Santosafe W/G fluids depends upon their water content. The Santosafe W/G fluids contain between 40-45% water and are considered "fire resistant" as long as the water content is maintained. Exposure to elevated temperatures can cause boiling and evaporation which will reduce the safety of this fluid. Every precaution should be taken to prevent a reduction in water content.

Corrosion Protection

Santosafe W/G fluids contain special additives to give improved liquid and vapor phase corrosion protection. Tests show compatibility with steel, stainless steel, aluminum, nickel, tin, copper and copper alloys. Zinc, galvanized iron and cadmium plated parts should not be used.

Heat Transfer

Water and water containing fluids such as Santosafe W/G are known to be excellent heat transfer media. As a result, Santosafe W/G fluids provide lower operating temperatures than other common hydraulic fluids.

Storage & Handling

Santosafe W/G fluids do not require special handling precautions; normal procedures for handling hydraulic fluids should be used. Because these fluids are water-soluble, spillage can be removed with water.

Santosafe W/G fluids can be stored up to six months without problems. For extended storage the fluid should be agitated in some manner to redistribute the vapor phase inhibitor.

0019826

TOWOLDMON0020917
WATER_PCB-00005386

Santosafe® W/G

TYPICAL PHYSICAL PROPERTIES

FLUID SANTOSAFE®		W/G 15	W/G 20	W/G 30
Appearance		Red Liquid with a slight haze		
Specific Gravity @ 20/20°C		1.076	1.08	1.073
Water Content (% by weight)		43.4	43.0	40.0
Viscosity				
Centistokes	@ 130°F	21.1	28.0	29.7
	100°F	32.6	47.0	59.3
	0°F	499.6	700	1050
Saybolts as measured				
	130°F	97	130	140
	100°F	150	200	275
	0°F	2300	2600	4600
Absolute Saybolts (SSU x density)	130°F	104	140	150
	100°F	161	216	296
	0°F	2475	2808	4950
Viscosity Index		155 min.	155 min.	155 min.
Pour Point Min.		−40°F	−40°F	−40°F
pH at 25°C		9.4	9.4	9.3
Alkaline Content (ml. 0.1N HCl to neutralize 100 ml. of fluid to pH 5.5)		164	165	176
Rust Test (ASTM)		Pass	Pass	Pass
Flash Point (COC)		None	None	None
Weight per gallon, lbs @ 60°F		9.00	9.00	9.00

0019827

TOWOLDMON0020918
WATER_PCB-00005387





0019828

TOWOLDMON0020919
WATER_PCB-00005388

Santosafe® W/G

LUBRICATION AND PERFORMANCE

Santosafe W/G fluids will perform satisfactorily in all types of hydraulic pumps at rated speeds and pressures recommended by the pump manufacturers. Of course the fluid itself must be kept free of contamination and in good condition chemically. Proper maintenance procedures (i.e., adequate filtration, proper fluid temperature, viscosity and alkalinity control) are vital to good performance.

Lubrication:

Usage in vane type pumps at pressures to 2000 psig and speeds to 1200 RPM are well within the capabilities of Santosafe W/G fluids. The fluids have also performed in axial piston pumps at 3500 psig and 1200 RPM.

Higher speeds (1750 RPM) generally require lowering the pressure to attain equivalent service. Use of Santosafe W/G fluids is not recommended in radial piston pumps. Gear pumps with bronze sleeve bearings present no difficulties and can be operated at full capacity. Heavily loaded needle bearings may require derating or a change in the type of bearing to a more suitable configuration.

Santosafe W/G fluids exhibit the best pump wear seen when compared to commercial water glycols in standard pump tests due to the high level of anti-wear protection in Santosafe W/G formulation.

In all tests to date no sludge formation or serious corrosion was found. Pumping efficiency showed no significant change.

Low Pressure Systems:

Pump tests on Santosafe W/G fluids at pressures of 1000 psig in vane pumps show less than 0.1% total wear.

High Pressure:

As a result of the low wear in low pressure tests, tests were made more severe to discover the fluids' capabilities. Table I shows the results for a V105E Vickers Vane pump. The wear rates of 71mg and 57mg are considered excellent.

Table II (page 5) shows even more severe tests of Santosafe W/G compared to 3 other commercially available hydraulic fluids.

The results of the V105C Vickers Vane pump show Santosafe W/G superior to all fluids tested.

These results indicate Santosafe W/G can operate in the most critical systems with good performance.

Table I

VICKERS PUMP TEST

FLUID	SANTOSAFE® W/G 15	W/G 20
Pump Type	V105E	V105E
Pump Capacity (GPM)	2	2
Fluid Temperature (°F)	130°F	130°F
Pressure (PSIG)	1000	1000
Duration (Hrs)	1000	1000
Total Wear in Mg. (Ring+Vanes)	71	57

TOWOLDMON0020920
WATER_PCB-00005389



Table II

FLUID	SANTOSAFE® W/G 15	SANTOSAFE W/G 20	SANTOSAFE W/G 30	WATER/GLYCOL A	WATER/GLYCOL B	R&O OIL
Pump Type	V105C	V105C	V105C	V105C	V105C	V105C
Pump Capacity	8 GPM	8 GPM	8 GPM	8 GPM	8 GPM	8 GPM
Fluid Temperature	140°F	140°F	140°F	140°F	140°F	150°F
Pressure (PSIG)	1800	1800	1800	1800	1800	1800
Speed	1200 RPM	1200 RPM	1200 RPM	1200 RPM	1200 RPM	1200 RPM
Duration (Hrs)	258	260	260	49*	258	50*
Wear						
Ring	476.0 mg	275.7	56.3	4,365.8	7,552.2	332.2
Vanes	60.1 mg	48.2	17.5	17.9	40.6	11.5
Total	536.1 mg[1]	323.9[1]	73.8[1]	4,383.7[2]	7,592.8[3]	343.7[4]

* Test discontinued due to irregular wear causing high internal leakage essentially causing test failure. (System pressure could not be maintained.)

1. Ring showed even wear—no washboarding. Rotor and end plates were in excellent condition. Light varnish on vanes.
2. Ring showed excessive wear and washboarding. Heavy varnish deposits on vanes and rotor.
3. Ring showed medium washboarding and searing wear. Vanes and end plates showed light wear and medium varnish deposits.
4. Ring showed excessive washboarding and searing wear. Vanes and end plates showed light wear and medium varnish deposits.

Tests conducted in Monsanto laboratories.

0019830

TOWOLDMON0020921
WATER_PCB-00005390

Santosafe® W/G

6

COMPATIBILITY

Hoses, Packings and Seals:
No special hoses, seals or packings are needed when changing over from petroleum oil to Santosafe W/G fluids. The following materials have been found compatible with Santosafe W/G:

Natural Rubber	Butyl
SBR	Chloroprene
Viton*	Nitrile Rubber
Teflon*	EPR

Fabricated neoprene, homogeneous Buna N and Viton are the most common seals used. Nylon, butyl or neoprene is common for hoses.

Because of the water content materials such as leather, cork, untreated cotton and cellulose packing should not be used.

Paints:

Solvent properties of Santosafe W/G fluids make conventional paints unsuitable. When converting systems, questionable paint should be removed and the surface left unpainted or painted with a compatible paint. Most leading paint suppliers handle compatible paints for water glycols.

Filters:

Fine mesh metal screens and water proofed cotton or cellulose fiber filters are satisfactory for Santosafe W/G fluids. The use of active clay or other adsorbent filters is not recommended because they could remove constituents of the Santosafe W/G formulation.

Pipe Dopes:

Santosafe W/G fluid may dissolve certain pipe dopes. Use only types known compatible with water/glycol fluids.

*Registered trademarks of E. I. Du Pont de Nemours & Co., Inc.

TOXICITY AND SAFE HANDLING

Santosafe W/G fluids are materials of low toxicity by all means of testing. They are not skin irritants or sensitizers and will cause only mild eye discomfort on contact with the liquid. The organic components have very low vapor pressure and are consequently not expected to have vapor inhalation toxicity.

On the basis of the toxicological, physical and chemical properties of Santosafe W/G fluids, no precautionary labeling is used on the containers.

0019831

TOWOLDMON0020922
WATER_PCB-00005391

MONSANTO INTERNATIONAL LIST

ARGENTINA
Monsanto Argentina S.A.I.C.
Avda Madero 1020, Floors 17th & 18th
Buenos Aires, Argentina

AUSTRALIA
Monsanto Australia Limited
East Tower, Princes Gate Bldg.
151 Flinders Street
Melbourne, Victoria 3001
Australia

Monsanto Australia Limited
35 Terry Street
Rozelle, Sydney, NSW
Australia 2039

Monsanto Australia Limited
Post Office Box 1111K, Adelaide
South Australia 5031

Monsanto Australia Limited
Brisbane
P. O. Box 63, Hamilton Central
Queensland, Australia 4007

Monsanto Australia Limited
Perth
P. O. Box 77
Doubleview
West Australia 6018

AUSTRIA
Monsanto GmbH Austria
Rudolfsplatz 12
A-1010 Wien 1, Austria

BELGIUM
Monsanto Europe S.A.
1, Place Madou
1030 Brussels, Belgium

Monsanto Europe NV/SA
163 Mechelsesteenweg
2000 Antwerp, Belgium

BRAZIL
Industrias Monsanto Ltda.
Rua Araujo 216, 6 Andar
Sao Paulo, Brazil 01220

CANADA
Monsanto Canada Ltd.
175 Rexdale Blvd.
Rexdale, Ontario, Canada

Monsanto Canada Ltd.
100 Park Royale, Suite 701
West Vancouver, B.C., Canada

CHILE
Monsanto Chile Cumercial e Industrial Limitada
Edificio Espana Oficina 502
Calle Estado 337
Santiago de Chile

COLOMBIA
Monsanto Colombiana Inc.
Carrera 14, No. 77 - 59
Bogota, Colombia

DENMARK
Monsanto A/S
6 Rysensteensgade
DK 1564 Copenhagen
Denmark

EL SALVADOR
Monsanto Centroamerica (El Salvador) S.A.
Edificio Plaza
67 Avenida Sur y Calle a Santa Tecla
San Salvador, El Salvador

FINLAND
Monsanto (Scandinavia) AB
Arkadiankatu 8 C 20
00100 Helsinki 10, Finland

FRANCE
Societe Monsanto S.A.
9 rue d'Argenson
75 Paris (8) France

GUATEMALA
Monsanto Guatemala Inc.
Edificio Cass
7a Avenida 7-11 Zona 9
Guatemala City, Guatemala

HONG KONG
Monsanto Far East Ltd.
Management House, 2nd Floor
26 Canal Road West
Hong Kong, B.C.C.

INDIA
Mindia Chemicals Ltd.
Monsanto Chemical of India Pvt. Ltd.
(Ag Products)
Wakefield House
11 Sprott Rd., Ballard Estate
Bombay 400 001, India

Mindia Chemicals Ltd.
19 Rajendranath Mukherjee Rd.
Calcutta 700 001, India

Mindia Chemicals Ltd.
Monsanto Chemicals of India, Pvt. Ltd.
(Ag Products)
310-311 Linghi Chetty Street
Madras 600 001, India

Mindia Chemicals Ltd.
3/8 Asaf Ali Road
New Delhi 110 001, India

INDONESIA
P. T. Monsanto Pan Electronics
191 Dj. Dr Sahardjo
Jakarta, Indonesia

ITALY
Monsanto Italiana S.p.A.
Via Melchiorre Gioia 8
Milano 20124, Italy

JAPAN
Monsanto Japan Ltd.
Room 217, Shin Kokusai Bldg.,
4-1, Marunouchi 3-chome
Chiyoda-ku, Tokyo, Japan

MALAYSIA
Monsanto Far East Ltd.
(Malaysia Branch)
116, Jalan Semangat
Petaling Jaya, Selangor, Malaysia

MEXICO
Monsanto Comercial S.A. de C.V.
Thiers No. 248
Mexico 5, D.F., Mexico

NETHERLANDS
Monsanto B.V.
Jan Van Nassaustraat 53-55
Den Haag
The Netherlands, Holland

NEW ZEALAND
Monsanto New Zealand Ltd.
19 Great South Road
Remuera
Auckland 5, New Zealand

NICARAGUA
Monsanto (Nicaragua) S.A.
P. O. Box 288
Managua, Nicaragua

NORWAY
Monsanto Norge A.S.
Fred Olsensgate 11
Oslo 1, Norway

PHILIPPINES
Monsanto Philippines Inc.
Suite 1101 Security Bank & Trust
6788 Ayala Ave.
Makati Rizal D-708, Philippines

PUERTO RICO
Monsanto Puerto Rico Company
Munoz Rivera Ave. Borniquen St.
Rio Piedras, Puerto Rico

SINGAPORE
Monsanto Singapore Company (Pte.) Ltd.
Suite 706 Cathay Bldg., 7th Floor
Mount Sophia, Singapore 9

SOUTH AFRICA
Monsanto South Africa (Pty.) Ltd.
11th Floor, Sandton City Bldg.
Sandton, Transvaal, South Africa

SPAIN
Monsanto Iberica S.A.
Lepanto 350-5
Barcelona 13, Spain

SWEDEN
Monsanto (Scandinavia) AB
Ulvsundavagen 108
Bromma, Sweden

SWITZERLAND
Monsanto (Suisse) S.A.
Tiefenhofe 10,
CH8022 Zurich, Switzerland

TAIWAN
Monsanto Far East Ltd. - (Taiwan Branch)
36 Chang An East Road, 6th Floor
Section 1, Taipei
Taiwan

THAILAND
Monsanto Thailand Ltd.
5th Floor, Kasemkij Bldg.
120 Silom Road
Bangkok, Thailand

UNITED KINGDOM
Monsanto Ltd.
10-18 Victoria Street
Monsanto House
London SW1H ONO England

VENEZUELA
Monsanto (Venezuela) CA
Torre Pheips Piso 24
Plaza Venezuela
Caracas 101, Venezuela

WEST GERMANY
Monsanto (Deutschland) GmbH
Immermannstrasse 3
D-4000 Dusseldorf, West Germany

0019832

TOWOLDMON0020923
WATER_PCB-00005392

CUSTOMER SERVICE CENTERS

AKRON, OHIO 44313
260 Springside Drive
Montrose Development Park
Tel. (216) 666-4111

ATLANTA, GEORGIA 30339
320 Interstate North Parkway
Suite 500
Tel. (404) 432-7111

BOSTON, MASSACHUSETTS 02149
Everett Station
Tel. (617) 387-5010

HOUSTON, TEXAS 77027
1301 Post Oak Tower
5051 Westheimer Road
Tel. (713) 621-9550

LOS ANGELES, CALIFORNIA 90022
6670 E. Flotilla St.
Tel. (213) 723-2492

NEW YORK, NEW YORK 10036
1114 Avenue of the Americas
Tel. (212) 764-5000

ST. LOUIS, MISSOURI 63166
800 N. Lindbergh Blvd.
Tel. (314) 694-1000

SAN FRANCISCO BAY AREA
2710 Lafayette
Santa Clara, California 95052
Tel. (408) 243-0414

WILMINGTON, DELAWARE 19810
Suite 204, Bancroft Bldg.
3411 Silverside Road
Tel. (302) 478-4600

Monsanto Industrial Chemicals Co.
A Unit of Monsanto Company
800 N. Lindbergh Blvd., St. Louis, Mo. 63166

For technical information phone your Monsanto representative or the nearest sales office (listed on this page).

To place an order for Pydraul products from Monsanto dial toll free 800-325-3850.

Monsanto

0019833

TOWOLDMON0020924
WATER_PCB-00005393

In This Pocket...

Additional Information on Pydraul® and Santosafe® W/G Products

Monsanto

0019834

TOWOLDMON0020925
WATER_PCB-00005394

0019835

Monsanto 800 N. LINDBERGH BLVD., ST. LOUIS, MISSOURI 63166

2-3656 0675-44 LITHO IN U.S.A.

TOWOLDMON0020926
WATER_PCB-00005395