


Aladdin Heating Corporation

1111 West Ave. 137, San Leandro, Calif.


Manufacturers of Centrifugal Blowers,
Heating and Ventilating Equipment.



BB Fans



FC Fans




RB Fans


BB FAN—Backwardly inclined blade fan with non-overloading horsepower characteristic. Manufactured in 22 sizes, single and double width, all arrangements, 2 classes of construction. Request *Bulletin 605-A, 605-B*.

FC FAN—Forward curved fan, slow speed for quiet operation. Manufactured in 22 sizes, single and double width, all arrangements, 2 classes of construction. Request *Bulletin 605-A, 605-C*.


RB FAN—Radial blade fan well suited for handling grease or other sticky materials. Manufactured in 13 sizes, single width only, all arrangements, 2 classes of construction. Request *Bulletin 450-B*.



EX Fans



Utility Sets




FC Junior Fans


EX FAN—Radial blade fan used chiefly for conveying materials, fume exhaust, etc. Manufactured in 15 sizes, single width only, all arrangements, 5 classes of construction, 3 wheel types. Request *Bulletin 461*.

UTILITY SETS—Self contained units for a wide variety of ventilating applications. Manufactured in 12 sizes with forward curved rotors, 10 sizes with backwardly inclined blade rotors, single width only. Request *Bulletins 610, 611*.


FC JUNIOR FANS—Self contained direct connected fans with forward curved rotors. Manufactured in 5 sizes with 13 motor speeds, single width only. Request *Bulletin 422*.



HV Units



Roof Ventilator



Fuseair Ceiling Outlets

HV UNITS—Heating and ventilating unit of universal design. Can be furnished with air filters, face and by-pass dampers or mixing box. Manufactured in 7 sizes with unlimited flexibility as to arrangement. Request *Bulletin 510*.

ROOF VENTILATOR—Backwardly inclined blade centrifugal type. Manufactured in 13 belt driven and 12 direct driven sizes with steel, aluminum, copper or stainless steel housings. Request *Bulletin 410-A*.

CEILING DIFFUSERS—Fuseair ceiling outlets are manufactured in a complete range of sizes in both supply and combination supply and return types. Request *Bulletins 623 and 615*.




American Coolair Corporation

3604 Mayflower Street, Jacksonville 3, Florida.

Exhaust Fans and Related Equipment for Industrial and Home Cooling
Authorized Distributors and Dealers in Most Communities
District Representatives

ATLANTA, GA.—John L. Underwood Co., Inc., 555 Whitehall St., S. W., Atlanta 3, Ga. Phone: Main 7373
CINCINNATI, O.—Halsey E. Kendrick, 5167 Valley Ridge Rd., Cincinnati 11, O. Phone: Humbolt 4573
DALLAS, TEX.—J. D. Clower, Whiteright, Tex. L.D. Phone: Whiteright 919F2

JACKSON, MISS.—Bert White, P. O. Box 4264 Fondren Station, Jackson 6, Miss. Phone: 6-4853
NEW YORK, N. Y.—E. R. Dexter, 117 N. Middle-town Rd., Pearl River, N. Y. L. D. Phone: Pearl River 5-2725
WASHINGTON, D. C.—Robert A. Magee, Dryden, Md., Phone: Great Mills 37432, Western Union, Leonardtown, Md.



COOLAIR BELT DRIVE FANS are specifically engineered to move large volumes of air *quietly* and at low cost.

Certified Ratings: Coolair Fans are rated in accordance with the ASHVE Standard Test Code for Centrifugal and Axial Fans (1938). In addition, most sizes up to and including 62-inch are rated by the A & M College of Texas.

1. **Type H Fans** spring mounted for ultra-quiet home and commercial use. Reversible. Most models available with two-speed motors. Install at any angle.

2. **NEW Type P Fans** for attic packages. New efficiency in these installations. Two speeds. Spring mounted. With or without suction box.

3. **Belt Drive Window Fans** available in sizes 24 in., 28 in. and 32 in. Heavy duty fans for window and wall installation.

4. and 5. **Types C & CT** for heavy duty commercial and industrial installations. Single and Twin Units. Available without motors or fitted with standard semi-enclosed, enclosed and explosion-proof motors for all types of service.

6. **Automatic Ceiling Shutters.** Open when fan is turned on. Close when fan goes off. Fusible link for fire protection.

7. **Motor Wall Shutters,** also available in manual models, in many sizes to fit every requirement.

8. **Types S & SX Fans** for rugged industrial use. In sizes up to 9 ft. Double frame construction with special pillow block, ball-bearing drive.

9. **Type U Fans.** With and without guards and stand. For high speed exhaust use or for directional and spot cooling.

10. **The Famous Coolair Hub.** Secret of the long, trouble-free life of Coolair Fans. No torque, hence no chatter, even after years of service.