

CO 03 CODE KY-787-D PKG.

JAN 11 33737

EST. WGT. 1090 LBS.

STD. MRS. 8.9 TIME 11 P M

 14 - YC-2-B 98 4 Lot 23966, 1.850 #
 Lot 24171, 1.50 #
 Lot 24068, 1.00 #
 2.400

PROCESSES		APPROVED BY	
() KY-787-D	()	FWK	9/22/76
()	()	DCG	9/27/76
()	()	MTW	9/30/76
()	()		
TYPED BY			
N.E. 2/12/77			


Total Wgt. - 3490#

NON-BLEEDING


SHIPMENT	NAME	USE LBS.	N CODE	ACCT. LBS.
203	6" "KROLOR" - YELLOW MEDIUM			
&	1 Run 10" (992 G) water into V-203 AND ADD	30	7-D	15
205	2 Weigh in drum & pour in	320	32-D	320
1	3 Dump in and stir 5 min	48 x 50	YC-2-B	2400
	Record: Start 5:20 AM Lot 23966			
	Fin 6:35 AM 24171			
	24068			
	4 Add to 70" (1200 G) 2400-2600			
	5 Pump V-203 thru Homog #3 at 1800-2200 psi into V-205	48		
	6 When V-203 MTY, wash color thru Homog at 1800-2000 psi using minimum water			
	7 Record V-205 Vol 42" & adj to 60" (2100 G)			
	8 Inspect Homog strainer & clean if necessary			
205	9 Run 10" (514G) water into SV & start agitator			
&	10 Pump V-205 thru Homog at 4800-5200 psi into V-243			
SV	Record: Time start 5:05 PM Total Min 14.5			
2	NOTE: If Homog pressure falls below 4800 psi, 3-way valve will recirculate slurry to V-205			
	11 When V-205 MTY, run in 5" (240 G) water and pump thru Homog at 4800-5200 psi			
SP	12 SP Step 01 - Set Formula Selector to position #2 (V-243) or #7 (V-244)			
&	13 Press SV Cam Reset PB-set 22TC in Auto Remote (Temperature is set at 190-194F)			
CP	14 Record levels and set Raw Materials Counter #1 as follows:			
3	a. 11LG 35% - preset #1 80 Gal 15-A 160			
	b. 13LG % - preset #6 135 Gal 20-A 135			
	15 Set strike flow controllers as follows:			
	a. 3FC10 (N-27-D Controller) in Manual 0.83 GPM 27-D 275			
	b. 3FC20 (N-27-D Water) in Manual Local 5.28 GPM			
	c. 3FR10 (N-27-D/Water Ratio) 0.64			
	d. 8FC10 (N-32-D Controller) in Manual 1.08 GPM 32-D 1840			
	e. 8FC20 (N-32-D Water) in Manual Local 4.47 GPM			
	f. 8FC20 (N-32-D Water) in Remote			
	g. 8FR10 (N-32-D/Water Ratio) 0.83			
SV	16 Operator Step PB			
SP	17 Record Level 2 LG 66%. If below 35% follow solution make-up procedure for N-27-D			
&	18 Adj to 48" (2470 G)			
CP	19 Record pH 9.3			
4	20 Adj to 11.1 - 11.3 using N-7-D diluted to 5% Assume 50% (10 parts water to 1 part N-7-D) 50 7-D 25			
	Siphon into SV. Record pH 11.3			
	21 Operator Step PB			


V-243

NT	PAGE 2	CG 03	CODE KY-787-D	EST. WGT. 3490	LBS.	USE LBS.	N CODE	ACC LBS.
	22	SB Step 06/49 - After heat up Record: pH <u>7.1</u> (9.5-10.0)						
	23	Switch 3FC20, 8FC10, 8FC20 to Auto						
	24	Operator Step PB						
	25	SP Step 10/43 - When 3FC20, 8FC10, 8FC20 water flows in limits						
		Switch 3FC10 to Auto. Operator Step PB						
	26	SP Step 11/44 - When 3FC10, 3FC20 flows in limits, switch 3FC20 to Remote.						
	27	Operator Step PB						
	28	During strike, record pH & time as follows: <u>10:45 PM</u>						
		SP STEP						
		V-243/V-244	pH	Range	Time			
		13/46 (30 min)	<u>9.3</u>	9.0-10.0	<u>11:15 PM</u>			
		14/47 (60 min)	<u>9.3</u>	9.0-10.0	<u>11:45</u>			
		15/48 (2 hrs)	<u>9.3</u>	9.0-10.0	<u>12:45</u>			
		16/49 (2 hrs 25 min)	<u>9.3</u>	9.0-10.0	<u>1:10</u>			
		17/50 (3 hrs Final)	<u>7.7</u>	7.5-8.5	<u>1:45 AM</u>			
		NOTE: If not as specified notify Supervisor & note in log						
		If final pH is above 8.5, add pH to 7.5-8.5 &						
		Record: pH Assume 77%					27-D	
9	29	While striking, run 30" (234 G) water into V-339						
	30	Add in 7-8 min				250	530-A	350
	31	Add to 49" (382 G) at 80 - 100°F						
	32	Stir 5 min & record pH <u>10.2</u> (9.5-10.5)						
	33	Stir 15 min or longer to dissolve for SP Step 26						
	34	Record Vol <u>49</u> & calculate <u>49</u> (Vol) x 0.78 = <u>38.2 G</u>						
	35	Set preset #8 to <u>38.2</u> G from S 34						
	36	Add 30" (360 G) water to V-302						
	37	Add & stir 2 min For S 41 Assume 50%				160	7-D	80
3	38	SP Step 17/50 - After checking pH, Operator Step PB						
	39	SIFT in 2 Bags				100	128-A	100
P	40	SP Step 23/53 - Record: pH <u>3.5</u> (3.7-4.2)						
&	41	Run in N-7-D from S 37 in 10-12 min & sti 5 min						
P	42	Record: pH <u>9.3</u> (9.0-9.5) & if necessary add pH 9.0-9.5						
B		& Record: pH Assume 77%					27-D	
		(Dilute 10 parts water to 1 part N-7-D) Assume 50%					7-D	
		Siphon N-7-D into SV						
	43	Operator Step PB						
	44	SP Step 29/58 Record: pH <u>9.3</u> (9.0-10.0) Time <u>2:50 A.M.</u>						
	45	Operator Step PB						
	46	SP Step 60 - Batch complete						
		Start	Finish	Optr				
		Time	SP Step	Time	SP Step			
		<u>11 AM</u>		<u>3 PM</u>		<u>282-381</u>		
		<u>3:00 PM</u>		<u>11:00 PM</u>		<u>237-320</u>		
		<u>11:00 PM</u>		<u>2:50 A.M.</u>		<u>235-34</u>		



G CONTROLS CORPORATION BUFFALO, NEW YORK





GRAPHIC CONTROLS CORPORATION BUFFALO, NEW

DUP050093140

