

## ----- SECTION I -----

AMERICHEM, INC.

8 Broadway East

Lynchburg Falls, Ohio 44221

Product Name : 6459-T1 CLAY

Product Type : COLOR CONCENTRATE FOR PVC

Phone: 1-216-929-4213

## ----- SECTION II - HAZARDOUS INGREDIENTS -----

| INGREDIENT                 | CAS NO.     | WT % | NATURE OF HAZARD                     | COMMENTS                                                    |
|----------------------------|-------------|------|--------------------------------------|-------------------------------------------------------------|
| PLASTICIZER                | 117-81-7    | 10.3 | POSSIBLE<br>CARCINOGEN               | REPORTABLE UNDER<br>SARA SECTION 313<br>CALIFORNIA PROP. 65 |
| *<br>*                     |             |      |                                      |                                                             |
| STABILIZER<br>(BARIUM CPD) | PROPRIETARY | 1.2  | TOXIC - DO<br>NOT INGEST             | REPORTABLE UNDER<br>SARA SECTION 313                        |
| PIGMENT<br>(LEAD COMPOUND) | 1344-37-2   | 22.6 | HEAVY METAL CONTENT<br>DO NOT INGEST | REPORTABLE UNDER<br>SARA SECTION 313                        |

ALL RAW MATERIALS IN THIS FORMULATION ARE ON THE TSCA INVENTORY LIST. THIS PRODUCT, HOWEVER, IS NOT LISTED SINCE IT IS A MIXTURE OF LISTED INGREDIENTS.

THE EPA, UNDER SECTION 313 OF SARA, REQUIRES EMISSIONS REPORTING OF PRODUCTS WHICH CONTAIN COMPOUNDS OF ANTIMONY, ARSENIC, BARIUM, CADMIUM, CHROMIUM, COBALT, COPPER, LEAD, MANGANESE, MERCURY, NICKEL, SELENIUM, AND ZINC.

SINCE ANY HAZARDOUS INGREDIENTS ARE ENCAPSULATED IN POLYMER, NO HAZARDS ARE EXPECTED DURING NORMAL USE OF THIS PRODUCT.

## ----- SECTION III - PHYSICAL DATA -----

|                         |     |                   |       |
|-------------------------|-----|-------------------|-------|
| MELTING POINT:          | N/A | BOILING POINT:    | N/A   |
| PERCENT VOLATILE:       | N/A | EVAPORATION RATE: | N/A   |
| APPEARANCE: CLAY POWDER |     | SPECIFIC GRAVITY: | 1.912 |

## ----- SECTION IV - FIRE AND EXPLOSION DATA -----

D.O.T. CATEGORY: DRY PAINT FLASH POINT: N/A  
NON REGULATED

EXTINGUISHING MEDIA: Water, foam, CO2, etc.

UNUSUAL FIRE OR EXPLOSION HAZARDS: Use self-contained breathing devices for enclosed fires.

SPECIAL FIRE FIGHTING PROCEDURES: Possible toxic combustion products

## ----- SECTION V - HEALTH HAZARD DATA -----

THRESHOLD LIMIT VALUE: N/A TOXICITY: Not Toxic

EFFECTS OF OVEREXPOSURE: N/A

EMERGENCY & FIRST AID PROCEDURES: If hot material contacts bare skin, cool rapidly with cold water and secure medical treatment of a thermal burn.

## ----- SECTION VI - REACTIVITY DATA -----

## STABILITY

## CONDITIONS TO AVOID

:X: STABLE : : UNSTABLE Excessive heat during processing

INCOMPATIBILITY: N/A

HAZARDOUS DECOMPOSITION PRODUCTS: Combustion products may include CO, HCl.

HAZARDOUS POLYMERIZATION

: : MAY OCCUR

CONDITIONS TO AVOID: N/A

:X: WILL NOT OCCUR

## ----- SECTION VII - SPILL OR LEAK PROCEDURES -----

STEPS TO BE TAKEN IN CASE OF A SPILL OR LEAK: Good housekeeping procedures

WASTE DISPOSAL METHOD: Dispose in accordance to federal regulations

RESPIRATORY PROTECTION (specify type): N.I.O.S.H. approved dust respirator desirable but not necessary.

VENTILATION: Desirable

Protective Gloves: N/A

Eye Protection: Desirable

OTHER PROTECTIVE EQUIPMENT: N/A

## ----- SECTION IX - SPECIAL PRECAUTIONS -----

HANDLING AND STORAGE PRECAUTIONS: Store in a clean, dry area and keep container closed.

OTHER PRECAUTIONS: N/A