FORMULA RECORD

CONTROL LAB Cleveland T. S. DATE 8-18-54 REV. NO. 193

NAME S W P Woodland Brown CARD NO. 19

CUSTOMER Sherwin-Williams Co.

MFG. INSTR. *CAUTION:(8A12)POISON AVOID CONTACT WITH SKIN-USE GLOVES WHEN HANDLING.

Label Caution A1

WT./GAL 8.98 VISC. 30± 2 sec. @75°F

GRIND 5H VISC. on #3 cup

OUTPUT 100 BLEED

MFG. LOSS 2% DEPT. PKG.

STOR. LOSS MILL BATCHING

SOLIDS RATE/HR. LABEL ANALYSIS N

PARALLELS no PLASTICIZER LABEL: NO RED□ RED□

ROYALTY: YES □: NO □: X □: W □

REASON FOR REVISION To improve brushing.

FORMULATOR [signature] DEPT. 476

SEE CARD 100°F+

POUNDS	GALLONS	NEW MAT'L.	OLD MAT'L.
25	1.1	6324	2209
75	1.9	82C13	82C13
40	1.1	8280	1430
50	1.3	8260	1220
4	.3	7040	2501
3	.1	6805	18
100	11.1	BI 72	BI 72
?		BO 20	BO 20
?		AB 65	AB 65
?		BB 10	BB 10
166	22	(27C7)	(27C7)
60	8	(27A7)	(27A7)
23	3	(902)	(4230)
216	26	(3870)	(4106)
7	1	(948)	(543)
7	1	(1083)	(1767)
8	1	(8A12)	(8A12)*
133	20 1/4	(151)	(5027)

TO MATCH Neutral Oil Std. #92

APPLICATION: SURFACE Wood Ext. NO. COATS 1 & 2

UNDERCOATER USED Rx 450

METHOD 1 Brush

REDUCTION: AMOUNT ____ REDUCER USED ____

METHOD 2 ____

REDUCTION: AMOUNT ____ REDUCER USED ____

DRYING TIME: TOUCH 8-12hr RECOAT 2-4days STENCIL ____

HARD ____ SAND ____ HANDLE ____

TACK FREE ____ RUB ____ WRAP ____

BAKING TIME AND TEMP. ____

GLOSS Oil FILM ____

SPECIAL TESTS ____

REX. NO. 2493 Medium - 8-26-54

CARD NO. 19 Trade Sales "

DATE 8-18-54 Contract "

DATE	SHIP NO.	AMOUNT
Mpls	"	
Kan	"	
Wpeg	"	
Memphis	"	
Detroit	"	
Chicago	"	

FACTORY	FORMULA	SPEC. CARD
EXEC. COST DEPT.	"	
CLEVELAND A	"	
KENSINGTON C	"	8-26-54
PAINT RESEARCH	"	
KENS. TECH. SERV.	"	8-26-54
KENS. LACQUER		
NEWARK N	"	8-26-54
OAKLAND O	"	
M. SENOUR M	"	8-26-54
DETROIT D	"	
LOS ANGELES P	"	
DALLAS T	"	
DAYTON L	"	
GIBBSBORO F	"	
EXEC. MFG.	"	
CUBA H	"	
MONTREAL G	"	
BUENOS AIRES Z	"	
BRAZIL S	"	
RES ADM	"	

0007-SWP-062495

FORMULA RECORD 6

CONTROL LAB. Cleveland T. S. DATE 6-19-52 REV. NO. 193

NAME S W P Woodland Brown CARD NO. 13

POUNDS	GALLONS	MATERIAL NO.
175	8.3	2188 + +
95	2.8	1133 +
15	.4	1430 + +
30	.6	442 + +
110	3.1	1220 + +
2	.1	104 + +
6	.1	1128 + +
25	.5	89 +
?		BC 1, BB 10
4	1/2	(5094)
287	38 1/4	(2538)
70	9	(2)
23	3	(4230)
166	20	(4106)
7	1	(543)
3	1/2	(5026)
89	13 3/4	(348)

CUSTOMER Sherwin-Williams Co. Cr

TO MATCH Neutral Oil Std. #92

REASON FOR REVISION To show (2538) in place of (310). (2538) is (310) at 70% NVM.

VISCOSITY 25-30" @75°F AT ___ HRS. AFTER GRIND

VISCOSITY on #3 cup AT ___ HRS. AFTER GRIND

% SOLIDS (RUN) ___

WT./GAL. T 10.86

BAUME ___

STD. OF FINENESS 4H

NORMAL OUTPUT 100

EST. MFG. LOSS 2%

DEPARTMENT 30

PACKAGE ___

PARALLEL NO.'S No Parallel

ROYALTY; YES ☐; NO ☐; X ☐; W ☐

LABEL ANALYSIS CHECKED ___

LABEL: NO. RED ☐; RED ☐

NEW STD. SAMPLE REQUIRED ___

DATE REC'D ___

MILL Ball Mill BLEED? ___

LBS. OR GALS. PER HOUR 30

APPROVED ___

FORMULATOR PJS

SUPT. 8/16

MANUFACTURING INSTRUCTIONS:

1950-51 2046
50146

APPLICATION: SURFACE Wood Ext.

NO. COATS 1 & 2

UNDERCOATER USED Rx 450

METHOD 1 Brush

REDUCTION: AMOUNT REDUCER USED

METHOD 2

REDUCTION: AMOUNT REDUCER USED

DRYING TIME: TOUCH 8-10hrs RECOAT 2-1day STENCIL

HARD SAND HANDLE

TACK FREE RUB WRAP

BAKING TIME AND TEMP.

GLOSS Oil FILM Elastic

SPECIAL TESTS

Rex 493

DATE	STD NO.	AMOUNT
		52
		"
		"
		"
		"
		"
		"
		"

FACTORY	FORMULA	SPEC. CARD
EXEC. COST DEPT.	"	
CLEVELAND A	"	
KENSINGTON C	"	7-8-52
ALLIED RESEARCH	"	
KENS. TECH. SERV.	"	
KENS. LACQUER		
NEWARK N	"	7-8-52
OAKLAND O	"	
M. SENOUR M	"	7-8-52
DETROIT D	"	
LOS ANGELES P	"	
DALLAS T	"	
DAYTON L	"	
GIBBSBORO F	"	
EXEC. MFG.	"	
CUBA H	"	
MONTREAL G	"	
BUENOS AIRES Z	"	
BRAZIL S	"	
RES ADM	"	
MEXICO	"	

0007-SWP-062497

FORMULA RECORD 6

CONTROL LAB Cleveland T. S. DATE 12-19-51 REV. NO. 493

NAME S W P Woodland Brown CARD NO. 11

POUNDS	GALLONS	MATERIAL NO.
150	7.1	2188
260	9.1	2170
60	1.7	1220
1	.1	2501
15	.5	22
20	.4	12311
30	.6	412
25	.5	89
6	.1	1128
?	BY 20,	BB 10, BO 31
4	1/2	(5094)
201	25	(310)
70	9	(2)
65	10	(348)
165	20	(4106)
23	3	(4230)
7	1	(543)
3	1/2	(5026)
86	13 1/4	(348)

CUSTOMER Sherwin-Williams Co.

TO MATCH Neutral Oil Standard #92

REASON FOR REVISION Replacing 20 dry with 2188 dry for better texture, also increasing grind Limits.

VISCOSITY 25-30" @75°F ~~#3~~ H HRS. AFTER GRIND

VISCOSITY #3 cup AT HRS. AFTER GRIND

% SOLIDS (RUN)

WT./GAL T 11.6 4

BALANCE

STD. OF FINENESS 4H

NORMAL OUTPUT 200

EST. MFG. LOSS 2%

DEPARTMENT

PACKAGE

PARALLEL NO.'S No Parallel

ROYALTY: YES ☐; NO ☐; X ☐; W ☐

LABEL ANALYSIS CHECKED H

LABEL: NO. RED ☐; RED ☐

NEW STD. SAMPLE REQUIRED

DATE RECD.

MILL Ball Mill BLEEDS

LBS. OR GALS. PER HOUR

APPROVED

FORMULATOR

SUPT.

0007-SWP-062498

MANUFACTURING INSTRUCTIONS:

PREPARATION SURFACE Wood Det.

NO. COATS 2 & 2

UNDERCOATER USED Rx 150

METHOD 1 Brush

REDUCTION: AMOUNT _____ REDUCER USED _____

METHOD 2 _____

REDUCTION: AMOUNT _____ REDUCER USED _____

DRYING TIME: TOUCH 8-10hr RECOAT 2-4days STENCIL _____

HARD _____ SAND _____ HANDLE _____

TACK FREE _____ RUB _____ WRAP _____

BAKING TIME AND TEMP. _____

GLOSS Oil FILM Tough & Elastic

SPECIAL TESTS _____

Rex 493

DATE	SUPPLY	AMOUNT
1-2-52	Glass	1-2-52
"	Brass	"
"	Steel	"
"	Paint Rack	"
"	Chemical	"
"	Carlton	"
"	Marbon	"
"	Bert Bronson	"
"	Schaaf	"

FACTORY	FORMULA	SPEC. CARD
EXEC. COST DEPT.	"	
CLEVELAND A	"	
KENSINGTON C	"	1-2-52
ALLIED RESEARCH	"	
KENS. TECH. SERV.	"	
KENS. LACQUER		
NEWARK N	"	1-2-52
OAKLAND O	"	
H. SENOUR M	"	1-2-52
DETROIT D	"	
LOS ANGELES P	"	
DALLAS T	"	
DAYTON L	"	
GIBBSBORO F	"	
EXEC. MFG.	"	
CUBA H	"	
MONTREAL G	"	
BUENOS AIRES Z	"	
BRAZIL S	"	
RES ADM	"	
MEXICO	"	

0007-SWP-062499

FORMULA RECORD

A135

CONTROL LAB Cleveland T.S. DATE 3/30/50 REV. NO. 493

NAME S W P Woodland Brown CARD NO. 7

POUNDS	GALLONS	MATERIAL NO.
200	8.4	20
95	2.8	1133
15	.4	1430
30	.6	412
110	3.1	1220
2	.1	104
6	.1	1128
25	.5	89
~~?~~		~~BO 1~~
~~?~~		~~BB 10~~
4	1/2	(5094)
201	25	(48) or (310)
165	20	(4106)
70	9	(2)
65	10	(348)
23	3	(4230)
7	1	(543)
3 1/2	1/2	(4232)
3	1/2	(5026)
107	16 1/2	(348)

CUSTOMER Sherwin Williams Co.

TO MATCH Standard Neutral Oil Std #92 AST 5-17-50

REASON FOR REVISION To show (310) as alternate for (48) and add (5094).

VISCOSITY 25-30" @75 deg F. HRS. AFTER GRIND

VISCOSITY On #3 Cup AT HRS. AFTER GRIND

% SOLIDS (RUN)

WT./GAL. T 11.6

BAUME

STD. OF FINENESS 3H

NORMAL OUTPUT 100

ESTIMATED LOSS 2%

DILUENT

PACKAGE

PARALLEL NO.'S No parallel

ROYALTY: YES ☐ NO ☐ ALL ☐ WILL ☐

LABEL ANALYSIS CHECKED

LABEL NO. RED ☐ RED ☐

NEW STD. SAMPLE REQUIRED

DATE REC'D

MILL Ball Mill BLEED?

LBS. OR GALS. PER HOUR

APPROVED

FORMULATOR

SUPT.

CARD

0007-SWP-062500

MANUFACTURING INSTRUCTIONS:

APPLICATION: SURFACE Wood

NO. COATS 1 & 2

UNDERCOATER USED Rx 450

METHOD 1 Brush

REDUCTION: AMOUNT ____ REDUCER USED ____

METHOD 2 ____

REDUCTION: AMOUNT ____ REDUCER USED ____

DRYING TIME: TOUCH 6-8hrs RECOAT 2-4days STENCIL ____

HARD ____ SAND ____ HANDLE ____

TACK FREE ____ RUB ____ WRAP ____

BAKING TIME AND TEMP. ____

GLOSS Oil FILM Tough & Elastic

SPECIAL TESTS ____

493

DATE	SLIP NO.	AMOUNT
Mun	4/7/52	
Bayless	"	
[illegible]	"	
[illegible]	"	
Schuck	"	
DD	"	
F. Dyatt	"	
Caylor	"	
Porter	"	

FACTORY	FORMULA	SPEC. CARD
EXEC. COST DEPT.	"	
CLEVELAND A	"	
KENSINGTON C	"	4/7/52
ALLIED RESEARCH	"	
KENS. TECH. SERV.	"	
KENS. LACQUER		
NEWARK N	"	4/7/52
OAKLAND O	"	
M. SENOUR M	"	4/7/52
DETROIT D	"	
LOS ANGELES P	"	
DALLAS T	"	
DAYTON L	"	
GIBBSBORO F	"	
EXEC. MFG.	"	
CUBA H	"	
MONTREAL G	"	
BUENOS AIRES Z	"	
BRAZIL S	"	
RES ADM	"	
MEXICO	"	

FORMULA RECORD

CONTROL LAB Cleveland T.S. DATE 6/22/49 REF. NO. 4/3 ✓

NAME S W P Woodland Brown CARD NO. 6

POUNDS	GALLONS	MATERIAL NO.
200	8.4	20
95	2.8	1133
15	.4	1430
30	.6	412
110	3.1	1220
2	.1	104
6	.1	1128
25	.5	89
?		BO 1
? 4	1/2	BB 10 (509
201	25	(48)
165	20	(4106)
70	9	(2)
65	10	(348)
23	3	(4230)
7	1	(543)
3 1/2	1/2	(4232)
3	1/2	(5026)
107 ~~111~~	~~17~~ 16½	(348)

CUSTOMER Sherwin Williams Co.

TO MATCH Standard Lr

REASON FOR REVISION To improve color an quality.

VISCOSITY 25-30" @75 deg F ___ HRS. AFTER G

VISCOSITY On #3 Cup AT ___ HRS. AFTER G

% SOLIDS (RUN) ___

WT./GAL. T 11.07

BAUME ___

STORMER FINENESS 3H

NORMAL PRODUCTION 200

EST. MFG. LOSS 2%

DEPARTMENT ___

PACKAGE ___

PARALLEL NO.'S ___

ROYALTY: YES ☐; NO ☐; X ☐; V ☐

LABEL ANALYSIS CHECKED-DATE 12-28-49

LABEL: NO. RED ☐; RED ☐

NEW STD. SAMPLE REQUIRED ___

DATE REC'D ___

MILL Ball Mill BLEED? ___

LBS. OR GALS. PER HOUR ___

APPROVED ___

FORMULATOR [signature]

SUPT. [signature]

0007-SWP-062502

MANUFACTURING INSTRUCTIONS:

APPLICATION: SURFACE Wood Bldg

NO. COATS 1 & 2

UNDERCOATER USED 450

METHOD 1: Brush

REDUCTION: AMOUNT _____ REDUCER USED _____

METHOD 2: _____

REDUCTION: AMOUNT _____ REDUCER USED _____

DRYING TIME: TOUCH 6hrs RECOAT 2-4days STENCIL _____

HARD _____ SAND _____ HANDLE _____

TACK FREE _____ RUB _____ WRAP _____

BAKING TIME AND TEMP. _____

GLOSS Oil FILM Tough, Elastic

SPECIAL TESTS _____

493

DATE	SLIP NO.	AMOUNT
M. Schwartz	7-22-49	
[illegible]	6-23-49	
[illegible]	"	
[illegible]	"	
[illegible]	"	
[illegible]	"	
[illegible]	"	

FACTORY	FORMULA	SPEC. CARD
EXEC. COST DEPT.	6-23-49	
CLEVELAND A	"	
KENSINGTON C	"	6-23-49
ALLIED RESEARCH	"	
KENS. TECH. SERV.	"	
KENS. LACQUER	"	
NEWARK N	"	
OAKLAND O	"	
M. SENOUR M	"	
DETROIT D	"	
LOS ANGELES P	"	
DALLAS T	"	
DAYTON I	"	
GIBSBORO F	"	
EXEC. MFG.	"	
CUBA H	"	
MONTREAL G	"	
BUENOS AIRES Z	"	
BRAZIL S	"	
RES ADM	"	
MEXICO	"	

0007-SWP-062503

FORMULA RECORD · 6

CONTROL LAB Cleveland T. S. DATE 6-1-52 REC. NO. 493

NAME S W P Woodland Brown CARD NO. 12

POUNDS	GALLONS	MATERIAL NO.
175	8.3	2188
95	2.8	1133
15	.4	1430
30	.6	412
110	3.1	1220
2	.1	104
6	.1	1128
25	.5	89
?		BO 1
?		BB 10
4	1/2	(5094)
201	25	(6310)
70	9	(2)
22 1/2	3	(4230)
65	10	(348)
166	20	(4106)
7	1	(543)
3	1/2	(5026)
111	17	(348)

CUSTOMER Sherwin-Williams Co.

TO MATCH Neutral Oil Standard #92

REASON FOR REVISION Showing Ferrite replacement for 2170 dry and 12311 dry.

VISCOSITY 25-30" @ 75° F AT HRS. AFTER GRIND

VISCOSITY QTL #3 cup AT HRS. AFTER GRIND

% SOLIDS (RUN)

WT./GAL. T 10.86

BAUME

STD. OF FINENESS 4H

NORMAL OR PLUS 00

EST. MFG. LOSS %

DEPARTMENT

PACKAGE

PARALLEL NO.'S No Parallel

ROYALTY: YES CHARGED CREDITED

LABEL ANALYSIS CHECKED

LABEL: NO. USED CHANGED

NEW STD. SAMPLE REQUIRED

DATE REC'D

MILL: Bell Mill BLEED?

LBS. OR GALS. PER HOUR

APPROVED

FORMULATOR

SUPT.

0007-SWP-062504

MANUFACTURING INSTRUCTIONS:

APPLICATION: SURFACE Wood Ext. NO. COATS 1 & 2

UNDERCOATER USED Rx 450

METHOD 1 Brush

REDUCTION: AMOUNT REDUCER USED

METHOD 2

REDUCTION: AMOUNT REDUCER USED

DRYING TIME: TOUCH 8-10hrs RECOAT 2-4days STENCIL

HARD SAND HANDLE

TACK FREE RUB WRAP

BAKING TIME AND TEMP.

GLOSS Oil FILM Elastic

SPECIAL TESTS

Rex 493

DATE	SLIP NO.	AMOUNT
Geo Prusa	6	6-10-52
Mimi Bigelow	"	"
Ignatz Gates	"	"
Paul Post	"	"
Geo Cardarelli	"	"
Charles Brown	"	"
Rex	"	"
Lorraine	"	"
Schaeffer	"	"

FACTORY	FORMULA	SPEC. CARD
EXEC. COST DEPT.	"	
CLEVELAND A	"	
KENSINGTON C	"	6-10-52
ALLIED RESEARCH	"	
KENS. TECH. SERV.	"	
KENS. LACQUER		
NEWARK N	"	6-10-52
OAKLAND O	"	
M. SENOUR M	"	6-10-52
DETROIT D	"	
LOS ANGELES P	"	
DALLAS T	"	
DAYTON L	"	
GIBBSBORO F	"	
EXEC. MFG.	"	
CUBA H	"	
MONTREAL G	"	
BUENOS AIRES Z	"	
BRAZIL S	"	
RES ADM	"	
MEXICO	"	

FORMULA RECORD 6

CONTROL LAB Cleveland T. S. DATE 6-13-51 REV. NO. 493

NAME S W P Woodland Brown CARD NO. 10

POUNDS	GALLONS	MATERIAL NO.
175	7.4	20
260	9.1	2170
60	1.7	1220
1	.1	2501
15	.5	22
20	.4	12311
30	.6	412
6	.1	1128
25	.5	89
?	BY 20.80	31. BB 10
4	1/2	(5094)
201	25	(310)
165	20	(4106)
65	10	(348)
70	9	(2)
23	3	(901)
7	1	(543)
3	1/2	(5026)
84	13	(348)

CUSTOMER Sherwin-Williams Co.

TO MATCH Neutral Oil Standard #92

REASON FOR REVISION Showing replacement for Ferrite.

VISCOSITY 25-30" @ 75° F. KU HRS. AFTER GRIND

VISCOSITY ON #3 CUP HRS. AFTER GRIND

% SOLIDS (RUN)

WT./GAL. 11.87

BAUME

STR. OF FINENESS 3H

NORMAL OUTPUT 200

EST. MFG. LOSS

DEPARTMENT

PACKAGE

PARALLEL NO.'S No Parallel

ROUTINE NO. CHECK

LABEL ANALYSIS CHECKED

LABEL CHG.; REVISE; REDO

NEW STD. SAMPLE REQUIRED

DATE REC'D

Ball Mill BLEED?

LBS. OR GALS. PER HOUR 18hrs

APPROVED

FORMULATED

SUPT.

0007-SWP-062506

493

MANUFACTURING INSTRUCTIONS:

APPLICATION: SURFACE Wood

NO. COATS 1 & 2

UNDERCOATER USED Rx 450

METHOD 1 Brush

REDUCTION: AMOUNT _____ REDUCER USED _____

METHOD 2 _____

REDUCTION: AMOUNT _____ REDUCER USED _____

DRYING TIME: TO TOUCH 6-8 hrs RECOAT 1 day STENCH _____

HARD _____ SAND _____ HANDLE _____

TACK FREE _____ RUB _____ WRAP _____

BAKING TIME AND TEMP. _____

GLOSS Oil FILM Tough & Elastic.

SPECIAL TESTS _____

SHIPPED TO	SHIPPED OR CAT	AMOUNT
Schaeffer		
Warren Bryan	6-15-37	
Parkmoor	"	
Fort	"	
Lebanon	"	
Walkerton	"	
Salem	"	
Olympia	"	
Fortune	"	
Compton	"	

FACTORY	FORMULA	SPEC. CARD
CHEM. COST DEPT.	"	
CLEVELAND A	"	
KENSINGTON C	"	6-15-37
ALLIED RESEARCH	"	
KENS. TECH. SERV.	"	
KENS. LACQUER		
NEWARK N	"	6-15-37
OAKLAND O	"	
N. SENOUR M	"	6-15-37
DETROIT D	"	
LOS ANGELES P	"	
DALLAS T	"	
DAYTON	"	
GIBSONBURG	"	
[illegible] MFG.	"	
CU	"	
[illegible]	"	
BUENOS AIRES	"	
BRAZIL S	"	
RES ADM.	"	
MEXICO	"	

0007-SWP-062507

FORMULA RECORD 6

CONTROL LAB Cleveland T. S. DATE 1-5-51 REV. NO. 493

NAME S W P Woodland Brown CARD NO. 9

POUNDS	GALLONS	MATERIAL NO.
200	8.4	20
95	2.8	1133
15	.4	1430
30	.6	412
110	3.1	1220
2	.1	104
6	.1	1128
25	.5	89
~~?~~		BO 1
~~?~~		BB 10
~~4~~	~~1/2~~	(5094)
~~201~~	~~25~~	~~(48) or (310)~~
~~165~~	~~20~~	(4106)
70	9	(2)
65	10	(348)
~~7~~	~~1~~	(543)
23	3	(901) or (900)
3	1/2	(5026)
110	17	(348)

CUSTOMER Sherwin-Williams Co

TO MATCH Neutral Oil Standard #92

REASON FOR REVISION To show Sherwin-Williams Mfg. Driers and also Purchased Tallate Driers.

VISCOSITY 25-30" #3 CUP AT 77° F HRS. AFTER GRIND

VISCOSITY on #3 cup AT HRS. AFTER GRIND

% SOLIDS (RUN)

WT./GAL. T 11.09

BAUME

STD. OF FINENESS 3H

NORMAL OUTPUT 100

EST. MFG. LOSS 2%

DEPARTMENT

PACKAGE

PARALLEL NO.'S No Parallel

ROYALTY YES ☐ NO ☐ X ☐

LABEL ANALYSIS CHECKED

LABEL NO. RED ☐ RED ☐

NEW STD. SAMPLE REQUIRED

DATE REC'D

Mills Ball Mill BLEED?

LBS. OR GALS. PER HOUR

APPROVED

FORMULATOR

SUPT.

0007-SWP-062508

MANUFACTURING INSTRUCTIONS:

APPLICATION: SURFACE Wood

NO. COATS 1 & 2

UNDERCOATER USED Rx 450

METHOD 1 Brush

REDUCTION: AMOUNT _____ REDUCER USED _____

METHOD 2 _____

REDUCTION: AMOUNT _____ REDUCER USED _____

DRYING TIME: TOUCH 6-8hrs RECOAT 2-4days SWERCIL _____

HARD _____ SAND _____ HANDLE _____

TACK FREE _____ RUB _____ WRAP _____

BAKING TIME AND TEMP. _____

GLOSS Oil FILL Tough & Elastic

SPECIAL TESTS _____

Rex 493

DATE	SLIP NO.	AMOUNT
Harry Bayer	1-12-57	
W. Fay	"	
Schwartz	"	
Bashwinger	"	
Culver	"	
Ehlert	"	
Dyer	"	
Bourget	"	

FACTORY	FORMULA	SPEC. CARD
EXEC. COST DEPT.	"	
CLEVELAND A	"	
KENSINGTON C	"	1-12-57
ALLIED RESEARCH	"	
KENS. TECH. SERV.	"	
KENS. LACQUER		
NEWARK N	"	1-17-57
OAKLAND O	"	
N. SENOUR M	"	1-12-57
DETROIT D	"	
LOS ANGELES P	"	
DALLAS T	"	
DAYTON L	"	
GIBBSBORO F	"	
EXEC. MFG.	"	
CUBA H	"	
MONTREAL G	"	
BUENOS AIRES Z	"	
BRAZIL S	"	
RES ADM	"	
MEXICO	"	

0007-SWP-062509

FORMULA RECORD 6

A135

CONTROL LAB Cleveland T. P. DATE 5-17-50 REV. NO. 493

NAME S W P Woodland Brown CARD NO. 8

POUNDS	GALLONS	MATERIAL NO.
200	8.4	20
95	2.8	1133
15	.4	1430
30	.6	412
110	3.1	1220
2	.1	804
6	.1	1128
25	.5	89
?		BO 1
4 ?	1/2	BB 10 (5094)
201	25	(48) or (310)
165	20	(4106)
70	9	(2)
65	10	(348)
~~9?~~	~~?~~	~~(2 30)~~ (90) or (890)
7	1	(543)
~~3-1/2~~	~~1/2~~	~~(4232)~~
3	1/2	(5026)
110 ~~107~~	~~16 1/2~~ 17	(348)

CUSTOMER Sherwin-Williams Co.

TO MATCH Neutral Oil Standard #92

REASON FOR REVISION To show Neutral Oil Standard #92.

VISCOSITY 25-30" @ 75° deg. F. HRS. AFTER GRIND

VISCOSITY #3 CUP @ AT HRS. AFTER GRIND

% SOLIDS (RUN)

WT./GAL. T 11.09

BAUME

STD. OR FINENESS 3H

NORMAL OUTPUT 100

EST. MFG. LOSS 2%

DEPTH (MIN)

PACKAGE 5-51

PARALLEL NO.'S No Parallel

ROYALTY: YES ☐; NO ☐; X ☐; W ☐

LABEL ANALYSIS CHECKED-DATE 12-8-50

LABEL NO. RED ☐; RED ☐

NEW STD. SAMPLE REQUIRED

DATE REC'D

MILL Ball-Mill BLEED?

LBS. OR GALS. PER HOUR

APPROVED

FORMULATOR

SUPT.

MANUFACTURING INSTRUCTIONS:

APPLICATION: SURFACE Wood

NO. COATS 1 & 2

UNDERCOATER USED Rx 450

METHOD 1 Brush

REDUCTION: AMOUNT _____ REDUCER USED _____

METHOD 2 _____

REDUCTION: AMOUNT _____ REDUCER USED _____

DRYING TIME: TOUCH 6-8hrs RECOAT 2-4days STENCIL _____

HARD _____ SAND _____ HANDLE _____

TACK FREE _____ RUB _____ WRAP _____

BAKING TIME AND TEMP. _____

GLOSS Oil - FILM Tough & Elastic

SPECIAL TESTS _____

Rex 493

DATE	SLIP NO.	AMOUNT
Meany	5/19/52	
Dayton	"	
Lester	"	
DD	"	
Gibbsboro	"	
Clayton	"	
Detroit	"	
Schmidt	"	

FACTORY	FORMULA	SPEC. CARD
EXEC. COST DEPT.	"	
CLEVELAND A	"	
KENSINGTON C	"	5/19/52
ALLIED RESEARCH	"	
KENS. TECH. SERV.	"	
KENS. LACQUER		
NEWARK N	"	5/19/52
OAKLAND O	"	
M. SENOUR M	"	5/19/52
DETROIT D	"	
LOS ANGELES P	"	
DALLAS T	"	
DAYTON I	"	
GIBBSBORO F	"	
EXEC. MFG.	"	
CUBA H	"	
MONTREAL G	"	
BUENOS AIRES Z	"	
BRAZIL S	"	
RES ADM	"	
MEXICO	"	

0007-SWP-062511

FORMULA RECORD

A135 WHITE

Ex. No. [illegible] Date 4/23/48 Class 6 Rex. No. 493 4

Name [illegible] W P Woodland Brown Card No. Replaces No.

POUNDS	GALLONS	MATERIAL No.
166		20 F
40		1133
40		1430
24	414 F) or 60#	
36	511) 412	
1		104
130		1220
6		1128
25		89
39 5		(2325)
112 14		(48)
85 30		(2)
1 1/2 1		(4090)
7 1		(4221)
3 1/2	1/2	(4633)
1 1/2 2		(3231)
60 8	(4990)G or (2841)G	
43 1/4 9	3/4	(348)
136 17		(46)
3 1/4	1/2	(5026)

Customer Sherwin Williams Co.

To Match Standard

Reason for Revision To use a 414 and 511 combination.

Viscosity 25-30-275 deg F at hrs. after grind

Viscosity #3 Cup at hrs. after grind

% Solids (Run)

Wt./Gal. 10.71

Baume

Std. of Fineness

Normal Output 100 V

Est. Mfg. Loss 2%

Department

Package

Parallel No.'s

Royalty: Yes ☐; No ☐ X ☐ W ☐

Label Analysis Checked-Date

Label: No Red ☐; Red ☐

New Std. Sample Required

Date Rec'd

Mill Mill Bleed? hrs.

Lbs. or Gals. per hour 5/4/48

Approved

Formulator K F Dauer

Supt. [illegible]

0007-SWP-062512

MANUFACTURING INSTRUCTIONS:

Application: Surface Buildings No. Coats 1 & 2

Undercoater Used No. Coats

Method 1 Brush

Reduction: Amount Reducer Used

Method 2

Reduction: Amount Reducer Used

Drying Time: Touch 4-6hrs Recoat 4-5days Stencil

Hard Sand Handle

Tack Free Rub Wrap

Baking Time and Temp.

Gloss Oil Film Flexible, Hard & Elastic

Special Tests

CS 5/14/48

DATE	SLIP No.	AMOUNT
1/18/48	7/6649	
Lee	4/19/49	
Nyleen	5/5/48	
Bepex	"	
Otten	"	
Carlson	"	

FACTORY		FORMULA	SPEC. CARD
Exec. Cost Dept.		"	
Cleveland	A	" Chg 3/23/49	5/5/48
Kensington	C	"	
Allied Research		"	
Kens. Tech. Serv.		"	
Kens. Lacquer			
Newark	N	"	
Oakland	O	"	
M. Senour	M	"	
Detroit	D	"	
Los Angeles	P	" Chg 4/14/49	
Dallas	T	"	
Dayton	B	"	
Gibbsboro	F	"	
Pittsburgh	H		
Cuba	V	"	
Montreal		"	
Buenos Aires	Z	"	
Brazil		"	
[illegible]		"	

0007-SWP-062513

FORMULA RECORD

A135 WHITE

Exp. No. ____ Date 3/15/48 Class 6 Rex. No. 493

Name S W P Woodland Brown Card No. ____ Replaces No. 3

POUNDS	GALLONS	MATERIAL No.
166		20 F
40		1133
40		1430
60		412
1		104
110		1220
6		1128
25		89
39	5	(2325)
112	14	(48)
85	11	(2)
9 1/2	1	(4090)
7	1	(4231)
3 1/2	1/2	(4232)
130	20	(348)
60	8	(4950)G on
63 1/4	9 3/4	(348)
136	17	(48)
3 1/4	1/2	(5026)
Ball Mill Slush Grind 5hrs.		*(2841)G

Customer Sherwin Williams Co.

To Match Standard LR

Reason for Revision To improve initial gloss and give closer match to standard

Viscosity 25-30" @ 75 Deg. F. ____ hrs. after grind

Viscosity On #3 Cup ____ at ____ hrs. after grind

% Solids (Run) ____

Wt./Gal. T 10.76

Baume ____

Std. of Fineness 3H

Normal Output ____

Est. Mfg. Loss 2%

Department ____

Package ____

Parallel No.'s ____

Royalty: Yes ☐ No ☐ X ☐ W ☐

Label Analysis Checked-Date ____

Label: No Red ☑ Red ☐

New Std. Sample Required ____

Date Rec'd ____

Mill Ball Mill Bleed? ____

Lbs. or Gals. per hour ____

Approved ____

Formulator Kaiser James

Supt. ____

0007-SWP-062514

MANUFACTURING INSTRUCTIONS:

Application: Surface Buildings No. Coats 1 & 2

Undercoater Used No. Coats

Method 1 Brush

Reduction: Amount Reducer Used

Method 2

Reduction: Amount Reducer Used

Drying Time: Touch 6hrs. Recoat 4-5days Stencil

Hard Sand Handle

Tack Free Rub Wrap

Baking Time and Temp.

Gloss Oil Film Med. Hard, Elastic

Special Tests

DATE	SLIP No.	AMOUNT
Myers	3/24/48	
Eyers	"	
Cotton	"	
Carlson	"	

FACTORY		FORMULA	SPEC. CARD
Exec. Cost Dept.		"	
Cleveland	A	"	3/24/48
Kensington	C	"	
Allied Research		"	
Kens. Tech. Serv.		"	
Kens. Lacquer			
Newark	N	"	
Oakland	O	"	
M. Senour	M	"	
Detroit	D	"	
Los Angeles	P	"	
Dallas	T	"	
Dayton	B	"	
Gibbsboro	F	"	
Pittsburgh	H	"	
Cuba	V	"	
Montreal		"	
Buenos Aires	Z	"	
Brazil		"	
Glamm		"	
T-S			

0007-SWP-062515

FORMULA RECORD — A135 WHITE

Exp. No. ____ Date 11/19/47 Class 6 Rec. No. 493

Name S W P Woodland Brown Card No. 3 Replaces No. 2

POUNDS	GALLONS	MATERIAL No.
220		20 L
80		1133
60		412
2		104
120		1220
6		1128
25		89
39	5	(2325)
104	13	(48)
85	11	(2)
9 1/2	1	(4090)
7	1	(4231)
3 1/2	1/2	(4232)
130	20	(348)
60	8	(4950)G or(2841)G
52	8	(348)
136	17	(48)
3 1/4	1/2	(5026)
Ball Mill		Slush Grind Smgs.

Customer Sherwin Williams Co.

To Match Std.

Reason for Revision To use (2325)

Viscosity 25-30" @ 77 deg F. at ____ hrs. after grind

Viscosity On #4 Cup at ____ hrs. after grind

% Solids (Run) T 11.22

Wt./Gal.

Baume

Std. of Fineness 3H

Normal Output 100

Est. Mfg. Loss 2%

Department

Package

Parallel No.'s

Royalty: Yes □; No □; X □; W

Label Analysis Checked-Date

Label: No Red □; Red □

New Std. Sample Required

Date Req'd

Mill Ball Bleed?

Lbs. or Gals. per hour

Approved

Formulator Sam Hay

Supt. SHP

0007-SWP-062516

MANUFACTURING INSTRUCTIONS:

Application: Surface Buildings No. Coats 1 & 2

Undercoater Used No. Coats

Method 1 Brush

Reduction: Amount Reducer Used

Method 2

Reduction: Amount Reducer Used

Drying Time: Touch 6hrs. Recoat 4-5days Stencil

Hard Sand Handle

Tack Free Rub Wrap

Baking Time and Temp.

Gloss Oil Film Med. Hard, Elastic

Special Tests

DATE	SLIP No.	AMOUNT
Mann	12/12/47	
Graham	"	
Carlton	"	

FACTORY		FORMULA	SPEC. CARD
Exec. Cost Dept.		"	
Cleveland	A	"	
Kensington	C	"	12/12/47
Allied Research		"	
Kens. Tech. Serv.		"	
Kens. Lacquer			
Newark	N	"	
Oakland	O	"	
M. Senour	M	"	
Detroit	D	"	
Los Angeles	P	"	
Dallas	T	"	
Dayton	B	"	
Gibbsboro	F	"	
Pittsburgh	H		
Cuba	V	"	
Montreal		"	
Buenos Aires	Z	"	
Brazil		"	
Mann		"	
4-5		"	

0007-SWP-062517

FORMULA RECORD

Exp. No. _____ Date 4/8/45 Class 6 Rex. No. 423

Name S W P Woodland Brown Card No. 2 Replaces No. 1

POUNDS	GALLONS	MATERIAL No.
220		20 L
30		1133
50		412
2		104
320		1220
5		1128
	~~38~~ 15½	(48) (23/45=)
	11	(2)
	1	(4090)
	1	(4231)
	1/2	(4232)
	20	(348)
	1/2	(5026)
	8	(4950) G
	9	(348)
	17	(48)

Ball Mill slush grind 5hrs.

164

Customer S W Co.

To Match Std.

Reason for Revision Replacing (2325) and (1157) with (48) and (4950)G

6/24/47 HH.

Viscosity #A-3 @25-30" @75° at hrs. after grind

Viscosity On Cup at hrs. after grind

% Solids (Run)

Wt./Gal. 11.00

Baume

Std. of Fineness 3H

Normal Output 100

Est. Mfg. Loss 2%

Department

Package

Parallel No.'s

Royalty: Yes □; No □; X □; W □

Label Analysis Checked-Date

Label: No Red □; Red □

New Std. Sample Required

Date Rec'd

Mill Ball Bleed?

Lbs. or Gals. per hour

Approved

Formulator

Supt.

0007-SWP-062518

MANUFACTURING INSTRUCTIONS:

Application: Surface Buildings No. Coats 1 & 2

Undercoater Used No. Coats

Method 1 Brush

Reduction: Amount Reducer Used

Method 2

Reduction: Amount Reducer Used

Drying Time: Touch 6Hrs. Recoat 4-5days Stencil

Hard Sand Handle

Tack Free Rub Wrap

Baking Time and Temp.

Gloss Off Film Med. Hard, Elasti

Special Tests

c/ 3/29/47 c8 5/23/47 c8 6/24/47

493

DATE	SLIP No.	AMOUNT
N. Mills	2-24-47	

FACTORY		FORMULA	SPEC. CARD
Exec. Cost Dept.		59-46	
Cleveland	A	11	
Kensington	C	11	5-9-46
Allied Research		11	
Kens. Tech. Serv.		11	
Kens. Lacquer			
Newark	N	11	
Oakland	O	11	
M. Senour	M	11	
Detroit	D	11	
Los Angeles	P	11	
Dallas	T	11	
Dayton	B	11	
Gibbsboro	F	11	
Pittsburgh	H		
Cuba	V	11	
Montreal		11	
Buenos Aires	Z	11	
Brazil		11	
Plant		11	
ES		11	

0007-SWP-062519

FORMULA RECORD

A135 WHITE 1-45 3043

Exp. No. _____ Date 8-29-45 Class 6 TS Rex. No. 403 Y

Name S W P Woodland Brown Card No. _____ Replaces No. _____

POUNDS	GALLONS	MATERIAL No.
220		20 L
80		1133
60		412
2		104
120		1220
6		1128
	1/2	(5026)
	10	(2325)
	c	(48)
	8 1/2	(2)
	5	(ADD)
	1	(4090)
	1	(4231)
	1/4	(4232)
	20	(348)
	20 1/2	(48)
	10	(348)

NO. ADD

Customer S.W.CO.

To Match STD.

3.74 lb oil/B a.m. 9-11-45

Reason for Revision Re-Aligning Trade Sale Rex-numbers. per letter V.Mill 7/30/45.

SUPERSEDES REX-393

Viscosity 20-26" @75° #3 at hrs. after grind

Viscosity #4 at hrs. after grind

% Solids (Run)

Wt./Gal. T 11.06

Baume

Std. of Fineness 3H

Normal Output 100

Est. Mfg. Lbs. 2%

Department M

Package

Parallel No.'s

Royalty Yes □; No □; X □; W □

Label Analysis Checked-Date

Label: No Red □; Red □

New Std. Sample Required yes

Date Rec'd 10-1-45

Mill Ball Bleed?

Lbs. of Sols. per hour

Approved

Formulator Wm Budnick

Supt. [signature]

0007-SWP-062520

MANUFACTURING INSTRUCTIONS:

Application: Surface Buildings No. Coats
Undercoater Used No. Coats 1 & 2

Method 1 Brush
Reduction: Amount Reducer Used
Method 2
Reduction: Amount Reducer Used

Drying Time: Touch Recoat Stencil
Hard Sand Handle
Tack Free Rub Wrap
Baking Time and Temp
Gloss Oil Film Fish Hard, Elast
Special Tests

Send back after 8/31/45

DATE	SLIP No.	AMOUNT

FACTORY		FORMULA	SPEC. CARD
Exec. Cost Dept.		9-7-45	
Cleveland	A	9-6-45	
Kensington	C	"	9-7-45
Allied Research		"	
Kens. Tech. Serv.		"	
Kens. Lacquer			
Newark	N	"	
Oakland	O	"	
M. Senour	M	"	
Detroit	D	"	
Los Angeles	P	"	
Dallas	T	"	
Dayton	B	"	
Gibbsboro	F	"	
Pittsburgh	H		
Cuba	V	"	
Montreal		"	
Buenos Aires	Z	"	
Brazil		"	
25		"	

0007-SWP-062521