Final Report upon the Physical Condition and the [illegible] of 101 Employees in the U.S.Gypsum Plant at [illegible].

by the Saranac Laboratory.
August 1933.

PLAINTIFF'S EXHIBIT
MET-355

The following report is submitted on the study begun on June 19, 1933, of the dust hazard in the Oakfield plant of the U.S Gyps[illegible]

A SURVEY OF THE PLANT was first made and our impressions were fully discussed in the preliminary report of June 27, 1933. Briefly these observations yielded the following points which were regarded as significant:

The mine apparently offered no particular hazard as the ventilation was excellent, the operating methods generated no great amount of dust and the rock and ore were [illegible] damage.

The portions of the plant devoted to crushing, calcining and grinding gypsum were quite dusty but owing to the nature of the dust this was not considered hazardous except in one particular. Certain grinding operations are done in [illegible] stone mills. The stones themselves of quartz contained high percentages of crystalline [illegible] which in a well-recognized cause of pulmonary fibrosis. [illegible] particular stress was laid upon the possibility [illegible]ecting the man or men who dress the buhr stones [illegible] persons would be subjected to dangerous quanti-

PCC
EXHIBIT
MET-085

tion of high temperature cure.

[illegible] mill, sand plant, power [illegible] sand plasters involved exposures to considerable quantities of free silica. The lack of any protection for the operators appeared to expose the workmen to grave hazard. The Bates Packer, #12, and the mixing done by men on the second [illegible]

DUST SAMPLING - Representative samples have been taken from various portions of the plant and mine at the points where men might be exposed. The method employed has been the standard procedure of the U.S. Bureau of Mines, which depends upon the collection of dust and settling particles in a Wedgewood-Greiner [illegible] Both methods were used with the other methods of dark field illumination, one at a magnification of 100 and another at 430. By the use of the higher magnification and the dark field illumination smaller particles are visualized than can be detected by the standard procedure.

[illegible] a tabulation of the [illegible] dust:

Sample No.1 June 10, 1932

Location: 1st.West - 1st.South - 14 Ft.Main South - Ft.Entry.

Operation: Drilling in Gypsum

Time: First Hole Second Hole
Started 10:00 Started 11:[illegible]
Finished 11:[illegible]

Air Pressure: 21 lbs.

Notes: Electric Drill. Drilled one hole. Started second at time of sample. 2 min. breaking through ten feet. Rose 4 ft. Height to impinger 3 ft. 3 to 4 ft. from floor. Fall of material not heavy. [illegible] Hole dripping - drilling place 22 deg.

Remarks: The [illegible] [illegible] [illegible]

ple No. 3 [illegible]

Location: Room 87 - 18 Rt. 3rd South - 11 Rt. Main South

Operation: Drilling in Gypsum

Time: Started: 10:37
Finished: 10:57

Air Pressure: 32 lbs.

[illegible]: [illegible] Drilled 2 holes. Dead ended - air in from nearby room. No marking. Roof 3 1/2 ft.

Counts: Number of particles [illegible] per cu.ft. of air.

Light Field		1,[illegible]
Dust	" Illumination	2,[illegible]
"	" [illegible]	[illegible]

Remarks: The [illegible] light field count is [illegible]

The average standard light field count of Sample No.1 and No.2 is approximately 1,800,000

Sample No. 4 [illegible]

Location: [illegible] - 2nd South - 6th [illegible] South - 2nd Entry

Operation: Drilling in anhydrite

Time: Started 11:10
Finished 11:39
29 minutes

Noted: Air machine - Auto. feed - 1" Drill. No [illegible].

Counts: Number of particles (less than 10 u) per cu.ft. of air.

Light field		10,100,000
Dark	[illegible]	[illegible]
Dark	Diffracting	40,000,000

[illegible] Light field [illegible] this study [illegible] - Static Precipitation which does not exceed 1 million at the minimum.

Sample No.5 [illegible]

Location: 1st.West - 3rd South - 11th Rt.Main South - 3rd Entry

Operation: Drilling in anhydrite

Time: Started: 11:34
Finished 11:44
10 minutes

Notes: Air machine - Auto.feed - 1" Drill. No smoking.
[illegible]

Counts: Number of particles (less than 10 μ) per cu.ft.of air.

Light field		11,000,000
Light	" Plankton	24,000,000
Light	" Blastering	71,000,000

Results: The [illegible] light field count is approx. 11,000,000 per c.f. silica concentration which does not exceed 0.5% silica at the maximum.

[illegible] sample No. [illegible] approximately 11,000,000

mple No.C

Location: Weighing floor

Operation: Weighing and Crushing

Time: Started 1:36
Finished 1:59

Notes: One car per chute (2 chutes) dumped [illegible]
center of chute.

Counts: Number of particles less than 10 u per cu.ft.of air.

[illegible]	[illegible]	[illegible]
Dust	" Filtration	[illegible]
Dust	" Settling	[illegible]

Results: The effective light field count is approximately 2,000,000 with low silica concentration.

Sample No.7 [illegible]

Location: Set-up next to top at elevator at conveyer belt (conveyer belt was carrying gypsum)

Operation: Conveying and storage of crushed gypsum

Time: Started 2:31 2/3
Finished [illegible]

[illegible]

Weather: [illegible]
1 ft. above conveyer belt. Note: windows open and strong draft across floor.

Remarks: Number of particles /[illegible] than 11 u) per cu.ft. of air.

[illegible]		4,111,[illegible]
[illegible]	[illegible]	[illegible]
[illegible]	[illegible]	[illegible]

Remarks: The [illegible] light field count is approximately 4,[illegible] [illegible] value. [illegible]

Sample No. 3. [illegible]

Location: Set-up next to [illegible] building cement-mill area. Level with ground. Windward and close to mill.

Operation: Packing gypsum plaster in [illegible] in mill [illegible].

Plaster Fine Dust

Air Pressure: 40 lbs.

Notes: Machine used: This machine has exhaust system. Two bags are used. From machine was operating, but bag was torn, allowing dust to escape around machine. Outside of mill dusty. Mill was not busy. Not a good sample from operating viewpoint.

Results: Sample #1 [illegible] particles [illegible] than 10 μ, per cu. ft. of air;

[illegible]	[illegible]
[illegible]	[illegible]

Remarks: The standard light field count is approximately 12,000,000 with a low silica concentration.

Unknown

Sample No. 1 June 20, 1933

Location: Set-up next to [illegible] machine printing wall-paper plaster. Close to operator as for sample #8.

Operation: Printing wall-paper plaster in paper [illegible]

Time: Started: 7:00
[illegible] minutes

Air Pressure: 40 lbs.

Notes: Fan over intake 10 ft. from machine was operating, blowing air from intake, under operator, toward machine. Finishing grain, most light, medium and large amount of blue (10% per ten). No sanded plaster being made at present time.

[illegible] particles (less than 10 μ) per cu. ft. of air:

Light field		18,100,000
Dark	" Plankton	[illegible]
Dark	" Dissecting	80,000,000

Remarks: The standard light field count is approximately 18,000,000 with a low silica concentration.

Sample No. 10. [illegible]

Location: Set-up next to [illegible] machine. Packing jute bags with gypsum.

Operation: Packing gypsum plaster in jute bags on machine provided with exhaust system.

Finished: [illegible]

[illegible]: 40 lbs.

Notes: Machine No. 1 has exhaust system. Spring [illegible] breaks and must be [illegible].
No sample plaster [illegible] is plainly visible.

[illegible]: [illegible]

Right field	[illegible]	[illegible]
[illegible]	[illegible]	[illegible]
[illegible]	[illegible]	[illegible]

Results: The [illegible] would appear to approximately [illegible] with a low silica concentration.

Sample No. 11 June 1, 1922

Location: Near Keller crusher sand plant.

Operation: Rolling crusher room

Time: Started: 9:55 A/M
Finished: 5:00 P/M

Air Pressure: 40 lbs.

Notes: Plant was in operation [illegible]
average, 4 1/2 ft. above floor, in path of
air current from crusher out third door.
Note: Three samples are returned herewith
of U. S. Royal Arsenal mesh.
Another sample for wet analysis.

Results: Number of particles in one cubic foot of air is
as follows:

Light field		600,000
Dark "	Crusher	800,000,000
Dark "	Screening & Conveying	2,000,000

Remarks: The average count (dark light field) for
samples in mill room is approximately 687,000,000.
Chemical analysis of the dark sand is as follows:

Loss on Ignition	10.0%
Si O_2 (silica)	39.2%
Al$_2$O$_3$,Fe$_2$O$_3$	7.2%
[illegible]	2.2%
Ca	21.6%
Mg	1.2

Free silica (as quartz) determined microscopically
at [illegible].
Significant analysis discloses this sand to be
[illegible] quality.

[illegible] Plant

Sample No. [illegible] June 20, 1933

Location: [illegible] roller crusher sand plant.

Operation: Roller crusher room.

Plant: Screened [illegible]
[illegible]

Air Pressure: [illegible] lbs.

Notes: [illegible] ft. from crusher, 3 ft. from floor in path of air current from crusher pit through floor.

Counts: [illegible]
[illegible]

[illegible]	[illegible]	[illegible]
[illegible]	[illegible]	[illegible]
[illegible]	[illegible]	[illegible]

Remarks: [illegible]

[illegible] Plant

Sample No. 12 [illegible]

Location: Farmdale Mill - Sand Drier Plant

Operation: Farmdale Farm

Ty[illegible]: [illegible]
Fineness: [illegible]
[illegible] Minutes

Mix Proportions: [illegible]

Notes: Plant set [illegible], 61 feet [illegible]
Area, 5 1/2' above floor.
[illegible] [illegible] [illegible]
[illegible] [illegible] [illegible]

Results: [illegible] [illegible] [illegible] [illegible]
[illegible] [illegible]:

Light Fields	[illegible]
Loam [illegible]	[illegible]
Loam [illegible]	[illegible]

Remarks: The stabilized [illegible] fields serve an approximately [illegible]. Statistical analysis of the above data is as follows:

Loss on [illegible]	27.31
Total [illegible]	32.10
[illegible], Fifty to [illegible]	[illegible]
[illegible]	[illegible]
[illegible]	[illegible]
[illegible]	[illegible]
[illegible]	[illegible]

[illegible] [illegible] [illegible] [illegible] [illegible]
[illegible]
[illegible] [illegible] [illegible] [illegible] [illegible]
[illegible] [illegible] [illegible] [illegible].

[illegible]

Sample No. 13 June 21, 1910

Location: Dock at Main Shipping Water Street

Operation: Bulk stone trimming

Time: [illegible]

Air Pressure: 60 lbs.

Notes: Plugs set 2 1/2 ft. above floor; 1 1/2 ft. above end 2 ft. over drum shipping [illegible]

Results: The standard light file count is approximately 8,500,000 and the dust is principally pure silica.

Sample No. 24 [illegible]

Location: among suhr Stone Grinders

Operation: Suhr Stone Grinding

Time: Started: 1:35
Finished: [illegible]

[illegible]

Notes: [illegible]
[illegible]
about 4 1/2 above floor; about 3 ft. above and 3 ft. from opening of flume. Stands front of six worst men.

Dress: [illegible]

[illegible]

Dept. No.12 June 11, 1973

Location: Near hammer mill, elevator and conveyor in crushing plant.

Operation: Hammer mill operation.

Time: Started 2:15 P/M
Finish " 11 "

Air sources: 1. Loc.

[illegible] about 12 ft. from and level with point where conveyor empties into crusher. Wall 70 ft. away with 2 open windows; door open at rock slow mill. Moderate draft - rough wall.

Dounts: [illegible] of particles (less than 5 [illegible] of air.

[illegible]	[illegible]	[illegible]
[illegible]	" [illegible]	[illegible]

[illegible] [illegible] [illegible] [

Sample No. 13. Jan. 21, 1903

Location: Next to #9 Miner. Cement-Plaster.

Operation: Mixing gypsum plaster.

Time: Started: 2:50 1/2
Finished: 2:54 3/4
4 1/4 minutes

[illegible] at Lot.

Notes: [illegible] above floor, 20 ft. from side wall and open windows. [illegible]

Results: [illegible]

[illegible]		[illegible]
[illegible]	[illegible]	[illegible]
[illegible]	[illegible]	[illegible]

Remarks: The standard light field count is approximately 12,000,000 with a low silica concentration.

mple No. 17 June 21, 1968

Location: Plant to #7 Mixer - Wood fiber

Operation: Mixing wood fiber filler

Time: Started: 8:00
Finished: 2 PM 1/2

Air Pressure: [illegible]

Notes: [illegible] 20 ft. from side wall and open windows; next to #7. [illegible] Plant is also flash tube fire to [illegible], where [illegible]. No [illegible].

Result: Number of [illegible] particles [illegible]

Right [illegible]			22,000,000
Left	"	Filtrex	21,000,000
Left	"	Electrolux	180,000,000

Remarks: [illegible] sample without [illegible] sample of one gal. is approximately 22,000,000 with a low initial concentration.

Sample No. 13 [illegible]

Location: above accelerator grinder in board plant.

Operation: Grinding accelerator.

Time: Started: 4.04 1/2
Finished: [illegible]

Air Pressure: [illegible]

[illegible]
2 ft. over dust grinder.
Not so well ventilated; reports window
about 10 ft.

Counts: [illegible]

[illegible]	[illegible]	[illegible]
[illegible]	[illegible]	[illegible]
[illegible]	[illegible]	[illegible]

Remarks: [illegible]

Sample No. 19 [illegible]

Location: Vent to #21 Machine grinding sanded plaster.

Operation: Finishing sanded plaster. Machine not provided with exhaust system.

Dust: [illegible]

Air Pressure: 40 lbs.

Notes: No exhaust on machine. Flask 1 ft. from operator's head at shoulder level. Operator 10 ft. from wall and open door.

Limits: Number of [illegible] particles (less than 10 M) per cu. ft. of air:

Light Tight		[illegible]
Dark	Machine	21,211,000
Dark	" Dissecting	70,000,000

Remarks: The statistical limit of [illegible] is a practically negligible risk as [illegible] considered as silica.

Note: See analysis of Sauk Valley Sand Plant. The formula for this plastic contains 60% of coarse sand and 40% of fine sand per 100% of mix.

Sample No. 10 [illegible] 10, 1903

Location: Next to #12 Machine pitching wooden plaster.

Position: Pitching wooden plaster.

Time: Started: 9: 27 1/2
Finished: 9: 31 1/2

Air Pressure: 12 lbs.

[illegible]: [illegible] operator's head; at shoulder level. Operator 10 ft. from mill and room dirt.

Counts: Number of [illegible] particles [illegible] per c.c. as follows:

Light [illegible]		[illegible]
Light	Siliceous	[illegible]
Dark	Dolomitic	40,000,000

Remarks: The standard light field would [illegible] [illegible] [illegible]

Sample No. 61 [illegible]

Location: Next to #10 Mixer - Sanded Plaster

Operation: Mixing Sanded Plaster.

Time: Start: 9:41
Finish 9:42

[illegible]

Notes: Fl ch Wall [illegible]
[illegible] wall and 3 men 12 feet away. Some dust from [illegible] but not very [illegible]

Remark: [illegible] of particles [illegible] of [illegible] particles in [illegible]:

[illegible]	11,000,000,000
[illegible]	[illegible]
[illegible]	8,800,000,000

Remarks: [illegible] This will provide an approximately [illegible] [illegible] will [illegible] within [illegible].

Note: This is the test taken directly opposite the sand discharge chute and represents the highest possible exposure at this location. The analysis of sand under dust. The formula for this plaster contains 600# plast sand and 700# of fine sand per batch of 7½.

Sample No. 22 June 22, 1933

Location: Next to #12 Miner - Sanded Plaster

Operation: Mining sanded plaster

Time: Started: 9:30 A.M.
Finished: 1:00 P.M.

Air Pressure: 40 lbs.

Notes: Same as #21 except floor held 3 to 4 ct. from machine in different positions.

Counts: Number of [redacted] particles (less than 10 μ) per cu. ft. of air:

Light field	[illegible]
Dark " Division	[illegible]
Dark " Division; Tyndall [illegible]	[illegible]

Remarks: The standard light field count is approximately [illegible] This is very objectionable concentration of dust.

[illegible] a small funnel directly opposite the sand sandblast guns showed a count of [illegible] See multiple of dust which sand plant.
The formula for this plaster contains 90% coarse sand and 70% of fine sand per batch of mix.

Note No. 11 [illegible]

Location: [illegible] 10 Board Floor.

Operation: [illegible]

Time: Started: 11:00
[illegible]

Air Pressure: 41 lbs.

[illegible] [illegible] 3 1/4 ft. above floor, in center of room (300' [illegible]). Windows open on E side, door on W side. [illegible] wide.

It was: [illegible]

[illegible]	[illegible]
[illegible]	[illegible]
[illegible]	[illegible]

Remarks: The triangle is by field error in [illegible]

Sample No. 24

Location: 3rd North - 3rd South,1e Rt.-Main South - In Passageway.

Operation: Hauling Open

Time: Started 1:37
Finished 1:50

Air Pressure: 30 to 40 lbs.

Water: [illegible] each of drive [illegible] over track and close 5' to junction with other drift.

Counts: Number of particles (less than 10 μ) per cu.ft.of air.

Right Right		1,111,111
Left "	Plankton	[illegible]
Mid. "	Settling	[illegible]

Remarks: The standard light field count is approximately [illegible] of the [illegible].

Sample No.C8 [illegible]

Location: [illegible] - 14 Ft.Main South. Next to Air Drill

Operation: Drilling in the Roof.

Time: Started 2:20
Finished 2:25 1/2

Notes: Fine: held close to head of man operating air drill.
[illegible]

Counts: Number of particles (less than 10 u) per cu.ft.of air.

Light field			1,000,000,000
Dark	"	Diameter	[illegible]
Dark	"	Resolving	[illegible]

Remarks: [illegible]
Petrographic analysis shows the material to be
[illegible]

[illegible]

Sample No.[illegible]

Location: At foot of #3 shaft. 75 ft. South

Operation: Loading

Time: Started 3:47 1/2
Finished 3:62 1/2

Notes: Flask 5' above ground near middle of [illegible] exhaled past set-up. Moderate draft of air through passage.

Counts: Number of particles [illegible] per cu.ft. of air.

Light field	[illegible]
Dark " Illumination	[illegible]
Dark " Intensifier	[illegible]

Remarks: The standard light field count is approximately [illegible]

[illegible] PLANT

Sample No. [illegible] [illegible]

Location: Block Plant - Over Accelerator Grinder

Operation: Grinding Accelerator.

Time: Started [illegible]
Finished [illegible]

Air Pressure: 40 lbs.

Notes: Flask 3' above and 4' over from route where accelerator dust is being shaken on moving belt covered with screen. Approx 10' from wall (windows closed); direct current of air [illegible]

Counts: Number of particles [illegible]

[illegible]			[illegible]
Dark	"	Plankton	[illegible]
Dark	"	Dissecting	[illegible]

Remarks: [illegible]

Sample No. 28 [illegible]

Location: Block Plant - Hand Mixer

Operation: Hand Mixing Operation [illegible]
(Same as above except that the machine operation.)

Time: Started: 9:30 A.M.
Finished: 11:

Wet Material: 21-3 Lbs.

[illegible]
(Approx. 6 gal. water), 2 cups salt, and 2 cups
(approx. 6½ cups) to 2nd Lake bucket 3 times
each batch, stirring each time with
times in order to [illegible], keep in
each pail will [illegible]. Pail
[illegible]
[illegible]

Dried: [illegible]

Pail [illegible]	[illegible]
[illegible]	[illegible]
[illegible]	[illegible]

Remarks: Standard 12-pint pails should be approximately 2,100 cc. when filled to capacity.

Sample No.20 [illegible]

Location: Between Cliclners (Rotary Kiln)

Operation: Calcining

Time: Started 10:07 1/2 10:12 1/2
Finished 10:11 1/2 [illegible]

Air pressure: 40 lbs.

Noted: Filter 8 1/2' high, 6' from each kiln 80' from furnace end of kiln. Set-up in particular, 70' from open door, adjacent movement of [illegible]. Impinger with [illegible] from prior [illegible].

Remarks: Number of particles [illegible] plus of [illegible] [illegible].

[illegible] [illegible]
[illegible] [illegible]
- [illegible] " Electrical [illegible] - Bacteria noted.

[illegible]

Sample No. 33 [illegible]

Location: Next to Hummer Screens

Operation: Hummer Screen

Time: Started: 10:34 1/4
Finished: 11:10 1/4

Notes: [illegible]
exit of air jet screen conveyors, just flask and cut between screens.

Counts: Flask spoiled - no count.

Sample No. 31 June 23, 1933

Location: Between Ball Mills

Operation: Ball Mill Grindi[illegible]

Time: Started: 11:13
Finished 11:[illegible]

Air Exposure: 41 Hrs.

Notes: Floor 8' high, 40' from ball mill - 20' from end wall [illegible] open manhole. Moderate movement of air. Floor covered with fine dust; small amount leaking from one mill.

Counts: Not counted - bacteria noted.

[illegible] OF ANALYSES OF DUST FROM GYPSUM PLANT

July 11, 1958

Percentage of Acid Insoluble Material

[illegible]	[illegible]
" # 7 "	[illegible]
" " "	[illegible]
Gypsum Dust (for [illegible])	[illegible]
Dust Cone	[illegible]
Ash in Paid Bank	
White	[illegible]
[illegible]	[illegible]
Gray	[illegible]

DISCUSSION OF THE SIGNIFICANCE OF THE DUST AND ITS RELATIONSHIP TO SILICOSIS IN WORKERS EMPLOYED IN THE PLANT. [illegible] of silicosis or any other form of pneumoconiosis must rest upon the presence in the industrial atmosphere of a sufficient quantity of silica particles or other dusts known to produce permanent injury to the lungs in such a state of fineness that they can be inhaled. The foregoing tables report in detail the results of dust sampling in representative locations throughout the plant and in addition there are appended, in appropiate places, analyses of the various types of material encountered.

MINING. In the mining operations men are engaged in work upon three principal types of rock, of which gypsum constitutes the greatest quantity. Chemical analysis of representative samples of gypsum shows that the total acid insoluble material varies from a trace to about 10%. Petrographic analysis of this rock indicates that it contains approximately 75.0% gypsum ($CaSO_4 \cdot 2H_2O$), 10.0% anhydrite ($CaSO_4$), and 15.0% calcite ($CaCO_3$). Fortunately there is not enough silica present in the native gypsum to constitute a hazard unless the concentrations of the total particles in the air are in excess of 250,000,000 particles per cubic foot. The actual dust concentration produced by drilling gypsum rock is less than 2,000,000 particles per cubic foot of air. Previous studies have failed to indicate that there is any hazard associated with calcium carbonate dust. Consequently it is is evident that there is nothing associated with the mining of ordinary gypsum which could be considered responsible for the production of silicosis.

The second most important rock encountered underground is termed anhydrite and represents a native anhydrous calcium sulphate.

This material shows from a trace to 3.6% acid insoluble material. Since this rock is [illegible] is required in the drilling operation and hence dust counts result. Average counts obtained during this operation showed 11,600,000 particles per cubic foot of air. Since the silica content of the rock is negligible, the dust produced in drilling it can not be regarded as capable of producing silicosis until concentrations of nearly 1,000,000,000 particles per cubic foot of air are created.

The third and least [illegible] ground involves the removal of roof rock from the haulage ways. This roof rock is called the shale, [illegible] to 58.0% of acid insoluble material. Petrographic analysis of this material indicates that it is an argillaceous limestone containing about 60% calcite and 40% clay. Clay contains aluminum silicate and therefore it can not be said that drilling the roof rock presents no dust hazard since certain silicates are known to produce pulmonary fibrosis. The operation of removing this roof rock from the haulage ways is performed with a jack hammer drill and the dust concentrations produced are very large. A count made near the head of an operator during a typical operation disclosed 1,900,000,000 particles per cubic foot of air. Obviously, this work is theoretically the most hazardous from the pneumonokoniosis standpoint of all the tasks performed underground, and yet it can not be regarded as a serious hazard for several reasons. The work is not very extensive, it is intermittent in character, it involves only a few workmen, and the dust produced is not free silica but contains less than 40% aluminum silicate.

Dust samples secured in the [illegible] territory and near the loading [illegible] suspended in the general mine air is not excessive.

RAW GYPSUM PLANT. Men engaged in this portion of the plant are exposed only to the dust of raw gypsum. Samples were taken on the weighing floor, over the conveyors on the upper floor, and near the hammer mill. These samples were all taken during regular operations and the counts obtained indicate that there is not an excessive quantity of dust present throughout the [illegible] hammer mill the concentration was found to be 12,000,000 particles per cubic foot. This amount of gypsum dust is probably not dangerous, but it is advisable to install equipment which will reduce the concentration to less than 10,000,000 per cubic foot.

CALCINING AND GRINDING PLANT. The general dust treated in this plant is calcined gypsum. Chemical analysis of this dust shows that the acid insoluble material does not exceed 3.0%. Petrographic analysis indicates approximately: 73% hemihydrate ($CaSO_4 \frac{1}{2} H_2O$), 8% acid burned gypsum, 18.0% calcite ($CaCO_3$), and 1% anhydrite ($CaSO_4$).

There are two sources from which a siliceous contamination may occur in this plant, namely: the refractory material lining the kiln and the buhr stones used in one portion of the grinding operation. Neither of these sources of silica can be regarded as creating a real hazard for the following reasons: both the refractory material and the buhr stones are well enclosed, the actual amount of siliceous contamination added to the gypsum is very small (less than 1.0%), and the dust concentrations around these operations is not excessive. Samples taken

between the calciners and [illegible] [illegible] particles per cubic foot of air respectively. Samples were also taken near the hammer screens and near the ball mills but due to bacterial contamination it will be necessary to obtain new samples from these locations. One individual operation, that of trimming the board stones, will be considered later.

BLOCK PLANT. The dust created in the block plant is largely [illegible] air but this is not regarded as significant. A sample recovered near the head of an operator using a hand mixer showed less than 8,000,000 particles per cubic foot of air. This concentration is low and would be permissible under any conditions. The grinding of accelerator (gypsum blocks) produces concentrations of approximately 12,000,000 particles per cubic foot of air and though the dust is not considered hazardous, equipment should be provided which will reduce this concentration to less than 10,000,000 particles per cubic foot of air.

BOARD PLANT. The dust created in the board plant is identical with that produced in the block plant and consists almost entirely of gypsum. A sample taken near the center of the plant shows only about 800,000 particles per cubic foot of air. This concentration is lower than that found on most city streets. The grinding of accelerator (gypsum blocks) produces concentrations of approximately 12,000,000 particles per cubic foot of air. This operation might be improved to reduce the concentration of dust, though it is not hazardous in either composition or quantity. At the southern end of the board plant is a machine for polishing veneered boards. Samples were not obtained near

the operation of this machine, but it was [illegible], [illegible] be used in this process. Asbestos paper is being used at the present time and its continued use is recommended. Research in this laboratory has shown alunite to be relatively incapable of producing fibrosis, while the introduction of silica abrasives would create a very significant hazard.

WAREHOUSE. There are a great variety of dusts present in the air of the warehouse. The largest single contributor of these [illegible] Chemical analysis of the fine sand floor dust [illegible] silica, and that 82.0% of the sand is free quartz. Petrographic analysis discloses this sand to be approximately 80.0% calcite and 20.0% free quartz. Other contaminants present in the air of the dust bin, coarse sand, wood fiber, jute fiber, and organic matter as dust in the operation. Potentially pure quartz sand, asbestos, and talc are used in plasters and a certain amount of dust from these materials must enter the atmosphere. The dust from the sand loses silica on chemical analysis and 20.0% of the sand exists as quartz. Petrographic analysis discloses this coarse sand to be 75.0% calcite and 25.0% free quartz.

Dust collected from the rafters over the #12 mixer at the southern end of the warehouse shows about 40.0% acid insoluble material. Similar dust from over #7 mixer shows 8.0% acid insoluble material, while the dust above #4 mixer shows only 2.0% acid insoluble material. The largest part of the sanded plasters are made at the #12 machine. Sanded plaster may contain as much as 51.0% sand and since the sand contains from 20.0% to 80.0% quartz, the dust in the air may contain from 10.0% to 33.0% quartz. Obviously, the dust created in the making of sanded plaster must be regarded as hazardous but this hazard appears to be

fairly well localized to the pill machine.

Samples obtained during the packing of ordinary cement plaster in both paper and jute bags on machines provided with exhaust ventilation showed from 6,000,000 to 11,000,000 particles per cubic foot of air. Another sample taken near the same machines during the packing of wood fiber plaster showed 15,000,000 particles per cubic foot of air. These concentrations represent about the highest permissible counts and it would appear advisable to improve the exhaust system so that not more than 5,000,000 particles per cubic foot of air reached the head of the operator. In general, however, the packing of gypsum or wood fiber plaster on the machines protected with exhaust ventilation can not be considered hazardous.

Samples taken on the second floor of the warehouse during the mixing of ordinary gypsum plaster or wood fiber plaster showed counts from 18,000,000 to 38,000,000 particles per cubic foot of air. Though the dust created in this operation does not contain significant quantities of silica, the concentrations are two or three times greater than the usual standards permit.

Samples secured near the #12 Bates Packer (which has no exhaust system) during the packing of sanded plaster showed from 28,000,000 to 44,000,000 particles per cubic foot of air. Since as much as one third of this dust can be pure quartz, it is obvious that men packing sanded plaster breath an atmosphere containing from 9,000,000 to 15,000,000 quartz particles per cubic foot of air. This is considered to be a definitely hazardous concentration of harmful dust. The concentration of quartz particles per cubic foot of air

ought never to exceed 5,000,000 but even this number may not be safe. For this reason it is urgently recommended that the operations involved in the manufacture of sanded plasters be given special consideration.

A sample taken near the #12 mixer during the mixing of sanded plaster showed 146,000,000 particles per cubic foot of air. This concentration is excessive and hazardous and should be reduced to within 10,000,000 particles. A sample recovered near the point where fine sand is delivered to the mixer showed more than 11,000,000,000 particles suspended in a cubic foot of air.

The mixing and packing of sanded plasters should be done in a section of the warehouse which is separately enclosed and special equipment should be installed to reduce the amount of dust suspended in the air to the minimum.

SAND PLANT. The dust created in the sand plant is all produced by the processing of the sands whose analysis have been given in the section dealing with the warehouse. The silica content varies from 81.0% to 91.0% and the amount of free quartz varies from 26.0% to 52.0%. A sample taken in front of the furnace showed approximately 3,000,000 particles per cubic foot of air. Though the dust is definitely dangerous, the concentration is not high and the hazard can not be very great in this position which the operator of the sand plant occupies a considerable portion of his time. A sample taken in the center of the roller crusher room showed the excessive concentration of 287,000,000 particles per cubic foot of air. Every effort should to made to keep the amount of dust in the air of this plant to a minimum which should never exceed 10,000,000 particles per cubic foot for in these con-

concentrations this dust is dangerous.

Buhr Stone Trimming. Chemical analysis of the buhr stones has shown that they contain 97.0% acid insoluble material and petrographic analysis indicates that the material is practically pure normal quartz. A sample obtained near the head of the man engaged in trimming these stones with an air hammer showed 6,500,000 particles per cubic foot of air. This concentration is near the maximum permissible for pure quartz dust and is to be regarded as hazardous. It would appear advisable to move this operation to a separate room, or to equip the operator with special exhaust ventilation.

It is recommended that the following men be required to wear special respirators until such time as the dust concentrations in which they are working are reduced to within the recommended limits.

1. Miners drilling roof rock or ash.
2. Men mining, packing, or sorting sandid plasters in the warehouse.
3. All employees in the sand plant.
4. Men trimming buhr stones.

By the methods employed it would [illegible] exposed to excessive concentrations of dust. Since it is [illegible] severe pulmonary damage is produced by silica, and if it is assumed that gypsum or calcium sulphate is relatively harmless it becomes essential to ascertain the relative proportions of these two substances in the atmospheric dust of this plant. It was assumed that this could be accomplished by making a preliminary count of the total dust particles in the air samples, then dissolving the calcium sulphate by treatment with acid and [illegible] particles which would not be attacked by acid. For technical reasons this procedure has proven unsatisfactory and it is deemed advisable to make a special study of this problem in another visit to the plant which will be made in the immediate future. It is proposed to employ an Owens-Jet Dust Counting apparatus which will permit the collection of dust samples on cover glasses in such form that by direct microscopic examination the relationship of various particles can be observed and their petrographic characterization can be determined. By the use of this apparatus it will be possible to determine not only the relative proportions of gypsum and silica in the atmospheric dust but to learn whether the gypsum may not have been responsible for the formation of aggregates of silica particles too large to be inhaled. The subsequent sections dealing with the condition of the workmen will disclose there is no demonstrable silicosis among them, and some explanation is necessary in view of the high concentrations of silica to which they have been exposed.

PHYSICAL EXAMINATIONS - were made on 101 men employed for maximum periods in various portions of the plant. With two exceptions there was no evidence of disease of the lungs and in the two cases

[illegible] apparently not particularly [illegible]. [illegible] [illegible] [illegible] [illegible] [illegible] [illegible] lateral curvature of the spine and a few changes in breath sounds with rales in the top of his left lung. His x-ray picture showed changes which could be interpreted as healed tuberculosis. Another man, Arthur Monette, was employed for nine years as a mason and bricklayer. While he worked in all departments he spent most of his time in the power plant furnace and repairing the calciners. "Squeaks," both expiratory and inspiratory, suggestive of asthma, were discovered on two physical examinations. His x-ray picture showed a third degree of interstitial fibrosis but none of the nodular characteristic of fully developed silicosis. Otherwise the physical examinations of the chests in the 6 men were quite negative.

In 76 of the 101 cases cloudiness of the sinuses in the head were noted on transillumination. In the absence of a definite history of sinus disease and without a thorough x-ray study of this condition a definite diagnosis of sinusitis could not be made. An equally high incidence of this condition has been observed in other dusty occupations.

Two cases of heart disease and one of hyperthyroidism were discovered but neither of these could in any way be caused by inhalation of dust. In addition there were numerous cases with bad teeth, tonsils and nasal conditions which were reported to the men thru Mr. Daniels with the recommendation that they be given proper medical or dental attention.

ROENTGENOLOGICAL EXAMINATION showed some evidence of abnormality in the lungs of 68 of the group of 101, but in none were the changes very pronounced. No case could be diagnosed as silicotic.

The changes observed could not be correlated with the type or duration of occupational exposure. [illegible] classification the men were grouped according to the theoretical hazard of their occupation as follows:

Table I.

Occupation	Number in Group
Buhr Stone Dressers	2
Warehouse only	6
Warehouse plus Other Maintenance	9
[illegible]	11
Miscellaneous Occupations with Certain Mill Work in Warehouse	11
Miscellaneous Occupations with No Warehouse Work	19
Block Plant	10
Mining Only	22
Laboratory Tester	1

Two main types of change, which might be due to dust, were observed in the roentgenograms, (1) an increase in prominence of the normal linear shadows of the lung and (2) a diffuse haziness throughout the central portions of the lung fields. In the table following, the first change is designated as "F" and the second as "P". The appended numerals indicate the intensity of these changes. Their significance will be discussed below.

Table II.

Summary of Roentgenological Findings

Occupation	No. in Group	Pneumonokoniosis							Tuberculosis	
		0	F1	F2	F3	P1	P2	P3	Healed Childhood	Healed Adult
Miners	22	1	10	0	0	8	3	0	3	2
Block Plant Only	10	1	3	0	0	0	6	0	1	0
Miscellaneous with Occasional Warehouse exposure	13	2	3	0	0	3	4	1	2	1

Table II (continued)

Occupation	No. in Group	Roentgenological: 0	F_1	F_2	F_3	A_1	A_2	P_3	Tuberculosis: Reduced children	Tuberculosis: Reduced adult
Board Plant Only	19	5	2	2	0	8	2	0	4	1
Warehouse Only	6	2	1	0	0	2	1	0	1	0
Warehouse plus some work elsewhere	9	2	1	0	0	2	4	0	3	0
Miscellaneous Occupation with no Warehouse	18	1	1	0	0	8	9	0	3	0
Buhr Stone Dressing	2	0	0	0	0	0	2	0	1	1
Laboratory	1	0	1	0	0	0	0	0	0	0

[illegible] classification indicating a diffuse type of interstitial (f) reaction occurs most frequently in men exposed to pure gypsum dust. The presence of this type of reaction in the different occupational groups is summarized as follows:

Table III

Mining Only	48%
Block Plant Only	30%
Miscellaneous Occupations with Occasional Work in Warehouse	22%
Board Plant	17%
Warehouse Only	16%
Warehouse with Miscellaneous Occupations Elsewhere	11%
Miscellaneous occupations with no Warehouse Exposure	6%
Buhr Stone Dressing	0

The significance of this change has not been definitely ascertained for lack of autopsy material upon which to base an interpretation. Individuals do not always show a degree of reaction corresponding to the duration of their employment, but among the

group of miners 38% of those employed for 5 to 12 years show it while after mining from 13 to 21 years [illegible] changes of this type. In the block plant group the corresponding percentages for the same employment periods were 20 and 40% respectively, while in the "Occasional Warehouse Employment Group" none showed it under 13 years of exposure. In two miners exposed for 9 and 21 years respectively this change was complicated by some emphysema. For these reasons we are inclined to associate this change with an exposure to gypsum dust, but we have no clear understanding of the underlying pathological conditions.

The other type of roentgenological change encountered which is labeled "F" consists of an accentuation of the linear shadows cast by the bronchi and blood vessels. This change could not be correlated with the type of dust to which the men in the various groups were exposed. It occurred in both the bulk stone dressers who must have been exposed to considerable quantities of fine silica but only two-thirds of the x-rays of Warehouse men displayed it. John Smith, who had worked for 12 years on the Bates Packer where he would theoretically inhale large amounts of silica had a normal chest picture. This warehouse group of only 6 men is probably too small and the duration of their exposures is too limited (all under 12 years) to permit statistical analysis. Possibly if the group were larger the figures would have proved more enlightening. It is still our belief that if silicosis should appear after further exposure it would occur in men exhibiting an "F" type of roentgenogram.

One man, Monette, a mason and bricklayer for 9 years, as already mentioned, showed a change classified as F_2. In his case the accentuation of the linear markings was accompanied by a sug-

portion of beading along the trunks such as occurs in early silicosis. This man may have inhaled considerable quantities of silica in his work of repairing furnaces and calciners which are presumably lined with refractory silica brick. However, even he could not be called a case of fully developed silicosis.

Tuberculosis was always manifested as healed lesions in the roentgenograms. The changes were of two types, (1) the "childhood type" which represents the first contact of the body with the tubercle bacillus and (2) the "adult type" which occurs when the body is again infected with this germ. The childhood reaction consists of one or more isolated nodules of tuberculosis somewhere in the lung and another focus in a lymph node situated at the root of the lung. Such nodules of infection tend to heal with a deposition of lime salts which renders them easily visible in an x-ray film. In the gypsum workers these nodules healed with an excessive deposition of lime so that they were unusually large. The incidence of such infectious lesions was no greater than that in any group of individuals.

The other type of tuberculous change, the "adult lesion", generally occurs in the upper portion of the lung. It also normally tends to heal but occasionally it spreads and gives rise to widespread manifest clinical tuberculosis with symptoms and possibly fatal termination. Five or possibly seven in this series of gypsum workers showed evidence of a previous adult type of tuberculosis, but in every case the lesion had completely healed without exhibiting the slightest tendency to spread. If a corresponding number of men exposed to pure silica dust were in question, it is safe to assume that some of these adult types and possibly even the childhood types of tuberculosis would have shown evidence of spread and progression.

Following is a list of the individual workers, grouped according to occupation, together with their [illegible]

10 Blast[illegible] 21 Miners

Employed	Name	Case No.	Notes
7 yrs.	Frank Manke	46	F_2
8 yrs.	A. Ferris	48	F_2
11 "	C. Brown	41	F_2
12 "	F. Waterstreet	51	F_1
13 "	E. [illegible]	[illegible]	
14 "	Fred. Manke	47	F_1
15 "	A. Ramsey	53	F_1
16 "	L. Olmstead	42	F_1
19 "	Carl Lutz	19	F_1
21 "	F. Urtel	43	0 ? Primary Complex

2 Rock Stone Dressers

9 "	M. Whitney	33 (6 yrs. elsewhere)	F_1	Primary Complex,?
11 "part time)	C. Rinehart	40	F_2	Fibrosis ?Tuberculo

1 Laboratory Tester

10 "	Cummings	101	F_1	

22 Miners

9 "	E. Cassiano	77	F_1	
9 "	C. Nelson (Brusher)	76	F_1	and emphysema
9 "	J. Jerome (Loader Hard Coal)	61	F_2	
10 "	A. Domagoila	62	F_2	calcified apices
11 "	S. Scopano (Pig Iron Loader 2 years)	57	F_1	

20 Lungs (Continued)

Employed	Name	Case No.		
11 years	J. Malta	78	P_1	
12 "	D. Paolucci	74	P_1	Primary complex, L
12 "	A. Paolucci	63	P_1	
12 "	A. Frigeni	64	P_1	Primary complex, R
12 "	N. Paolucci	67	P_1	Large Heart
12 "	A. Ferrari	68	P_2	
12 "	D. DeAngelis	69	P_1	Primary complex, Rt.
12	S. Zanni	70	P_1	
13 "	F. Vanik	71	P_1	Large Heart
16 "	P. Taddei	80	P_1	
17 "	E. Capone	73	0	
17 "	S. Balliet	100	P_1	Calcification Rt. Apex
18 "	G. Cafaro	66	P_1	
19 "	J. Callanan	75	P_1	
21 "	J. Bilinski	79	P_1	Emphysema
24 "	R. Dure	24	P_1	
25 "	P. Malta	96	P_1	

19 Board Plant Only

5 "	L. Heidenrich	52	P_1	
7 "	J. Woods	54	P_1	Primary complex, Rt. and Lt.
8 "	B. Werth (2 yrs. outside)	53	P_1	Ditto
8 "	E. Green	25	P_2	Ditto
8 "	Wm. Adams	50	0	
10 "	Winbistern	37	0	
10 "	S. Davidson	35	P_2	Calcified both apices

19 Power Plant Only (Continued)

Employed	Name	Int. No.	Grade	
10 years	T. Pettitt	34	O	
10 "	E. Bumstead	32	F_1	Primary complex, Lt
10 "	I. Davis	3	F_1	" "
10 "	S. Davis	2	F_1	
11 "	M. Allen	30	F_2	
12 "	R. Harris	26	O	
12 "	W. Greene	38	O	
13	F. Tuber	31	F_2	
14 "	V. Seaburg	24	F_1	
15 "	W. Allen	33	P_1	
18 "	R. Allen	39	P_1	
22 "	S. Dick	27	F_1	

6 Warehouse Only

5 "	R. Valena	14	F_1	
6 "	Fred Bernard	11	O	
6 "	Wm. Shepard	10	F_2	
10 "	John Smith (Bates Packer)	51	O	
11 "	A. Beckwith	17	P_1	
12 "	T. Joslyn	18	F_1	Primary Complex, Lt.

9 Warehouse and Operations Elsewhere in Plant

5+5 "	Wm. Farnsworth	5	F_1	Primary complex, Rt.+ Lt.
5+25 "	E. Dinehart	13	O	
7 1/2-1 yrs.	Natzka	9	F_2	
8+3 yrs.	E. Earl	7	F_2	
9 +1 "	A. Hensel	93	F_2	

9 Warehouse and Operations Elsewhere . . . (Cont.)

Employed	Name	Case No.	Notes
9 1/2+21 yrs.	J. Reddins	10	F_2 Primary Complex Rt.+ L
10 + 19 "	Mike Marrah	15.	P_1
12 + 10 "	Chas. Miller	6	F_1
15 + 7 "	Burt Smith	8	C? Primary Complex Rt.+ L

13 Miscellaneous with Occasional Work in Warehouse

Chiefly Temple & Maintenance Crew

9 years	A. Monette (Mason, boilers and flues)	84.	F_3
11 "	F. Miller (Carpenter)	87.	F_2
12 "	D. Bowden	88.	C
12 "	E. Bogden	83.	F_1
13 "	S. Fosdick	91.	F_1
13 "	Balfour	4.	C
15 "	M. Freiday	89.	P_1 Primary Complex Rt.
15 "	E. Pender	92.	P_1
16 "	S. Christopherb	49.	F_2
17 "	Manni	90.	P_1 (Isolated CB
20 "	H. Holm	88.	P_1 (both roots.
21 "	M. J. Hordan	97.	F_2
25 "	G. Lehman	98.	F_2 Primary Complex, Rt.

19 Miscellaneous - No Warehouse Exposure

9 "	D. Tillet	94.	F_2
9 "	F. Neth	98.	F_1
10 "	A. Burr	20.	F_1
10 "	L. Park	21.	F_1

Employed	Name	Case No.	Index	
11 years	E. Newton	44	F_2	
11 "	Kent	1	F_1	
11 "	Ed. Hale	99	F_2	Primary Complex Rt.
13 "	C. Minetta	80	F_2	
13 "	B. Ianni (Mine 7 yrs.)	81	F_2	
14 "	H. McGuire	28	0	
14 "	L. Ehret (Brother 6 yrs.)	86	F_1	
14 "	R. Lumsey (Mine 6 yrs.)	40	F_2	Old Tuberculosis
14 "	A. Schulk	82	F_1	
15 "	D. Caton (Mine 12 yrs.)	72	F_2	
15 "	K. Stevens	84	F_1	
19 "	L. Jaclyn	89	F_2	
21 "	J. Ianni (Mine 18 yrs.)	66	F_1	
28 "	R. Schultz (Mine 11 yrs.)	88	F_2	
30 "	A. Speed	18	F_1	Primary Complex, Rt. and Lt.

From this analysis of the x-ray and clinical examinations, it would appear that gypsum dust inhaled in high concentrations over periods as long as 20 to 28 years does not produce changes in the lung which are incompatible with normal function. It cannot be maintained that this dust has no effect on the lungs for only 13 of the 101 men examined show what could be interpreted as negative lung roentgenograms, but there was no clinical evidence that gypsum inhalation had produced disability. When silica dust is also present in the industrial atmosphere with the gypsum dust this substance has not excited the reaction

which experience in other industries [illegible] at least 17 men appear to have had a sufficient exposure to silica to have brought about changes in their lungs demonstrable by x-ray but such changes could not be discovered. Two explanations have suggested themselves: either that the gypsum by virtue of its physical properties clumps the silica particles in the air into aggregates too large to be inhaled or that gypsum chemically modifies the tissue reaction to silica. In the absence of any data on the subject it seems more likely that the former explanation may be the proper one. As suggested, further study of the [illegible] is desirable, and it would also be desirable to procure autopsy material from men exposed as long as possible to mixtures of silica and gypsum, so that chemical analyses of their lungs might demonstrate how much silica actually penetrated their tissues. Opportunity for such a study is, of course, quite fortuitous.

The investigation has also demonstrated a complete lack of progressive tuberculosis among the gypsum workers who were examined. This finding substantiates the view that little silica has been inhaled, for any group exposed to silica for as much as 20 years should contain 10 to 15% with active tuberculous lesions. It has been claimed that gypsum dust protects against tuberculosis. H. Haendl (Zeitschrift für Tuberkulose 1921,XXXV,194) quotes Fiesak, without citing the source of his figures, to the effect that of 40,824 deaths among lime and gypsum workers only 17 or 0.41% were due to tuberculosis and that among 400 employees in one gypsum plant (presumably German or Austrian) no death from tuberculosis had occurred in 17 years. Examination of the death records in Oakfield and the nearby towns might demonstrate whether the incidence of deaths from tuberculosis or other respiratory disease was equal to or below that for other industrial

communities. Two cases of active tuberculosis in gypsum workers from Caldfield have come to our attention so that we know it can occur.

PATHOLOGY - Lack of material forbids any elaborate discussion of the tissue changes produced by the inhalation of gypsum in pure form or in combination with silica or other substances. Animal experiments are in progress but the exposure period has not been sufficiently long to hazard an opinion as to the nature of the reaction. One autopsy on a gypsum worker was obtained through the efforts of Mr. Daniels at Caldfield. This man was not employed by the U. S. Gypsum Co. but by a competitor for a period of 6 years, presumably in various capacities but his occupational history was not obtained in detail. No x-ray films had been made of his chest prior to his death so that a comparison between roentgenogram and pathological lesions was not possible. Presumably the picture would have shown an accentuation of the linear markings, as there was a rather marked accumulation of dust along the lymphatic vessels accompanying bronchi, blood vessels and the connective tissues between the lung lobules. These structures were pigmented by the dust and slightly thickened by the formation of a small amount of new connective tissue but there was no fibrosis and no nodules such as occur in silicosis. There were nodules in the lungs and lymph nodes of "childhood tuberculosis" which had healed with very extensive calcification. Death occurred from coronary arterial disease which could not be associated with dust inhalation. The character of the pulmonary changes was that of the reaction produced by many non-irritating dusts, like soft coal and marble.

This report discloses that among the 101 long term employees of the U. S. Gypsum Company who have been examined, there is no case of definite silicosis nor one of active pulmonary tuberculosis. These findings were somewhat surprising in view of the fact that in some portions of the plant, notably near the mixer over the #12 Packer, there were total dust counts as high as 11 billion particles per cubic foot of air with a free silica content which might be as high as 3 billion particles. The fact that no silicosis occurred in the group of 6 men employed exclusively in this part of the plant, and that the one man who had worked on this particular machine for 10 years showed a normal chest, throws some doubt upon the existence of a hazard under the conditions encountered in this gypsum plant.

As an explanation the hypothesis was suggested that the tendency of gypsum to form aggregates clumped the silica particles into masses too large to be inhaled in significant quantities. Nevertheless it must not be taken for granted that with further exposure of 10 or more years these men would remain free from disease. The occurrence of an "F" classification in so many of the roentgenograms suggests that with continued exposure some of these men might ultimately develop serious pulmonary damage.

As far as gypsum dust is concerned nothing has been observed which would disturb our original feeling that this dust would prove to be quite harmless. Probably it is responsible for certain changes in the x-ray pictures of the lungs but there is nothing to indicate that these changes are associated with physical disability. Traces of active pulmonary tuberculosis are wanting and

the experience quoted from [illegible] gypsum workers. The evidence suggests that when a tuberculous infection is present the dust inhaled in this plant does not tend to cause it to become active for 18% of the pictures showed well healed foci of childhood tuberculous infections and 5% of them disclosed healed adult tuberculosis. However, it cannot be claimed that such infection never becomes progressive in men with gypsum exposures.

For these reasons it is of utmost importance to select for test cases individuals without active tuberculosis or obvious silicosis in order that unfavorable precedents may not be established in the gypsum industry. If it can be discovered that perchance such conditions exist among the group of cases scheduled for trial, we would urge that they be settled by compromise and that the test be based upon the typical case.

Leroy U. Gardner

LEROY U. GARDNER, M.D.
DIRECTOR

D. E. Cummings (by)

DONALD E. CUMMINGS
ASST. DIRECTOR