


WASHERS (WROUGHT)-776

PLATED


Diameter	Part No.
5/16 in.	3-9120
3/8 in.	3-9121
1/2 in.	3-9122
5/8 in.	3-9123



VACUUM GAUGE-908

(SEE INDEX 218, PAGES 84-86 FOR VARIOUS MOUNTING PANELS.)

MANIFOLD VACUUM GAUGE



3-5788

ILLUMINATED

0-30 inches


2" diameter gauge is graduated in inches of vacuum and color coded to indicate most efficient engine operation. Indicates carburetion and ignition malfunctions. Chrome plated with U clamp. Use with 3-5785 single panel and 3-5786 light source kit.

DIESEL TACHOMETERS-908


HIGHEST QUALITY PRECISION ELECTRIC TACHOMETERS FOR DIESEL TACH-GENERATOR SYSTEMS

ICC Regulations require large trucks to make an immediate stop and repair or replace inoperative tachometers.


TACH HEADS



STANDARD
90° SCALE
HEAD



SWEEP SCALE
250°
HEAD



RUGGEDIZED
AND SEALED
HEAD

Simplest tachometers to install - no make-or-break points in generator therefore longer, maintenance free life.

No batteries or relays to check or replace.

No battery replacement.

No maintenance care necessary - gives higher accuracy over longer periods.

Four shunts provided with Tach heads take care of ratio changes - no different power units to stock and handle.

(Wired for Illumination)

Available in 4 RPM ranges and in three head styles.

R.P.M. Range	Standard 90° Scale	Sweep Scale 250° Scale	Ruggedized and Sealed 90° Scale
0 - 2000	3-5700	3-5701	3-5702
0 - 2500	3-5703	3-5704	3-5705
0 - 3000	3-5706	3-5707	3-5708
0 - 4000	3-5709	3-5710	3-5711

Standard and Sweep Scales can be mounted in 3-3/8" dia., SAE Standard panel cut-out or may be mounted on column or above dash using Balkamp Chrome Housing 3-5690.

Ruggedized and Sealed head is designed for severe environment and vibration. Meter movement internally suspended in shock mounts and entire head is hermetically sealed, mounts into 3 3/4" dia. panel cut-out. Non-illuminated.

Replacement Parts