


FILE NAME: RT Vanderbilt (RTV)

DATE: 0000

DOC#: RTV110

DOCUMENT DESCRIPTION: RTV Mineral Safety Data Sheet



MINERAL PRODUCT SAFETY DATA SHEET

NOTE: Exposure to asbestos mineral dusts is subject to OSHA regulations in accordance with Section 1910.33 of the Occupational Health and Safety Administration Standards as published in the Federal Register of October 16, 1972, starting on page 22139.

SECTION I		
TRADE NAME AND SYNONYMS	MOULDENE, II FIBER No. 2	Industrial Fibrous Talc
MATERIAL FAMILY	Hydrous silicates	
CHEMICAL COMPOSITION	Complex hydrous calcium magnesium silicates	

SECTION II INGREDIENTS		% RANGE
Asbestiform talc and/or asbestiform anthophyllite		40 - 60
Talc - non-asbestiform		5 - 15
Non-asbestiform tremolite and/or anthophyllite		30 - 60
Quartz		1 - 5
Serpentine		5 - 10

SECTION III PHYSICAL DATA			
COLOR	White	SPECIFIC GRAVITY (20-25)	±2.7
APPEARANCE	Fibrous		
OTHER PROPERTIES			

SECTION IV HEALTH HAZARD DATA		TLV
Asbestiform talc and asbestiform anthophyllite	5 fibers/cc > 5 µm. in length	
Talc - non-asbestiform		20 Mppcf
Non-asbestiform		20 Mppcf
Serpentine		50 Mppcf
Quartz	30 mg./cu.m. ± 5% Quartz ± 2	

SECTION V SPECIAL PRECAUTIONS	
PRECAUTIONS TO BE TAKEN IN HANDLING AND STORAGE	
Avoid breathing dust. Use respirator if TLV's exceeded.	

DATE: May 1, 1975

OVER 100 TONS PER YEAR

This information is furnished solely for the purpose of disclosure regarding health hazards and should not be used or relied upon by any person for any other purpose.

Dec 10-75-75
Cite: Billed to - v. Owens
Department: Hazardous
Reporter: John A. Breen
Cite: Billed to - v. Owens
Cite: Billed to - v. Owens
Cite: Billed to - v. Owens