

NORWOOD



HOUSE PAINT

171 WHITE

ONE GALLON

U. S. MEASURE

DUQUESNE PAINT COMPANY

PITTSBURGH, PA.

MAR 12 1900 11429 L

NORWOOD HOUSE PAINT
A good quality general-purpose paint for all surfaces. May be used on wood, brick, masonry, & durable protective coating.

DIRECTIONS FOR USE
MIX THOROUGHLY: If paint is slightly thick, add a little turpentine or kerosene. Stir liquid from the top of the can into a dense coating paste thoroughly, adding liquid gradually. **BO** from one can to another several times before u
FIRST COAT: To each gallon of paint add raw linseed oil and one pint of pure turpentine. On extremely porous surfaces additional oil is the paint.

SECOND OR FINISH COAT: Apply paint can or thin very slightly with Lawrence Un
ease brushing.

NEW HOUSES: Should be primed with paint and allowed to stand several weeks durin
so that all moisture on the interior of the house
oughly before applying Two-Coat Finish as di

COLD WEATHER: For best results paint
plied during cold or damp weather. If paint is s
temperatures before being thoroughly dry.

CHALKY SURFACES: Never paint over d
properly and very excessive chalking may re
this causes blistering and peeling in practice
Before painting, inspect and repair all gutters
and eave around window frames to prevent rot
ing the wood which also causes blistering and

Copyright, 1900, by Duquesne Paint Company, Pittsburgh, Pa. All rights reserved. No part of this publication may be reproduced without permission in writing from the Duquesne Paint Company, Pittsburgh, Pa.