GP 0-9

GEORGIA-PACIFIC

INTERDEPARTMENTAL COMMUNICATION

Dave B
Ed Eds
Sterling

DATE: February 8, 1973

TO: *See Below

LOCATION:

FROM: M. F. Fink

LOCATION: Tigard

SUBJECT: ASBESTOS CONTROL PROGRAM

Lets check this out & see what we must do to comply — KWB

THIS COPY FOR

To: *K. W. Brown - Acme
M. A. Palmowski - Chicago
J. D. Rauch - Akron
R. V. Favero - Marietta
H. W. Scharf - Milford
H. W. Peele - Wilmington Gypsum

Ed
See KWB on this ASAP
B

cc: T. W. Richards - Tigard
E. B. Hollingsworth - Wilmington Gypsum
C. W. Lehnert - Tigard

We wish to call your attention to the rules and regulations effective January 7, 1973. See attached.

There are several clauses that are not clear and we expect a ruling very shortly. The rule as it refers to posting areas where counts are above allowable threshhold limits is one. 14 point Gothic type is rather small print, approximately 5/16". The type sizes specified are minimum, we recommend larger type. Incidentally, we have had surveys conducted in all plants. Generally speaking the counts based on fiber counts, 5 microns or larger are below the allowable limit. Two areas or operations where limits are exceeded, loading hopper during shaking and operator dumping bags. In addition often the bags are filled and toppled over. The spout will contain small amounts of the mix which are released when the bag is toppled. The dust counts were extremely high and it was difficult to determine the fiber counts or length of fibers. We recommend that signs be posted in the joint system areas as instructed on Page 11321. Also wearing of respirators must be strictly enforced.

PLAINTIFF'S EXHIBIT
GP-2138

Label specifications. You will be notified by R & D how this will be handled.

While preparing this letter one of the joint system plants has been inspected by OSHA. Eight hour air tests were taken, also other clauses were discussed. The plant should receive a report in 3 or 4 weeks, also recommendations to correct any violation of the regulations. You will be informed of the recommendations and how they shall be applied in your operation.

MFF:jg
Attachment

M. F. F.

SGP 0006714

With the exception of asbestos, we can find no OSHA requirement for an employer to monitor environmental exposures to toxic materials. However, this is changing rapidly. The asbestos standard requiring both monitoring, recordkeeping, and employee apprisal is now in effect. Similar proposals have already been made by NIOSH for noise, carbon monoxide, beryllium, and heat stress. According to our information 40 more, over the next 24 months, are in the mill.

The four proposed standards follow the pattern of that set for asbestos. Let's look at how the situation is changing for the OSHA inspector and you.

1. If you are using asbestos, you must (by Jan. 7, 1973) monitor every place of employment where asbestos fibers are released to the working environment so as to make an initial determination of asbestos levels.

2. You must establish sampling frequencies and patterns that are representative. In no case can the sampling be more than six months apart in areas where you can reasonably foresee exceeding the exposure limits.

3. You must post caution signs and labels at each location where asbestos concentrations may exceed the exposure limits. Size and wording of the signs and labels are specified.

4. You must provide at your cost, preplacement, annual, and termination medical examinations for those exposed to asbestos.

5. You must maintain records of all personal or environmental sampling data as well as medical examinations.

6. Every employee has the right of access to any of these records which may indicate any of his exposures. Also employees shall be given a reasonable opportunity to observe the actual monitoring.

7. How the sampling is done is outlined in detail. Clean-up method, etc. are specified.

All of this is in the current OSHA standards (para. 1910.93 a). The OSHA inspector's job has become much simpler. All he needs to do is ask to see your records, etc. If you have not followed the above procedures, you are subject to a citation regardless of the results.

The pattern should be clear. Rather than having to prove overexposures, the OSHA inspector now only has to prove that you have failed to conduct an occupational health evaluation of asbestos exposures and kept records.

Obviously many employers are not prepared for this. To assist you in deciding how you will meet these obligations, we have prepared a list of equipment and materials needed, exact counting techniques, sampling calibration information, etc. (If you want this kit, please request it on the enclosed card.) As standards are adopted for the other materials we will try to release similar sets of information for each one.

§ 1910.93 Air contaminants.

• • • • •

TABLE G-3—MINERAL DUSTS

Substance	Mppcf	Mg/M³
Silica:		
Crystalline:		
Quartz (respirable)	250 ‡	10mg/M³ ÷
	%SiO₂+5	%SiO₂+2
Quartz (total dust)		30mg/M³ ÷
		%SiO₂+2
Cristobalite: Use ½ the value calculated from the count or mass formulae for quartz.		
Tridymite: Use ½ the value calculated from the formulae for quartz.		
Amorphous, including natural diatomaceous earth	20	80mg/M³ ÷
		%SiO₂
Silicates (less than 1% crystalline silica):		
Asbestos	2†	
Portland cement	50	
Graphite (natural)	15	
Coal dust (respirable fraction less than 5% SiO₂)		2.4mg/M³ or 10mg/M³ ÷
For more than 5% SiO₂		%SiO₂+2
Inert or Nuisance Dust:		
Respirable fraction	15	5mg/M³
Total dust	50	15mg/M³

NOTE: Conversion factors—
mppcf×35.3=million particles per cubic meter
=particles per c.c.

‡ Millions of particles per cubic foot of air, based on impinger samples counted by konimeter techniques.

† The percentage of crystalline silica in the formula is the amount determined from samples collected in the breathing zone in which other methods have been shown to be of interest.

* As determined by the membrane filter method at 43× (high-dust count) using phase contrast illumination.

◊ Both concentration and percent quartz for the application of this limit are to be determined from the fraction passing a size-selector with the following characteristics:

Aerodynamic diameter (unit density sphere)	Percent passing selector
2	90
2.5	75
3.5	50
5.0	25
10	0

The measurements under this note refer to the use of an AEC (now MSHA) instrument. If the respirable fraction of coal dust is determined with a MRE Gravimetric dust sampling unit, then the 2.4 Mg/M³ in the table for coal dust is 4.5 Mg/M³.

2. A new § 1910.93a is added to Part 1910, reading as follows:

§ 1910.93a Asbestos.

(a) *Definitions.* For the purpose of this section, (1) "Asbestos" includes chrysotile, amosite, crocidolite, tremolite, anthophyllite, and actinolite.

(2) "Asbestos fibers" means asbestos fibers longer than 5 micrometers.

(b) *Permissible exposure to airborne concentrations of asbestos fibers*—(1) *Standard effective July 7, 1972.* The 8-hour time-weighted average airborne concentrations of asbestos fibers to which any employee may be exposed shall not exceed five fibers, longer than 5 micrometers, per cubic centimeter of air, as determined by the method prescribed in paragraph (e) of this section.

(2) *Standard effective July 1, 1976.* The 8-hour time-weighted average airborne concentrations of asbestos fibers to which any employee may be exposed shall not exceed two fibers, longer than 5 micrometers, per cubic centimeter of air, as determined by the method prescribed in paragraph (e) of this section.

(3) *Ceiling concentration.* No employee shall be exposed at any time to airborne concentrations of asbestos fibers in excess of 10 fibers, longer than 5 micrometers, per cubic centimeter of air, as determined by the method prescribed in paragraph (e) of this section.

(c) *Methods of compliance*—(1) *Engineering methods.* (i) *Engineering controls.* Engineering controls, such as, but not limited to, isolation, enclosure, exhaust ventilation, and dust collection, shall be used to meet the exposure limits prescribed in paragraph (b) of this section.

(ii) *Local exhaust ventilation.* (a) Local exhaust ventilation and dust collection systems shall be designed, constructed, installed, and maintained in accordance with the American National Standard Fundamentals Governing the Design and Operation of Local Exhaust Systems, ANSI Z9.2–1971, which is incorporated by reference herein.

(b) See § 1910.6 concerning the availability of ANSI Z9.2–1971, and the maintenance of a historic file in connection therewith. The address of the American National Standards Institute is given in § 1910.100.

(iii) *Particular tools.* All hand-operated and power-operated tools which may produce or release asbestos fibers in excess of the exposure limits prescribed in paragraph (b) of this section, such as, but not limited to, saws, scorers, abrasive wheels, and drills, shall be provided with local exhaust ventilation systems in accordance with subdivision (ii) of this subparagraph.

(2) *Work practices*—(i) *Wet methods.* Insofar as practicable, asbestos shall be handled, mixed, applied, removed, cut, scored, or otherwise worked in a wet state sufficient to prevent the emission of airborne fibers in excess of the exposure limits prescribed in paragraph (b) of this section, unless the usefulness of the product would be diminished thereby.

(ii) *Particular products and operations.* No asbestos cement, mortar, coating, grout, plaster, or similar material containing asbestos shall be removed from bags, cartons, or other containers in which they are shipped, without being either wetted, or enclosed, or ventilated so as to prevent effectively the release of airborne asbestos fibers in excess of the limits prescribed in paragraph (b) of this section.

(iii) *Spraying, demolition, or removal.* Employees engaged in the spraying of asbestos, the removal, or demolition of pipes, structures, or equipment covered or insulated with asbestos, and in the removal or demolition of asbestos insulation or coverings shall be provided with respiratory equipment in accordance with paragraph (d)(2)(iii) of this section and with special clothing in accordance with paragraph (f)(3) of this section.

(d) *Personal protective equipment*—(1) Compliance with the exposure limits prescribed by paragraph (b) of this section may not be achieved by the use of respirators or shift rotation of employees, except:

(i) During the time period necessary to install the engineering controls and to institute the work practices required by paragraph (c) of this section;

(ii) In work situations in which the methods prescribed in paragraph (c) of this section are either technically not feasible or feasible to an extent insufficient to reduce the airborne concentrations of asbestos fibers below the limits prescribed by paragraph (b) of this section; or

(iii) In emergencies.

(iv) Where both respirators and personnel rotation are allowed by subdivisions (i), (ii), or (iii) of this subparagraph, and both are practicable, personnel rotation shall be preferred and used.

(2) Where a respirator is permitted by subparagraph (1) of this paragraph, it shall be selected from among those approved by the Bureau of Mines, Department of the Interior, or the National Institute for Occupational Safety and Health, Department of Health, Education, and Welfare, under the provisions of 30 CFR Part 11 (37 F.R. 6214, Mar. 25, 1972), and shall be used in accordance with subdivisions (i), (ii), (iii), and (iv) of this subparagraph.

(i) *Air purifying respirators.* A reusable or single use air purifying respirator, or a respirator described in subdivision (ii) or (iii) of this subparagraph, shall be used to reduce the concentrations of airborne asbestos fibers in the respirator below the exposure limits prescribed in paragraph (b) of this section, when the ceiling or the 8-hour time-weighted average concentrations of asbestos fibers are reasonably expected to exceed no more than 10 times those limits.

(ii) *Powered air purifying respirators.* A full facepiece powered air purifying respirator, or a powered air purifying respirator, or a respirator described in subdivision (iii) of this subparagraph, shall be used to reduce the concentrations of airborne asbestos fibers in the respirator below the exposure limits prescribed in paragraph (b) of this section, when the ceiling or the 8-hour time-weighted average concentrations of asbestos fibers are reasonably expected to exceed 10 times, but not 100 times, those limits.

(iii) *Type "C" supplied-air respirators, continuous flow or pressure-demand class.* A type "C" continuous flow or pressure-demand, supplied-air respirator shall be used to reduce the concentrations of airborne asbestos fibers in the respirator below the exposure limits prescribed in paragraph (b) of this section, when the ceiling or the 8-hour time-weighted average airborne concentrations of asbestos fibers are reasonably expected to exceed 100 times those limits.

(iv) *Establishment of a respirator program.* (a) The employer shall establish a respirator program in accordance with

SGP 0006716

the requirements of the American National Standards Practices for Respiratory Protection, ANSI Z88.2–1969, which is incorporated by reference herein.

b. See § 1910.6 concerning the availability of ANSI Z88.2–1969 and the maintenance of an historic file in connection therewith. The address of the American National Standards Institute is given in § 1910.100.

(c) No employee shall be assigned to tasks requiring the use of respirators if, based upon his most recent examination, an examining physician determines that the employee will be unable to function normally wearing a respirator, or that the safety or health of the employee or other employees will be impaired by his use of a respirator. Such employee shall be rotated to another job or given the opportunity to transfer to a different position whose duties he is able to perform with the same employer, in the same geographical area and with the same seniority, status, and rate of pay he had just prior to such transfer, if such a different position is available.

(3) Special clothing: The employer shall provide, and require the use of, special clothing, such as coveralls or similar whole body clothing, head coverings, gloves, and foot coverings for any employee exposed to airborne concentrations of asbestos fibers, which exceed the ceiling level prescribed in paragraph (b) of this section.

(4) Change rooms: (i) At any fixed place of employment exposed to airborne concentrations of asbestos fibers in excess of the exposure limits prescribed in paragraph (b) of this section, the employer shall provide change rooms for employees working regularly at the place.

(ii) Clothes lockers: The employer shall provide two separate lockers or containers for each employee, so separated or isolated as to prevent contamination of the employee's street clothes from his work clothes.

(iii) Laundering: (a) Laundering of asbestos contaminated clothing shall be done so as to prevent the release of airborne asbestos fibers in excess of the exposure limits prescribed in paragraph (b) of this section.

(b) Any employer who gives asbestos-contaminated clothing to another person for laundering shall inform such person of the requirement in (a) of this subdivision to effectively prevent the release of airborne asbestos fibers in excess of the exposure limits prescribed in paragraph (b) of this section.

(c) Contaminated clothing shall be transported in sealed impermeable bags, or other closed, impermeable containers, and labeled in accordance with paragraph (g) of this section.

(e) *Method of measurement.* All determinations of airborne concentrations of asbestos fibers shall be made by the membrane filter method at 400–450 × (magnification) (4-millimeter objective) with phase contrast illumination.

(f) *Monitoring*—(1) *Initial determinations.* Within 6 months of the publication of this section, every employer shall cause every place of employment where asbestos fibers are released to be monitored in such a way as to determine whether every employee's exposure to asbestos fibers is below the limits prescribed in paragraph (b) of this section. If the limits are exceeded, the employer shall immediately undertake a compliance program in accordance with paragraph (c) of this section.

(2) *Personal monitoring*—(i) Samples shall be collected from within the breathing zone of the employees, on membrane filters of 0.8 micrometer porosity mounted in an open-face filter holder. Samples shall be taken for the determination of the 8-hour time-weighted average airborne concentrations and of the ceiling concentrations of asbestos fibers.

(ii) Sampling frequency and patterns. After the initial determinations required by subparagraph (1) of this paragraph, samples shall be of such frequency and pattern as to represent with reasonable accuracy the levels of exposure of employees. In no case shall the sampling be done at intervals greater than 6 months for employees whose exposure to asbestos may reasonably be foreseen to exceed the limits prescribed by paragraph (b) of this section.

(3) *Environmental monitoring*—(i) samples shall be collected from areas of a work environment which are representative of the airborne concentrations of asbestos fibers which may reach the breathing zone of employees. Samples shall be collected on a membrane filter of 0.8 micrometer porosity mounted in an open-face filter holder. Samples shall be taken for the determination of the 8-hour time-weighted average airborne concentrations and of the ceiling concentrations of asbestos fibers.

(ii) *Sampling frequency and patterns.* After the initial determinations required by subparagraph (1) of this paragraph, samples shall be of such frequency and pattern as to represent with reasonable accuracy the levels of exposure of the employees. In no case shall sampling be at intervals greater than 6 months for employees whose exposures to asbestos may reasonably be foreseen to exceed the exposure limits prescribed in paragraph (b) of this section.

(4) *Employee observation of monitoring.* Affected employees, or their representatives, shall be given a reasonable opportunity to observe any monitoring required by this paragraph and shall have access to the records thereof.

(g) *Caution signs and labels.* (1) *Caution signs.* (i) *Posting.* Caution signs shall be provided and displayed at each location where airborne concentrations of asbestos fibers may be in excess of the exposure limits prescribed in paragraph (b) of this section. Signs shall be posted at such a distance from such a location so that an employee may read the signs and take necessary protective steps before entering the area marked by the signs. Signs shall be posted at all approaches to areas containing excessive concentrations of airborne asbestos fibers.

(ii) *Sign specifications.* The warning signs required by subdivision (i) of this subparagraph shall conform to the requirements of 20" x 14" vertical format signs specified in § 1910.145(d)(4), and to this subdivision. The signs shall display the following legend in the lower panel, with letter sizes and styles of a visibility at least equal to that specified in this subdivision.

Legend	Notation
Asbestos	1" Sans Serif, Gothic or Block.
Dust Hazard	½" Sans Serif, Gothic or Block.
Avoid Breathing Dust	¼" Gothic.
Wear Assigned Protective Equipment.	¼" Gothic.
Do Not Remain In Area Unless Your Work Requires It.	¼" Gothic.
Breathing Asbestos Dust May Be Hazardous To Your Health.	14 point Gothic.

Spacing between lines shall be at least equal to the height of the upper of any two lines.

(2) *Caution labels*—(i) *Labeling.* Caution labels shall be affixed to all raw materials, mixtures, scrap, waste, debris, and other products containing asbestos fibers, or to their containers, except that no label is required where asbestos fibers have been modified by a bonding agent, coating, binder, or other material so that during any reasonably foreseeable use, handling, storage, disposal, processing, or transportation, no airborne concentrations of asbestos fibers in excess of the exposure limits prescribed in paragraph (b) of this section will be released.

(ii) *Label specifications.* The caution labels required by subdivision (i) of this subparagraph shall be printed in letters of sufficient size and contrast as to be readily visible and legible. The label shall state:

CAUTION

Contains Asbestos Fibers
Avoid Creating Dust
Breathing Asbestos Dust May Cause Serious Bodily Harm

(h) *Housekeeping*—(1) *Cleaning.* All external surfaces in any place of employment shall be maintained free of accumulations of asbestos fibers if, with their dispersion, there would be an excessive concentration.

(2) *Waste disposal.* Asbestos waste, scrap, debris, bags, containers, equipment, and asbestos-contaminated clothing, consigned for disposal, which may produce in any reasonably foreseeable use, handling, storage, processing, disposal, or transportation airborne concentrations of asbestos fibers in excess of the exposure limits prescribed in paragraph (b) of this section shall be collected and disposed of in sealed impermeable bags, or other closed, impermeable containers.

(i) *Recordkeeping*—(1) *Exposure records.* Every employer shall maintain records of any personal or environmental monitoring required by this section. Records shall be maintained for a period of at least 3 years and shall be made available upon request to the Assistant Secretary of Labor for Occupational Safety and Health, the Director of the National

SGP 0006717

Institute for Occupational Safety and Health, and to authorized representatives of either.

(2) *Employee access.* Every employee and former employee shall have reasonable access to any record required to be maintained by subparagraph (1) of this paragraph, which indicates the employee's own exposure to asbestos fibers.

(3) *Employee notification.* Any employee found to have been exposed at any time to airborne concentrations of asbestos fibers in excess of the limits prescribed in paragraph (b) of this section shall be notified in writing of the exposure as soon as practicable but not later than 5 days of the finding. The employee shall also be timely notified of the corrective action being taken.

(j) *Medical examinations*—(1) *General.* The employer shall provide or make available at his cost, medical examinations relative to exposure to asbestos required by this paragraph.

(2) *Preplacement.* The employer shall provide or make available to each of his employees, within 30 calendar days following his first employment in an occupation exposed to airborne concentrations of asbestos fibers, a comprehensive medical examination, which shall include, as a minimum, a chest roentgenogram (posterior-anterior 14 x 17 inches), a history to elicit symptomatology of respiratory disease, and pulmonary function tests to include forced vital capacity (FVC) and forced expiratory volume at 1 second ($FEV_{1.0}$).

(3) *Annual examinations.* On or before January 31, 1973, and at least annually thereafter, every employer shall provide, or make available, comprehensive medical examinations to each of his employees engaged in occupations exposed to airborne concentrations of asbestos fibers. Such annual examination shall include, as a minimum, a chest roentgenogram (posterior-anterior 14 x 17 inches), a history to elicit symptomatology of respiratory disease, and pulmonary function tests to include forced vital capacity (FVC) and forced expiratory volume at 1 second ($FEV_{1.0}$).

(4) *Termination of employment.* The employer shall provide, or make available, within 30 calendar days before or after the termination of employment of any employee engaged in an occupation exposed to airborne concentrations of asbestos fibers, a comprehensive medical examination which shall include, as a minimum, a chest roentgenogram (posterior-anterior 14 x 17 inches), a history to elicit symptomatology of respiratory disease, and pulmonary function tests to include forced vital capacity (FVC) and forced expiratory volume at 1 second ($FEV_{1.0}$).

(5) *Recent examinations.* No medical examination is required of any employee, if adequate records show that the employee has been examined in accordance with this paragraph within the past 1-year period.

(6) *Medical records*—(i) *Maintenance.* Employers of employees examined pursuant to this paragraph shall cause to be maintained complete and accurate records of all such medical examinations. Records shall be retained by employers for at least 20 years.

(ii) *Access.* The contents of the records of the medical examinations required by this paragraph shall be made available, for inspection and copying, to the Assistant Secretary of Labor for Occupational Safety and Health, the Director of NIOSH, to authorized physicians and medical consultants of either of them, and, upon the request of an employee or former employee, to his physician. Any physician who conducts a medical examination required by this paragraph shall furnish to the employer of the examined employee all the information specifically required by this paragraph, and any other medical information related to occupational exposure to asbestos fibers.

3. A new § 1910.19 is added to Subpart Z of Part 1910, reading as follows:

§ 1910.19 Asbestos dust.

Section 1910.93a shall apply to the exposure of every employee to asbestos dust in every employment and place of employment covered by § 1910.12, § 1910.13, § 1910.14, § 1910.15, or § 1910.16, in lieu of any different standard on exposure to asbestos dust which would otherwise be applicable by virtue of any of those sections.

Effective date. Paragraph (b)(2) of § 1910.93a shall become effective July 1, 1976. All other provisions of §§ 1910.93a, 1910.93, and 1910.19 shall become effective July 7, 1972. The current emergency temporary standard remains in effect until July 7, 1972.

(Secs. 6, 8, 81 Stat. 1593, 1598; 29 U.S.C. 655, 657; 33 CFR 1910.4; Secretary of Labor's Order No. 12-71, 36 F.R. 8754)

Signed at Washington, D.C., this 2d day of June 1972.

G. C. GUENTHER,
Assistant Secretary of Labor.

[FR Doc.72-8574 Filed 6-6-72;8:48 am]

Title 41—PUBLIC CONTRACTS AND PROPERTY MANAGEMENT

Chapter 9—Atomic Energy Commission

PART 9-1—GENERAL

Subpart 9-1.1—Procurement Regulations

MISCELLANEOUS AMENDMENTS

The changes made in AECPR Subpart 9-1.1, Procurement Regulations, have been made in order to establish the AECPR Temporary Regulations, which are a part of the AEC Procurement Regulations and the Federal Procurement Regulations System. The AECPR Temporary Regulations implement and supplement the FPR Temporary Regulations. They also contain policies and procedures initiated by the AEC which are to be effective for a period of 6 months or less. The AEC Procurement Instruction section has been revised accordingly. Minor editorial changes have also been made.

1. Section 9-1.101 *Scope of subpart,* is revised to read as follows:

§ 9-1.101 Scope of subpart.

This subpart describes the Atomic Energy Commission Procurement Regulations and the AECPR Temporary Regulations. It also describes exclusions from the AECPR as contained in the AEC Procurement Instructions.

2. Section 9-1.102 *Establishment of AEC Procurement Regulations,* is revised to read as follows:

§ 9-1.102 Establishment of the AEC Procurement Regulations and the *AECPR Temporary Regulations.*

§ 9-1.102-1 AEC Procurement Regulations.

(a) The AEC Procurement Regulations (AECPR) are hereby established.

(b) These regulations implement and supplement the Federal Procurement Regulations (FPR) and are a part of the Federal Procurement Regulations System.

(c) The effective date of FPR issuances throughout AEC will be the date indicated in the respective issuances unless otherwise provided in the AEC Procurement Regulations.

(d) The effective date of AECPR issuances throughout AEC will be the date indicated in the respective issuances.

§ 9-1.102-2 AECPR *Temporary* Regulations.

(a) The AECPR Temporary Regulations are hereby established.

(b) These regulations implement and supplement the Federal Procurement Regulations Temporary Regulations. They also contain policies and procedures initiated by the AEC which are expected to be effective for a period of 6 months or less.

(c) The effective date of the FPR Temporary Regulations issuances throughout AEC will be the date indicated in the respective issuances unless otherwise provided in the AECPR Temporary Regulations.

(d) The effective date of the AECPR Temporary Regulations issuances throughout AEC will be the date indicated in the respective issuances.

(e) The AECPR Temporary Regulations are a part of the AEC Procurement Regulations and the Federal Procurement Regulations System. All references to the AEC Procurement Regulations or AECPR in §§ 9-1.103 through 9-1.109 of this subpart shall be deemed to include the AECPR temporary regulations.

3. Section 9-1.103 *Authority,* is revised to read as follows:

§ 9-1.103 Authority.

The AEC Procurement Regulations are prescribed by the General Manager, Assistant General Manager for Administration, or the Director, Division of Contracts of the AEC, pursuant to the authority of the Atomic Energy Act of 1954, and the Federal Property and Administrative Services Act of 1949.

SGP 0006718