

WOOD FIBER PLASTER**UNITED STATES GYPSUM****USE**

Wood Fiber Plaster is excellent for patching holes and filling large cracks in old plaster surfaces. Do not use for fine cracks. Spackling putty is recommended for fine cracks.

MIXING

Mix with water only in a clean container - allow to soak a few minutes before mixing.

APPLICATION

Apply directly to gypsum lath, wood lath or metal lath. For patching, remove all broken or defective plaster and provide a firm base. Wet adjoining plaster and wood lath thoroughly, then fill in patch and trowel to a smooth surface. Plaster will not adhere to smooth, oily or dusty surfaces. On wood lath and metal lath it is recommended that a $\frac{1}{4}$ " thick coat be troweled on cross raked, or broomed, and allowed to set before filling in to level of old surface.

CAUTION

After application protect against drying out until the plaster has set hard, then allow to dry naturally. Mix no more than can be used in one half hour. Do not mix one batch with another. Do not use any mix that has begun to set.

Since methods and conditions of application and use are beyond the control of the United States Gypsum Company, its warranties of FITNESS and MERCHANTABILITY as well as any other warranties express or implied, made in connection with the sale of this product SHALL NOT BE EFFECTIVE OR ACTIONABLE UNLESS the product is applied according to United States Gypsum Company's directions or specifications.

WEIGHTS**9.91 LBS. NET****10 LBS. GROSS**