

(Approved by U.S. Department of Labor "Essentially Similar" to Form OSHA 20)  
Conforms with air pollution rules and regulations

|         |   |                       |
|---------|---|-----------------------|
| SECTION | 2 | HAZARDOUS INGREDIENTS |
|---------|---|-----------------------|

SECTION 3 PHYSICAL DATA

SOLUBILITY IN WATER NO

## SPECIAL FIRE FIGHTING PROCEDURES

Fire fighters must wear self contained breathing apparatus or air masks.  
Containers exposed to fire should be kept cool with water spray.

UNUSUAL FIRE AND EXPLOSION HAZARDS

END

[illegible]

| THRESHOLD LIMIT VALUE | HEALTH       | AND DATA      |
|-----------------------|--------------|---------------|
|                       | Not Required | Miscellaneous |

#### EFFECTS OF OVEREXPOSURE

RESPIRATORY IRRITATION, DIZZINESS, NAUSEA, LOSS OF CONSCIOUSNESS

#### EMERGENCY AND FIRST AID PROCEDURES

IMMEDIATELY REMOVE PERSON FROM EXPOSURE AREA

IF BREATHING HAS STOPPED, USE MOUTH TO MOUTH RESUSCITATION

AND GET MEDICAL ATTENTION

EYE CONTACT: FLUSH WITH WATER FOR 15 MINUTES.

SKIN CONTACT: WASH WITH SOAP AND WATER

#### SECTION 6 REACTIVITY DATA

| STABLE | UNSTABLE | CONDITIONS TO AVOID |
|--------|----------|---------------------|
| X      |          |                     |

INCOMPATIBILITY NONE

#### HAZARDOUS DECOMPOSITION PRODUCTS

CARBON DIOXIDE AND CARBON MONOXIDE

| HAZARDOUS POLYMERIZATION | CONDITIONS TO AVOID |
|--------------------------|---------------------|
| NONE                     | MAY OCCUR           |
| X                        |                     |

#### SECTION 7 SPILL OR LEAK PROCEDURES

VENTILATE AREA. AVOID BREATHING OF VAPORS

USE SELF-CONTAINED BREATHING APPARATUS OR AIR MASK

FOR LARGE SPILLS IN A CONFINED AREA

AVOID CONTACT WITH EYES

Wipe up or absorb on suitable material and shovel up

#### WASTE DISPOSAL METHOD

Dispose in chemical disposal area or in a manner that complies with local, state and federal regulations. Do not incinerate closed containers

#### SECTION 8 SPECIAL PROTECTION INFORMATION

##### RESPIRATORY PROTECTION

Use appropriate Bureau of Mines approved respiratory device in confined areas and for spray application

| VENTILATION                                     | LOCAL | OTHER |
|-------------------------------------------------|-------|-------|
| Required for spraying or in a confined area.    |       |       |
| Ventilation equipment should be explosion proof |       | NONE  |

PROTECTIVE GLOVES USUAL HAND PROTECTION FOR PAINT APPLICATION

EYE PROTECTION USUAL EYE PROTECTION FOR APPLYING PAINT

##### OTHER PROTECTIVE EQUIPMENT

USUAL CLOTHING FOR PAINTING OPERATIONS

#### SECTION IX SPECIAL PRECAUTIONS

##### PRECAUTIONS TO BE TAKEN IN HANDLING AND STORAGE

Containers should be grounded when pouring. Avoid free fall of liquid in excess of a few inches. Keep away from heat, sparks and open flames. Keep container closed when not in use. Do not store above 100°F. Based on the product flash point and vapor pressure suitable storage should be provided in accordance with OSHA Regulation 1910.106

ISSUE DATE 7/10/79  
 Supersedes 3/19/75 Issue

This data is based on information in effect at date of issue  
 Contains information on current publications

# Mobil Chemical

220 2240 (9/73)  
Plainfield  
EDISON

## MATERIAL SAFETY DATA SHEET

(Approved by U.S. Department of Labor "Essentially Similar" to Form OSHA 20)

Conforms with air pollution rules and regulations

| SECTION 1                                                                |                                                   |
|--------------------------------------------------------------------------|---------------------------------------------------|
| MANUFACTURER'S ADDRESS <u>See 2nd Page of Material Safety Data Sheet</u> |                                                   |
| CHEMICAL NAME OR FAMILY<br>Exterior Latex Vinyl Acrylic Primer           | EMERGENCY TELEPHONE 212/853-5366                  |
| FORMULA<br>N/A                                                           | TRADE NAME<br>Latex Block Filler.<br>White 79-W-8 |

| SECTION 2 HAZARDOUS INGREDIENTS |                             |
|---------------------------------|-----------------------------|
|                                 | % WT. TLV (Units)           |
| ETHYLENE GLYCOL                 | <5 100 PPM                  |
| TEXANOL                         | <5 NOT ESTABLISHED BY ACGIH |
| ODORLESS MIN. SPIRITS           | <5 200 PPM                  |

| SECTION 3 PHYSICAL DATA                                           |                                 |                              |                                              |                         |                                |
|-------------------------------------------------------------------|---------------------------------|------------------------------|----------------------------------------------|-------------------------|--------------------------------|
| BOILING POINT<br>°F                                               | VAPOR PRESSURE<br>mmHg at 68 °F | VAPOR DENSITY<br>(AIR = 1.0) | SPECIFIC GRAVITY<br>(H <sub>2</sub> O = 1.0) | % VOLATILE BY<br>VOLUME | EVAP. RATE<br>(BUTYL ACET = 1) |
| 338                                                               | 1.19                            | 0.7                          | 1.52                                         | 53                      | 0.05                           |
| SOLUBILITY IN WATER NO                                            |                                 |                              |                                              |                         |                                |
| APPEARANCE AND ODOR<br>NORMAL FOR A PAINT OR COATING TYPE PRODUCT |                                 |                              |                                              |                         |                                |

| SECTION 4 FIRE AND EXPLOSION HAZARD                                             |                  |     |
|---------------------------------------------------------------------------------|------------------|-----|
| FLASH POINT<br>TCC/PM °F                                                        | FLAMMABLE LIMITS |     |
|                                                                                 | LEL              | UEL |
| NA                                                                              | NA               | NA  |
| EXTINGUISHING MEDIA<br>CARBON DIOXIDE, DRY CHEMICAL, FOAM,<br>AND/OR WATER FOG. |                  |     |

|                                                                                                                                                                            |
|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| SPECIAL FIRE FIGHTING PROCEDURES<br>Fire fighters must wear self contained breathing apparatus or air line<br>Containers exposed to fire should be cooled with water spray |
| UNUSUAL FIRE AND EXPLOSION HAZARDS                                                                                                                                         |

## SECTION 5 HEALTH HAZARD DATA

79-W-8

## THRESHOLD LIMIT VALUE

Not Required for Mixtures

## EFFECTS OF OVEREXPOSURE

None

## EMERGENCY AND FIRST AID PROCEDURES

INHALATION: NO PROBLEM AT NORMAL TEMPERATURE

EYE CONTACT: FLUSH WITH WATER FOR 15 MINUTES.

SKIN CONTACT: WASH WITH SOAP AND WATER

## SECTION 6 REACTIVITY DATA

## STABLE UNSTABLE CONDITIONS TO AVOID

X

## INCOMPATIBILITY

None

## HAZARDOUS DECOMPOSITION PRODUCTS

CARBON DIOXIDE AND CARBON MONOXIDE

## HAZARDOUS POLYMERIZATION CONDITIONS TO AVOID

NONE (MAY OCCUR)

X

## SECTION 7 SPILL OR LEAK PROCEDURES

AVOID CONTACT WITH EYES

Wipe up or absorb on suitable material and shovel up

## WASTE DISPOSAL METHOD

Dispose in chemical disposal area or in a manner that complies with local, state and federal regulations. Do not incinerate closed containers.

## SECTION 8 SPECIAL PROTECTION INFORMATION

## RESPIRATORY PROTECTION

Use appropriate Bureau of Mines approved respiratory device in confined areas and for spray applications

## VENTILATION

LOCAL

OTHER

Required for spraying or in a confined area.

Ventilation equipment should be explosion proof.

None

PROTECTIVE GLOVES USUAL HAND PROTECTION FOR PAINT APPLICATION

EYE PROTECTION USUAL EYE PROTECTION FOR APPLYING PAINT

## OTHER PROTECTIVE EQUIPMENT

USUAL CLOTHING FOR PAINTING OPERATIONS

## SECTION IX SPECIAL PRECAUTIONS

## PRECAUTIONS TO BE TAKEN IN HANDLING AND STORAGE

Containers should be grounded when pouring. Avoid free fall of liquid in excess of a few inches. Keep away from heat, sparks and open flames. Keep container closed when not in use. Do not store above 120 °F. Based on the product flash point and vapor pressure suitable storage should be provided in accordance with OSHA Regulation 1910.106

MOB-HarrisMaster  
00034

# MOB-HARRIS MASTER

EDISON

## MATERIAL SAFETY DATA SHEET

(Approved by U.S. Department of Labor "Essentially Similar" to Form OSHA 20)

Conforms with Air Pollution Rules & Regulations

| SECTION 1                                                                                                                                                                        |                                  |                              |                                                                                |                         |                              |
|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|----------------------------------|------------------------------|--------------------------------------------------------------------------------|-------------------------|------------------------------|
| MANUFACTURER'S ADDRESS P.O. Box 250, Edison, N.J. 08817                                                                                                                          |                                  |                              |                                                                                |                         |                              |
| CHEMICAL NAME OR FAMILY<br>Oleoresinous Varnish Coating                                                                                                                          |                                  |                              | EMERGENCY TELEPHONE 212/ 683-5368                                              |                         |                              |
| FORMULA<br>Not Applicable                                                                                                                                                        |                                  |                              | TRADE NAME<br>Dum Dum Masonoc /<br>Soft White 95W9                             |                         |                              |
| SECTION 2 HAZARDOUS INGREDIENTS                                                                                                                                                  |                                  |                              |                                                                                |                         |                              |
| EXEMPT MIN. SPIRITS                                                                                                                                                              | % WT<br>45                       | TLV (UNITS)<br>100 PPM       |                                                                                |                         |                              |
| SECTION 3 PHYSICAL DATA                                                                                                                                                          |                                  |                              |                                                                                |                         |                              |
| BOILING POINT<br>OF                                                                                                                                                              | VAPOR PRESSURE<br>mm Hg at 68 °F | VAPOR DENSITY<br>(AIR = 1.0) | SPECIFIC GRAVITY<br>(H <sub>2</sub> O = 1.0)                                   | % VOLATILE BY<br>VOLUME | EVAP RATE<br>(BUTYL ACETATE) |
| 314                                                                                                                                                                              | 1.03                             | 4.3                          | 1.03                                                                           | 57                      | 0.09                         |
| SOLUBILITY IN WATER NO                                                                                                                                                           |                                  |                              |                                                                                |                         |                              |
| APPEARANCE AND ODOR<br>NORMAL FOR A PAINT OR COATING TYPE PRODUCT                                                                                                                |                                  |                              |                                                                                |                         |                              |
| SECTION 4 FIRE AND EXPLOSION HAZARD                                                                                                                                              |                                  |                              |                                                                                |                         |                              |
| FLASH POINT<br>TCC/PM °F                                                                                                                                                         | FLAMMABLE LIMITS<br>LEL UEL      |                              | EXTINGUISHING MEDIA<br>CARBON DIOXIDE, DRY CHEMICAL, FOAM,<br>AND/OR WATER FOG |                         |                              |
| 113                                                                                                                                                                              | 1.0                              | 6.0                          |                                                                                |                         |                              |
| SPECIAL FIRE FIGHTING PROCEDURES<br>Fire fighters must wear self contained breathing apparatus or air masks.<br>Containers exposed to fire should be kept cool with water spray. |                                  |                              |                                                                                |                         |                              |
| UNUSUAL FIRE AND EXPLOSION HAZARDS<br>NONE                                                                                                                                       |                                  |                              |                                                                                |                         |                              |

The information on this sheet is based on the data available to the manufacturer at the time of preparation of the sheet. It is not intended to be used as a substitute for the manufacturer's safety data sheet. The user should consult the manufacturer's safety data sheet for more complete information. The information on this sheet is not intended to be used as a substitute for the manufacturer's safety data sheet. The user should consult the manufacturer's safety data sheet for more complete information.

## THRESHOLD LIMIT VALUE SECTION 5 Not Required for Mixtures

## EFFECTS OF OVEREXPOSURE

RESPIRATORY IRRITATION, DIZZINESS, NAUSEA, LOSS OF CONSCIOUSNESS

## EMERGENCY AND FIRST AID PROCEDURES

INHALATION: REMOVE PERSON FROM EXPOSURE AREA  
 IF BREATHING HAS STOPPED, USE MOUTH TO MOUTH RESUSCITATION  
 AND GET MEDICAL ATTENTION  
 EYE CONTACT: FLUSH WITH WATER FOR 15 MINUTES.  
 SKIN CONTACT: WASH WITH SOAP AND WATER

## SECTION 6 REACTIVITY DATA

STABLE UNSTABLE I CONDITIONS TO AVOID

X I I

INCOMPATIBILITY NONE

HAZARDOUS DECOMPOSITION PRODUCTS

CARBONDIOXIDE AND CARBON MONOXIDE

HAZARDOUS POLYMERIZATION CONDITIONS TO AVOID

NONE MAY OCCUR

X I

## SECTION 7 SPILL OR LEAK PROCEDURES

VENTILATE AREA. AVOID BREATHING OF VAPORS  
 USE SELF-CONTAINED BREATHING APPARATUS OR AIR MASK  
 FOR LARGE SPILLS IN A CONFINED AREA  
 AVOID CONTACT WITH EYES  
 Wipe up or absorb on suitable material and shovel up

## WASTE DISPOSAL METHOD

Dispose in chemical disposal area or in a manner that complies with local, state and federal regulations.  
 Do not incinerate closed containers.

## SECTION 8 SPECIAL PROTECTION INFORMATION

## RESPIRATORY PROTECTION

Use appropriate Bureau of Mines approved respiratory device in confined areas and for spray applications

VENTILATION

LOCAL

OTHER

Required for spraying or in a confined area.

Ventilation equipment should be explosion proof

NONE

PROTECTIVE GLOVES

USUAL HAND PROTECTION FOR PAINT APPLICATION

EYE PROTECTION

USUAL EYE PROTECTION FOR APPLYING PAINT

OTHER PROTECTIVE EQUIPMENT

USUAL CLOTHING FOR PAINTING OPERATIONS

## SECTION IX SPECIAL PRECAUTIONS

## PRECAUTIONS TO BE TAKEN IN HANDLING AND STORAGE

Containers should be grounded when pouring liquid free of liquid in excess of a few inches. Keep away from heat, sparks and open flames. Keep container closed when not in use. Do not store below 20 °F. Based on the product flash point and vapor pressure suitable storage should be provided in accordance with OSHA Regulation 1910.106

ISSUE DATE JD 6/25/75

This data is based on formulation in effect at date of issue.  
 Consult Manufacturer for current specifications