



ONE

GALLON



RUBBERIZED TRAFFIC PAINT

YELLOW

DANGER!
EXTREMELY
FLAMMABLE
See cautions
elsewhere on label.

MADE BY THE O'BRIEN CORPORATION

• SOUTH BEND, IND. • BALTIMORE, MD. • OKLAHOMA CITY, OKLA. • SAN FRANCISCO, CAL. • LOS ANGELES, CAL. •

REGISTERED

REG'N. No. 3573

DATE
RUBBERIZED TRAFFIC PAINT 4-27-64

Made with natural rubber, this sensational product is the real answer to perennial street marking problems. Fast drying, it dries in three to five minutes on concrete or asphalt — in five to seven minutes on brick. Insures minimum "hold-up" and confusion on the job plus a definite savings in time and labor.

O'Brien's rubberized Traffic Paint is extremely durable. Tests indicate that it will last at least 75% longer than normal traffic paints. It has excellent coverage and affords above average hiding and gloss. May be applied without difficulty at zero temperatures, although drying will be slightly retarded.

DO NOT TAKE INTERNALLY

CAUTION!

CONTAINS LEAD. HARMFUL IF SWALLOWED. Keep away from heat, sparks and open flame. Do not apply on window sills, toys, furniture or interior surfaces of rooms which may be used by children. Avoid prolonged contact with skin and breathing of vapor or spray mist. Close container after each use. Use with adequate ventilation. KEEP OUT OF THE REACH OF CHILDREN.

TRAFFIC PAINT YELLOW
Percent Composition
Zinc Oxide 51.17%
Calcium Carbonate 27.21%
Silicones 18.00%
Vulcanized Rubber 4.00%
Phenolic Resin 7.17%
Aluminum Oxide 1.50%
Aromatic Hydrocarbons 8.95%

DIRECTIONS

Thinning — comes ready to use for machine spray application and for normal brush application (see Application).

Application — Machine spray is recommended. Brush method may be used with satisfactory results. If brush method is used during hot weather over brick or concrete, thin the material approximately 10% with O'Brien's PX-107 thinner. Don't thin the material if it is to be used over asphalt as "bleeding" might occur. The addition of PX-107 thinner will slightly retard the speedy drying.

Use of Beads — if beads are added to the paint at once, it is practical to use them. Because the paint dries so extremely fast, the beads must be dropped into the paint immediately upon application.

Caution — this paint will lift other types of paint, if they are fresh. However, if the paint has been on the surface for at least three months, it will not be affected in any way.

THE O'BRIEN CORPORATION
SOUTH BEND, IND. OKLAHOMA CITY, OKLA.
BALTIMORE, M.D. SAN FRANCISCO, CALIF.
LOS ANGELES, CALIF.

20 69-4

49 TOC 001678