

88-VIII

EFFECTIVE JULY 15, 1966

SUBJECT TO CHANGE WITHOUT NOTICE

SUGGESTED
WHOLESALE
PRICE LIST

**GLIDDEN PAINTS
SPRED PRODUCTS**



Glidden

INTERIOR WALL, CEILING AND WOODWORK FINISHES

SPRED[®] SATIN Y-3400 LINE

(100% Latex Interior Paint)

Original 100% latex base paint for interior walls, ceilings, woodwork. Excellent for masonry, interior plaster, porous wallboards, acoustical tile, wallpaper. The ideal latex paint for schools, hospitals, residences, offices, motels, hotels, apartments, housing projects, etc. Extremely fast, easy application; self priming, cuts painting time in half. No disagreeable odor. Guaranteed washable. May be tinted with DRAMATONE Tinting Colors.

3400	High Hiding White	6.16	2.02	—	—
3470	Ceiling Flat White and Ready-Mixed Colors	6.16	2.02	—	—
\$3418	Decorator Tinting White (Pastel Tint Base) (124 oz.) (31 oz.)	6.02	1.96	—	—
\$3480	Deep Tint Base (120 oz.) (30 oz.)	5.60	1.81	—	—
\$3487	Intermediate Tint Base (122 oz.) (30.5 oz.) For Tinting Special Colors	5.65	1.85	—	—

SPRED SATIN DEEP COLORS

3434	Charcoal Black	6.16	2.02	—	—
3482	Beaver Brown	6.16	2.02	—	—
3484	Cherry Red	7.82	2.32	—	—

APPLICATION—Brush, Roller, Spray

DRYING TIME—20 minutes; may be recoated in 4 hours

THINNER—Water

COVERAGE—Up to 500 Sq. Ft. per gallon over most surfaces

*CRAFTSMAN LATEX PAINT Y-3050 LINE

A specially formulated ready-to-use interior latex paint for application by brush or roller for plaster, wallboard, acoustical tile, masonry and wallpaper.

*SPRED STIPPLE TEXTURE AND BLOCK FILLER Y-3090

(Silicated Latex for Masonry and Dry-Wall Construction)

Ready to use on new or old surfaces. Gives all the advantages of texture and all the beauty of paint in one application. Hides irregular surfaces on plaster, wallboard, masonry blocks and wallpaper, seals spackled nail heads and tape joints. Easily applied with brush or roller. May be stippled or lightly textured in a variety of patterns and techniques. Especially made for texturing and stippling and for filling masonry blocks, pores and voids, to eliminate "pinholing" in finish coat, to assure better water repellency and to develop excellent appearance on interior and exterior masonry. May be tinted with DRAMATONE Tinting Colors.

Bone White

APPLICATION—Brush for texturing, followed by stipple brush, sponge, trowel, whisk broom, comb, etc., as desired. Use roller for stipple effect. Brush, roll or spray when used as a block filler

DRYING TIME—Overnight

THINNER—Water

COVERAGE—Texturing and filling blocks—75 to 100 Sq. Ft. per gallon. Stippling—175 to 200 Sq. Ft. per gallon

6.28

2.02

—

—

*AVAILABLE IN 5-GAL. CANS
AT 10¢ PER GALLON LESS THAN 1-GAL. PRICES.
\$SHORT FILLED TO ALLOW ADDITION OF COLORANT.

Glidden

SPRED FLAT Y-3000
(OIL EMULSION INTERIOR PAINT)

One gallon makes six quarts of paint when mixed with two quarts of water. Easy to apply over wallpaper, new or old plaster, wallboard, painted surfaces, cement and rough tile walls. Has limited washability

White

APPLICATION—Brush, Roller, Spray

DRYING TIME—30 minutes; recoat 4 to 12 hours, depending upon surface

THINNER—Water

COVERAGE—Up to 650 Sq. Ft. per gallon

Gals.

Qts.

Pts.

½ Pts.

5.92

1.88

—

—

BRUSH-DAY-LITE ALKYD FLAT ENAMEL
Y-5700 LINE

Beautiful, completely washable, flat alkyd enamel for interior wall surfaces, including plaster, wood, concrete, wallboard and metal. Can be applied quickly with a wide brush or roller. Flows out smoothly. One coat is usually sufficient. Colors match SPRED SATIN

White and Colors

APPLICATION—Brush, Roller, Spray

DRYING TIME—4 hours; overnight for recoating

THINNER—Mineral Spirits or Turpentine

COVERAGE—Up to 550 Sq. Ft. per gallon

6.19

2.02

—

—

§5718 Tinting White (Pastel Tint Base) (124 oz.) (31 oz.)

5.11

1.75

—

—

§5787 Intermediate Tint Base (122 oz.) (30.5 oz.)

5.02

1.70

—

—

§5780 Deep Tint Base (120 oz.) (30 oz.)

4.93

1.66

—

—

For Tinting Brush-Day-Lite Alkyd Flat Enamel Colors

19-W-770 Craftsman Alkyd Flat Wall Finish White

—

—

—

—

UNDERCOATERS AND PRIMERS FOR
WALLS, CEILING AND WOODWORK

***SPRED PRIMER-SEALER Y-3416**
(A Latex Vapor-Barrier)

An excellent latex primer for porous surfaces of dry-wall construction, plaster, masonry and asbestos covered pipes. Seals high-suction plaster, most water stains, "hot spots" and discolored surfaces. Assures positive sealing and holdout for succeeding finishing coats of either latex or oil base paints. May be intermixed with latex paints for color, or tinted with DRAMATONE Tinting Colors. An approved vapor barrier which helps to prevent outside paint failures

APPLICATION—Brush, Roller, Spray

THINNER—Water

DRYING TIME—20 minutes; may be recoated in 4 hours

COVERAGE—Up to 400 Sq. Ft. per gallon on plaster; 100 Sq. Ft. per gallon on porous wallboard

6.01

1.96

—

—

*AVAILABLE IN 5-GAL. CANS

AT 10c PER GALLON LESS THAN 1-GAL. PRICES.

§SHORT FILLED TO ALLOW ADDITION OF COLORANT.

Glidden

***GLIDDENCOAT (White Enamel Undercoat) Y-555**

A perfect enamel undercoat for woodwork. Produces a firm opaque film to hold out succeeding coats of finishing enamel, making it possible to secure full luster and depth of gloss. Works easily, flows evenly without showing brush marks and requires only light sanding. Can be tinted with DRAMATONE Tinting Colors

APPLICATION—Brush, Spray

DRYING TIME—Overnight for sanding and recoating

THINNER—Mineral Spirits or Turpentine

COVERAGE—500 Sq. Ft. per gallon

39-W-740 Craftsman Enamel Undercoat

***SPEED-WALL ALKYD INTERIOR BASECOAT Y-4516**

A ready-to-use, low odor, alkyd-type primer-sealer for new and old interior wall surfaces of plaster, masonry or wallboard. Also for previously painted walls in poor condition and patched areas. Its remarkable ease of brushing and exceptional filling, sealing, hiding and alkali-resisting properties are gained through the use of special resins, pigments and oils

APPLICATION—Brush, Roller, Spray

DRYING TIME—Overnight for recoating

THINNER—Mineral Spirits or Turpentine

COVERAGE—Up to 450 Sq. Ft. per gallon

ENAMELS—SEMI-GLOSS

***SPRED LUSTRE SEMI-GLOSS ENAMEL
Y-4600 LINE**

(Interior-Exterior Washable Alkyd Enamel)

Ready to use. Covers most surfaces in One Coat. Requires no other primer on new plaster or new wood. Ideal for kitchens, bathrooms, hallways, walls, furniture, plaster, woodwork and metal. Washes like tile. Colors match SPRED SATIN. May be tinted with DRAMATONE Tinting Colors.

4600 Super White	7.29	2.24	1.28	—
4600 Ready-Mixed Colors	7.21	2.20	—	—
§4618 Tinting White (Pastel Tint Base) (124 oz.) (31 oz.)	7.12	2.16	—	—
§4680 Deep Tint Base (120 oz.) (30 oz.)	6.57	2.03	—	—
§4687 Intermediate Tint Base (122 oz.) (30.5 oz.) For Tinting Special Colors	6.78	2.07	—	—

*AVAILABLE IN 5-GAL. CANS
AT 10¢ PER GALLON LESS THAN 1-GAL. PRICES.
§SHORT FILLED TO ALLOW ADDITION OF COLORANT.

Glidden

SPRED LUSTRE DEEP COLORS

4634 Charcoal Black	7.21	2.20	—	—
4682 Beaver Brown	7.21	2.20	—	—
4684 Cherry Red	9.42	2.75	—	—

APPLICATION—Brush, Roller, Spray

DRYING TIME—Dust free 3 to 4 hours; recoat overnight

THINNER—Mineral Spirits or Turpentine

COVERAGE—Approx. 550 Sq. Ft. per gallon

***CRAFTSMAN SEMI-GLOSS ENAMEL WHITE
12-W-710**

ENAMELS-GLOSS

**JAPALAC ENAMEL Y-1200 LINE
(QUICK-DRYING, ALKYD GLOSS)**

An extra-durable, alkyd enamel in brilliant colors that cover in ONE COAT. Bright hues and muted tones give new life and sparkle to old surfaces—walls, ceilings, woodwork and furniture. JAPALAC Quick-Drying Alkyd Enamel is formulated for the finest enameling inside and outdoors. It looks, wears and washes like baked enamel. Colors may be tinted with DRAMATONE Tinting Colors.

	Gals.	Qts.	Pts.	½ Pts.	¼ Pts.
Ultra White, Brilliant Black, Flat Black and Colors	9.16	2.69	1.53	1.03	.66
§1218 Pastel Tint Base (124 oz.) (31 oz.)	8.98	2.65	—	—	—
§1280 Deep Tint Base (120 oz.) (30 oz.)	8.62	2.56	—	—	—
§1287 Intermediate Tint Base (122 oz.) (30.5 oz.)	8.80	2.60	—	—	—
For Tinting Special Colors					

APPLICATION—Brush, Roller, Spray

DRYING TIME—4 to 6 hours; 24 hours for recoating

THINNER—Mineral Spirits or Turpentine

COVERAGE—Approx. 500 Sq. Ft. per gallon

***CRAFTSMAN GLOSS ENAMEL WHITE 40-W-735**

A quality gloss enamel recommended for interior use on woodwork, furniture, kitchen and bathroom walls and cabinets

*AVAILABLE IN 5-GAL. CANS
AT 10c PER GALLON LESS THAN 1-GAL. PRICES.
§SHORT FILLED TO ALLOW ADDITION OF COLORANT.

Glidden

**DRAMATONE MULTI-PURPOSE
TINTING COLORS Y-1750 LINE**

(FOR TINTING LATEX, ALKYD AND OTHER PAINTS)

Tinting colors for use with SPRED SATIN Latex Paint, Alkyd Semi-Gloss Enamel, Alkyd Flat Enamel and Other Paints. See Dramatone displays for wide range of colors.

1750 (N-T) Neutral Toner	.64	—	—	—
1751 (F-R) Fast Red	.64	—	—	—
1752 (Y-OX) Yellow Oxide	.64	—	—	—
1753 (L-Y) Lemon Yellow	.64	—	—	—
1754 (YE-G) Yellow Green	.64	—	—	—
1755 (T-GR) Thalo Green	.64	—	—	—
1756 (T-BL) Thalo Blue	.64	—	—	—
1757 (VIO) Violet	.64	—	—	—
1758 (R-O) Rich Orange	.64	—	—	—
1782 (BLK) Black	.64	—	—	—
1786 (OX-R) Oxide Red	.64	—	—	—

Gals.	Qts.	Pts.	½ Pts.
1.oz. Per tube	Qts.		

WOOD FINISHING MATERIALS

WOOD STAINS, FILLERS, VARNISH STAINS

***Glid-Tone Redwood Stain Y-31**

A penetrating flat Redwood Stain and Sealer designed especially to protect and beautify natural exterior wood such as siding, shingles, shakes, panels, doors, fences, picnic tables and yard furniture. If gloss finish is desired use Clear Redwood Finish Y-30.

APPLICATION—Brush, Spray

DRYING TIME—Overnight

THINNER—Mineral Spirits, Turpentine, VM & P Naphtha

COVERAGE—First Coat on rough, new wood: 200-300 Sq. Ft. per gallon. Finished Wood: 300-400 Sq. Ft. per gallon, first coat. 2nd Coat: Up to 600 Sq. Ft. per gallon. 3rd Coat: Up to 800 Sq. Ft. per gallon.

Gals.	Qts.	Pts.	½ Pts.
5.11	1.70	—	—

GLID-TONE WOOD STAIN Y-242 LINE

An all-purpose, pigmented wiping stain for all types of wood, plywood and veneer, exterior and interior surfaces. Especially suitable for knotty pine wood paneling in recreation rooms. Excellent for use on new or old furniture, woodwork, cabinets, wall paneling and floors. GLID-TONE Stain heightens the beauty of the wood grain. Holds color evenly. May be coated with varnish, shellac or lacquer. May be tinted with DRAMATONE Tinting Colors to produce additional beautiful colors.

Stains, All Colors

APPLICATION—Wiping Cloth, Brush

DRYING TIME—12 hours

THINNER—Mineral Spirits....

5.74	1.79	1.13	.76
------	------	------	-----

*AVAILABLE IN 5-GAL. CANS
AT 10c PER GALLON LESS THAN 1-GAL. PRICES.

Glidden

GLID-TONE RE-GRAIN GROUND COAT Y-260

An enamel undercoater that produces a firm, opaque film, renews worn out finishes as described in "Step 1" in the Glid-Tone Re-Grain Process folder. For more detailed information see Glid-Tone Re-Grain Process Folder

GLID-TONE VARNISH STAIN Y-1201-02-03

Stains and varnishes in one operation. Dries quickly, to a high lustre. For use on furniture, woodwork and floors. Unusually waterproof

APPLICATION—Brush, Spray

DRYING TIME—4 to 6 hours; 24 hours for recoating

THINNER—Mineral Spirits or Turpentine

COVERAGE—600 Sq. Ft. per gallon

GLID-TONE WOOD FILLER Y-700

For use on all open-grained wood such as oak, chestnut, walnut and mahogany. Has pure silex base and will not shrink or break away from the pores of the wood when dry. Furnished in paste form. Must be reduced with naphtha or turpentine...

APPLICATION—Brush, Cloth

THINNER—Turpentine, Naphtha

XPRT SPRAY OIL STAINS Y-4801 LINE

Permanent pigment stains for staining new wood. They give traditional-modern tones for interior and exterior wood surfaces

WOOD FINISHING KITS AND AVAILABLE COMPONENTS

549 ANTIQUE KIT

This beautiful antique finish may be applied directly over old finishes or on new, unfinished wood

Components of Kit available separately:

507 Antique Base Coat

508 Patina Glaze

651 MARBLEIZING KIT

This is a beautiful finish which can be used in many areas of the home. Colors are available in the tones and hues of authentic marble

Components of Kit available separately:

657 M-1 Base

652 VENETIAN GOLD KIT

A lavish and elegant finish which may be applied to almost any sound surface. It is a dramatic accent for feature walls, table tops, doors, furniture and decorative panels

Components of Kit available separately:

653 V-1 Base

654 V-2 Gold

Gals.	Qts.	Pts.	½ Pts.
—	2.24	1.22	.84
6.91	2.23	1.26	.85
5.83	1.97	—	.76
(4 oz.) .77	—	—	—
(per kit) 3.56	—	—	—
—	—	1.67	—
—	—	—	1.12
(per kit) 4.76	—	—	—
—	—	—	.85
(per kit) 6.29	—	—	—
—	—	—	.71
—	—	—	1.12

Glidden

**CLEAR VARNISHES AND
FLOOR SEALERS**

GLID-TONE GLOSS VARNISH Y-1

A deluxe, general-purpose interior varnish. Epoxy resins give it extreme abrasion resistance, durability and lasting beauty. Excellent on all interior wood surfaces, bar and tabletops, woodwork, furniture and floors. Especially suitable over newly stained woodwork where Glid-Tone Stains have been applied. May be rubbed.....

APPLICATION—Brush

DRYING TIME—6 to 8 hours

THINNER—Mineral Spirits or Turpentine

COVERAGE—650 Sq. Ft. per gallon

Gals.

Qts.

Pts.

½ Pts.

8.26

2.51

1.40

.89

GLID-TONE SATIN SHEEN VARNISH Y-47

A new satin sheen varnish that dries free from all cloudiness and preserves the natural beauty of the wood. Excellent for use over GLID-TONE stains and for all interior work where a dull finish or rubbed effect is desired. Sufficiently pale for use over light modern stains. DO NOT USE ON FLOORS.....

APPLICATION—Brush

DRYING TIME—2 hours

THINNER—Mineral Spirits or Turpentine

COVERAGE—650 Sq. Ft. per gallon

7.54

2.33

1.31

.85

GLID-TONE SPAR VARNISH Y-48

Extra durable spar varnish for exterior surfaces exposed to weather. Recommended as the finest varnish available for exterior use—spars, hulls, decks, house sidings, paneling, porch ceilings, outdoor furniture, etc. Makes perfect finish over Glid-Tone Stain on exterior surfaces.....

APPLICATION—Brush

DRYING TIME—8 hours; 48 hours for recoating

THINNER—Mineral Spirits or Turpentine

COVERAGE—650 Sq. Ft. per gallon

8.80

2.60

1.49

1.07

***ROCKSPAR VARNISH Y-50**

Heavy bodied varnish for all interior surfaces. One coat equivalent to two coats of ordinary varnish. No shrinkage on drying. Dries with deep high gloss.....

APPLICATION—Brush

DRYING TIME—Overnight; 24 hours for recoating

THINNER—Mineral Spirits or Turpentine

COVERAGE—Up to 700 Sq. Ft. per gallon

7.36

2.33

1.35

.94

*AVAILABLE IN 5-GAL. CANS
AT 10c PER GALLON LESS THAN 1-GAL. PRICES.

Glidden

**CLEAR WOOD FINISHES—
POLYURETHANE**

***GLID-TONE POLYURETHANE REDWOOD FINISH
CLEAR Y-30**

A brilliant gloss finish for redwood, red cedar, pine and other exterior wood surfaces. Mildew and fume resistant. Provides a tough, erosion resistant film that maintains flexibility and resists checking, cracking, hardening

APPLICATION—Brush, Spray

DRYING TIME—Overnight

THINNER—Mineral Spirits, Turpentine, VM & P Naphtha

COVERAGE—First Coat on rough, new wood: 200-300 Sq. Ft. per gallon. Finished Wood: 300-400 Sq. Ft. per gallon. Second Coat: 500-600 Sq. Ft. per gallon. Third Coat: 600-800 Sq. Ft. per gallon.

Gals.

Qts.

Pts.

½ Pts.

7.63

2.33

—

—

**XPRT POLYURETHANE LIQUID PLASTIC
SATIN SHEEN Y-37**

Clear plastic satin-sheen finish for interior-exterior use. Outwears conventional interior finishes two to one. Provides 25% more durability for exteriors. For use on floors, furniture, paneling or exterior redwood, doors, shutters, etc. Not recommended over shellac, lacquer sanding sealers, lacquer or for large areas of exterior siding

10.24

3.05

1.67

—

**XPRT POLYURETHANE LIQUID PLASTIC
CLEAR GLOSS Y-51**

Clear, high gloss plastic finish that will outwear conventional lacquers and varnishes two to one for interior use. Gives up to 25% greater durability for exteriors. May be used on floors, furniture, paneling or exterior redwood, cedar doors, etc. Not recommended over shellac, lacquer sanding sealers, lacquer or for large areas of exterior siding

8.53

2.60

1.49

—

**XPRT SATIN SHEEN POLYURETHANE
CLEAR SPRAY Y-4035**

A clear, low-gloss polyurethane protective coating for finishing wood surface.....

(13 oz.)

1.61

—

—

—

**METAL PROTECTIVE PRIMERS
AND ENAMELS**

JAPALAC SCREEN AND IRON ENAMEL Y-1222

Gloss black, solid-covering enamel for exterior screens, wood and metal sash, wrought iron, decorative lamps, etc. Also ideal for interior ironwork, pipes, grills, furnaces, stoves, heaters, andirons, etc. Will not clog screen mesh. Resists weather and protects metal from rusting

APPLICATION—Brush, Spray or Special Applicator

DRYING TIME—6 to 8 hours

THINNER—Mineral Spirits or Turpentine

COVERAGE—600 Sq. Ft. per gallon

4.84

1.66

1.04

.67

***METALLITE ALL-PURPOSE ALUMINUM Y-592**

An extremely smooth, chrome-like aluminum finish for use on radiators, furnace jackets, airducts, hot water tanks and heaters, pipes and other interior surfaces. Will not tarnish under ordinary conditions. It maintains its brilliance. Makes an excellent sealer over asphalt. Retards corrosion caused by fumes and moisture. Withstands heat up to 500°F. Hides with one coat. Easily cleaned. Reflects light....

APPLICATION—Brush, Roller, Spray

DRYING TIME—2 to 4 hours; 24 hours for recoating

THINNER—Mineral Spirits or Turpentine

COVERAGE—650 Sq. Ft. per gallon

6.64

2.06

1.22

.80

*AVAILABLE IN 5-GAL. CANS
AT 10c PER GALLON LESS THAN 1-GAL. PRICES.

Glidden

RUSTMASTER GLOSS ENAMEL Y-470 LINE

A high quality versatile enamel of excellent quality. It has exceptional ease of application and may be applied by brushing or spraying as a finish coat over metal with Y-470 or Y-471 Rustmaster Primer. Rustmaster Gloss Enamel guards against rusting of machinery and equipment in the factory and on the farm as well as metal surfaces around the home and schools such as metal window frames and casings, iron fences, railings, bicycles, lawn mowers, playground equipment, etc.

Royal Blue, Greenfield, Slate, Gloss Black, Flat Black, Aluminum....

Suntone, Flare Red

White

APPLICATION—Brush, Spray

DRYING TIME—Overnight

THINNER—Turpentine or Mineral Spirits for Brushing; VM & P Naphtha for Spraying

COVERAGE—Up to 500 Sq. Ft. per gallon

Gals.

Qts.

Pts.

½ Pts.

8.08

2.51

1.44

.89

8.08

2.51

1.44

.89

8.08

2.51

1.44

.89

RUSTMASTER METAL PRIMER Y-470

A new, unexcelled, fast drying corrosion resistant exterior and interior metal primer containing revolutionary Phenolic Resin Penetrating (U.S. Patent No. 2978424) that cuts through rust and seals metal pores, locking out air and corrosive moisture. A finish coat of Rustmaster Enamel will provide an exceptionally durable coating

APPLICATION—Brush, Spray

DRYING TIME—Overnight

THINNER—Turpentine or Mineral Spirits for brushing; VM & P Naphtha for spraying

COVERAGE—Up to 500 Sq. Ft. per gallon

8.08

2.51

1.44

.89

RUSTMASTER GALVANIZED PRIMER Y-471

Provides longer-lasting protection for galvanized metal and aluminum. Use on new galvanized steel without chemical treatment. This prime coat may be used as a finish coat or recoated with Rustmaster Enamel, Endurance House Paint or Japalac.

APPLICATION—Brush, Roller, Spray

DRYING TIME—48 hours

THINNER—Turpentine, Mineral Spirits

COVERAGE—Approx. 350 Sq. Ft. per gallon

8.08

2.51

1.44

.89

PAINT AND VARNISH REMOVERS

AD-EL-ITE PAINT AND VARNISH REMOVER Y-70

A top-quality remover. Contains no alkalis, acids, oils or water. Does not raise the grain or discolor the wood. Evaporates very slowly. Very effective in removing old paint, enamel, lacquer and baked japan

4.84

1.61

1.04

.67

GLID-STRIP (Non-Flammable) Y-73 (Wash-Away Paint and Varnish Remover)

A non-flammable, water-flush paint and varnish remover that stays wet longer and permits working on larger areas. Has less tendency to run and sag on upright surfaces due to its heavy body. Easy to use. Just brush it on, wait a few minutes, then wash it off with water. GLID-STRIP also acts as a cleaner for old, hardened nylon and pure bristle paint and varnish brushes. Will soften latex paints for easy removal

7.00

2.33

1.22

.80

*AVAILABLE IN 5-GAL. CANS
AT 10¢ PER GALLON LESS THAN 1-GAL. PRICES.

Glidden

SPRAY ENAMELS AND PRIMER

**JAPALAC SPRAY ENAMEL Y-4000—LINE
In Ready-to-Spray Cans**

All-purpose, interior-exterior enamel in pressurized aerosol cans ready for immediate spraying. Extra-durable, quick-drying enamel of brilliant beauty. Gives professional appearance to porch and lawn furniture, bicycles, toys, tables, chairs, etc. Ideal for wickerwork. Colors match regular JAPALAC Alkyd Enamel colors. In addition, JAPALAC SPRAY ENAMEL is available in ready-to-spray interior-exterior Aluminum, rich Gold and a clear finish.

White, All Colors and Clear

APPLICATION—Spray

DRYING TIME—10 minutes

Gals.

Qts.

Pts.

½ Pts.

(13 oz.)

1.43

(4 oz.)

.77

—

—

RUSTMASTER PRIMER Y-4030 (Spray Can)

Same quality as Rustmaster Metal Primer Y-470, packed in handy spray can for easy, instant use. Ideal for hard-to-reach areas

APPLICATION—Spray

DRYING TIME—Overnight for recoating

(13 oz.)

1.70

—

—

—

MISCELLANEOUS

**SPRED SURFACENE Y-66
(Liquid Surface Conditioner and Brush Cleaner)**

A clear liquid that can be applied to old enameled, painted or varnished surfaces to clean the surface, dull the gloss and insure good adhesion for a new finish coat. Eliminates the work and dust of sanding and prepares surfaces for refinishing in one easy operation. SURFACENE may also be used as a brush cleaner

APPLICATION—Cloth or Brush

4.93

1.61

.99

—

**SPRED PATCH Y-3475
(100% Latex Spackling Compound)**

A ready-to-use spackling compound. Will not bleed through paint or flash. Does not shrink. Dries to a "puff" which may be easily sanded. Does not clog sandpaper. Excellent adhesion

APPLICATION—Putty Knife

DRYING TIME—30 minutes

THINNER—Water

6.91

2.15

—

.80

**SILICONE SLICK SPRAY Y-58
(Miracle Lubricant with 1001 Uses)**

A new, spray lubricant that protects and preserves while it lubricates. An excellent ice and water repellent. Push button spray lubricates hard-to-reach parts and areas. Makes windows, drawers, doors and other sticking items slide freely. Stops squeaks

(16 oz.)

2.66

(6 oz.)

1.43

—

—

SPRED BRUSH AND ROLLER CLEANER Y-60

A new easy way to clean Varnish, Enamel, Epoxy, Lacquer, Urethane, Synthetics, Shellac, Polyester and Silicone from brushes and rollers

4.48

1.52

.99

—

BLOCKAID Y-1971

An all-purpose, water-resistant material for masonry filling, sealing, patching and coating — stops water seepage. Can be tinted with DRAMATONE Tinting Colors

(50# bag)

10.34

(12½# bag)

3.14

—

—

Glidden

***DRIWAL (Silicone) Y-534**

A transparent, water-repellent finish for exterior, above-ground brick, stone and masonry. Does the job in ONE COAT. Keeps rain water from penetrating the pores. Resists efflorescence and staining. Masonry surfaces show no visible change in color or texture when treated with this material. Recommended for use on brick and mortar, concrete, cement-base paints, asbestos-cement combinations, sandstone, stucco and stones other than limestone. Not to be used on cinder block or other lightweight aggregate concrete blocks with extremely porous surfaces. This invisible water-repellent coating contains silicone to combat masonry deterioration. Not recommended for limestone surfaces

APPLICATION—Brush, Spray

DRYING TIME—2 hours

THINNER—None required

COVERAGE—125 to 275 Sq. Ft. per gallon depending on porosity of surface

Gals.

Qts.

Pts.

½ Pts.

4.66

—

—

—

SPRED CRETE Y-1955

A one part, pre-mixed latex-cement compound which offers outstanding advantages in patching and resurfacing masonry. Add water only. Repair concrete driveways, cement floors, masonry steps, loose bricks, loose mortar joints, stucco, set patio stones and blocks

(25# bag)

(12# bag)

5.66

4.49

—

—

PORCH AND DECK ENAMELS

**POLYURETHANE PLASTIC FLORENAMEL
Y-890 LINE**

A high quality enamel for interior and exterior floors of wood, metal and concrete.

White and Ready-Mixed Colors

§818 Pastel Tint Base (124 oz.) (31 oz.)

§880 Deep Tint Base (120 oz.) (30 oz.)

§887 Intermediate Tint Base (122 oz.) (30.5 oz.)
For Tinting Special Colors

7.54

2.33

—

—

7.18

2.24

—

—

6.82

2.15

—

—

7.05

2.20

—

—

APPLICATION—Brush, Roller

DRYING TIME—4-6 hours to touch, 24 hours for recoat

THINNER—Mineral Spirits

COVERAGE—Up to 600 Sq. Ft. per gallon

CRAFTSMAN FLORENAMEL Y-841 LINE

A high-gloss alkyd type enamel specially formulated for interior and exterior floors, steps and basement floors

APPLICATION—Brush, Roller

DRYING TIME—4-6 hours to touch; 24 hours for recoat

THINNER—Mineral Spirits or Turpentine

COVERAGE—600 Sq. Ft. per gallon

—

—

—

—

*AVAILABLE IN 5-GAL. CANS
AT 10c PER GALLON LESS THAN 1-GAL. PRICES.
§SHORT FILLED TO ALLOW ADDITION OF COLORANT.

Glidden

**EXTERIOR WOOD, MASONRY,
SHINGLE AND SHAKE FINISHES**

***SPRED HOUSE PAINT Y-3600 LINE**

(100% LATEX EXTERIOR PAINT)

A new blister-resistant house paint for exterior wood and masonry. May be applied without primer over sound previously painted surfaces which are in good condition. Has a remarkable fast drying time of thirty minutes, which practically eliminates damage from bugs, rain and dust. May be applied over damp surfaces. Has long lasting velvet-like sheen. Once the Spred House Paint system is used on a house, future paintings will require only one coat.

White and Colors

\$3625 White Tint Base (124 oz.) (31 oz.)
For Tinting Special Colors

APPLICATION—Brush, Roller, Spray Gun

DRYING TIME—4 hours for recoating

THINNER—Water

COVERAGE—Approx. 450 Sq. Ft. per gallon on smooth surface

Gals.

Qts.

Pts.

½ Pts.

7.63

2.38

—

—

7.54

2.33

—

—

***SPRED PRIME COAT Y-3651**

(Thin with Mineral Spirits)

Spred Primecoat provides a firm foundation on new or unpainted exterior surfaces. The ideal undercoat that creates the finest possible two coat paint job when porous surfaces have been previously painted. This Primecoat has been especially formulated for Spred House Paint

APPLICATION—Brush, Roller, Spray Gun

DRYING TIME—48 hours

THINNER—Turpentine or Mineral Spirits

COVERAGE—450-550 Sq. Ft. per gallon

7.63

2.38

—

—

***SPRED GLIDE-ON Y-3500 LINE**

(Vinyl-Latex Exterior Masonry Paint)

An exterior vinyl-latex masonry paint, unaffected by the alkalinity found in all masonry surfaces. Designed for use on stucco, concrete, brick, concrete block, cinder block, asbestos shingle and panel siding, unglazed tile and primed metal. Keeps out moisture yet the surface "breathes" to let vapor escape from inside. A tough vinyl film that resists driving rains, hottest sunshine, mildew, snow and ice, sea air and salt water spray, strongest smog, dust and chemical fumes. Resists cracking, peeling, fading, blistering, acid and alkali action.

White and Colors

\$3518 Pastel Tint Base (124 oz.) (31 oz.)

\$3580 Deep Tint Base (120 oz.) (30 oz.)

\$3587 Intermediate Tint Base (122 oz.) (30.5 oz.)

For Tinting Special Colors

APPLICATION—Brush, Roller, Spray

DRYING TIME—Overnight for recoating

THINNER—Water

COVERAGE—Up to 400 Sq. Ft. per gallon

6.64

2.06

—

—

6.46

2.02

—

—

5.74

1.93

—

—

6.06

1.97

—

—

*AVAILABLE IN 5-GAL. CANS

AT 10¢ PER GALLON LESS THAN 1-GAL. PRICES.

§SHORT FILLED TO ALLOW ADDITION OF COLORANT.

Glidden

GLID-TONE® WOOD STAINS—EXTERIOR Y-290

A completely new type stain with maximum beauty and durability for wood surfaces that are subjected to outdoor exposure

APPLICATION—Brush

DRYING TIME—24 hours under normal conditions

THINNER—Mineral Spirits

COVERAGE—200-300 Sq. Ft. per gallon

*ENDURANCE VELVET (Flat Exterior Finish) Y-2700 LINE

FOR WOOD SHINGLES, SHAKES, WOOD SIDING AND TRIM. May be used also on metal surfaces. It brushes easily and will produce a beautiful flat finish in one coat over most previously painted surfaces if the color contrast is not great. Dries dust free in one hour. It provides a "breather type" film which aids the elimination of internal moisture.

White and Colors

§2718 Pastel Tint Base (124 oz.) (31 oz.)

§2787 Intermediate Tint Base (122 oz.) (30.5 oz.)

§2780 Deep Tint Base (120 oz.) (30 oz.)

For Tinting Special Colors

APPLICATION—Brush, Spray

DRYING TIME—Dust-free 1 hour; 48 hours for recoating

THINNER—Mineral Spirits or Turpentine

COVERAGE—Up to 550 Sq. Ft. per gallon

*ENDURANCE BARN PAINT RED Y-500

A new, highest quality paint with excellent hiding power. It dries to a tough glossy film that withstands the rigors of the roughest weather. Provides long-lasting protection for barns, sheds, granaries, silos, water tank exteriors, storehouses, fences, etc. Use it on exterior wood and metal

APPLICATION—Brush, Spray

DRYING TIME—Overnight; 36 hours for recoating

THINNER—Mineral Spirits or Turpentine

COVERAGE—500 Sq. Ft. per gallon

*EVERON HOUSE PAINT Y-2200 WHITE

An excellent paint that stays clean and bright because of its special formula which provides controlled chalking. A superior finish for all wood surfaces exposed to weather and changing climatic conditions. Resists fumes in industrial areas! EVERON HOUSE PAINT brushes easily, penetrates deeply when used as a primer, adheres tenaciously as a finish coat, dries with an elastic, high gloss finish that remains firm and durable. EVERON is truly the economical HOUSE PAINT

APPLICATION—Brush, Roller, Spray

DRYING TIME—16 hours; recoat in 48 hours

THINNER—Mineral Spirits or Turpentine

COVERAGE—550 Sq. Ft. per gallon

*AVAILABLE IN 5-GAL. CANS

AT 10c PER GALLON LESS THAN 1-GAL. PRICES.

§SHORT FILLED TO ALLOW ADDITION OF COLORANT.

	Gals.	Qts.	Pts.	½ Pts.
GLID-TONE® WOOD STAINS—EXTERIOR Y-290	5.56	1.76	—	—
*ENDURANCE VELVET (Flat Exterior Finish) Y-2700 LINE				
White and Colors	6.73	2.11	—	—
§2718 Pastel Tint Base (124 oz.) (31 oz.)	6.64	2.06	—	—
§2787 Intermediate Tint Base (122 oz.) (30.5 oz.)	6.49	1.97	—	—
§2780 Deep Tint Base (120 oz.) (30 oz.)	6.41	1.88	—	—
*ENDURANCE BARN PAINT RED Y-500	5.74	1.79	—	—
*EVERON HOUSE PAINT Y-2200 WHITE	—	—	—	—



	Gals.	Qts.	Pts.	½ Pts.
*CRAFTSMAN HOUSE PAINT PRIMER 184-W-715	—	—	—	—
*CRAFTSMAN NON-CHALK WHITE 2-W-715	—	—	—	—
*STOCK FARM WHITE PAINT Y-596				
An excellent low cost exterior paint for use on wood surfaces such as fences, barns, outbuildings, sheds, etc. This material, produced for use in stock farms, is formulated without lead pigments, and contains wood preservatives. The creosote-like odor tends to repel livestock	5.92	—	—	—
APPLICATION—Brush, Spray				
DRYING TIME—Overnight, 24 hours for recoating				
THINNER—Mineral Spirits or Turpentine				
COVERAGE—Up to 450 Sq. Ft. per gallon depending upon surface condition				
*SURFACE BOND Y-55 (SEALS POWDERY MASONRY SURFACES)				
A high quality, clear finish bonding coat. Designed to penetrate deeply into chalky surfaces left by previous coats of cement bondings or powder type paints on masonry surfaces. Dries hard to help prevent further chalking. Anchors old surface to make a perfect bond for SPRED GLIDE-ON, as well as other exterior and interior masonry paints	6.46	2.06	—	—
APPLICATION—Brush, Spray				
DRYING TIME—1 to 4 days depending upon drying conditions				
THINNER—Turpentine or Mineral Spirits				
COVERAGE—300-400 Sq. Ft. per gallon				
NOTE: Although the formulations and recommendations contained in this price list have been established through careful evaluation, users of Glidden paints are urged to obtain specific information concerning their painting requirements. Seller's liability shall in no event exceed value of this material, which is warranted only to conform to formula or sample. Seller hereby expressly excludes all other express or implied warranties whatsoever.				

*AVAILABLE IN 5-GAL. CANS
AT 10¢ PER GALLON LESS THAN 1-GAL. PRICES.



Glidden

[illegible]

Glidden

[illegible]

CODE NUMBER AND DESCRIPTION

Y-1 Glid-Tone Glass Varnish	Y-983 Poly. Florenamel Harbor Gray	Y-3050 Craftsman Latex Pt. Alaska White	Y-4008 Japalac Spray Aluminum
Y-30 Glid-Tone Redwood Cl. Finish	Y-894 Poly. Florenamel Chat. Gray	Y-4009 Japalac Spray Gold	Y-4010 Japalac Spray Clear Plastic
Y-31 Glid-Tone Redwood Stain	Y-895 Poly. Florenamel Spice Wood	Y-4011 Japalac Spray Copper Tone	Y-4015 Japalac Spray Enamel Lemon Yellow
Y-37 Xpert Satin Sheen	Y-1201 Glid-Tone Var. Stain, Dk. Oak	Y-4016 Japalac Spray Enamel Greenbrier	Y-4017 Japalac Spray Flat White
Y-47 Glid-Tone Satin Sheen Varnish	Y-1202 Glid-Tone Var. Stain, Walnut	Y-4019 Japalac Spray Tan Bark	Y-4030 Rustmaster Primer
Y-48 Glid-Tone Spar Varnish	Y-1203 Glid-Tone Varn. Stain, Mah.	Y-4516 Interior Base Coat	Y-4550 Speedenamel White
Y-50 Rockspar Varnish	Y-1207 Japalac Brilliant Black	Y-4551 Speedenamel Black	Y-4552 Speedenamel Orange
Y-51 Xpert Clear Gloss	Y-1208 Japalac Flat Black	Y-4553 Speedenamel Deep Green	Y-4554 Speedenamel Med. Green
Y-55 Surface Bond	Y-1212 Japalac Bud Green	Y-4556 Speedenamel Fire Red	Y-4559 Speedenamel Lt. Yellow
Y-58 Silicone Slick Spray	Y-1217 Japalac Ultra White	Y-4560 Speedenamel Med. Yellow	Y-4561 Speedenamel Light Gray
Y-60 Spread Brush & Roller Cleaner	Y-1218 Japalac Pastel Tint Base	Y-4562 Speedenamel Mach. Gray	Y-4564 Speedenamel Imp. Blue
Y-66 Spread Surface	Y-1219 Japalac Dawn Gray	Y-4565 Speedenamel Bright Red	Y-4566 Speedenamel Light Green
Y-70 Adelite Paint & Var. Remover	Y-1222 Japalac Screen Black	Y-4569 Speedenamel Hydro Blue	Y-4570 Speedenamel Red Oxide Metal Primer
Y-74 Glid-Strip Paint & Var. Remover	Y-1246 Japalac Rich Blue	Y-4571 Speedenamel Spring Gr.	Y-4572 Speedenamel Neutral Gray
Y-242 Glid-Tone Stain—Hon. Maple	Y-1250 Japalac Delphinium	Y-4573 Speedenamel EZC Green	Y-4575 Speedenamel Tint White
Y-243 Glid-Tone Stain—Fr. Prov.	Y-1255 Japalac Light Ivory	Y-4576 Speedenamel Deep Orange	Y-4580 Speedenamel Deep Tint Base
Y-244 Glid-Tone Stain—Mod. Red Mahogany	Y-1256 Japalac Vermilion	Y-4587 Speedenamel Int. Tint Base	Y-4600 Spread Lustre White
Y-245 Glid-Tone Stain—Walnut	Y-1260 Japalac Rose Pink	Y-4618 Spread Lustre Tinting White	Y-4641 Spread Lustre Crocus Yellow
Y-246 Glid-Tone Stain—Wheat	Y-1263 Japalac Botany Brown	Y-4643 Spread Lustre Cotton Candy	Y-4647 Spread Lustre Sahara
Y-247 Glid-Tone Stain—Blonde	Y-1267 Japalac Ribbon Blue	Y-4649 Spread Lustre Oyster White	Y-4651 Spread Lustre Congo Ivory
Y-248 Glid-Tone Stain—Brown Mah.	Y-1270 Japalac Lemon Yellow	Y-4652 Spread Lustre Silver Tint	Y-4653 Spread Lustre Celadon Green
Y-249 Glid-Tone Stain—Platinum	Y-1271 Japalac Greenbrier	Y-4655 Spread Lustre Springtime	Y-4657 Spread Lustre Woodland
Y-250 Glid-Tone Stain—Suntan	Y-1280 Japalac Deep Tint Base	Y-4660 Spread Lustre Zircon	Y-4663 Spread Lustre Smoky White
Y-252 Glid-Tone Stain—Maple	Y-1287 Japalac Int. Tint Base	Y-4665 Spread Lustre Pink Haze	Y-4667 Spread Lustre Pebble Beach
Y-254 Glid-Tone Stain—Cherry	Y-1750 (N-T) Neutral Toner	Y-4672 Spread Lustre Medallion Gold	Y-4677 Spread Lustre Biscayne Blue
Y-258 Glid-Tone Stain—Fruitwood	Y-1751 (F-R) Fast Red	Y-4678 Spread Lustre Aquaglow	Y-4679 Spread Lustre Sherwood Gr.
Y-259 Glid-Tone Stain—Butternut	Y-1752 (Y-OX) Yellow Oxide	Y-4680 Spread Lustre Dramatone Tinting Base	Y-4682 Spread Lustre Beaver Brown
Y-260 Glid-Tone Regrain Gr. Coat	Y-1753 (L-Y) Lemon Yellow	Y-4684 Spread Lustre Cherry Red	Y-4687 Spread Lustre Tinting Base
Y-262 Glid-Tone Stain Charcoal	Y-1754 (YE-G) Yellow Green	Y-4688 Spread Latex H.P. White	Y-4689 Spread Latex H.P. Taffy
Y-266 Glid-Tone Stain Sagebrush	Y-1755 (T-GR) Thalo Green	Y-4690 Spread Latex H.P. Dover Gray	Y-4691 Spread Latex H.P. Bayberry
Y-267 Glid-Tone Stain Pinewood Gr.	Y-1756 (T-BL) Thalo Blue	Y-4692 Spread Latex H.P. Bark	Y-4693 Spread Latex H.P. Evergreen
Y-290 Glid-Tone St. Ext. Extender	Y-1757 (VIO) Violet	Y-4694 Spread Latex H.P. Onyx	Y-4695 Spread Latex H.P. Polo Tan
Y-292 Glid-Tone Stain Ext. Charcoal	Y-1758 (R-O) Rich Orange	Y-4696 Spread Lat. H.P. CapeCod Red	Y-4697 Spread H.P. Tinting White
Y-293 Glid-Tone St. Ext. Fr. Prov.	Y-1782 (BLK) Black	Y-4698 Spread Prime Coat No. 1	Y-4000 Japalac Spray Enamel White
Y-294 Glid-Tone Stain Ext. Cherry	Y-1786 (OX-R) Oxide Red	Y-4001 Japalac Spray En. Flat Black	Y-4002 Japalac Spray En. Glass Bl.
Y-295 Glid-Tone Stain Ext. Walnut	Y-1800 Endurance House Paint White	Y-4003 Japalac Spray Enamel Delphinium	Y-4004 Japalac Spray Enamel Dawn Gray
Y-296 Glid-Tone St. Ext. Sagebrush	Y-1802 Endurance House Paint Black	Y-4005 Japalac Spray Enamel Bud Green	Y-4006 Japalac Spray Enamel Vermilion
Y-298 Glid-Tone St. Ext. Fruitwood	Y-1813 End. H.P. Tobacco Brown		
Y-299 Glid-Tone Stain Ext. Platinum	Y-1818 End. H.P. Pastel Tint Base		
Y-470 Rustmaster Primer	Y-1828 End. H.P. Crylite Green		
Y-471 Rustmaster Galv. Primer	Y-1851 End. Basecoat Mildew & Fume Res.		
Y-472 Rustmaster Aluminum	Y-1855 End. H.P. Castle Red		
Y-475 Rustmaster White	Y-1856 End. H.P. Ivory		
Y-476 Rustmaster Black	Y-1857 End. H.P. Cream		
Y-477 Rustmaster Flat Black	Y-1859 End. H.P. Light Gray		
Y-478 Rustmaster Suntone	Y-1860 End. H.P. Medium Gray		
Y-479 Rustmaster Royal Blue	Y-1861 End. H.P. Shutter Green		
Y-480 Rustmaster Greenfield	Y-1867 End. H.P. Imperial White		
Y-481 Rustmaster Flare Red	Y-1871 End. H.P. Dark Blue		
Y-482 Rustmaster Slate	Y-1872 End. H.P. Dark Walnut		
Y-500 Endurance House Paint Barn Red	Y-1877 End. H.P. Int. Tint Base		
Y-507 Glid-Tone Stain Exterior Antique Base Coat	Y-1886 End. H.P. Light Canary		
Y-508 Glid-Tone Stain Antique Patina Glaze	Y-1880 End. H.P. Deep Tint Base		
Y-549 Glid-Tone Stain Antique Kit	Y-1887 End. H.P. Pastel Green		
Y-555 Gliddencoat En. Und. White	Y-1892 End. H.P. Non-Chalk. White		
Y-651 Glid-Tone Stain Marbleizing Kit	Y-1971 Blockaid		
Y-652 Glid-Tone Stain Venetian Kit	Y-1955 Spread Crete		
Y-653 V-1 Base	Y-2200 Everon House Paint White		
Y-654 V-2 Gold	Y-2217 Craftsman H.P. Mild. Resis.		
Y-657 M-1 Base	Y-2218 Craftsman House Paint White		
Y-592 All-Purpose Metalite Alum. Pt.	Y-2240 Craftsman Non-Chalk. White		
Y-596 Stock Farm Paint White	Y-2718 Endurance Velvet Pastel Base		
Y-700 Glid-Tone Natural Wood Filler	Y-2750 End. Velvet H.P. White		
Y-800 Poly. Florenamel White	Y-2751 End. Vel. H.P. Mayflower Yel.		
Y-818 Poly. Florenamel Pastel Tint Base	Y-2752 End. Vel. H.P. Sterling Gray		
Y-841 Craftsman Flor. Deck Red	Y-2756 End. Vel. H.P. Cottage Ivory		
Y-842 Craftsman Flor. Deck Gray	Y-2758 End. Vel. H.P. Granada Red		
Y-843 Craftsman Flor. Tile Green	Y-2759 End. Vel. H.P. Shrub Green		
Y-844 Craftsman Flor. Dark Oka	Y-2761 End. Vel. H.P. Brown Antique		
Y-880 Poly. Flor. Deep Tint Base	Y-2764 End. Velvet Shadow Green		
Y-887 Poly. Florenamel Int. Tint Base	Y-2765 End. Vel. H.P. Oxford Gray		
Y-891 Poly. Florenamel Tile Red	Y-2766 End. Velvet H.P. Safari		
Y-892 Poly. Florenamel Tile Green	Y-2780 End. Velvet Deep Tint Base		
	Y-2787 End. Velvet Int. Tint Base		
	Y-3000 Spread Flat White		

THE GLIDDEN COMPANY

National Headquarters
900 Union Commerce Building
Cleveland, Ohio 44115

SALES OFFICES AND FACTORIES: New York • San Francisco • Los Angeles
Minneapolis • Dallas • Chicago • St. Louis • New Orleans • Cleveland
Atlanta • Portland • Reading • Canada: Toronto and Montreal

Branches in principal cities throughout the United States

CI 0027743