The Vinco Company, Inc.

305 East 45th Street — New York 17, N. Y.

Only a clean boiler can be an efficient boiler. A clean boiler means saving fuel, as well as safeguarding boiler metal. Both are now a patriotic duty.



Boiler Cleanser 5 and 6 lb Cans

A positively harmless insoluble powder cleaner for new, remodeled and old heating systems. A unique, scientifically processed compound on a special formula not to be confused with other powder boiler cleaners.

What Vinco Boiler Cleanser Does

VINCO removes oil, grease, scale, rust and dirt from the internal surfaces and from the boiler water *without the labor, expense, and uncertain results of blowing boilers over the top or of wasting returns.*

By this thorough cleaning Vinco prevents or cures foaming, priming, surging, and slow steaming.

How Vinco Boiler Cleanser Works

Each minute grain of VINCO powder adsorbs several times its own weight of oil, rust and dirt. These larger grains of adsorbed impurities then settle and are drained through the bottom according to directions on each can.

Vinco Guarantees


1. VINCO contains no potash, lye, soda of any kind, oil, acid, or other harmful ingredients.
2. Purchase price is refunded if results are not as claimed when VINCO has been used according to directions.



Rust Preventer 1 qt cans only

VINCO RUST PREVENTER

When used after VINCO Boiler Cleanser has removed oil, grease, rust, scale and dirt, it will add and keep the rust inhibiting factors at the optimal constant for a year or more. (Test kit below has complete instructions and chart.)



Vinco Test Kit No. 10 (Patent applied for)

VINCO TEST KIT No. 10

for Testing Heating Boiler Waters

The kit enables the layman to make simple, rapid tests to diagnose and prescribe correct treatment of boiler waters right on the job.

A new time saving method that permits valid conclusions heretofore requiring complicated and often lengthy laboratory analysis and technique.

Each kit has sufficient material for complete tests on 100 jobs.

Refills cost about 2 cents per test.

HELP WIN THE WAR BY SAVING FUEL AND BOILER METAL.

SPECIFICATIONS FOR COMPLETE VINCO TREATMENT OF NEW OR REMODELED STEAM, VAPOR, OR HOT WATER SYSTEMS

Do not use as a cleaning agent soda or any alkali, vinegar or any acid. Use Vinco.

1. AFTER THE SYSTEM IS TESTED AND TIGHT, USE THE PROPER QUANTITY OF VINCO LISTED.

After this first clean-out of any new or remodeled heating system, Vinco Boiler Cleaner need be used only if more piping, radiation, or another boiler is added to the original installation, or if the system is fouled by unwise cleaning or leak-sealing experiments.

2. After using Vinco Boiler Cleaner, Vinco Field Test Kit should be used to determine and apply the proper quantity of Vinco Rust Preventer. Vinco Rust Preventer should be applied annually or whenever the boiler water is drained for necessary repairs to the system.

SPECIFICATION FOR OLD HEATING SYSTEMS THAT DO NOT PERFORM PROPERLY

Diagnose and treat according to Vinco Field Test Kit. If a test kit is not available, consult table of quantities on this page and follow directions on Vinco cans.

SPECIFICATION FOR HOT WATER SYSTEMS

Use half quantities listed for treatment of steam systems to remove impurities. Then use test kit to determine proper quantity of Vinco Rust Preventer.

CONSULT THIS TABLE FOR NEW AND REMODELED HEATING SYSTEMS AND When a Vinco Field Test Kit No. 10 is not available if cleaning old heating systems.

QUANTITIES OF VINCO (IN POUNDS) REQUIRED FOR HEATING SYSTEMS

(Note that quantities are based on actual installed radiation, not on boiler capacity.)

Sq Ft of Radiation	For Steam or Vapor Systems, to prevent or cure priming or foaming. Also for Hot Water Heating Systems Maintained at approx. 200 F or above.	Annually, to remove rust scale, dirt and for Hot Water Systems below 200 F.
up to 350	3	1½
351 " 600	5	2½
601 " 1100	8	4
1101 " 1400	10	5
1401 " 1800	13	6½
1801 " 2100	15	7½
2101 " 2700	18	9
2701 " 3100	20	10
3101 " 3700	23	11½
3701 " 4200	26	13
4201 " 4600	28	14
4601 " 5000	30	15
5001 " 5300	31	15½
5301 " 5600	32	16
5601 " 5900	33	16½
5901 " 6200	34	17
6201 " 6500	35	17½
6501 " 6800	36	18
6801 " 7100	37	18½
7101 " 7400	38	19
7401 " 7700	39	19½
7701 " 8000	40	20
8001 " 8300	41	20½
8301 " 8600	42	21
8601 " 8900	43	21½
8901 " 9200	44	22
9201 " 9500	45	22½
9501 " 9800	46	23
9801 " 10100*	47	23½

*Above 10100 sq ft use an additional pound Vinco for each additional 300 sq ft of actual installed radiation.



Soot-Off—1 lb cans 50 and 100 lb drums


VINCO SOOT-OFF

Safely and thoroughly removes the insulating blanket of soot on fire pot, flues and chimney. It also insures against external corrosion (caused by dampness and soot forming sulphuric acid during summer layoff.) No dangerous chemicals.

REMOVE SOOT WITH VINCO SOOT-OFF SEVERAL TIMES A YEAR

VINCO SUPERFINE LIQUID BOILER SEAL

A different liquid seal. Unique in that it does not induce priming and foaming. It has no unpleasant smell. Makes speedy and permanent repairs of boiler and heating system leaks. Fine to tighten up new jobs. Directions simple.



Liquid Boiler Seal 1 qt. cans only

Quantities

Steam and Vapor Systems—Use 1 quart VINCO Liquid Boiler Seal to each 6 sq ft *grate* area.

Hot Water Systems—Use 2 quarts VINCO Liquid Boiler Seal to each 6 sq ft *grate* area.