

TABLE 1. TEMPERATURE AND DRAFT IN 9 IN. BY 9 IN. MASONRY CHIMNEY^a

CHIMNEY HEIGHT, Ft		FUEL OIL EQUIVALENT* OF CHIMNEY GASES	FLUE GAS TEMP., F INLET, F	AVERAGE CHIMNEY GAS TEMP. F	OUTSIDE TEMP. F	OBSERVED DRAFT INCH WATER	COMPUTED STATIC DRAFT INCH WATER	CORRECTED DRAFT ^b		INDICATED FRACTIONAL LOSS INCH WATER
Nominal	Height Above Thimble							Fuel Oil Gal/Hr	CO ₂ Per Cent	
35	31.5	0.5	10	142	68	0.040	0.093	0.076	0.089	+0.013
35	31.5	1.5	8	158	71	0.043	0.095	0.083	0.098	+0.012
35	31.5	1.5	10	158	71	0.043	0.095	0.083	0.098	+0.012
35	31.5	0.5	8	273	80	0.092	0.117	0.135	0.162	+0.024
35	31.5	1.5	10	488	77	0.153	0.191	0.208	0.242	+0.028
35	31.5	1.5	8	601	78	0.169	0.214	0.216	0.261	+0.045
30	27.5	0.5	10	190	83	0.043	0.049	0.070	0.076	+0.008
30	27.5	1.5	8	195	84	0.055	0.064	0.097	0.106	+0.009
30	27.5	0.5	10	213	98	0.075	0.084	0.107	0.116	+0.009
30	27.5	1.5	8	289	62	0.146	0.168	0.174	0.199	+0.024
30	27.5	1.5	10	608	72	0.158	0.193	0.204	0.228	+0.025
25	23.5	0.5	10	171	92	0.034	0.037	0.072	0.076	+0.003
25	23.5	1.5	8	200	94	0.034	0.036	0.072	0.076	+0.002
25	23.5	0.5	10	243	78	0.096	0.073	0.097	0.105	+0.006
25	23.5	1.5	8	301	79	0.095	0.091	0.116	0.123	+0.005
25	23.5	0.5	10	604	79	0.124	0.137	0.174	0.187	+0.013
25	23.5	1.5	8	1000	80	0.146	0.159	0.177	0.190	+0.013
20	17.2	0.5	10	179	94	0.029	0.032	0.059	0.060	+0.003
20	17.2	1.5	8	200	94	0.031	0.032	0.059	0.060	+0.001
20	17.2	0.5	10	270	81	0.058	0.052	0.082	0.086	+0.004
20	17.2	1.5	8	297	55	0.075	0.081	0.087	0.093	+0.006
20	17.2	0.5	10	800	50	0.086	0.091	0.095	0.100	+0.005
20	17.2	1.5	8	425	55	0.104	0.108	0.116	0.118	+0.002
20	17.2	0.5	10	628	87	0.120	0.130	0.133	0.140	+0.006
20	17.2	1.5	8	915	44	0.129	0.134	0.135	0.141	+0.006
15	11.3	0.5	10	182	87	0.025	0.023	0.041	0.041	+0.000
15	11.3	1.5	8	200	84	0.025	0.024	0.042	0.041	+0.000
15	11.3	0.5	10	258	32	0.053	0.055	0.054	0.056	+0.001
15	11.3	1.5	8	400	43	0.056	0.057	0.060	0.061	+0.001
15	11.3	0.5	10	399	34	0.068	0.071	0.069	0.071	+0.003
15	11.3	1.5	8	800	42	0.072	0.076	0.076	0.076	+0.004
15	11.3	0.5	10	877	55	0.092	0.092	0.092	0.092	+0.002
15	11.3	1.5	8	984	55	0.092	0.092	0.100	0.098	-0.002

Actual inside dimensions of flue lining $7\frac{1}{4} \times 7\frac{1}{4}$ in.

^aActual inside dimensions of tube lining $7\frac{1}{2} \times 7\frac{1}{4}$ in.
^bCorrected for outside temperature 32 F. Barometer 29.92 in. Hg.

a Actual inside dimensions of flue lining $7\frac{1}{2} \times 7 \times 7\frac{1}{2}$ in.
b Corrected for outside temperature 32°F . Barometer 29.02 in. Hg.
c 15 gal per hour of fuel oil burned with 10 per cent CO_2 produces 13.4 cfm or 1.38 lb per minute of flue gases (corrected to 70 $^\circ\text{F}$, 1 atmosphere pressure); 1½ gal per hour of fuel oil burned with 8 per cent CO_2 produces 87.5 cfm or 6.08 lb per minute of flue gas (corrected to 70 $^\circ\text{F}$, 1 atmosphere pressure).

Chimneys and Draft Calculations

367

TABLE 2. TEMPERATURE AND DRAFT IN 9 IN. BY 13 IN. MASONRY CHIMNEY^a

CHIMNEY HEIGHT, Ft		FUEL OIL EQUIVALENT* OF CHIMNEY GASES		AVERAGE CHIMNEY GAS TEMP. F	OUTSIDE TEMP. F	OBSERVED DRAFT INCH WATER	COMPUTED STATIC DRAFT INCH WATER	CORRECTED DRAFT ^b		INDICATED FRICTION INCH WATER
Nominal	Height Above Thimble	Fuel Oil Gal/Hr	CO ₂ Per Cent					Observed Inch Water	Computed Static Inch Water	
35	31.5	0.5	10	125	78	0.035	0.034	0.078	0.077	-0.001
35	31.5	1.5	8	200	82	0.047	0.052	0.093	0.093	+0.005
35	31.5	1.5	8	350	83	0.060	0.065	0.106	0.106	+0.004
35	31.5	0.5	10	272	77	0.104	0.117	0.163	0.163	+0.013
35	31.5	0.5	10	438	78	0.178	0.178	0.205	0.221	+0.013
35	31.5	1.5	8	642	84	0.189	0.201	0.236	0.247	+0.012
30	27.5	0.5	10	155	83	0.040	0.045	0.081	0.086	+0.005
30	27.5	1.5	8	199	83	0.048	0.047	0.089	0.088	+0.001
30	27.5	1.5	8	378	80	0.130	0.143	0.174	0.174	+0.014
30	27.5	1.5	8	438	91	0.135	0.148	0.179	0.191	+0.013
30	27.5	0.5	10	606	89	0.166	0.168	0.225	0.227	+0.002
25	22.3	0.5	10	155	86	0.034	0.034	0.069	0.069	0.000
25	22.3	1.5	8	200	86	0.039	0.037	0.074	0.072	-0.002
25	22.3	0.5	10	312	86	0.086	0.090	0.122	0.126	+0.004
25	22.3	0.5	8	382	83	0.096	0.110	0.140	0.144	+0.007
25	22.3	1.5	8	438	83	0.139	0.144	0.174	0.174	+0.005
25	22.3	1.5	8	607	84	0.151	0.153	0.184	0.183	+0.002
20	17.2	0.5	10	280	79	0.030	0.028	0.062	0.060	-0.002
20	17.2	1.5	8	250	81	0.044	0.041	0.069	0.066	-0.003
20	17.2	0.5	10	598	74	0.089	0.079	0.089	0.099	+0.010
20	17.2	1.5	8	604	74	0.090	0.094	0.111	0.115	+0.004
20	17.2	1.5	8	695	79	0.125	0.125	0.135	0.125	+0.003
20	17.2	1.5	8	1000	74	0.125	0.127	0.140	0.125	+0.003
15	11.3	0.5	10	270	88	0.022	0.021	0.041	0.040	-0.001
15	11.3	1.5	8	200	85	0.022	0.020	0.040	0.038	-0.002
15	11.3	0.5	10	804	86	0.055	0.052	0.073	0.070	-0.003
15	11.3	1.5	8	899	84	0.066	0.062	0.082	0.078	-0.004
15	11.3	0.5	10	1000	86	0.066	0.074	0.082	0.091	+0.008
15	11.3	1.5	8	1000	85	0.083	0.082	0.101	0.100	-0.001

Actual Inside Dimensions of Flue Lining 6 1/2" X 11 in.

*Actual inside dimensions of flue lining $6\frac{1}{2} \times 11$ in.

*Actual inside dimensions of flue lining $9\frac{1}{4} \times 11$ in.
 bCorrected for outside temperature 32 F. Barometer 29.92 in. Hg.
 c $\frac{1}{2}$ gal per hour of fuel oil burned with 10 per cent CO₂ produces 18.4 cfm or 1.38 lb per minute of flue gases (corrected to 70 F, 1 atmosphere pressure). $1\frac{1}{2}$ gal per hour of fuel oil burned with 8 per cent CO₂ produces 97.6 cfm or 6.98 lb per minute of flue gas (corrected to 70 F, 1 atmosphere pressure).